



| CONTENTS | | |
|--|---|------|
| BALUSTRADE CHA | ANNELS | 6-25 |
| BACH BAEC | BALUSTRADE CHANNEL | 6 |
| EZM | MEDIUM DUTY GLAZING CHANNEL | 7 |
| NG.20KG | TECGROUT C NON SHRINK | 7 |
| RESIGROUT LV | RESIGROUT LV TWO PART | 7 |
| BR | SMART-RAIL TILT-LOCK BASE RAIL SYSTEM | 8 |
| BR68.SCP BR68.CPS | SMART-RAIL TILT-LOCK COVER PLATES | 9 |
| BR68 | SMART-RAIL TILT-LOCK BASE CHANNEL MODEL | 9 |
| BR78 | SMART-RAIL TILT-LOCK HIGH STRENGTH MODEL | 9 |
| PG120.B PG120.S PG180.S | POSIGLAZE BALUSTRADE SYSTEM | 10 |
| BA124 | INFINITY SIDEFIX GLASS BALUSTRADE SYSTEM | 12 |
| BA124 | INFINITY TYPICAL INSTALLATION EXAMPLES | 14 |
| CKI.1 | INFINITY HEAVY DUTY CLAMP EXTRUSION | 14 |
| RCI.118 | INFINITY REAR COVER/CLAMP BASE WITH BULB SEAL | 15 |
| FCI.124 | INFINITY FRONT COVER WITH BULB SEAL | 15 |
| CKI.12 | INFINITY CLAMP KIT SUITABLE FOR 12MM GLASS THICKNESS | 16 |
| CKI.15 | INFINITY CLAMP KIT SUITABLE FOR 15MM GLASS THICKNESS | 16 |
| RSI.1 | INFINITY REAR COVER SPACER PLATE | 16 |
| SOI.15 | INFINITY STAND OFF PLATE | 16 |
| ECI.124.6 ECI.124.7 | INFINITY EXTRUSION END CAP WITH NO.6/7 PLUG AND SCREWS | 17 |
| GGSI.F GGSI.R | INFINITY GLASS GASKET SET FRONT AND REAR | 17 |
| GGI.12F GGI.12R GGI.15F GGI.15R | INFINITY GLASS GASKET SUITABLE FOR 12/15MM GLASS THICKNESS | 17 |
| GBS.124 | INFINITY GLASS BULB SEAL | 17 |
| EDC | RESIDENTIAL FLOOR MOUNT CHANNEL MONTREUX | 18 |
| EDC EDCEND | COMMERCIAL FLOOR MOUNT CLAMP GENOA | 20 |
| EFC | RESIDENTIAL FACE FIX CHANNEL LUGANO | 22 |
| EGL | COMMERCIAL FACE FIX CLAMP MONACO | 24 |
| ВТІ | BONDING AND SEALING QUICK CEMENT FIXIT AND RAPID | 25 |

| CONTENTS | | |
|-----------------|---|-------|
| MINI POSTS | | 26-48 |
| ERP | MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST | 26 |
| ERPT | MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST TOP FIXED | 27 |
| ERPF | MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST FACE FIXED | 27 |
| ERPH | MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST | 28 |
| ECP | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST CONCRETE OR BOLT THROUGH TIMBER | 28 |
| ECPFC | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO CONCRETE SUBSTRATE | 29 |
| ECPFBT | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO TIMBER SUBSTRATE | 29 |
| ECPTC | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST TOP FIXED TO CONCRETE SUBSTRATE | 30 |
| ECPR | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) | 30 |
| ECPRBT | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) SUITABLE FOR TIMBER | 31 |
| ECPRS | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) SUITABLE FOR STEEL | 31 |
| ECPRC | MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) | 32 |
| EMP250.CD.FF.RD | CORE DRILLED FRICTION FIT MINI POST ROUND | 32 |
| EMP250.CD.FF.SQ | CORE DRILLED FRICTION FIT MINI POST SQUARE | 33 |
| EMP350.BM.FF.RD | BASE MOUNTED FRICTION FIT MINI POST ROUND | 33 |
| EMP350.BM.FF.RD | BASE MOUNTED FRICTION FIT MINI POST ROUND | 34 |
| EMP450.BM.FF.SQ | BASE MOUNTED FRICTION FIT MINI POST SQUARE | 34 |
| EMP450.BM.FF.RD | BASE MOUNTED FRICTION FIT MINI POST ROUND | 35 |
| EB1 | EUROBRACE MINI POST ROUND | 35 |
| EB2 | EUROBRACE MINI POST SQUARE | 36 |
| FMP250 | CORE DRILLED MINI POST ROUND | 36 |
| FMP250.R | MINI POST RING | 37 |
| FMP250.C | MINI POST COVER | 37 |
| FMP350 | BASE MOUNTED MINI POST ROUND | 37 |



114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia



| CONTENTS | | |
|-----------------------------|--|-------|
| MINI POSTS | | 26-48 |
| TL | TILT-LOCK MINI POST HEAVY DUTY RANGE | 38 |
| TL9642G | TILT-LOCK CORE DRILLED MINI POST | 39 |
| TL9642G.SCP TL9642G.CP | TILT-LOCK CORE DRILLED MINI POST COVER PLATE | 39 |
| TL9642B | TILT-LOCK BASE MOUNTED MINI POST | 39 |
| TL9642B.CP | TILT-LOCK BASE MOUNTED MINI POST COVER PLATE | 39 |
| STL9642B | TILT-LOCK BASE MOUNTED MINI POST SQUARE BASE PLATE | 40 |
| STL9642B.CP | TILT-LOCK BASE MOUNTED MINI POST SQUARE BASE PLATE COVER PLATE | 40 |
| EDGE92 | TILT-LOCK SIDE FIX MINI POST | 41 |
| TLSF96 | TILT-LOCK SIDE FIX CLAMP | 41 |
| NBF168 | NAUTECH STRUT POST BASE FIX | 42 |
| NSF315 | NAUTECH STRUT POST FACE FIX | 44 |
| PL200 PL200.1 PL200.6 | STRUT POST BASE FIX | 46 |
| PL400 PL400.1 PL400.6 | STRUT POST FACE FIX | 47 |
| SP155 | STRUT POST BASE FIX | 48 |

| CONTENTS | | |
|--------------|--|-------|
| GLASS CLAMPS | | 50-55 |
| BCRD6 | GLASS CLAMP ROUND PROFILE ROUND BACK SUITABLE FOR 6/8MM GLASS THICKNESS | 50 |
| BCFD6 | GLASS CLAMP ROUND PROFILE FLAT BACK SUITABLE FOR 6/8MM GLASS THICKNESS | 50 |
| BCRD10 | GLASS CLAMP ROUND PROFILE ROUND BACK SUITABLE FOR 10/12MM GLASS THICKNESS | 51 |
| BCFD10 | GLASS CLAMP ROUND PROFILE FLAT BACK SUITABLE FOR 10/12MM GLASS THICKNESS | 51 |
| BCRS8 | GLASS CLAMP SQUARE PROFILE ROUND BACK SUITABLE FOR 8/10MM GLASS THICKNESS | 51 |
| BCFS8 | GLASS CLAMP SQUARE PROFILE FLAT BACK SUITABLE FOR 8/10MM GLASS THICKNESS | 51 |
| BCRS10 | GLASS CLAMP SQUARE PROFILE ROUND BACK SUITABLE FOR 10/12MM GLASS THICKNESS | 52 |
| BCFS10 | GLASS CLAMP SQUARE PROFILE FLAT BACK SUITABLE FOR 10/12MM GLASS THICKNESS | 52 |
| BCI | BALUSTRADE CLAMP GLASS TO GLASS | 52 |
| BC90 | BALUSTRADE CLAMP 90° CORNER | 52 |
| BC135 | BALUSTRADE CLAMP GLASS TO GLASS | 53 |
| BCWM | BALUSTRADE CLAMP WALL MOUNT | 53 |
| BCWML | BALUSTRADE CLAMP RECTANGLE WALL MOUNT WITH LEG | 53 |
| BB70 | BALUSTRADE BRACKET ROUND WALL MOUNT | 54 |
| BB70.SQ | BALUSTRADE BRACKET SQUARE WALL MOUNT | 54 |
| BBD70 | BALUSTRADE BRACKET ROUND GLASS TO GLASS | 55 |
| BBD70.SQ | BALUSTRADE BRACKET SQUARE GLASS TO GLASS | 55 |



114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia

| CONTENTS | | |
|--|--|-------|
| GLASS ANCHORS | | 56-91 |
| B19.M6 B25.M6 B32.M6/M10 | GLASS ANCHOR BUTTON HEAD WITH THREADED ROD OR LAG SCREW | 56 |
| BB19.M6 BB25.M6 BB32.M6/M10 | GLASS ANCHOR DOUBLE BUTTON HEAD | 57 |
| BSOM | GLASS ANCHOR BUTTON HEAD AND BODY FIXING OPTIONS | 57 |
| BSOM6.19 | GLASS ANCHOR 19MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING | 58 |
| BSOM6.25 | GLASS ANCHOR 25MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING | 58 |
| BSOM6.32 | GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING | 59 |
| BSOM10.32 | GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING | 59 |
| CBMSO | GLASS ANCHOR COUNTER SUNK HEAD AND BODY FIXING OPTIONS | 60 |
| CBM6SO.19 | GLASS ANCHOR 18MM COUNTER SUNK HEAD 19MM BODY DIAMETER WITH OPTIONAL FIXING | 60 |
| CBM6SO.25 | GLASS ANCHOR 18MM COUNTER SUNK HEAD 25MM BODY DIAMETER WITH OPTIONAL FIXING | 61 |
| CBM6SO.32 | GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING | 61 |
| CBM10SO.32 | GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING | 62 |
| CCBM6SO.19 | GLASS ANCHOR 22MM COUNTER SUNK HEAD WITH CAP 19MM BODY DIAMETER WITH OPTIONAL FIXING | 62 |
| CCBM6SO.25 | GLASS ANCHOR COUNTER SUNK HEAD WITH CAP 25MM BODY DIAMETER WITH OPTIONAL FIXING | 63 |
| CCBM6SO.32 | GLASS ANCHOR COUNTER SUNK HEAD WITH CAP 32MM BODY DIAMETER WITH OPTIONAL FIXING | 63 |
| CCBM10SO.32 | GLASS ANCHOR COUNTER SUNK HEAD WITH CAP 32MM BODY DIAMETER WITH OPTIONAL FIXING | 64 |
| EUBFSD38 | EUROANCHOR 38MM DIAMETER STEPPED DISC | 64 |
| EUBFSD50 EUBFSD51 | EUROANCHOR 50MM DIAMETER STEPPED DISC | 65 |
| EUBFCS | EUROANCHOR 50MM DIAMETER COUNTER SUNK STEPPED DISC | 65 |
| EUBFSQ | EUROANCHOR 50MM DIAMETER SQUARE STEPPED DISC | 66 |
| EUBFSQD | EUROANCHOR RECTANGULAR STEPPED DISC | 66 |
| MB50 | GLASS ANCHOR ADJUSTABLE | 68 |
| MB50.AS.T45.40 MB50.AS.T45.50 MB50.CS.AS.T45 | GLASS ANCHOR 50MM DIAMETER ADJUSTABLE | 69 |
| PF150 | PLATEFIX SINGLE ANCHOR | 70 |

| CONTENTS | | |
|---|---|----------|
| GLASS ANCHORS | | 56-91 |
| PRADIS | PRADIS RESIDENTIAL BALUSTRADE SYSTEM | 72 |
| PRADIS | PRADIS COMMERCIAL BALUSTRADE SYSTEM | 74 |
| EUBFSD.50 EUBFSD.51 EUBFSQ EUBFCS EUBFSQD | EUROANCHOR BALUSTRADE SYSTEM RESIDENTIAL INSTALL EXAMPLES COMMERCIAL INSTALL EXAMPLES | 76 78 |
| MB50.S | BALUSTRADE ANCHOR HEAVY WEIGHT 50MM SQUARE EDGE HEAD | 79 |
| MB50.R | BALUSTRADE ANCHOR HEAVY WEIGHT 50MM ROUND EDGE HEAD | 79 |
| MB50.R.T30 | BALUSTRADE ANCHOR HEAVY WEIGHT 50MM ROUND EDGE HEAD OPTIONAL FIXING | 80 |
| MB75.T.T30 | BALUSTRADE ANCHOR HEAVY WEIGHT 75MM SINGLE DISC | 81 |
| MB75.SQ | SQUARE COVER KIT CONVERT MB75.T.T30 | 81 |
| MB100.S.T30 | BALUSTRADE ANCHOR HEAVY WEIGHT 100MM SINGLE DISC | 82 |
| EGSBF1000.38 | GLASS ANCHOR 38MM DIAMETER FLAT BUTTON HEAD | 83 |
| EGSBF1000.50 | GLASS ANCHOR 50MM DIAMETER FLAT BUTTON HEAD | 84 |
| EGSBF1100.38 | GLASS ANCHOR 38MM DIAMETER CONCAVE BUTTON HEAD | 84 |
| EGSBF1100.50 | GLASS ANCHOR 50MM DIAMETER CONCAVE BUTTON HEAD | 85 |
| EGSBF1150.38 | GLASS ANCHOR 38MM DIAMETER FLAT BUTTON HEAD | 85 |
| EGSBF1150.50 | GLASS ANCHOR 50MM DIAMETER FLAT BUTTON HEAD | 86 |
| EGSBF1200 | HANDRAIL FIXING GLASS OPTION FLAT BUTTON HEAD | 86 |
| EGSBF1250 | HANDRAIL FIXING GLASS OPTION FLAT BUTTON HEAD | 87 |
| EGSBF1300 | HANDRAIL FIXING GLASS OPTION CONCAVE BUTTON HEAD | 87 |
| EGSBF1400 | POST ATTACHMENT GLASS PANEL FLAT BUTTON HEAD | 88 |
| EGSBF1500 | POST ATTACHMENT GLASS PANEL CONCAVE BUTTON HEAD | 88 |
| EUHB.50 | HANDRAIL BRACKET ROUND | 89 |
| EUHB.50.SQ | HANDRAIL BRACKET SQUARE | 89 |
| EUHBTF50 | HANDRAIL BRACKET ROUND SUITABLE FOR TIMBER FIX | 90 |
| EUHBTF50.SQ | HANDRAIL SQUARE SUITABLE FOR TIMBER FIX | 90 |
| EGSBF1600 | POST ATTACHMENT GLASS PANEL FLAT BUTTON HEAD - LONG FIXING LEG | 91 |
| EGSBF1700 | POST ATTACHMENT GLASS PANEL CONCAVE BUTTON HEAD - LONG FIXING LEG | 91 |



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia



| CONTENTS | | |
|----------------------|-------------------------------------|-------|
| COMPONENTS AN | D PARTS | 92-99 |
| EGSBF600.38 | SPACER 38MM DIAMETER | 92 |
| SP3820 | SPACER 38MM DIAMETER 20MM LENGTH | 93 |
| SP5025 SP5025.T | SPACER 50MM DIAMETER 25MM LENGTH | 93 |
| EGSBF600.50 | SPACER 50MM DIAMETER | 93 |
| SPC5010 | SPACER COUNTERSUNK FIXING DISC | 94 |
| SPG32 | GIB SPACER | 94 |
| EGSBF610 | TAPERED NUT | 94 |
| EGSBF620 | FLANGE TAPERED RANGE | 94 |
| SD50M10 | STEPPED DISC 50MM DIAMETER | 95 |
| EGSBF630 | COVERED FLANGE PLATE | 95 |
| SD38M8 | STEPPED DISC 38MM DIAMETER | 95 |
| EGSBF640 | NUT | 95 |
| EGSBF650 | COVER RANGE | 96 |
| EGSBF660 | LONG PLATE WITH THREADED ROD | 96 |
| EGSBF670 | SHORT PLATE WITH THREADED ROD | 96 |
| EGSBF700 | WALL BRACKET 75MM OFFSET | 96 |
| EGSBF710 | WALL BRACKET 80MM OFFSET | 97 |
| EGSBF720 | POST BRACKET M12 OFFSET | 97 |
| EGSBF730 | MASONRY WALL BRACKET | 97 |
| EGSBF740 | ROD THREAD STRAIGHT | 97 |
| EGSBF750 | ROD THREAD 150MM | 98 |
| EGSBF750.LS | LAG SCREW | 98 |
| EGSBF830 | WASHER COLLARED BLACK NYLON | 98 |
| EGSBF800 EGSBF820 | WASHER BLACK NYLON | 98 |
| EGSBF810 | PROTECTIVE SLEEVE CLEAR | 99 |

| CONTENTS | | |
|--------------------------|--|--------|
| TOP RAILS | 10 | 00-108 |
| EH.TOPRAIL.SQ | FRAMELESS GLASS TOP RAIL SQUARE ULTRA SLIM | 100 |
| EH.WB.SQ | WALL BRACKET SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 101 |
| EH.ENDCAP.SQ | END CAP SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 101 |
| EH.180.SQ.JOINER | STRAIGHT 180° JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 101 |
| EH.90.SQ.JOINER | FIXED 90° CORNER JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 101 |
| EH.HOR.VAR.SQ. JOINER | HORIZONTAL VARIABLE JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 102 |
| EH.VER.SQ.JOINER | HINGE VERTICAL JOINER SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 102 |
| EH.ADJ.JOINER | ADJUSTABLE JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 102 |
| EH.INLINE.JOINER | INLINE JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 102 |
| EH.SLEEVE.JOINER | SLEEVE JOINER SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM | 103 |
| EH.TOPRAIL.RD | FRAMELESS GLASS TOP RAIL ROUND ULTRA SLIM | 104 |
| EH.WB.RD | WALL BRACKET SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 104 |
| EH.ENDCAP.RD | END CAP SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 104 |
| EH.180.RD.JOINER | STRAIGHT 180° JOINER SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 105 |
| EH.90.RD.JOINER | FIXED 90° CORNER JOINER SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 105 |
| EH.HOR.VAR.RD. JOINER | HORIZONTAL VARIABLE JOINER SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 105 |
| EH.VER.RD.JOINER | HINGE VERTICAL JOINER SUITABLE FOR TOP RAIL ROUND ULTRA SLIM | 105 |
| BH1 BH2 | HANDRAIL SLIMLINE WITH END CAP | 106 |
| SOLO | HANDRAIL FLAT TUBE | 106 |
| SOLO.WB | WALL BRACKET SUITABLE FOR HANDRAIL FLAT TUBE | 106 |
| SOLO.ENDCAP | END CAP SUITABLE FOR HANDRAIL FLAT TUBE | 107 |
| SOLO.180°.JOINER | STRAIGHT 180° JOINER SUITABLE FOR HANDRAIL FLAT TUBE | 107 |
| SOLO.90°.JOINER | FIXED 90° CORNER JOINER SUITABLE FOR HANDRAIL FLAT TUBE | 107 |
| SOLO.VAR.JOINER | HORIZONTAL VARIABLE JOINER SUITABLE FOR HANDRAIL FLAT TUBE | 107 |
| HRB.HB | CLAMP WALL TO FLAT HANDRAIL SUITABLE FOR HANDRAIL FLAT TUBE | 108 |
| HRB | CLAMP GLASS TO FLAT HANDRAIL SUITABLE FOR HANDRAIL FLAT TUBE | 108 |



114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au




BALUSTRADE CHANNEL

| Item number | • BACH • BAEC - end cap |
|-----------------|---|
| Description | balustrade channel 6 meter stock length handrail options available for installation use Tecgrout C (NG.20KG) |
| Suitable for | • 12mm and 15mm glass thickness |
| Material finish | mill silver pearl powdercoat selected powdercoat (lead time applies) |



SIDE VIEW





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105



MEDIUM DUTY GLAZING CHANNEL

| Item number | EZM |
|-----------------|---|
| Description | medium duty glazing channel designed for use on parapets, and if correctly installed, the creation of toeholds may be avoided it may also be used for some full height balustrades, (*subject to relative design criteria) internal recess of 74mm high x 41mm wide utilises Axiom glazing rubbers SRB retained back seal and SWZ9 wedge rubber when using 12mm glass thickness for installation use Tecgrout C (NG.20KG) end caps available on request |
| Suitable for | supporting free standing glass balustrade parapets some full height balustrades 10mm, 12mm and 15mm glass thickness |
| Material finish | • mill • powdercoat |


TECGROUT C NON SHRINK

| Item number | NG.20KG |
|--------------|--|
| Description | Tecgrout C is a flowable, non shrink type C grout based on ordinary Portland cement, specially graded aggregates and admixtures to produce a flowable grout at a low water cement ratio |
| Suitable for | • for installation of Balustrade Channel (BACH) and Medium Duty Glazing Channel (EZM) |

NG.20KG



EZM



RESIGROUT LV TWO PART

| Item number | RESIGROUT LV |
|-------------|---|
| Description | Resigrout LV is a low viscosity epoxy grout for the repair of cracks in concrete pavement |

RESIGROUT LV



SIDE VIEW





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

SMART-RAIL TILT-LOCK BASE RAIL SYSTEM

Item number

BR (available in 5.85 meter lengths)

Description

The Smart-Rail Tilt-lock base rail system is a revolution in design and ease of installation. Never before has a base rail system been so simple to install for expert and the DIY installer. It greatly reduces the issues of uneven sites making the channel installation so much faster, on most sites just tilt the glass to resolve site issues simply and quickly. With modern design architects seeking clean clear lines the Smart-Rail meets the design demands of today and the future. Featuring three models to suit a range of glass from 12mm to 32.67mm and up to 3kn applications the system provides an unprecedented range of installation and glass options to meet the ever increasing demand for better frameless glass systems.

Whether you require top, rebated or side fixed option the system provides every thing you need in a simple and strong solution. The grub screw system is design to use full length covers for one or both sides and the internal clamping system can use either long or short covers. The recess model is designed to be installed in situations where the base rail is required to not be seen, this model is also suitable for use with curved glass.

The Smart-Rail system can be easily used for grout filled applications if this option is specified, although with the ease of the Tilt-lock system the need is unlikely.

Suitable for


- 12mm to 25mm glass thickness with the three available models
- top or side fixed applications
- indoor and outdoor installations

Material finish


- sections and covers are fully anodised for durability and come standard in a unique brushed anodised finish which give a "stainless steel effect"
- other aluminium finishes are available on request

TILT AND LOCK **Tightening**





Adjustment





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

7 Manfull Street Melrose Park

SA 5039 Australia

ADELAIDE OFFICE



1300 4 ELITE | 03 9314 6105

INTERNAL CLAMPING MOUNTING SYSTEM



GRUB SCREW MOUNTING SYSTEM



SMART-RAIL TILT-LOCK COVER PLATES

| Item number | BR68.SCP square style full cover model BR68.CPS square style top cover model |
|-----------------|---|
| Description | • smart-rail tilt-lock cover plates |
| Suitable for | BR68 and BR78 |
| Material finish | • duplex 2205 polished or satin stainless steel |

BR68.SCP/ CPS







BR68.CPS

SMART-RAIL TILT-LOCK BASE CHANNEL MODEL

| Item number | BR68 |
|-----------------|--|
| Description | smart-rail tilt-lock base channel model |
| Suitable for | 12mm to 19mm glass thickness (internal clamping system) 12mm to 25mm glass thickness (grub screw mounting system) |
| Material finish | duplex 2205 polished or satin stainless steel |

BR68



BR68

SMART-RAIL TILT-LOCK HIGH STRENGTH MODEL

| Item number | BR78 |
|-----------------|---|
| Description | • smart-rail tilt-lock high strength model |
| Suitable for | 12mm to 25mm glass thickness (internal clamping system) 12mm to 32.67mm glass thickness (grub screw mounting system) |
| Material finish | • duplex 2205 polished or satin stainless steel |

BR78



BR78



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105





Item number

- PG120.B base fix system 120mm high x 72mm wide x 3 meter lengths
- PG120.S side fix system 120mm high x 74mm wide x 3 meter lengths
- PG180.S side fix system 180mm high x 74mm wide x 3 meter lengths

Description

The PosiGlaze Glass Balustrade System was developed for cantilevered structural balustrades to cope with the transition from monolithic toughened safety glass to toughened laminated safety glass.

The unique design uses a special high strength hollow core aluminium extrusion and special glass clamp kits that clamp the glass and locate into the section. This means the system can be used on 12, 15, and 19mm toughened safety glass and 13.5, 17.5 and 21.5 laminated safety glass without holes in the glass. Holes can make the systems more complex and often the holes are the point of failure.

The other key to PosiGlaze is its clever locating and adjusting technique which allows the installers to adjust the glass panels once in place, with a turn of a spanner, saving on installation time.

Suitable for

The PosiGlaze Glass Balustrade System can be base fixed or side fixed for top or side (face) mounted balustrade applications.

The 120mm high x 72mm wide extrusion comes in 3 meter lengths all pre drilled ready for fixing and once the section is fitted the glass is easily dropped in and located. The systems also makes re-glazing easy, or the glass type or thickness can be easily changed at a later date.

A top seal strip section and gasket are installed after the glass has been adjusted to give a clean top edge look and matching end caps complete the system.

For the side fixed systems an additional clip on side cladding and tapered base cladding section is used for aesthetics and to cover the fixing holes.

Material finish

The sections and covers are fully anodized for durability and come standard in a unique brushed anodized finish which give a "Stainless Steel Effect"

Other aluminium finishes are available on request.



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

Design and testing

The PosiGlaze Glass Balustrade System has been designed and tested to New Zealand and British Standards, which use similar occupancy types and loading requirements.

The UK testing to BS 6180:2011, involved base and side fixed systems to concrete and steel and a range of glass types and thicknesses from 15mm - 21mm including TLSG with EVA and SG inter layer.

The NZ testing is to AS/NZS 1170 loadings in accordance with B1/VM1 Amend 8, for Occupancy A, B, E, C3 and the higher C1, C2 and D loadings.

Therefore the systems can be used for all residential applications and commercial applications, except for C5 (over-crowding).

Installation

The Posiglaze Glass Balustrade System can be glazed with Toughened, Heat soaked, Screen printed, Digital printed, Toughened Safety Glass (TSG) or SafeLite Toughened Laminated Safety Glass (TLSG), using either, PVB, CIP, EVA or SGP interlayer. Note that the breakage characteristic can alter with different interlayer's.

(Refer to Glass Manufacturer for more details).


Compliance


The PosiGlaze Glass Balustrade System can be used for compliance with NZ Building Code Clause F4 -Safety from falling, with barrier heights to suit the design application, normally 1 meter.


The maximum glass height is a function of the glass type, thickness, occupancy loading, and wind loading and a design table or specific design is available from Elite Structural Glass Fittings.

Test data and independent engineered and certified Producer Statements (PS1) are available for compliance with the NZ Building Code.

Heat Soaked TSG is recommended for barriers with interlinking handrails or top rails









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia




INFINITY SIDEFIX GLASS BALUSTRADE SYSTEM


| Item number | BA124 |
|-----------------|---|
| Description | Infinity sidefix glass balustrade system no holes are required in the glass panels, they are simple to install, align and adjust Residential A, C3 and pool fencing require 12mm toughened glass, clamps at 500mm centres with a maximum overhang of 250mm Commercial B, E and C3 require 15mm toughened glass, clamps at 400mm centres with a maximum overhang of 200mm PS1 and system manual with full set out details are available on request |
| Suitable for | side fix frameless glass balustrades pool fencing and the following balustrade occupancy types – Residential A and C3, Commercial B, E and C3 |
| Material finish | natural anodised aluminium with mill finish standard colour powder coat options also available |
| Order | • specify lengths of front and rear covers, plus the required number of glass clamps. All system components can be selected on pages to follow |








Residential A, C3 and Pool Fence



Commercial B, E and C3





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105



BA124

Timber Deck - M12 coach screw


Occupancy Residential A and C3 only



- 1 Coachscrews 90mm minimum thread engagement into joists
- 2 Bond all coachscrews with SIKA Supergrip to full depth
- 3 A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Waterproof timber deck - M12 coach screw

Occupancy Residential A and C3 only



- 1 Coachscrews 90mm minimum thread engagement into joists
- 2 Bond all coachscrews with SIKA Supergrip to full depth
- 3 A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Infinity glass clamps height options



'Normal height say 10mm below deck



Clamp with deck



Clamp below deck




Clamp flush with deck 15mm spacer

BA124

Concrete Deck - M12 Stud

Occupancy


Residential A & C3 = 12mm toughened glass Commercial B, E & C3 = 15mm toughened glass



- 1 All fixings must engage into the structural slab
- 2 A Rubber, EPDM or foam tape layer must be installed between the clamp and concrete


Steel structure - M12 bolt

Occupancy Residential A and C3 = 12mm glass



1 - A Rubber, EPDM or foam tape layer must be installed between the clamp and steel

Infinity glass clamps height options



'Normal height say 10mm below deck



Clamp flush with deck



Clamp below deck



Clamp flush 15mm spacer



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

INFINITY TYPICAL INSTALLATION EXAMPLES

BA124

Waterproof timber deck


Occupancy Commercial B, E or C3



- 1 Coachscrews 120mm minimum thread engagement into joists
- 2 Bond all coachscrews with SIKA Supergrip to full depth
- 3 A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Timber deck - M12 coach screw

Occupancy Commercial B, E or C3



- 1 Coachscrews 90mm minimum thread engagement into joists
- 2 Bond all coachscrews with SIKA Supergrip to full depth
- 3 A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Infinity glass clamps height options



'Normal' height say 10mm below deck



Clamp flush with deck



Clamp below deck





Clamp flush with deck 15mm spacer

INFINITY HEAVY DUTY CLAMP EXTRUSION

| Item number | CKI.1 |
|-----------------|---|
| Description | Infinity heavy duty clamp extrusion the infinity balustrade clamp comes as a kit - clamp extrusion, front and rear gasket extrusions gaskets, glass bottom packer and all adjusting screws (M12 fastener not included) |
| Suitable for | • 12mm, 13.52mm, 15mm, 17.52mm, 19mm and 21.52mm glass thickness |
| Material finish | • aluminium |









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105




INFINITY REAR COVER/CLAMP BASE WITH BULB SEAL

| Item number | RCI.118.N.5000 118mm height natural anodised 5 meter length RCI.118.N.2500 118mm height natural anodised 2.5 meter length RCI.118.M.5000 118mm height |
|-----------------|--|
| | mill aluminium 5 meter length • RCI.118.M.2500 118mm height mill aluminium 2.5 meter length |
| Description | Infinity rear cover/clamp base with bulb sealacts as a template |
| Suitable for | Infinity system |
| Material finish | natural anodised mill aluminium standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A. |


INFINITY FRONT COVER WITH BULB SEAL

| Item number | FCI.124.N.5000 124mm height natural anodised 5 meter length FCI.124.N.2500 124mm height natural anodised 2.5 meter length FCI.124.M.5000 124mm height mill aluminium 5 meter length FCI.124.M.2500 124mm height mill aluminium 5 meter length FCI.124.M.2500 124mm height mill aluminium 2.5 meter length |
|-----------------|---|
| Description | Infinity front cover with bulb seal |
| Suitable for | • Infinity system |
| Material finish | natural anodised mill aluminium standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A. |

RCI.118



FCI.124





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

INFINITY CLAMP KIT SUITABLE FOR 12MM GLASS THICKNESS

| Item number | CKI.12 |
|-----------------|--|
| Description | • Infinity clamp kit |
| Suitable for | Infinity system12mm glass thickness |
| Material finish | • matt black |




INFINITY CLAMP KIT SUITABLE FOR 15MM GLASS THICKNESS

| Item number | CKI.15 |
|-----------------|--|
| Description | • Infinity clamp kit |
| Suitable for | Infinity system15mm glass thickness |
| Material finish | • matt black |


CKI.15

CKI




INFINITY REAR COVER SPACER PLATE

| Item number | RSI.1 |
|-----------------|--|
| Description | Infinity rear cover spacer plate 1mm to align rear cover if structure is not straight use only if required |
| Suitable for | • Infinity system |
| Material finish | • silver frost • mill |



INFINITY STAND OFF PLATE

| Item number | SOI.15 |
|-----------------|---|
| Description | Infinity stand off platewill stand the infinity system15mm off the structureuse only if required |
| Suitable for | • Infinity system |
| Material finish | • silver frost • mill |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105




INFINITY EXTRUSION END CAP

| Item number | ECI.124.6 no.6 plastic plug + 6g x 25 SS CS screw ECI.124.7 no.7 plastic plug + z x 25 SS CS screw |
|-----------------|--|
| Description | • infinity extrusion end cap complete with plugs and screws |
| Suitable for | • Infinity system |
| Material finish | natural anodisedmill |



INFINITY GLASS GASKET SET FRONT AND REAR

| Item number | • GGSI.F - front • GGSI.R - rear |
|--------------|--|
| Description | • Infinity glass gasket set front and rear |
| Suitable for | Infinity system |



INFINITY GLASS GASKET SUITABLE FOR 12/15MM GLASS THICKNESS

| Item number | 12mm glass thickness • GGI.12F front - 2mm thick x 100mm wide • GGI.12R rear - 2mm thick x 150mm wide |
|--------------|---|
| | 15mm glass thickness • GGI.15F front - 1mm thick x 100mm wide • GGI.15R rear - 1mm thick x 150mm wide |
| Description | • Infinity glass gasket |
| Suitable for | Infinity system12mm and 15mm glass thickness |



INFINITY GLASS BULB SEAL

| Item number | GBS.124 |
|--------------|----------------------------|
| Description | • Infinity glass bulb seal |
| Suitable for | • Infinity system |

GBS.124





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


RESIDENTIAL FLOOR MOUNT CHANNEL MONTREUX

Item number • EDC • EDCEND - end cap Description • residential floor mount channel Montreux • 1.25 meter, 2.5 meter and 5 meter stock lengths • supplied complete with clamping kits and cover plates vertical adjustment up to 15mm • Out of plumb adjustment: +/- 50mm @ 1 meter high +/- 60mm @ 1.2 meters high • M10 coach screw at 200mm centres fixing in timber • M10 s/s epoxy bolts at 400mm centres fixing in concrete and steel • clamping kits no greater than 400mm centres • supporting base channel is anotec powder coated with 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass based on barrier loads from AS/NZS1170.1 • very high wind zone 1.76 kPa or less • maximum heights above floor level are for residential occupancies A & C3 of Table 3.3 AS/NZS1170.1 – 1.1 meters from finish floor level - 1.2 meter with glass corners at the top connected by elite glass balustrade clamps, or an interlinking handrail at 900mm to 1 meter, end panels must be connected to the building by clamps or interlinking rail Suitable for • 12mm or 13.52mm glass thickness • pool fencing protecting a fall of 1 meter or more Material finish • mill • silver pearl powdercoat selected powdercoat (lead time applies)



GLASS CUT OUT DETAIL







Order

HEAD OFFICE

• specify glass thickness


114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia




EDC


FIXING DETAIL - CONCRETE




FIXING DETAIL - TIMBER



FIXING DETAIL - STEEL









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105


COMMERCIAL FLOOR MOUNT CLAMP GENOA

| Item number | EYB |
|-----------------|---|
| Description | commercial floor mount clamp Genoa stock lengths available in 1.2 meter, 2.4 meter and 4.8 meter fixing options (concrete and steel) end caps available glass cut out required 10 year warranty PS1 available for use with Viridian 'Balustrade 100' toughened safety glass based on design loads from AS/NZS 1170.1 and a maximum uls wind pressure of 2.13 kPa (extra high wind zone), minimum glass thicknesses are: for commercial occupancies B, E and C3 of table 3.3 AS/NZS 1170.1, up to 1.1 meter high balustrade measured from floor level Viridian 'Balustrade 100' 15mm toughened safety glass or 17.5mm laminated toughened glass |
| Suitable for | • 15mm toughened and 17.5mm laminated glass |
| Material finish | millsilver pearl powdercoatselected powdercoat (lead time applies) |





GLASS CUT OUT DETAIL






114 Endeavour Way Sunshine West VIC 3020 Australia


ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia




FIXING DETAIL - STEEL



FIXING DETAIL - CONCRETE



FIXING DETAIL - STEEL CONCRETE FIXING PLATE









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

LUGANO

RESIDENTIAL FACE FIX CHANNEL Item number EFC Description • residential face fix channel Lugano • stock lengths available in 1.2 meter, 2.4 meter or 4.8 meter • fixing options (concrete, steel, bolt through timber and lag screw) recommended installation tools available • end, internal and external corner caps available • no glass cut outs or holes required • 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass • based on barrier loads from AS/NZS 1170.1, Viridian 12mm 'Balustrade 100' toughened safety glass or 13.5mm toughened laminated safety glass, maximum height above the channel is: - for residential occupancy A, B, C3 of Table 3.3 AS/NZS 1170.1, very high wind zone 1.76 kPa or less: 1.2 meters high with glass corners at top edge connected by elite glass balustrade clamps or with an interlinking rail at 900mm to 1 meter • end panels must be connected to the building by clamps or interlinking rail • extra high wind zone 2.13 kPa or less - 1.1 meter high without balustrade corner clamps or interlinking rail Suitable for • 12mm toughened and 13.5mm laminated glass • suitable for pool fencing protecting

a fall of 1 meter or more

• silver pearl powdercoat selected powdercoat (lead time applies)









• mill

Material finish

HEAD OFFICE

114 Endeavour Way **Sunshine West** VIC 3020 Australia


ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia






EFC


FIXING DETAIL - CONCRETE



FIXING DETAIL - TIMBER SLATTED DECK BOLT THROUGH FIXING




FIXING DETAIL - TIMBER SLATTED DECK LAG SCREW FIXING




EFC


FIXING DETAIL - TIMBER ENCLOSED DECK LAG SCREW FIXING



FIXING DETAIL - STEEL (EXTERNAL & INTERNAL)



FIXING DETAIL - STEEL (INTERNAL)





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105


COMMERCIAL FACE FIX CLAMP MONACO

Item number EGL Description • commercial face fix clamp Monaco • stock lengths available in 1.2 meter, 2.4 meter and 4.8 meter • fixing options (concrete, steel and bolt through timber) recommended installation tools available • end, internal and external corner caps available • glass cut out required • 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass • based on design loads from table 3.3 of AS/NZS 1170.1 and a maximum uls wind pressure of 3.0 kPa, minimum glass thicknesses and maximum balustrade heights measured from top of clamp are: - Occupancy B, E & C3 'Viridian Balustrade 100' 15mm toughened safety glass or 17.5mm toughened laminated safety glass up to 1.2 meters - Occupancy C1/C2 & D: Viridian 'Balustrade 100' 15mm toughened safety glass up to 1.1 meter with corner connectors, or Viridian 'Balustrade 100' 19mm toughened safety glass or 21.5mm laminated toughened glass up to 1.2 meter Suitable for • 15mm and 19mm toughened and 17.5mm and 21.5mm


laminated glass

• silver pearl powdercoat selected powdercoat (lead time applies)

• mill



GLASS CUT OUT DETAIL





Material finish


114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia




EGL


FIXING DETAIL - CONCRETE



FIXING DETAIL - TIMBER SLATTED DECK



FIXING DETAIL - STEEL



BONDING AND SEALING

QUICK CEMENT FIXIT AND RAPID

| C | |
|--------------|--|
| Item number | BTI |
| Description | bonding and sealing quick cement fixit and rapid no corrosion enhancing effect with metals apart from lead the appropriate quick cement for every application quickly hardening free from chlorides high pressure and flexural strength waterproof and free of cracks fixit is pasty and can be poured for processing flowingly |
| Suitable for | bonding and sealing for quick interior and exterior anchoring and fixing of steel and plastic parts; for fixing cable ducts, switching units, pipes, gratings, consoles, protective edges, etc anchoring door frames and windows filling in gaps and holes cement/concrete, chalk cement grout and cement attics masonry and stone |

BTI





HEAD OFFICE


114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia





1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au



MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST

| Item number | ERP |
|-----------------|--|
| Description | milano post semi-frameless residential balustrade post based on design loads from AS/NZS 1170.1 and a maximum uls wind pressure of 1.76 kPa (very high wind zone) fixed at 1.65 meters centres maximum height 1.1 meter maximum glass overhang 500mm PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | Viridian 'Balustrade 100' 10mm toughened safety glass or 11.5mm toughened laminate glass residential occupancy A and C3 |
| Material finish | silver pearl powdercoatselected powdercoat |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST TOP FIXED

| Item number | ERPT |
|-----------------|--|
| Description | milano post semi-frameless residential balustrade post top fixed concrete or steel supplied complete with fixing to suit substrate four fixings per post minimum edge distance for fixings is 50mm |
| Suitable for | • residential |
| Material finish | mill finish natural anodised |


ERPT






MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST FACE FIXED

| Item number | ERPF |
|-----------------|--|
| Description | milano post semi-frameless residential balustrade post face fixed minimum edge distance for fixings is 60mm two fixings per post |
| Suitable for | concrete, steel or bolt through timberresidential |
| Material finish | mill finish natural anodised |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST


| Item number | ERPH |
|-----------------|---|
| Description | milano post semi-frameless residential balustrade post concealed face fixed minimum edge distance for fixings is 30mm two fixings per post |
| Suitable for | • steel or bolt through timber • residential |
| Material finish | mill finish natural anodised |

ERPH ERPH M8 csk bolt. Installer to apply Duralac DTD369B to bolt, cap 1-1.1 Stainless and bar before fitting steel cap 2mm I 10mm toughened or 11.5mm toughened laminated glass 100mm maximum Duralloy powder coated aluminium post



MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST CONCRETE OR BOLT THROUGH TIMBER

| Item number | ECP |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post concrete or bolt through timber fixed at 1.1 meter centres maximum height 1.1 meter maximum glass overhang 500mm PS1 available for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | Virdian 'Balustrade 100' 10mm toughened safety glass or 11.5mm toughened laminated glass commercial occupancy B, E and C3 |
| Material finish | silver pearl powdercoatselected powdercoat |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105




MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO CONCRETE SUBSTRATE

| Item number | ECPFC |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post face fixed to concrete substrate |
| Suitable for | • commercial occupancy B, E and C3 |
| Material finish | mill finish natural anodised |

ECPFC ECPFC Handrail as required Commercial buildings and common areas multi-unit dwellings 1.1 meter Installer to apply Duralac DTD269B to bolts, cap and aluminium before fixing 2mm Ĭ Duralloy powdercoated aluminium post Ramset Epcon C6 anchor with T316 s.s. threaded rod, 50x50x3 s.s. washer, nylon bush and gasket to separate stainless steel and aluminium M12xT316 s.s. dome nut, s.s. washer, s.s. spring washer, nylon bush and gasket to separate aluminium and stainless steel 60 270mm 150mm 150mm aluminium cap

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO TIMBER SUBSTRATE

| Item number | ECPFBT |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post face fixed to timber substrate |
| Suitable for | • commercial occupancy B, E and C3 |
| Material finish | mill finish natural anodised |





110mm

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au


www.eliteglasssolutions.com.au

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST TOP FIXED TO CONCRETE SUBSTRATE

| Item number | ECPTC |
|-----------------|--|
| Description | milano post semi-frameless commercial balustrade post top fixed to concrete substrate |
| Suitable for | • commercial occupancy B, E and C3 |
| Material finish | mill finish natural anodised |

ECPTC







MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5)

| Item number | ECPR |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post (C5) two fixings per post fixed at 1.1 meter centres maximum height 1.1 meter maximum glass overhang 300mm PS1 available for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | concrete, steel or bolt through timber commercial occupancy C1, C2, D and C5 Viridian 'Balustrade 100' 15mm toughened safety glass or 17.2mm toughened laminated glass |
| Material finish | silver pearl powdercoatselected powdercoat |

ECPR



Dow Corning 580 silicon to gap, both sides of glazing bar





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105





MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) SUITABLE FOR TIMBER

| Item number | ECPRBT |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post (C5) substrate fixings are concealed |
| Suitable for | commercial occupancy C1, C2, D and C5 face fixed to timber substrate |
| Material finish | mill finish natural anodised |

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5) SUITABLE FOR STEEL

| Item number | ECPRS |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post (C5) substrate fixings are concealed |
| Suitable for | face fixed to steel substrate commercial occupancy C1, C2, D and C5 |
| Material finish | mill finish natural anodised |







114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5)


| Item number | ECPRC |
|-----------------|---|
| Description | milano post semi-frameless commercial balustrade post (C5) substrate fixings are concealed |
| Suitable for | face fixed to concrete substrate commercial occupancy C1, C2, D and C5 |
| Material finish | mill finish natural anodised |

ECPRC ECPRC -Milano Europost s.s. bar insert Viridian 15mm toughened or 17.5mm toughened laminated safety glass 800mm M12 s.s. threaded rod in Ramset Epcon C6 anchor 320 x 125 x 12mm thick s.s. plate

CORE DRILLED FRICTION FIT MINI POST **ROUND**

| Item number | EMP250.CD.FF.RD |
|-----------------|---|
| Description | core drilled friction fit mini post round no holes in glass required 285mm overall height supplied with dress ring to conceal core drilling and M16 threaded rod for height adjustment |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105



CORE DRILLED FRICTION FIT MINI POST **SQUARE**

| Item number | EMP250.CD.FF.SQ |
|-----------------|--|
| Description | core drilled friction fit mini post square no holes in glass required 285mm overall height supplied with dress ring to conceal core drilling and M16 threaded rod for height adjustment |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | duplex 2205 polished or satin stainless steel |


78.5mm 40mm 185mm EMP250.CD.FF.SQ 100mm



BASE MOUNTED FRICTION FIT MINI POST ROUND

| Item number | EMP350.BM.FF.RD |
|-----------------|--|
| Description | base mounted friction fit mini post round no holes in glass required 156mm overall height supplied with dress ring to conceal structural fittings |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |





M8*2



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

BASE MOUNTED FRICTION FIT MINI POST ROUND


| Item number | EMP350.BM.FF.RD |
|-----------------|--|
| Description | base mounted friction fit mini post round 156mm overall height no holes in glass required supplied with dress ring to conceal structural fittings |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |







BASE MOUNTED FRICTION FIT MINI POST SQUARE

| Item number | EMP450.BM.FF.SQ |
|-----------------|---|
| Description | base mounted friction fit mini post square 175mm height no holes in glass required supplied with dress ring to conceal structural fittings |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | duplex 2205 polished or satin stainless steel |









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia





1300 4 ELITE | 03 9314 6105



BASE MOUNTED FRICTION FIT MINI POST ROUND

| Item number | EMP450.BM.FF.RD |
|-----------------|--|
| Description | base mounted friction fit mini post round 175mm height no holes in glass required supplied with dress ring to conceal structural fittings |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |







EUROBRACE MINI POST ROUND

| Item number | EB1 |
|-----------------|---|
| Description | Eurobrace mini post round posts are set into concrete (Ø50 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) 26mm diameter holes in glass 45mm typical clearance from ground surface distance from inside face of glass and post centre is 40mm PS1 available for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | • 10mm, 12mm and 15mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |

EB1



GLASS CUT OUT DETAIL





11mm

HEAD OFFICE

084.29

-0111

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

EUROBRACE MINI POST **SQUARE**

| Item number | EB2 |
|-----------------|--|
| Description | Eurobrace mini post square posts are set into concrete (Ø50 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) 26mm diameter holes in glass 45mm typical clearance from ground surface distance from inside face of glass and post centre is 32mm PS1 available for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | • 10mm, 12mm and 15mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |




GLASS CUT OUT DETAIL




CORE DRILLED MINI POST ROUND

| Item number | FMP250 |
|-----------------|--|
| Description | core drilled mini post round set 85mm into concrete (Ø60 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) 26mm diameter holes in glass 45/50mm typical clearance from ground surface PS1 available on request optional ring (FMP205.R) and cover (FMP250.C) available |
| Suitable for | • 12mm and 15mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




1300 4 ELITE | 03 9314 6105

MINI POST RING

| Item number | FMP205.R |
|--------------|-----------------------------|
| Description | • mini post ring (optional) |
| Suitable for | • FMP250 |

FMP250.R



MINI POST COVER

| Item number | FMP250.C |
|--------------|-----------------------|
| Description | • optional post cover |
| Suitable for | • FMP250 |


FMP250.C




BASE MOUNTED MINI POST ROUND

| Item number | FMP350 |
|-----------------|--|
| Description | based mounted mini post round 26mm diameter holes in glass 45mm - 50mm typical clearance from ground surface posts can be fastened to concrete or wooden surfaces using two M10 bolts/screws PS1 available on request. |
| Suitable for | 12mm and 15mm glass thicknessconcrete or wooden surfaces |
| Material finish | • 316 grade polished or satin stainless steel |





GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

TILT-LOCK MINI POST **HEAVY DUTY RANGE**

| Item number | TL |
|-----------------|--|
| Description | tilt-lock mini post heavy duty range tilt-lock adjustable mounting systems are designed to support glass from 12mm to 25.52mm thickness using a vast range of fixing solutions range of six models including top, side and edge mounting options provide installation answers to almost every mounting issue imaginable without holes in the glass the system offers great flexibility, lower cost and fast installation the tilt-lock feature of the mounting systems offers a unique and simple levelling method by tilting the glass vertical and locking the grub screws ensuring a perfect result in half the time fully engineered tested |
| Suitable for | • 12mm to 25.52mm glass thickness • use with SGP |
| Material finish | • duplex 2205 polished or satin stainless steel |







TILT-LOCK means "tilt and lock" a simple process that allows you to simply tilt the glass in the spigot to the correct alignment and lock the grub screws, for the perfect finish in half the time. TILT-LOCK is the only answer!



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

TILT-LOCK CORE DRILLED MINI POST


| Item number | TL9642G |
|-----------------|--|
| Description | • tilt-lock core drilled mini post |
| Suitable for | 12mm through to 25.52mm glass thicknessno holes in glass required |
| Material finish | • duplex 2205 polished or satin stainless steel |

TL9642G



TILT-LOCK CORE DRILLED MINI POST COVER PLATE


| Item number | • TL9642G.SCP - square • TL9642G.CP - round |
|-----------------|--|
| Description | tilt-lock core drilled mini post cover plate |
| Suitable for | • TL9642G mini post |
| Material finish | duplex 2205 polished or satin stainless steel |




TILT-LOCK BASE MOUNTED MINI POST

| Item number | TL9642B |
|-----------------|--|
| Description | • tilt-lock base mounted mini post |
| Suitable for | 12mm through to 25.52mm glass thicknessno holes in glass required |
| Material finish | • duplex 2205 polished or satin stainless steel |

TL9642B





TILT-LOCK BASE MOUNTED MINI POST COVER PLATE

| Item number | TL9642B.CP |
|-----------------|---|
| Description | • tilt-lock base mounted mini post cover plate |
| Suitable for | • TL9642B mini post |
| Material finish | • duplex 2205 polished or satin stainless steel |

TL9642B. CP





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia





1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

TILT-LOCK BASE MOUNTED MINI POST SQUARE BASE PLATE

| Item number | STL9642B |
|-----------------|--|
| Description | • tilt-lock base mounted mini post square base plate |
| Suitable for | 12mm through to 25.52mm glass thicknessno holes in glass required |
| Material finish | • duplex 2205 polished or satin stainless steel |

STL9642B





TILT-LOCK BASE MOUNTED MINI POST SQUARE BASE PLATE COVER PLATE

| Item number | STL9642B.CP |
|-----------------|--|
| Description | • tilt-lock base mounted mini post square base plate cover plate |
| Suitable for | • STL9642B mini post |
| Material finish | • duplex 2205 polished or satin stainless steel |








TILT-LOCK SIDE FIX MINI POST


| Item number | EDGE92 |
|-----------------|--|
| Description | • tilt-lock side fix mini post |
| Suitable for | 12mm through to 25.52mm glass thicknessno holes in glass required |
| Material finish | duplex 2205 polished or satin stainless steel |

TILT-LOCK SIDE FIX CLAMP

| Item number | TLSF96 |
|-----------------|--|
| Description | • tilt-lock side fix clamp |
| Suitable for | 12mm through to 25.52mm glass thicknessno holes in glass required |
| Material finish | • duplex 2205 polished or satin stainless steel |

TLSF96





| EDGE92 | | |
|--------|-------|--------|
| 152 | 32 mm | EDGE92 |
| 158 | 8mm | 92mm |



114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

NAUTECH STRUT POST BASE FIX

Item number

NBF168 (Patent NZP561106)

Description

- NauTech strut post base fix
- the system is a unique strut post design which is unobtrusive, strong and durable
- the system features horizontal and vertical adjustment for the glass
- the vertical adjustment is attained by the use of a patented clamping and adjustment technique which is the heart of the fitting, it clamps the glass without the need for holes and this saves on glass processing costs and installation time
- the strut post is 168mm high and provides a 50mm clearance between the top of the deck and underside of the glass pane
- the NauTech system has been tested in NZ to AS/NZS 1170 barrier loadings in accordance with B1/VM1 Amendment 8

Suitable for


- 12mm glass thickness (no holes or cutouts required)
- domestic and commercial balustrades and pool fences
- base fixing to masonry, timber and steel structures

Material finish


- 16mm thick 316 grade polished or satin stainless steel
- bead blast




NBF168



FIXING DETAIL - DOMESTIC WOOD FIX (CSW100)



FIXING DETAIL - DOMESTIC CONCRETE FIX (MF43)





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia






1300 4 ELITE | 03 9314 6105




NBF168


FIXING DETAIL - COMMERCIAL AND DOMESTIC STEEL FIX (SF25)



FIXING DETAIL - COMMERCIAL AND DOMESTIC WOOD FIX (SBW120 OR DBW140)



FIXING DETAIL - COMMERCIAL CONCRETE FIX (DF100)



NAUTECH TWO STRUT POSTS PER PANEL SET OUT DETAILS

Commercial occupancy C3, B and E

H = 1.1 meter X = 700 mm, C = 1


X = 700mm, C = 150mm, W = 1 meter

Pool fence

H = 1.2 meter

X = 1 meter, C = 500mm, W = 2 meters

TWO STRUTS



NAUTECH THREE STRUT POSTS PER PANEL SET OUT DETAILS

Domestic and residential occupancy A & A other (C3)

H = 1 meter

X = 1 meter

C = 200mm W = 2.4 meter OR X = 700mm C = 350mm

W = 2.1 meter

Commercial occupancy C3, B and E

H = 1.1 meter


X = 700mm, C = 150mm, W = 1.7 meters

Pool fence

H = 1.2 meter

X = 1 meter, C = 500mm, W = 3 meters

THREE STRUTS



Note: Larger panels can be used by applying the above spacings.



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

NAUTECH STRUT POST FACE FIX

Item number

NSF315 (Patent NZP561106)

Description

- NauTech strut post face fix
- the system is a unique strut post design which is unobtrusive, strong and durable
- the system features horizontal and vertical adjustment for the glass
- the vertical adjustment is attained by the use of a patented clamping and adjustment technique which is the heart of the fitting, it clamps the glass without the need for holes and this saves on glass processing costs and installation time
- 315mm high in total (168 above FFL) and provides a 50mm clearance between the top of the deck and underside of the glass pane
- the NauTech system has been tested in NZ to AS/NZS 1170 barrier loadings in accordance with B1/VM1 Amendment 8

Suitable for


- 12mm glass thickness (no holes or cutouts required)
- domestic and commercial balustrades and pool fences
- base fixing to masonry, timber and steel structures

Material finish


- 16mm thick 316 grade polished or satin stainless steel
- bead blast




NSF315



FIXING DETAIL - DOMESTIC WOOD FIX (CSW100)



FIXING DETAIL - DOMESTIC CONCRETE FIX (MF43)





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




1300 4 ELITE | 03 9314 6105




NSF315


FIXING DETAIL - COMMERCIAL AND DOMESTIC STEEL FIX (SF25)



FIXING DETAIL - COMMERCIAL AND DOMESTIC WOOD FIX (SBW120 OR DBW140)



FIXING DETAIL - COMMERCIAL CONCRETE FIX (DF100)



NAUTECH TWO STRUT POSTS PER PANEL SET OUT DETAILS

Pool fence
H = 1.2 meter X = 1 meter, C = 500mm, W = 2 meters

TWO STRUTS

W

W


C

X

C

X

NAUTECH THREE STRUT POSTS PER PANEL SET OUT DETAILS




Commercial occupancy C3, B and E

H = 1.1 meter X = 700mm, C = 150mm, W = 1.7 meters

Pool fence

H = 1.2 meter X = 1 meter, C = 500 mm, W = 3 meters



Note: Larger panels can be used by applying the above spacings.



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105✓ sales@eliteglasssolutions.com.auwww.eliteglasssolutions.com.au

STRUT POST BASE FIX

Item number

- PL200 silver frost powder coat
- PL200.1 selected powder coat colour one to five units
- PL200.6 selected powder coat colour six plus units

Description

- strut post base fix
- compliant to AS/NZS1170
- adjustable for glass alignment
- concealed fixings


Suitable for

- 12mm toughened glass
- occupancy A, B, E and C3
- use in balustrades and pool fences


Material finish

- standard silver frost powder coat
- available in special colours on request
- powder coated aluminium





MAIN FEATURES FOR A BASE FIX BRACKET





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




1300 4 ELITE | 03 9314 6105




STRUT POST FACE FIX

| Item number | PL400 silver frost powder coat PL400.1 selected powder coat colour one to five units PL400.6 selected powder coat colour six plus units |
|-----------------|---|
| Description | strut post face fixcompliant to AS/NZS1170adjustable for glass alignmentconcealed fixings |
| Suitable for | 12mm toughened glassoccupancy A, B, E and C3use in balustrades and pool fences |
| Material finish | standard silver frost powder coat available in special colours on request powder coated aluminium |





MAIN FEATURES FOR A SIDE FIX BRACKET





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105


STRUT POST BASE FIX

| Item number | SP155 |
|-----------------|--|
| Description | strut post base fix 155mm high and comes with drop on covers to hide the fixings |
| Suitable for | 12mm toughened safety glass balustrades (no holes or cutouts required) base fixing on top of masonry or other solid structures occupancy A, B, C3, E and pool fences |
| Material finish | • 2205 duplex grade polished or satin stainless steel |

SP155




TWO STRUT POST RESIDENTIAL SET OUT











GLASS CLAMP ROUND PROFILE ROUND BACK SUITABLE FOR 6/8MM GLASS THICKNESS

| Item number | BCRD6 |
|-----------------|--|
| Description | glass clamp - round profileround back to suit 50mm tubular post |
| Suitable for | • 6mm and 8mm glass thickness • post mount |
| Material finish | • polished or satin stainless steel |



GLASS CLAMP ROUND PROFILE FLAT BACK SUITABLE FOR 6/8MM GLASS THICKNESS

| Item number | BCFD6 |
|-----------------|--|
| Description | glass clamp - round profileflat back for fixing to square section and wall mounting |
| Suitable for | • 6mm and 8mm glass thickness • wall mount |
| Material finish | • polished or satin stainless steel |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




GLASS CLAMP ROUND PROFILE ROUND BACK SUITABLE FOR 10/12MM GLASS THICKNESS

| Item number | BCRD10 |
|-----------------|--|
| Description | glass clamp - round profileround back to suit 50mm tubular post |
| Suitable for | • 10mm and 12mm glass thickness • post mount |
| Material finish | • polished or satin stainless steel |




GLASS CLAMP ROUND PROFILE FLAT BACK SUITABLE FOR 10/12MM GLASS THICKNESS

| Item number | BCFD10 |
|-----------------|--|
| Description | glass clamp - round profileflat back for fixing to square section and wall mounting |
| Suitable for | • 10mm and 12mm glass thickness • wall mount |
| Material finish | • polished or satin stainless steel |




GLASS CLAMP SQUARE PROFILE ROUND BACK SUITABLE FOR 8/10MM GLASS THICKNESS

| Item number | BCRS8 |
|-----------------|---|
| Description | glass clamp - square profileround back to suit 50mm tubular post |
| Suitable for | • 8mm and 10mm glass thickness • post mount |
| Material finish | • polished or satin stainless steel |



GLASS CLAMP SQUARE PROFILE FLAT BACK SUITABLE FOR 8/10MM GLASS THICKNESS

| Item number | BCFS8 |
|-----------------|---|
| Description | glass clamp - square profileflat back for fixing to square section and wall mounting |
| Suitable for | • 8mm and 10mm glass thickness • wall mount |
| Material finish | • polished or satin stainless steel |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia



√ 1300 4 ELITE | 03 9314 6105✓ sales@eliteglasssolutions.com.au✓ www.eliteglasssolutions.com.au


GLASS CLAMP SQUARE PROFILE ROUND BACK SUITABLE FOR 10/12MM GLASS THICKNESS

| Item number | BCRS10 |
|-----------------|---|
| Description | glass clamp - square profileround back to suit 50mm tubular post |
| Suitable for | • 10mm and 12mm glass thickness • post mount |
| Material finish | • polished or satin stainless steel |




GLASS CLAMP SQUARE PROFILE FLAT BACK SUITABLE FOR 10/12MM GLASS THICKNESS

| Item number | BCFS10 |
|-----------------|--|
| Description | glass clamp - square profile flat back for fixing to square section and wall mounting |
| Suitable for | • 10mm and 12mm glass thickness • wall mount |
| Material finish | • polished or satin stainless steel |




BALUSTRADE CLAMP GLASS TO GLASS

| Item number | BCI |
|-----------------|---|
| Description | balustrade clamp - glass to glasssupplied with rubber gasket inserts |
| Suitable for | • 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |



BALUSTRADE CLAMP 90° CORNER

| Item number | BC90 |
|-----------------|---|
| Description | balustrade clamp - 90° cornersupplied with rubber gasket inserts |
| Suitable for | • 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




BALUSTRADE CLAMP GLASS TO GLASS

| Item number | BC135 |
|-----------------|---|
| Description | • balustrade clamp - 135° corner glass to glass |
| Suitable for | • 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |




BALUSTRADE CLAMP WALL MOUNT


| Item number | BCWM |
|-----------------|---|
| Description | balustrade clamp - wall mountsupplied with rubber gasket inserts |
| Suitable for | • 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |



BALUSTRADE CLAMP RECTANGLE WALL MOUNT WITH LEG

| Item number | BCWML |
|-----------------|---|
| Description | balustrade clamp wall mount with leg |
| Suitable for | • 12mm glass thickness |
| Material finish | • duplex 2205 polished or satin stainless steel |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

BALUSTRADE BRACKET ROUND


WALL MOUNT

| Item number | BB70 |
|-----------------|---|
| Description | balustrade bracket round - wall mount |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |

| BB70 | |
|------|------|
| | |
| | |
| | |
| | |
| | BB70 |
| | |
| | |
| | |



GLASS CUT OUT DETAIL




BALUSTRADE BRACKET SQUARE


WALL MOUNT

| Item number | BB70.SQ |
|-----------------|---|
| Description | balustrade bracket square - wall mount |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |





GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




BALUSTRADE BRACKET ROUND GLASS TO GLASS

| Item number | BBD70 |
|-----------------|---|
| Description | balustrade bracket round - glass to glass |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |

BBD70







BALUSTRADE BRACKET SQUARE GLASS TO GLASS

| Item number | BBD70.SQ |
|-----------------|---|
| Description | balustrade bracket square - glass to glass |
| Suitable for | • 10mm and 12mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |

BBD70.SQ







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 xales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au




GLASS ANCHOR BUTTON HEAD WITH THREADED ROD OR LAG SCREW

Item number • B19.M6 - 19mm button diameter • B25.M6 - 25mm button diameter • B32.M6 - 32mm button diameter • B32.M10 - 32mm button diameter Description • glass anchor button head, 10mm button thickness • threaded rod 30mm in length or lag screw 50mm in length • complete with plastic washer/spacer • select fixing (included - threaded rod or wood fix lag screw) Suitable for • 6mm, 8mm, 10mm and 12mm glass thickness Material finish • 304 grade polished or satin stainless steel (lead time applies except B32.M10



FIXING OPTIONS THREADED ROD OR WOOD FIX LAG SCREW



GLASS CUT OUT DETAIL





B19/B25

B32



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

GLASS ANCHOR DOUBLE BUTTON HEAD

| Item number | BB19.M6 - 19mm button diameter BB25.M6 - 25mm button diameter BB32.M6 - 32mm button diameter BB32.M10 - 32mm button diameter |
|-----------------|---|
| Description | glass anchor double button head, 10mm button thickness complete with plastic washer/spacer |
| Suitable for | • 6mm, 8mm, 10mm and 12mm glass thickness |
| Material finish | • 304 grade polished or satin stainless steel (lead time applies - except BB32.M10 |

BB19/25/32 19mm, 25mm or 32mm button diameter 10mm BB19/25/32



please specify glass thickness

GLASS CUT OUT DETAIL






GLASS ANCHOR BUTTON HEAD AND BODY FIXING OPTIONS

| • glass anchor button head and body fixing options | Item number | BSOM |
|---|-------------|---|
| threaded rod wood fix lag screw hallow wall timber insert masonry | Description | body fixing options - threaded rod - wood fix lag screw - hallow wall - timber insert |














114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

GLASS ANCHOR 19MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING

Item number

19mm button head diameter

- BSOM6.19.10 19mm button diameter 10mm body length M6 thread 10mm hole in glass
- BSOM6.19.20 19mm button diameter 20mm body length M6 thread 10mm hole in glass
- BSOM6.19.30 19mm button diameter 30mm body length M6 thread 10mm hole in glass
- BSOM6.19.50 19mm button diameter 50mm body length M6 thread 10mm hole in glass

Description

- glass anchor 19mm button head and body, M6 thread
- 10mm button thickness
- body length available in 10mm, 20mm, 30mm or 50mm
- 10mm hole in glass required
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)


Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness


Material finish

• 304 grade polished or satin stainless steel

BSOM6.19 BSOM6.19



GLASS CUT OUT DETAIL



GLASS ANCHOR 25MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING

Item number

25mm button head diameter

- BSOM6.25.10 25mm button diameter 10mm body length M6 thread 10mm hole in glass
- BSOM6.25.20 25mm button diameter 20mm body length M6 thread 10mm hole in glass
- BSOM6.25.30 25mm button diameter 30mm body length M6 thread 10mm hole in glass
- BSOM6.25.50 25mm button diameter 50mm body length M6 thread 10mm hole in glass

Description

- glass anchor 25mm button head and body, M6 thread
- 10mm button thickness
- body length available in 10mm, 20mm, 30mm or 50mm
- 10mm hole in glass required
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel


BSOM6.25

BSOM6.25

Optional body length 10mm, 20mm, 30mm or 50mm M6 thread 25mm button 0 diameter Optional fixing

thickness **GLASS CUT OUT DETAIL**

10mm button





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING

Item number • BSOM6.32.10 32mm button diameter

- 10mm body length M10 thread 10mm hole in glass
- BSOM6.32.20 32mm button diameter 20mm body length
- M10 thread 10mm hole in glass
- BSOM6.32.30 32mm button diameter 30mm body length M10 thread 10mm hole in glass
- BSOM6.32.50 32mm button diameter 50mm body length M10 thread 10mm hole in glass


Description

- glass anchor 32mm button and body, M10 thread
- 10mm button thickness
- body length available in 10mm, 20mm, 30mm or 50mm
- 10mm hole in glass required
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

- 6mm, 8mm, 10mm and 12mm glass thickness
- Material finish
- 304 grade polished or satin stainless steel

BSOM6.32 BSOM6.32 Optional body length 10mm, 20mm, 30mm or 50mm



GLASS CUT OUT DETAIL



GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING

Item number 32mm button head diameter

- BSOM10.32.10 32mm button diameter 10mm body length M10 thread 10mm hole in glass
- BSOM10.32.20 32mm button diameter 20mm body length M10 thread 10mm hole in glass
- BSOM10.32.30 32mm button diameter 30mm body length M10 thread 10mm hole in glass
- BSOM10.32.50 32mm button diameter 50mm body length M10 thread 10mm hole in glass

Description

- glass anchor 32mm button and body, M10 thread
- 10mm button thickness
- body length available in 10mm, 20mm, 30mm or 50mm
- 10mm hole in glass required
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for


• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel

BSOM10.32





GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


GLASS ANCHOR COUNTER SUNK HEAD AND BODY FIXING OPTIONS

| • glass anchor counter sunk head and body fixing options - threaded rod - wood fix lag screw - hallow wall - timber insert - masonry |
|--|
| |


FIXING OPTIONS











GLASS ANCHOR 18MM COUNTER SUNK HEAD 19MM BODY DIAMETER WITH OPTIONAL FIXING

Item number

19mm body diameter

- CBM6SO.19.10
 19mm body diameter
 10mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter
- CBM6SO.19.20
 19mm body diameter
 20mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter
- CBM6SO.19.30
 19mm body diameter
 30mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter
- CBM6SO.19.50
 19mm body diameter
 50mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter

Description


- glass anchor 18mm counter sunk head 19mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M6 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105



GLASS ANCHOR 18MM COUNTER SUNK HEAD 25MM BODY DIAMETER WITH OPTIONAL FIXING

Item number 25mm body diameter

CBM6SO.25.10 25mm body diameter 10mm body length M6 thread 18mm counter sunk head diameter 10mm counter sunk base diameter

- CBM6SO.25.20
 25mm body diameter
 20mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter
- CBM6SO.25.30
 25mm body diameter
 30mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter
- CBM6SO.25.50
 25mm body diameter
 50mm body length
 M6 thread
 18mm counter sunk head diameter
 10mm counter sunk base diameter

Description

- glass anchor 18mm counter sunk head 25mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M6 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel

CBM6 Optional body length CBM6SO.25 10mm, 20mm, 30mm or 50mm M6 thread Counter sunk head 0 diameter Optional fixing 18mm Body diameter 25mm Counter sunk base diameter 10mm Head Glass hole preparation A diameter = 18mm B diameter = 10mm

GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number 32mm body diameter

- CBM6SO.32.10
 32mm body diameter
 10mm body length
 M6 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter
- CBM6SO.32.20
 32mm body diameter
 20mm body length
 M6 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter
- CBM6SO.32.30
 32mm body diameter
 30mm body length
 M6 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter
- CBM6SO.32.50
 32mm body diameter
 50mm body length
 M6 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter

Description


- glass anchor 24mm counter sunk head 32mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M6 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING

GLASS ANCHOR 22MM COUNTER SUNK HEAD WITH CAP 19MM BODY DIAMETER WITH OPTIONAL FIXING

• CCBM6SO.19.20

Item number

32mm body diameter

- CBM10SO.32.10 32mm body diameter 10mm body length M10 thread
- 24mm counter sunk head diameter 16mm counter sunk base diameter
- CBM10SO.32.20
 32mm body diameter
 20mm body length
 M10 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter
- CBM10SO.32.30
 32mm body diameter
 30mm body length
 M10 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter
- CBM10SO.32.50
 32mm body diameter
 50mm body length
 M10 thread
 24mm counter sunk head diameter
 16mm counter sunk base diameter

Description

- glass anchor 24mm counter sunk head 32mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M10 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

CBM10

• 304 grade polished or satin stainless steel

Counter sunk head diameter 24mm Optional body length CBM10SO.32 M10 thread Optional fixing Body diameter 32mm Counter sunk base

Glass hole preparation A diameter = 24mm B diameter = 16mm

Item number

19mm body diameter

- CCBM6SO.19.10
 19mm body diameter
 10mm body length
 M6 thread
 22mm counter sunk head diameter
 10mm counter sunk base diameter
- 19mm body diameter
 20mm body length
 M6 thread
 22mm counter sunk head diameter
 10mm counter sunk base diameter
- CCBM6SO.19.30
 19mm body diameter
 30mm body length
 M6 thread
 22mm counter sunk head diameter
 10mm counter sunk base diameter
- CCBM6SO.19.50
 19mm body diameter
 50mm body length
 M6 thread
 22mm counter sunk head diameter
 10mm counter sunk base diameter

Description


- glass anchor counter sunk head with cap 19mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M6 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)


Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel







diameter 16mm

HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105



GLASS ANCHOR COUNTER SUNK HEAD WITH CAP

25MM BODY DIAMETER WITH OPTIONAL FIXING

Item number

- CCBM6SO.25.10 25mm body diameter 10mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter
- CCBM6SQ 25 20 25mm body diameter 20mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter
- CCBM6SO.25.30 25mm body diameter 30mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter
- CCBM6SO.25.50 25mm body diameter 50mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter

Description

- glass anchor counter sunk head with cap 25mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- · M6 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel

GLASS ANCHOR COUNTER SUNK HEAD WITH CAP 32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number 32mm body diameter • CCBM6SO.32.10 32mm body diameter 10mm body length M10 thread 30mm counter sunk head diameter 18mm counter sunk base diameter

- CCBM6SO.32.20 32mm body diameter 20mm body length M10 thread 30mm counter sunk head diameter 18mm counter sunk base diameter
 - CCBM6SO.32.30 32mm body diameter 30mm body length M10 thread 30mm counter sunk head diameter 18mm counter sunk base diameter
 - CCBM6SO.32.50 32mm body diameter 50mm body length M10 thread 30mm counter sunk head diameter 18mm counter sunk base diameter

Description


- glass anchor counter sunk head with cap 32mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- M10 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)


Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness

Material finish

• 304 grade polished or satin stainless steel







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

GLASS ANCHOR COUNTER SUNK HEAD WITH CAP 32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number

- CCBM10SO.32.10 32mm body diameter 10mm body length M10 thread
- 30mm counter sunk head diameter 18mm counter sunk base diameter
- CCBM10SO.32.20 32mm body diameter 20mm body length M10 thread
- 30mm counter sunk head diameter 18mm counter sunk base diameter
- CCBM10SO.32.30 32mm body diameter 30mm body length M10 thread
- 30mm counter sunk head diameter 18mm counter sunk base diameter
- CCBM10SO.32.50 32mm body diameter 50mm body length M10 thread
- 30mm counter sunk head diameter 18mm counter sunk base diameter

Description

- glass anchor counter sunk head with cap 32mm body diameter
- body length available in 10mm, 20mm, 30mm or 50mm
- · M10 thread
- select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)

Suitable for

• 6mm, 8mm, 10mm and 12mm glass thickness


Material finish

• 304 grade polished or satin stainless steel


CCBM10 SO.32 Optional body length CCBM10SO.32 10mm, 20mm, 30mm or 50mm M10 thread Counter sunk head diameter 30mm Optional fixing Body diameter 32mm Counter sunk base diameter 18mm Head Glass hole preparation A diameter = 30mm B diameter = 18mm

EUROANCHOR 38MM DIAMETER STEPPED DISC

| Item number | EUBFSD38 |
|-----------------|--|
| Description | euroanchor 38mm stepped disc anodised to over 20um 20mm spacer, M8 includes washer, PVC sleeve and fixing (threaded rod only) glass fixing hole 20mm diameter fixing centres are set as per PS1 PS1 available on request |
| Suitable for | • concrete, steel and timber |
| Material finish | satin silver anodised316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way **Sunshine West** VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




EUROANCHOR 50MM DIAMETER STEPPED DISC

| Item number | EUBFSD50 includes 25mm thick spacer EUBFSD51 includes 10mm thick spacer |
|-----------------|---|
| Description | euroanchor 50mm stepped disc anodised to over 20um includes washer, PVC sleeve and fixing (threaded rod or lag screw) glass fixing hole 26mm diameter 25mm spacer can be threaded M10 or 10.5mm through hole fixing centres as per PS1 PS1 available on request |
| Suitable for | • concrete, steel and timber |
| Material finish | satin silver anodised316 grade polished or satin stainless steel |




GLASS CUT OUT DETAIL




EUROANCHOR 50MM DIAMETER COUNTER SUNK STEPPED DISC

| Item number | EUBFCS |
|-----------------|--|
| Description | euroanchor 50mm counter sunk stepped disc spacers available in 10mm or 25mm includes washer, PVC sleeve and fixing (threaded rod or lag screw) glass fixing hole 22mm diameter 25mm spacer threaded M10 M10 counter sunk hex bolt 35mm fixing centres as per PS1 PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | • concrete, steel and timber |
| Material finish | • 316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au

EUROANCHOR 50MM DIAMETER SQUARE STEPPED DISC

| Item number | EUBFSQ |
|-----------------|---|
| Description | euroanchor 50mm square stepped disc includes washer, PVC sleeve and fixing (threaded rod or lag screw) glass fixing hole 26mm diameter fixing centres as per PS1 PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | • concrete, steel and timber |
| Material finish | • 316 grade polished or satin stainless steel |




GLASS CUT OUT DETAIL




EUROANCHOR RECTANGULAR STEPPED DISC

| Item number | EUBFSQD |
|-----------------|---|
| Description | euroanchor rectangular stepped disc double 25mm spacer 10.5mm through hole includes washer, PVC sleeve and fixing (threaded rod or lag screw) glass fixing hole 22mm diameter fixing centres as per PS1 PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass |
| Suitable for | • concrete, steel and timber |
| Material finish | satin silver anodised316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia






GLASS ANCHOR ADJUSTABLE

MB50 INNOVATIVE AND SUPERIOR FEATURES

- 1. Cap with snake eyes and chamfered edge to match mounting body. Square edge cap with countersunk machine screw fixing also available.
- Step in cap allows correct penetration of M10 threaded rod.
- 3. 49mm x 1mm acetal plastic cap washer.
- 4. M10 threaded rod to suit 12mm toughened glass, other lengths available on request.
- 5. 49mm x 1mm acetal plastic mounting body washer with integrated bush.
- **6.** Step in mounting body in conjunction with washer/bush aids in supporting the glass panel while the caps are being installed and during adjustment.
- 7. Mounting body is adjustable for a wall clearance between 40mm and 50mm via the use of an allen key through the centre before and after installation of the glass panels.
- 8. Recessed mark in mounting body indicates maximum recommended adjustment of 10mm.
- 9. Recess for rubber O-Ring.
- 10. Rubber O-Ring creates friction for finer adjustment, restricts movement prior to glass panels being installed and also helps to prevent foreign matter entering the inside of the anchor.
- 11. Allen key recess at centre of the base body allows tightening onto M10 threaded rods and helps with insertion of lagscrews into timber with the use of a battery drill and allen key bit.
- 12. Base body.
- 13. Recess in base body allows for tightening hard against concrete slab after excess epoxy may have emerged around the M10 threaded rod.
- 14. 115mm x M10 threaded rod. Other fixing methods including lagscrews available on request.







GLASS ANCHOR 50MM DIAMETER ADJUSTABLE

| Item number | MB50.AS.T45.40 40mm length MB50.AS.T45.50 50mm length MB50.CS.AS.T45 counter sunk |
|-----------------|--|
| Description | glass anchor 50mm diameter adjustable anchor adjustable with allen key before and after installation passed AS/NZS1170 testing loads due to a 20mm diameter glass hole preparation and 50mm diameter mounting body/cap telescopic body hides the thread for a seamless appearance |
| Suitable for | • 12mm toughened glass thickness |
| Material finish | • polished or satin stainless steel |

MB50. AS.T45



MB50. CS.AS.T45





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street


7 Manfull Street Melrose Park SA 5039 Australia




PLATEFIX SINGLE ANCHOR

| Item number | PF150 |
|-----------------|--|
| Description | • the PlateFix PF150 was born from the double disc fixings by joining the discs into a single piece profile base plate with a outer clamping plate for a stronger multipurpose balustrade fixing. This enables the PF150 to be used with single or double fixings and it can be used vertically, horizontally, angled or a combination of the above |
| Suitable for | • concrete, steel and timber |
| Material finish | 316 grade polished or satin stainless steel bead blast |

PF150



TYPICAL SET OUT 400MM MAXIMUM CENTRES




Domestic installation H = 550mm 10mm toughened glass Domestic installation H = 1,050mm 12mm toughened glass Commercial installation H = 1,250mm 15mm toughened glass Pool fence installation H = 1,250mm 12mm toughened glass Note: X is from centre of top fixing to top edge of glass

PF150


INSTALLATION COMMERCIAL GLASS THICKNESS 15MM DOMESTIC GLASS THICKNESS 12MM

Typical PF150 fixing details to comply with AS/NZS1170. Full details available on request.


TIMBER SINGLE POINT FIX - WOOD FIX CBW - 130



STEEL SINGLE POINT FIX - METAL FIX SF50 - 12



CONCRETE SINGLE POINT FIX - HILTI 12MM MF125





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105




PF150


INSTALLATION COMMERCIAL GLASS THICKNESS 15MM DOMESTIC GLASS THICKNESS 12MM

Typical PF150 fixing details to comply with AS/NZS1170. Full details available on request.


TIMBER DOUBLE POINT FIX - WOOD FIX CBW - 120



STEEL DOUBLE POINT FIX - METAL FIX SF50 - 10




CONCRETE DOUBLE POINT FIX - HILTI 10MM MF110





PF150


DESIGN OPTIONS BALUSTRADE SYSTEM VARIATIONS

Fitting variations shown relate to design table PF150. Full details available on request.











HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

72 **PRADIS** Item number Description

- Pradis residential balustrade system
- the system complies with New Zealand Building Code Clauses B1 Structure, F2 Hazardous Building Materials and F4 Safety from falling third edition, subject to:
- all products meeting the required performance specification
- site installation carried out in accordance with intent of this drawing
- minimum balustrade height of 1 meter from finished floor level
- based on 12mm Viridian "Balustrade 100" toughened safety glass, maximum height of glass above the top of the clamp for residential occupancies A and C3 of Table 3.3 AS/NZS 1170.1 and clamp spacings are:
- very high wind zone 1.76 kPa maximum height 1.1 meter
- Pradis clamps @ 800mm crs for steel, concrete and bolt through with timber
- Pradis clamps @ 600mm crs for timber with lagscrew
- the design of the concrete, steel or timber support for the balustrade is the responsibility of others.
- a handrail of 32mm 50mm diameter is required for stairs and ramps exceeding 1:20 slope. Refer NZBC D1/AS1.
- the guidance on narrier design published by the Department of Building and Housing states that if any part of the balustrade panel is 5 meters or higher than the ground or floor below, an interlinking handrail or laminated toughened glass with a top rail or capping to protect the edge should be provided. Fit handrail 900mm above floor level.

Description


- minimum width of glass panel is 1 meter unless connected by interlinking handrail or mechanical connector to adjacent panels
- maximum distance from side edge of glass to fixings - 200mm for both occupancies.
- this system is not suitable for balustrades in areas susceptible to overcrowding such as theatres, cinemas, assembly halls, stadiums etc.

Suitable for


• concrete, internal, wet exposed SG8 timber and dry concealed SG8 timber

Material finish

- satin
- anodised aluminium



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park


SA 5039 Australia




1300 4 ELITE | 03 9314 6105

PRADIS


PRADIS BALUSTRADE SYSTEM - RESIDENTIAL



FIXING DETAIL - CONCRETE




FIXING DETAIL - DRY CONCEALED SG8 TIMBER




FOR INTERNAL INSTALLATION ONLY


PRADIS




FOR INTERNAL INSTALLATION ONLY



FIXING DETAIL - WET EXPOSED SG8 TIMBER



FIXING DETAIL - SG8 TIMBER (BOLT THROUGH)





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105



PRADIS COMMERCIAL BALUSTRADE SYSTEM

Item number


PRADIS

Description


- this system complies with New Zealand Building Code Clauses B1 Structure, F2 Hazardous building materials and F4 Safety from falling third edition, subject to:
- all products meeting the required performance specification
- site installation carried out in accordance with intent of this drawing
- minimum balustrade height of 1.1 meters from finished floor level.
- based on 15mm Viridian toughened safety glass, maximum heights of glass above the top of the clamps for commercial occupancies B, E and C3 of table 3.3 AS/NZS 1170.1 and clamp spacings are:
- extra high wind zone 2.13 kPa maximum height 1.2 meters
- Pradis clamps @ 800mm crs for all occupancies.
- a handrail of 32-50mm diameter is required for stairs and ramps exceeding 1:20 slope. Refer NZBC D1/AS1.
- the Guidance on Barrier Design published by the Department of Building and Housing states that if any part of the balustrade panel is 5 meters or higher than the ground or floor below, an interlinking handrail or laminated toughened glass with a top rail or capping to protect the edge should be provided. Fit handrail 900mm above floor level.
- minimum width of glass panel is 1 meter unless connected by interlinking handrail or mechanical connector to adjacent panels
- maximum distance from side edge of glass to fixings - 200mm for both occupancies.
- this system is not suitable for balustrades in areas susceptible to overcrowding such as theatres, cinemas, assembly halls, stadiums etc.

PRADIS


PRADIS BALUSTRADE SYSTEM - COMMERCIAL



FIXING DETAIL - CONCRETE



FIXING DETAIL - SG8 TIMBER BOLT THROUGH





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




PRADIS

FOR INTERNAL INSTALLATION ONLY



FOR INTERNAL INSTALLATION ONLY



GLASS CUT OUT DETAIL





EUROANCHOR BALUSTRADE SYSTEM RESIDENTIAL INSTALLATION EXAMPLES

Examples using these item numbers

- EUBFSD.50 includes 25mm thick spacer
- EUBFSD.51 includes 10mm thick spacer
- EUBFSQ
- EUBFCS
- EUBFSQD

Description

- maximum distance from side edge of glass to fixings is 300mm for occupancy A and 200mm for occupancy C3 10 year warranty
- PS1 available for use with Viridian 'Balustrade 100' toughened safety glass

Suitable for

- residential occupancies A, B, C3 of Table 3.3 AS/NZS 1170.1 based on 12mm Viridian 'Balustrade 100' toughened safety glass, maximum heights of glass above top anchors for residential occupancies A and C3 of Table 3.3 AS/NZS 1170.1 are:
- very high wind zone 1.76 kPa -1.1 meters
- high wind zone 1.36 kPa 1.2 meters with corner connectors or interlinking handrail


Material finish

• 316 grade polished or satin stainless steel




EUBFSD


BALUSTRADE SYSTEM - RESIDENTIAL



FIXING DETAIL - CONCRETE



FIXING DETAIL - TIMBER SLATTED DECK BOLT THROUGH





HEAD OFFICE

114 Endeavour Way **Sunshine West** VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105




EUBFSD


FIXING DETAIL - TAPPED STEEL INTERNAL ONLY



FIXING DETAIL - STEEL




FIXING DETAIL - TIMBER LEG SCREW INTERNAL ONLY




EUBFSD


FIXING DETAIL - WEATHERED, ANGLE SPACER ENCLOSED DECK ONLY



FIXING DETAIL - TIMBER, CAVITY CLADDING ENCLOSED DECK



FIXING DETAIL - TIMBER LEG SCREW SLATTED DECK





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105



EUROANCHOR BALUSTRADE SYSTEM COMMERCIAL INSTALLATION EXAMPLES

Item number

- EUBFSD.50 includes 25mm thick spacer
- EUBFSD.51 includes 10mm thick spacer
- EUBFSQ
- EUBFCS
- EUBFSQD

Description

- 10 year warranty
- PS1 available for use with Viridian 'Balustrade 100' toughened safety glass

Suitable for

- commercial occupancies B, E, C3 of Table 3.3 AS/NZS 1170.1 based on 15mm Viridian 'Balustrade 100' toughened safety glass, maximum heights of glass above top anchors for commercial occupancies B, E, C3 of Table 3.3 AS/NZS 1170.1 are:
 - extra high wind zone 2.13 kPa
 1.2 meters


Material finish

• 316 grade polished or satin stainless steel




EUBFSD

BALUSTRADE SYSTEM - COMMERCIAL



FIXING DETAIL - CONCRETE





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia


ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia






EUBFSD

FIXING DETAIL - TIMBER SLATTED DECK BOLT-THROUGH




FIXING DETAIL - STEEL



BALUSTRADE ANCHOR HEAVY WEIGHT 50MM SQUARE EDGE HEAD

| Item number | MB50.S |
|-----------------|---|
| Description | balustrade anchor heavy weight 50mm square edge head 6mm standoff glass to cleat fixing |
| Suitable for | • 10mm, 12mm and 15mm toughened glass |
| Material finish | • 316 grade machined, polished or satin stainless steel |


MB50.S



BALUSTRADE ANCHOR HEAVY WEIGHT 50MM ROUND EDGE HEAD

| Item number | MB50.R |
|-----------------|--|
| Description | balustrade anchor heavy weight 50mm round edge head 6mm standoff glass to cleat fixing |
| Suitable for | • 10mm 12mm and 15mm toughened glass |
| Material finish | • 316 grade machined, polished or satin stainless steel |

MB50.R





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

BALUSTRADE ANCHOR HEAVY WEIGHT 50MM ROUND EDGE HEAD OPTIONAL FIXING


| Item number | MB50.R.T30 |
|-----------------|--|
| Description | Balustrade anchor heavy weight 50mm round edge head 6mm standoff glass to cleat fixing optional fixings ordered separately (threaded rod or stainless steel/ zinc plated lag screw) |
| Suitable for | • 10mm, 12mm and 15mm toughened glass |
| Material finish | • 316 grade machined, polished or satin stainless steel |

MB50.R.T30







FIXING DETAIL - DOMESTIC AND COMMERCIAL CONCRETE INSTALLATION WITH M10-R115 STAINLESS STEEL ROD FIXING



FIXING DETAIL - DOMESTIC AND COMMERCIAL STEEL INSTALLATION WITH M10-R50 ROD, WASHER AND NUT IN STAINLESS STEEL



FIXING DETAIL - COMMERCIAL TIMBER INSTALLATION WITH M10-R140 ROD, WASHER AND NUT IN STAINLESS STEEL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105






FIXING DETAIL - DOMESTIC ONLY INSTALLATION WITH M10-100SL STAINLESS STEEL LAG SCREW FIXING




TYPICAL BALUSTRADE PANEL LAYOUT AT 400MM CENTRES



H = Commercial = 100mm minimum H= Domestic = 75mm minimum

TYPICAL STAIR LAYOUT




BALUSTRADE ANCHOR HEAVY WEIGHT 75MM SINGLE DISC

| Item number | MB75.T.T30 |
|-----------------|---|
| Description | Balustrade anchor heavy weight 75mm single disc fitting suitable for single line fixings at 400mm maximum centres 30mm standoff optional fixings ordered separately (threaded rod - 60mm, 120mm or 150mm) |
| Suitable for | • 12mm and 15mm toughened glass |
| Material finish | • 316 grade polished or satin stainless steel |

MB75.T.T30






MB75.T.T30


SQUARE COVER KIT CONVERT MB75.T.T30

| Item number | MB75.SQ |
|-----------------|---|
| Description | • square cover kit to convert MB75.T.T30 to square fitting |
| Suitable for | • MB75.T.T30 |
| Material finish | • 316 grade polished or satin stainless steel |

MB75.SQ



MB75.SQ





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

BALUSTRADE ANCHOR HEAVY WEIGHT 100MM SINGLE DISC


| Item number | MB100.S.T30 |
|-----------------|---|
| Description | Balustrade anchor heavy weight 100mm single disc fitting suitable for single line compliant to NZS1170 for use in domestic and commercial installations maximum 400mm centres optional fixings ordered separately (threaded rod - 60mm, 120mm or 150mm) |
| Suitable for | • 12mm and 15mm toughened glass |
| Material finish | • 316 grade polished or satin stainless steel |

MB100.S. T30


FIXING DETAIL - CONCRETE




MB100.S. T30




FIXING DETAIL - STEEL



TYPICAL SETOUT FOR MB100.S.T30 AND MB75.T.T30 FITTINGS



FIXING DETAIL - TIMBER



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




1300 4 ELITE | 03 9314 6105







FIXING DETAIL - CONCRETE



FIXING DETAIL - STEEL



FIXING DETAIL - TIMBER



GLASS ANCHOR 38MM DIAMETER FLAT BUTTON HEAD

Item number • EGSBF1000.38.10 38mm diameter 10mm spacer • EGSBF1000.38.15 38mm diameter 15mm spacer • EGSBF1000.38.20 38mm diameter 20mm spacer • EGSBF1000.38.30 38mm diameter 30mm spacer • EGSBF1000.38.50 38mm diameter 50mm spacer Description • glass anchor 38mm flat button head • spacer length available in 10mm, 15mm, 20mm, 30mm or 50mm • M12 threaded rod standard 150mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request Suitable for • 10mm, 12mm, 15mm and 19mm glass thickness Material finish • 316 grade satin stainless steel

EGSBF1000 .38

Optional spacer body length
10mm, 15mm, 20mm, 30mm or 50mm

M12 threaded rod
150mm
flat button
diameter

21.6mm

EGSBF1000.38

GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE ○ 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


GLASS ANCHOR 50MM DIAMETER FLAT BUTTON HEAD

Item number • EGSBF1000.50.10 50mm diameter 10mm spacer • EGSBF1000.50.15 50mm diameter 15mm spacer • EGSBF1000.50.20 50mm diameter 20mm spacer • EGSBF1000.50.30 50mm diameter 30mm spacer • EGSBF1000.50.50 50mm diameter 50mm spacer Description • glass anchor 50mm flat button head • spacer length available in 10mm, 15mm, 20mm, 30mm or 50mm • M12 threaded rod standard 150mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request

EGSBF1000

Material finish

Suitable for




glass thickness

• 10mm, 12mm, 15mm and 19mm

• 316 grade satin stainless steel

GLASS CUT OUT DETAIL




GLASS ANCHOR 38MM DIAMETER **CONCAVE BUTTON HEAD**

Item number • EGSBF1100.38.10 38mm diameter 10mm spacer • EGSBF1100.38.15 38mm diameter 15mm spacer • EGSBF1100.38.20 38mm diameter 20mm spacer • EGSBF1100.38.30 38mm diameter 30mm spacer • EGSBF1100.38.50 38mm diameter 50mm spacer Description • glass anchor 38mm concave button head • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) other body sizes available on request Suitable for • 10mm, 12mm, 15mm and 19mm glass thickness Material finish • 316 grade satin stainless steel

EGSBF1100 Optional body length 10mm, 15mm, 20mm, 30mm or 50mm M12 thread 38mm button diameter Optional fixing 21.6mm EGSBF1100.38

GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

SA 5039 Australia





1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

GLASS ANCHOR 50MM DIAMETER CONCAVE BUTTON HEAD


| Item number | 50mm diameter • EGSBF1100.50.10 50mm diameter 10mm spacer • EGSBF1100.50.15 50mm diameter 15mm spacer • EGSBF1100.50.20 50mm diameter 20mm spacer • EGSBF1100.50.30 50mm diameter 30mm spacer • EGSBF1100.50.50 50mm diameter 50mm spacer |
|-----------------|--|
| Description | glass anchor 50mm concave button head spacer available in 10mm, 15mm, 20mm, 30mm or 50mm fixings available (threaded rod, wood fix lag screw, timber insert or masonry) other body sizes available on request |
| Suitable for | • 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel |

Optional body length 10mm, 15mm, 20mm, 30mm or 50mm M12 thread button diameter 21.6mm EGSBF1100.50

GLASS ANCHOR 38MM DIAMETER FLAT BUTTON HEAD

| Item number | 38mm diameter • EGSBF1150.38.10 38mm diameter 10mm spacer • EGSBF1150.38.15 38mm diameter 5mm spacer • EGSBF1150.38.20 38mm diameter 20mm spacer • EGSBF1150.38.30 38mm diameter 30mm spacer • EGSBF1150.38.50 38mm diameter 50mm spacer |
|-----------------|--|
| Description | glass anchor 38mm flat button head spacer available in 10mm, 15mm, 20mm, 30mm or 50mm fixings available (threaded rod, wood fix lag screw, timber insert or masonry) other body sizes available on request |
| Suitable for | • 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel |


EGSBF1150 .38



GLASS CUT OUT DETAIL



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



√ 1300 4 ELITE | 03 9314 6105✓ sales@eliteglasssolutions.com.au✓ www.eliteglasssolutions.com.au


GLASS ANCHOR 50MM DIAMETER FLAT BUTTON HEAD

Item number • EGSBF1150.50.10 50mm diameter 10mm spacer • EGSBF1150.50.15 50mm diameter 15mm spacer • EGSBF1150.50.20 50mm diameter 20mm spacer • EGSBF1150.50.30 50mm diameter 30mm spacer • EGSBF1150.50.50 50mm diameter 50mm spacer • glass anchor 50mm flat button head Description • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) Suitable for • 10mm, 12mm, 15mm and 19mm glass thickness Material finish • 316 grade satin stainless steel

HANDRAIL FIXING GLASS OPTION FLAT BUTTON HEAD


| Item number | • EGSBF1200.38 38mm diameter • EGSBF1200.50 50mm diameter |
|-----------------|--|
| Description | handrail fixing glass option flat button head diameter available in 38mm or 50mm saddle - flat or curved (loose or welded) |
| Suitable for | mounting handrails to glass panels 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel finish |

EGSBF1200




EGSBF1200


EGSBF1150 .50



GLASS CUT OUT DETAIL



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au


HANDRAIL FIXING GLASS OPTION FLAT BUTTON HEAD

| Item number | • EGSBF1250.38 38mm diameter • EGSBF1250.50 50mm diameter |
|-----------------|--|
| Description | handrail fixing glass option flat button head diameter available in 38mm or 50mm saddles for easy mounting to handrails included three saddles supplied with every fitting saddles to suit 38mm diameter and 50mm diameter round tube one flat saddle to this flat tube |
| Suitable for | mounting handrails to glass panels 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel finish |

EGSBF1250



Kit includes three saddles



Suits 38mm diameter handrail


n Suits 50.8mm andrail diameter handrail

Flat handrail

HANDRAIL FIXING GLASS OPTION CONCAVE BUTTON HEAD


| Item number | • EGSBF1300.38 38mm diameter • EGSBF1300.50 50mm diameter |
|-----------------|---|
| Description | handrail fixing glass option concave button head diameter available in 38mm or 50mm saddle - flat or curved (loose or welded) |
| Suitable for | mounting handrails10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel finish |

EGSBF1300




EGSBF1300

GLASS CUT OUT DETAIL



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE ○ 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


POST ATTACHMENT GLASS PANEL FLAT BUTTON HEAD

| Item number | • EGSBF1400.38 38mm diameter • EGSBF1400.50 50mm diameter |
|-----------------|---|
| Description | post attachment glass panel flat button head diameter available in 38mm or 50mm saddle - flat or curved (loose or welded) |
| Suitable for | welding to a vertical post to attach glass panels 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel finish |

EGSBF1400




GLASS CUT OUT DETAIL




POST ATTACHMENT GLASS PANEL **CONCAVE BUTTON HEAD**

| Item number | • EGSBF1500.38 38mm diameter • EGSBF1500.50 50mm diameter |
|-----------------|--|
| Description | post attachment glass panel concave button head diameter available in 38mm or 50mm saddle - flat or curved (loose or welded) |
| Suitable for | welding to a vertical post to attach glass panels 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel finish |



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia




HANDRAIL BRACKET ROUND

| Item number | EUHB.50 |
|-----------------|---|
| Description | handrail bracket roundsupplied 150mm high for on-site trimming |
| Suitable for | mounting handrails10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |


| EUHB.50 | 012 ↔ |
|--------------|-----------------------|
| 50mm | 5mm 150mm |
| diameter 6mm | EUHB.50 |

GLASS CUT OUT DETAIL




HANDRAIL BRACKET SQUARE

| Item number | EUHB.50.SQ |
|-----------------|--|
| Description | handrail bracket squaresupplied 150mm high for on-site trimming |
| Suitable for | mounting handrails10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





114 Endeavour Way Sunshine West VIC 3020 Australia


ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




HANDRAIL BRACKET ROUND SUITABLE FOR TIMBER FIX

| Item number | EUHBTF50 |
|-----------------|---|
| Description | handrail bracket roundsupplied 150mm high for on-site trimming |
| Suitable for | • timber fix |
| Material finish | • 316 grade polished or satin stainless steel |




GLASS CUT OUT DETAIL




HANDRAIL SQUARE SUITABLE FOR TIMBER FIX

| Item number | EUHBTF50.SQ |
|-----------------|--|
| Description | handrail bracket squaresupplied 150mm high for on-site trimming |
| Suitable for | • timber fix |
| Material finish | • 316 grade polished or satin stainless steel |



GLASS CUT OUT DETAIL





114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park


SA 5039 Australia




POST ATTACHMENT GLASS PANEL FLAT BUTTON HEAD - LONG FIXING LEG

| Item number | EGSBF1600 |
|-----------------|--|
| Description | post attachment glass panel flat button head - long fixing leg fixing leg can be cut to size as required available in long leg (150mm length) or short leg (80mm length) |
| Suitable for | any application, including staircases |
| Material finish | • 316 grade satin stainless steel |


EGSBF1600




LONG LEG - BACK




LONG LEG



SHORT LEG



GLASS CUT OUT DETAIL




POST ATTACHMENT GLASS PANEL CONCAVE BUTTON HEAD - LONG FIXING LEG

| Item number | EGSBF1700 |
|-----------------|---|
| Description | post attachment glass panel concave button head - long fixing leg fixing leg can be cut to size as required available in long leg (150mm length) or short leg (80mm length) spacer available in 10mm or 15mm |
| Suitable for | any application, including staircases |
| Material finish | • 316 grade satin stainless steel |

EGSBF1700




LONG LEG - BACK




LONG LEG



SHORT LEG



GLASS CUT OUT DETAIL





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au



SPACER 38MM DIAMETER

| Item number | 38mm diameter • EGSBF600.38.10 38mm diameter 10mm length • EGSBF600.38.15 38mm diameter 15mm length • EGSBF600.38.20 38mm diameter 20mm length • EGSBF600.38.30 38mm diameter 30mm length • EGSBF600.38.50 38mm diameter 50mm length |
|-----------------|---|
| Description | spacer 38mm diameter length available in 10mm, 15mm, 20mm, 30mm or 50mm custom sizes are available on order |
| Suitable for | • 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia



1300 4 ELITE | 03 9314 6105



SPACER 38MM DIAMETER 20MM LENGTH

| Item number | SP3820 |
|-----------------|--|
| Description | spacer 38mm diameter20mm length8.5mm diameter through hole |
| Material finish | satin silver anodisedpolished or satin stainless steel |




SPACER 50MM DIAMETER 25MM LENGTH

| Item number | SP5025 10.5mm diameter through hole SP5025.T threaded M10 hole |
|-----------------|---|
| Description | • spacer 50mm diameter • 25mm length |
| Material finish | satin silver anodisedpolished or satin stainless steel |



SPACER 50MM DIAMETER

| Item number | 50mm diameter • EGSBF600.50.10 50mm diameter 10mm length • EGSBF600.50.15 50mm diameter 15mm length • EGSBF600.50.20 50mm diameter 20mm length • EGSBF600.50.30 50mm diameter 30mm length • EGSBF600.50.50 50mm diameter 50mm length |
|-----------------|--|
| Description | spacer 50mm diameter length available in 10mm, 15mm, 20mm, 30mm or 50mm other sizes available on request (lead time applies) |
| Suitable for | • 10mm, 12mm, 15mm and 19mm glass thickness |
| Material finish | • 316 grade satin stainless steel |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au

www.eliteglasssolutions.com.au

SPACER COUNTERSUNK FIXING DISC


| Item number | SPC5010 |
|-----------------|--|
| Description | spacer or countersunk fixing disc50mm diameter10mm lengthdrilled and counter sunk |
| Suitable for | • M10 counter sunk hex bolt |
| Material finish | • polished or satin stainless steel |

SPC5010



TAPERED NUT

| Item number | • EGSBF610.38 38mm diameter • EGSBF610.50 50mm diameter |
|-----------------|--|
| Description | tapered nutdiameter available in 38mm or 50mm |
| Material finish | • 316 grade satin stainless steel |



EGSBF610


GIB SPACER

| Item number | SPG32.10 32mm diameter 10mm length SPG32.12 32mm diameter 12mm length |
|-----------------|--|
| Description | gib spacerlength available in 10mm and 12mm |
| Material finish | • plastic • aluminium |


FLANGE TAPERED RANGE

| Item number | • EGSBF620.38 38mm diameter • EGSBF620.50 50mm diameter |
|-----------------|---|
| Description | flange tapered rangediameter available in 38mm or 50mm |
| Material finish | • 316 grade satin stainless steel |

SPG32









HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

STEPPED DISC 50MM DIAMETER

| Item number | SD50M10 |
|-----------------|---|
| Description | stepped disc 50mm diameterM10 threaded blind hole |
| Material finish | satin silver anodisedpolished or satin stainless steel |


SD50M10



STEPPED DISC 38MM DIAMETER

| Item number | SD38M8 |
|-----------------|---|
| Description | stepped disc 38mm diameterM8 threaded blind hole |
| Material finish | satin silver anodisedpolished or satin stainless steel |


SD38M8



COVERED FLANGE PLATE

| Item number | • EGSBF630.38 38mm diameter • EGSBF630.50 50mm diameter |
|-----------------|---|
| Description | covered flange platediameter available in 38mm or 50mm |
| Material finish | • 316 grade satin stainless steel |


EGSBF630



NUT

| Item number | • EGSBF640.38 38mm diameter • EGSBF640.50 50mm diameter |
|-----------------|--|
| Description | nutdiameter available in 38mm or 50mm |
| Material finish | • 316 grade satin stainless steel |

EGSBF640





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au


COVER RANGE

| Item number | • EGSBF650.38 38mm diameter • EGSBF650.50 50mm diameter |
|-----------------|--|
| Description | cover rangediameter available in 38mm or 50mm |
| Material finish | • 316 grade satin stainless steel |

SHORT PLATE WITH THREADED ROD


| Item number | EGSBF670 |
|-----------------|---|
| Description | short plate with threaded rod50mm diameter80mm length |
| Suitable for | • EGSBF1600 • EGSBF1700 |
| Material finish | • 316 grade satin stainless steel |





LONG PLATE WITH THREADED ROD

| Item number | EGSBF660 |
|-----------------|-----------------------------------|
| Description | • long plate with threaded rod |
| Suitable for | • EGSBF1600 • EGSBF1700 |
| Material finish | • 316 grade satin stainless steel |



WALL BRACKET 75MM OFFSET

| Item number | EGSBF700 |
|-----------------|-----------------------------------|
| Description | • wall bracket 75mm offset |
| Material finish | • 316 grade satin stainless steel |

EGSBF700 EGSBF700 12mm 66mm



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia




WALL BRACKET 80MM OFFSET

| Item number | EGSBF710 |
|-----------------|-----------------------------------|
| Description | • wall bracket 80mm offset |
| Material finish | • 316 grade satin stainless steel |

EGSBF710 EGSBF710 EGSBF710 12mm

MASONRY WALL BRACKET


| Item number | EGSBF730 |
|-----------------|-----------------------------------|
| Description | • masonry wall bracket |
| Material finish | • 316 grade satin stainless steel |



POST BRACKET M12 OFFSET

| Item number | EGSBF720 |
|-----------------|-----------------------------------|
| Description | • post bracket M12 offset |
| Material finish | • 316 grade satin stainless steel |

EGSBF720



ROD THREAD STRAIGHT

| Item number | EGSBF740 |
|-----------------|--|
| Description | rod thread straight210mm length |
| Material finish | • 316 grade satin stainless steel |

EGSBF740





114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street


7 Manfull Street Melrose Park SA 5039 Australia



ROD THREAD 150MM

| Item number | EGSBF750 |
|-----------------|---|
| Description | rod thread150mm length |
| Material finish | • 304 grade satin stainless steel |


EGSBF750



WASHER COLLARED BLACK NYLON

| Item number | EGSBF830 |
|-----------------|---------------------------|
| Description | • washer collared • 1.6mm |
| Suitable for | • M12 threaded rod |
| Material finish | • black nylon |

EGSBF830




EGSBF830

LAG SCREW


| Item number | • EGSBF750.LS.M6 6mm diameter 90mm length • EGSBF750.LS.M10 10mm diameter 135mm length • EGSBF750.LS.M12.135 12mm diameter 135mm length • EGSBF750.LS.M12.165 12mm diameter 165mm length |
|-----------------|--|
| Description | • lag screw |
| Material finish | • 304 grade satin stainless steel |
| | |

EGSBF750.LS



WASHER BLACK NYLON

| Item number | • EGSBF800.06 0.6mm thickness • EGSBF800.10 1.0mm thickness • EGSBF800.16 1.6mm thickness • EGSBF820 1.6mm thickness* |
|-----------------|--|
| Description | • washer |
| Suitable for | • M12 threaded rod • EGSBF650 (*EGSBF820 only) |
| Material finish | • black nylon |



EGSBF800



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE | 03 9314 6105

PROTECTIVE SLEEVE CLEAR

| Item number | EGSBF810 |
|--------------|---------------------------------------|
| Description | • protective sleeve clear |
| Suitable for | • EGSBF750 head • M12 threaded rod |

EGSBF810




114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street


Melrose Park SA 5039 Australia





FRAMELESS GLASS TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.TOPRAIL.SQ |
|-----------------|--|
| Description | frameless glass top rail square ultra slim weld free installation precision manufactured in 5.8 meter lengths supplied complete with high strength u shaped rubber extrusion that provides a tight fit between the glass and top rail, standard is 12mm with an optional rubber to suit 10mm glass complies with Australian and NZ standards AS/NZS 1170.1.2002 compact shape ensures minimum disruption to the view all joints are weld free - assemble using Soudal T Rex Crystal or equal |
| Suitable for | • 10mm and 12mm glass thickness • indoor and outdoor applications |
| Material finish | • 2205 duplex satin or polished stainless |





114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia





1300 4 ELITE | 03 9314 6105

WALL BRACKET

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM


| Item number | EH.WB.SQ |
|-----------------|--|
| Description | • wall bracket |
| Suitable for | top rail square ultra slim EH.TOPRAIL.SQ fastening lug suits 6 or 12 o'clock installation |
| Material finish | • 2205 duplex satin or polished stainless |



STRAIGHT 180° JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.180.SQ.JOINER |
|-----------------|--|
| Description | • straight joiner |
| Suitable for | top rail square ultra slim EH.TOPRAIL.SQ slides into the top rail for a neat join |
| Material finish | • 2205 duplex satin or polished stainless |




END CAP

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.ENDCAP.SQ |
|-----------------|--|
| Description | • end cap |
| Suitable for | top rail square ultra slim EH.TOPRAIL.SQ fastening lug can be rotated to suit each installation |
| Material finish | • 2205 duplex satin or polished stainless |

EH.ENDCAP .SQ




FIXED 90° CORNER JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.90.SQ.JOINER |
|-----------------|--|
| Description | fixed 90° corner joiner slides into the top rail and ensures an accurate corner joint |
| Suitable for | • top rail square ultra slim EH.TOPRAIL.SQ |
| Material finish | • 2205 duplex satin or polished stainless |





EH.90.SQ.JOINER



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




HORIZONTAL VARIABLE JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.HOR.VAR.SQ.JOINER |
|-----------------|---|
| Description | horizontal variable joiner |
| Suitable for | • top rail square ultra slim EH.TOPRAIL.SQ |
| Material finish | • 2205 duplex satin or polished stainless |






EH.HOR.VAR.SQ.JOINER

ADJUSTABLE JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.ADJ.JOINER |
|-----------------|---|
| Description | • adjustable joiner |
| Suitable for | • top rail square ultra slim EH.TOPRAIL.SQ |
| Material finish | • 2205 duplex satin or polished stainless |




HINGE VERTICAL JOINER

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.VER.SQ.JOINER |
|-----------------|---|
| Description | hinge vertical joiner multi adjustable component for negotiating hand rail bends up and down stair wells. No more cutting and welding, just slide inside TBHR400 rail and glue with silicone |
| Suitable for | • top rail square ultra slim EH.TOPRAIL.SQ |
| Material finish | • 2205 duplex satin or polished stainless |






EH.VER.SQ.JOINER

INLINE JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

| Item number | EH.INLINE.JOINER |
|-----------------|---|
| Description | • inline joiner |
| Suitable for | • top rail square ultra slim EH.TOPRAIL.SQ |
| Material finish | • 2205 duplex satin or polished stainless |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105

SLEEVE JOINER

SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM


| Item number | EH.SLEEVE.JOINER |
|-----------------|--|
| Description | • sleeve joiner |
| Suitable for | top rail square ultra slim EH.TOPRAIL.SQ connects wall bracket to adjustable joiner |
| Material finish | • 2205 duplex satin or polished stainless |





FRAMELESS GLASS TOP RAIL **ROUND ULTRA SLIM**

| Item number | EH.TOPRAIL.RD |
|-----------------|--|
| Description | frameless glass top rail round ultra slim 25mm round diameter precision manufactured in 5.8 meter lengths supplied complete with high strength u shaped rubber extrusion that provides a tight fit between the glass and top rail, standard is 12mm with an optional rubber to suit 10mm glass complies with Australian and NZ standards AS/NZS 1170.1.2002 compact shape ensures minimum disruption to the view all joints are weld free - assemble using Soudal T Rex Crystal or equal |
| Suitable for | 10mm and 12mm glass thicknessindoor and outdoor applications |
| Material finish | • 2205 duplex satin or polished stainless |



WALL BRACKET

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.WB.RD |
|-----------------|---|
| Description | • wall bracket |
| Suitable for | top rail round ultra slim EH.TOPRAIL.RD fastening lug can be rotated to suit each installation |
| Material finish | • 2205 duplex satin or polished stainless |

EH.WB.RD




END CAP

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.ENDCAP.RD |
|-----------------|--|
| Description | • end cap |
| Suitable for | • top rail round ultra slim EH.TOPRAIL.RD |
| Material finish | • 2205 duplex satin or polished stainless |

EH.ENDCAP .RD





114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia






STRAIGHT 180° JOINER

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.180.RD.JOINER |
|-----------------|--|
| Description | straight joiner slides into the top rail for a neat join |
| Suitable for | • top rail round ultra slim EH.TOPRAIL.RD |
| Material finish | • 2205 duplex satin or polished stainless |




HORIZONTAL VARIABLE JOINER

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.HOR.VAR.RD.JOINER |
|-----------------|--|
| Description | horizontal variable joiner |
| Suitable for | • top rail round ultra slim EH.TOPRAIL.RD |
| Material finish | • 2205 duplex satin or polished stainless |






EH.HOR.VAR.RD.JOINER

FIXED 90° CORNER JOINER

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.90.RD.JOINER |
|-----------------|--|
| Description | fixed 90° corner joiner slides into the top rail and ensures an accurate corner joint |
| Suitable for | • top rail round ultra slim EH.TOPRAIL.RD |
| Material finish | • 2205 duplex satin or polished stainless |






HINGE VERTICAL JOINER

SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

| Item number | EH.VER.RD.JOINER |
|-----------------|---|
| Description | hinge vertical joiner multi adjustable component for negotiating hand rail bends up and down stair wells. No more cutting and welding, just slide inside TBHR400 rail and glue with silicone |
| Suitable for | • top rail round ultra slim EH.TOPRAIL.RD |
| Material finish | • 2205 duplex satin or polished stainless |





EH.VER.RD.JOINER



HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE


7 Manfull Street Melrose Park SA 5039 Australia



1300 4 ELITE ○ 03 9314 6105≤ sales@eliteglasssolutions.com.auwww.eliteglasssolutions.com.au

HANDRAIL SLIMLINE WITH END CAP

| • BH1 • BH2 - end cap |
|--|
| handrail slimline with end cap meets AS1288-2006 for hand railing for glass balustrades that are over 1 meter in height and only fixed to the base complies with NZS4203:1992 for handrails designed for easy fitting, clips directly over the glass: no welding required and can be installed after glass is fitted optional stainless steel cover and fixtures manufactured in marine grade 316 (lead time applies) |
| • 10mm and 12mm glass thickness • interior and exterior applications |
| mill or silver pearlspecial finishes available on request (lead time applies) |
| |




HANDRAIL FLAT TUBE

| Item number | SOLO |
|-----------------|---|
| Description | handrail flat tube 50mm width x 10mm height available in 2.5 meter and 5 meter lengths available uncapped or with 1 or 2 fully welded end caps |
| Material finish | • 2205 duplex satin or polished stainless |



WALL BRACKET SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | • SOLO.WB |
|-----------------|---|
| Description | • wall bracket |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 2205 duplex satin or polished stainless |







HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park

SA 5039 Australia






END CAP

SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | • SOLO.ENDCAP |
|-----------------|---|
| Description | • end cap |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 2205 duplex satin or polished stainless |

SOLO. ENDCAP




SOLO.ENDCAP

FIXED 90° CORNER JOINER

SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | SOLO.90°.JOINER |
|-----------------|---|
| Description | • fixed 90° corner joiner |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 2205 duplex satin or polished stainless |




SOLO.90°.JOINER

STRAIGHT 180° JOINER

SUITABLE FOR HANDRAIL FLAT TUBE


| Item number | • SOLO.180°.JOINER |
|-----------------|---|
| Description | • straight 180° joiner |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 2205 duplex satin or polished stainless |



HORIZONTAL VARIABLE JOINER

SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | • SOLO.VAR.JOINER |
|-----------------|---|
| Description | HORIZONTAL VARIABLE JOINER |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 2205 duplex satin or polished stainless |





HEAD OFFICE

114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street

7 Manfull Street Melrose Park SA 5039 Australia




1300 4 ELITE | 03 9314 6105 sales@eliteglasssolutions.com.au www.eliteglasssolutions.com.au

CLAMP WALL TO FLAT HANDRAIL SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | • HRB.HB.25 25mm diameter • HRB.HB.38 38mm diameter |
|-----------------|---|
| Description | wall to flat handrail clamp diameter available in 25mm or 38mm 50mm slotted body CNC machined body allows for various fixing options |
| Suitable for | • handrail flat tube SOLO |
| Material finish | • 316 grade polished or satin stainless steel |

HRB.HB






CLAMP GLASS TO FLAT HANDRAIL SUITABLE FOR HANDRAIL FLAT TUBE

| Item number | HRB.25 25mm diameterHRB.38 38mm diameter |
|-----------------|---|
| Description | glass to flat handrail clamp diameter available in 25mm or 38mm 50mm slotted body |
| Suitable for | 8mm, 10mm and 12mm glass thickness (can be supplied with longer studs to suit other glass thicknesses) handrail flat tube SOLO |
| Material finish | • 316 grade polished or satin stainless steel |

HRB



HRB





114 Endeavour Way Sunshine West VIC 3020 Australia

ADELAIDE OFFICE 7 Manfull Street Melrose Park SA 5039 Australia

