ELITE
GLASS
SOLUTIONS

ELITE GLASS
SOLUTIONS

ELITE GLASS CATALOGUE CONTENTS

ELITE GLASS
SOLUTIONS

SHOWER HARDWARE

ELITE GLASS SOLUTIONS

CONTENTS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CONTENTS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

INSTALLATION

ELITE GLASS provides a comprehensive range of accessories produced to give architects and decorators complete freedom of design when using toughened glass in showers.

European designed, and manufactured to the highest standard the ELITE GLASS range of fittings provide a slim and neat appearance so that the glass remains the central feature.

All hinges and handles are a combination of brass and stainless steel. Available in the following finishes:

• polished stainless steel,
• polished chrome,
• satin chrome,
• satin stainless steel and
• special finishes upon request, lead times apply.

INLINE SHOWERS

QUADRANT SHOWERS

SLIDING SHOWERS   CURVED SHOWER

BATH-END SHOWER   BI-FOLD BATH SCREEN

GLASS

All glass used in frameless glass shower assemblies must be approved 8mm or 10mm toughened float safety glass.

GLASS THICKNESS

10mm glass thickness is recommended in most assemblies, especially in glass to glass situations. 8mm glass thickness can be used when panels /doors are relatively narrow or especially when wall fixing (for door hanging) is suspect.

DOORS

All doors are standard double action opening both inwards and outwards. A single action stop may be provided if required.

Standard door widths are generally between 600mm to 700mm for wall hung doors and 550mm to 650mm for glass to glass doors.

Maximum recommended width / weight for two hinge doors:

• 8mm: 900mm width 35kg (1.75m^2)
• 10mm: 800mm width 35kg (1.40m^2) glass-to-glass
• 10mm: 800mm width 37.5kg (1.50m^2) wall hung

For doors outside either of the above maximums three hinges should be fitted. Standard door heights are generally between 1.85 meters and 2.1 meters.

WALL FIXING

For doors hinged directly from the wall adequate stud fixing is required – generally either a double stud or an approximate 90mm width of timber fitted between nogs at hinge levels.

Where inadequate wall fixing is suspected, it is recommended that the door be hung from a glass side panel.

SPECIAL BRACING REQUIREMENTS

Head support is recommended (in the form of either a top channel or a glass over panel) for glass to glass assemblies as follows:

• where the combined width of the door and side,
• panel/s it is hung from exceed 900mm and
• on all quadrant and curved showers.

Where a side panel (fixed only to the base and wall) exceeds 900mm in width a return panel of a minimum 150mm width would be required to stabilise the side panel.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SHOWER HARDWARE

SHOWER HINGES 10MM GLASS THICKNESS

SHOWER HINGES
10MM GLASS
THICKNESS

SHOWER HINGE WALL MOUNT

Item number	• ES1 - square edge • BES1 - beveled edge
Description	• shower hinge wall mount • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25° • maximum door weight 35kg • stud fixing recommended for all wall mount applications
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• fixing screws are not included, specify if required

ES1/BES1

51mm
90 mm
55mm
ES1

51mm
90 mm
55mm
BES1

GLASS CUT OUT DETAIL

Door
R10
64mm
44mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

SHOWER HINGE WALL MOUNT
WITH OFFSET THREE HOLE FIXING PLATE

Item number	• ES1L3 - square edge • BES1L3 - bevelled edge
Description	• shower hinge wall mount with offset three hole fixing plate • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • stud fixing recommended for all wall mount applications
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• fixing screws are not included, specify if required

SHOWER HINGE WALL MOUNT
WITH OFFSET EXTENDED FIXING PLATE

Item number	• ES1LCBP - square edge • BES1LCBP - bevelled edge
Description	• shower hinge wall mount with offset extended fixing plate • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • stud fixing recommended for all wall mount applications
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• fixing screws are not included, specify if required

ES1L3/ BES1L3

38mm 90mm 55mm

ES1L3   BES1L3

ES1LCBP/ BES1LCBP

68mm 90mm 55mm

ES1LCBP   BES1LCBP

GLASS CUT OUT DETAIL

Door

R10 64mm 44mm

INSITU APPLICATION

GLASS CUT OUT DETAIL

Door

R10 64mm 44mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

SHOWER HARDWARE

SHOWER HINGES 10MM GLASS THICKNESS

SHOWER HINGE WALL MOUNT WITH SHORT FIXING PLATE

Item number	• ES1.SB - square edge • BES1.SB - bevelled edge
Description	• shower hinge wall mount with short fixing plate • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness) • stud fixing recommended for all glass to wall applications
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies

ES1.SB/ BES1.SB

ES1.SB   BES1.SB

GLASS CUT OUT DETAIL   INSITU APPLICATION

SHOWER HINGE WALL MOUNT 135° CORNER WITH 90° FIXING PLATE

Item number	• ES1.90 - square edge • BES1.90 - bevelled edge
Description	• shower hinge wall mount 135° corner with 90° fixing plate • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness) • stud fixing recommended for all glass to wall applications
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies

ES1.90/ BES1.90

ES1.90   BES1.90

GLASS CUT OUT DETAIL   INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HINGE GLASS TO GLASS

Item number	• ES2 - square edge • BES2 - bevelled edge
Description	• shower hinge glass to glass • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness)
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

SHOWER HINGE 135° GLASS TO GLASS

Item number	• ES2.135 - square edge • BES2.135 - bevelled edge
Description	• shower hinge 135° glass to glass • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness) • custom angles available from minimum 125°
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

ES2/BES2

90 mm
55mm
55mm
90 mm
55mm
55mm

ES2

BES2

ES2.135/ BES2.135

90 mm
55mm
55mm
90 mm
55mm
55mm

ES2.135

BES2.135

GLASS CUT OUT DETAIL

Side panel
Door
R10
64 mm
R10
44mm
44mm

INSITU APPLICATION

GLASS CUT OUT DETAIL

Side panel
Door
R10
64 mm
R10
42mm
44mm

45˚ polished mitre to side panel

INSITU APPLICATION

135˚

SHOWER HARDWARE

SHOWER HINGES 10MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HARDWARE

SHOWER HINGES 10MM GLASS THICKNESS

SHOWER HINGE 90° GLASS TO GLASS

Item number	• ES2.90 - square edge • BES2.90 - bevelled edge
Description	• shower hinge 90° glass to glass • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25° • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness)
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

ES2.90/ BES2.90

ES2.90

BES2.90

90 mm
55mm
55mm
90 mm
55mm
55mm

GLASS CUT OUT DETAIL

Side panel   Door

64 mm
R10   R10
94mm
44mm   44mm
52mm

INSITU APPLICATION

SHOWER HINGE BIFOLD GLASS TO GLASS

| Item number	• ES2.BF - square edge • BES2.BF - bevelled edge
Description	• shower hinge bifold glass to glass • manufactured in brass • 180° single action hinge, opening inwards or outwards • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness)
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

ES2.BF/ BES2.BF

ES2.BF

BES2.BF

90 mm
55mm
55mm
90 mm
55mm
55mm

GLASS CUT OUT DETAIL

Door and side panel

56 mm
29mm
Ø16

INSITU APPLICATION

ELITE GLASS SOLUTIONS

SHOWER HINGE 90° L SHAPE GLASS TO GLASS

| Item number	• ES1.LB2B - square edge • BES1.LB2B - bevelled edge
Description	• shower hinge 90° L shape glass to glass • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 35kg • maximum door width 800mm (for 10mm glass thickness)
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

ES1.LB2B

38mm
90mm
55mm
ES1.LB2B

SHOWER LIFT OFF HINGE WALL TO GLASS

Item number	• LH101.90L - left opening • LH101.90R - right opening
Description	• shower lift off hinge wall to glass • maximum door weight 45kg • brass body • cover caps to conceal fixings (chrome plated only) • protective clear wrap on hinge plates
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

**LH101.90L
LH101.90R**


90mm
45mm
LH101.90L
LH101.90R

GLASS PREPARATION

40mm
60mm

GLASS CUT OUT DETAIL   INSITU APPLICATION

Return
70mm
27mm
Ø12

Ø12
50mm
31mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SHOWER HINGES 6MM GLASS THICKNESS

SHOWER HINGES
6MM GLASS
THICKNESS

SHOWER HINGE WALL MOUNT
SUITABLE FOR 6MM GLASS THICKNESS

Item number	CMES1
Description	• shower hinge wall mount suitable for 6mm glass thickness • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25° • maximum door weight 25kg • maximum door width 700mm • stud fixing recommended for all glass to wall applications
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

CMES1

51mm
70 mm
45mm

CMES1

GLASS CUT OUT DETAIL

Door
R6
52mm
38mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HINGE WALL MOUNT SINGLE SIDE SUITABLE FOR 6MM GLASS THICKNESS

Item number	CMES1.L
Description	• shower hinge wall mount single side suitable for 6mm glass thickness • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 28kg • maximum door width 710mm • stud fixing recommended for all glass to wall applications
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

CMES1.L

CMES1.L

SHOWER HINGE GLASS TO ROUND POST SUITABLE FOR 6MM GLASS THICKNESS

| Item number	CMES1.RP
Description	• shower hinge glass to round post suitable for 6mm glass thickness • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • designed for 40mm diameter post mount
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

CMES1.RP

CMES1.RP

GLASS CUT OUT DETAIL   INSITU APPLICATION

### GLASS CUT OUT DETAIL   INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HINGE 180° GLASS TO GLASS
SUITABLE FOR 6MM GLASS THICKNESS

Item number	CMES2
Description	• shower hinge 180˚ glass to glass suitable for 6mm glass thickness • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 25kg • maximum door width 700mm
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

CMES2


CMES2

GLASS CUT OUT DETAIL   INSITU APPLICATION

Side panel   Door

52 mm

R6   R6

38mm   38mm

SHOWER HINGE 135° GLASS TO GLASS
SUITABLE FOR 6MM GLASS THICKNESS

Item number	CMES2.135
Description	• shower hinge 135˚ glass to glass suitable for 6mm glass thickness • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 25˚ • maximum door weight 25kg • maximum door width 700mm
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

**CMES2.135**

CMES2.135

GLASS CUT OUT DETAIL   INSITU APPLICATION

Side panel   Door

52 mm

R6   R6

36mm   38mm

45˚ polished mitre
to side panel

135˚

SHOWER HINGE BIFOLD GLASS TO GLASS SUITABLE FOR 6MM GLASS THICKNESS

Item number	CMES2.BF
Description	• shower hinge bifold glass to glass suitable for 6mm glass thickness • manufactured in brass • hinge folds back 180˚ • maximum door weight 20kg • maximum door width 550mm
Suitable for	• 6mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

CMES2.BF

CMES2.BF

RIVIERA BOAT LATCH

Item number	• FF9306 - boat latch suitable for 6mm glass thickness FF9310 - boat latch suitable for 10mm glass thickness • FF930.K - glass keeper
Description	• Riviera boat latch • manufactured in brass • sliding bolt spring action non-locking
Suitable for	• 6mm glass thickness (FF9306) • 10mm glass thickness (FF9310) • to be used in conjunction with CMES hinge range
Material finish	• polished or satin chrome • special finishes on request, lead time applies

FF9306/ FF9310

FF9306

GLASS CUT OUT DETAIL

Door and side panel

45 mm

23.5 mm

Ø15

INSITU APPLICATION

GLASS CUT OUT DETAIL

Door and keeper glass cutout detail

55mm R10

40 mm

INSITU APPLICATION

SHOWER HARDWARE

SHOWER HINGES 6MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

SHOWER HINGES 10/12MM GLASS THICKNESS

SHOWER HINGES
10/12MM GLASS
THICKNESS

SHOWER HINGE WALL MOUNT SUITABLE FOR 10MM AND 12MM GLASS THICKNESS

Item number	HD.ES1
Description	• shower hinge wall mount heavy duty • manufactured in brass • dual action hinge, opening inwards and outwards • self closing from approximately 15˚ • using two hinges – maximum door weight 50kg – maximum door width 900mm • using three hinges – maximum door weight 60kg – maximum door width 900mm
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HD.ES1

57mm
100 mm
100 mm
58mm

HD.ES1

GLASS CUT OUT DETAIL

Door
R8
76mm
46mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HINGE WALL MOUNT SINGLE SIDE
SUITABLE FOR 10MM AND 12MM
GLASS THICKNESS

| Item number	HD.ES1L3

Description	• shower hinge wall mount single side heavy duty
	• manufactured in brass
	• dual action hinge, opening inwards and outwards
	• self closing from approximately 15°
	• using two hinges
	  – maximum door weight 50kg
	  – maximum door width 900mm
	• using three hinges
	  – maximum door weight 60kg
	  – maximum door width 900mm

Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HD.ES1L3

HD.ES1L3

GLASS CUT OUT DETAIL

INSITU APPLICATION

Door R8 76mm 46mm

SHOWER HINGE 180° GLASS TO GLASS
SUITABLE FOR 10MM AND 12MM
GLASS THICKNESS

Item number	HD.ES2

Description	• shower hinge 180° glass to glass heavy duty
	• manufactured in brass
	• dual action hinge, opening inwards and outwards
	• self closing from approximately 15°
	• using two hinges
	  – maximum door weight 50kg
	  – maximum door width 900mm
	• using three hinges
	  – maximum door weight 60kg
	  – maximum door width 900mm

Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HD.ES2

HD.ES2

GLASS CUT OUT DETAIL

INSITU APPLICATION

Door R8 76mm 46mm

SHOWER HARDWARE

SHOWER HINGES 10/12MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

SHOWER HINGES 10/12MM GLASS THICKNESS

SHOWER HINGE 135° GLASS TO GLASS SUITABLE FOR 10MM AND 12MM GLASS THICKNESS

Item number	HD.ES2.135

Description	• shower hinge 135° glass to glass
	• manufactured in brass
	• dual action hinge, opening inwards and outwards
	• self closing from approximately 15°
	• using two hinges
	  – maximum door weight 50kg
	  – maximum door width 900mm
	• using three hinges
	  – maximum door weight 60kg
	  – maximum door width 900mm

Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HD.ES2.135

100 mm

58mm

HD.ES2.135

GLASS CUT OUT DETAIL

Door

R8

76mm

46mm

INSITU APPLICATION

SHOWER HINGE 90° GLASS TO GLASS SUITABLE FOR 10MM AND 12MM GLASS THICKNESS

Item number	HD.ES2.90

Description	• shower hinge 90° glass to glass
	• manufactured in brass
	• dual action hinge, opening inwards and outwards
	• self closing from approximately 15°
	• using two hinges
	  – maximum door weight 50kg
	  – maximum door width 900mm
	• using three hinges
	  – maximum door weight 60kg
	  – maximum door width 900mm

Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HD.ES2.90

100 mm

58mm

HD.ES2.90

GLASS CUT OUT DETAIL

Door

R8

76mm

46mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SHOWER KITS

EUROGLIDE ROLLERS

Item number	SS21
Description	• Euroglide rollers • 50mm stainless steel discs with stainless steel bearings and black acetyl bush (two required per door) • 6.5mm gap required between door and fixed panel • glass detail and installation drawings supplied on request
Suitable for	• 8mm glass door and 10mm glass side panel featuring glass cut out, as supplied by Elite Glass Solutions
Material finish	• polished or satin stainless steel

SS21

SS21

Stainless steel bearing
Rubber washer
Split bush
10mm side panel
8mm sliding door

GLASS PREPARATION

Slot offset
Overlight width
Slot width
Overlight height
44mm
R20
80 mm
R15 4 places
Fixed panel height
10mm glass thickness
Wall line
Base width
Floor line

Hole offset
100mm 100mm
2 x Ø20
8mm glass thickness
Door height
See handle specs (maximum 50mm)
Door width

JULY 2016

ELITE SLIDER SLIDING SYSTEM

SHOWER HARDWARE

SHOWER KITS

F005/6/7/
8/9/10

Item number	• F001 - Elite slider inline • F002 - Elite slider square • F003 - Elite slider trio • F004 - Elite slider bracket • F005 - Elite slider door stop • F006 - Elite slider floor guide • F007 - Elite slider roller • F008 - Elite slider fixing • F009 - Elite slider bracket • F010 - Elite slider top track 1.65 meters and 2.4 meter lengths
Description	• Elite slider - sliding system is available in three configurations (inline, square and trio) • supplied in a kit, with a simple bolt together construction for quick and simple installation • rails can be cut to size and put together with bolts to the screen • no customisation required - the elite slider is adaptable to slide from either left or right • maximum door weight 45kg (8mm or 10mm glass thickness)
Suitable for	• a system to suit numerous bathroom configurations, even the most confined • 8mm and 10mm glass thickness
Material finish	• polished or satin stainless steel

F004
Bracket

F005
Door stop

F006
Floor guide

F007
Roller

F008
Fixing

F009
Bracket

F010
Top track

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HARDWARE

SHOWER KITS

F001

F001 - Elite slider inline

L = 1,150mm to 1,650mm   P = L/2   LM = P + 60mm   LF = L - P

Glass 1

Glass 2

INSTALLATION GUIDE F001

1. Install fixed panel using your preferred method (brackets, channel, etc.).

2. Install the centre of the mounting blocks from the ST01 wall brackets 12mm inside the fixed panel and inline with the centre of the holes on the fixed panel.

3. Cut the rail to length allowing clearance either end for the mounting blocks inside the ST01 wall brackets.

4. Slide 2 x ST02 door stops onto the rail, one at either end, followed by the ST01 wall bracket sleeves.

5. Install the rail onto the fixed panel and wall using the 2 x ST05 button fixings (remove extra nylon washer for 10mm glass) and slide the ST01 wall bracket sleeves over the mounting blocks and tighten grubscrews.

6. Install the ST04 rollers to the door and hang door on the rail.

7. Install the ST04 guides to the door and adjust in conjunction with the rollers.

8. Slide the ST02 door stops into position and tighten grub screws.

9. Install ST03 floor guide onto bottom of fixed panel and under door.

ELITE GLASS SOLUTIONS

F002

F002 - Elite slider square

L = 1,150mm to 1,650mm   P = L/2   LM = P + 60mm   LF = L - P

INSTALLATION GUIDE F002

1. Install fixed and side panel using your preferred method (brackets, channel, etc.).

2. Install the mounting block from the ST07 bracket on the side panel.

3. Install the centre of the mounting block from the ST01 wall bracket 12mm inside the fixed panel and inline with the centre of the holes on the fixed panel.

4. Cut the rail to length allowing clearance either end for the mounting blocks inside the ST01 wall bracket and ST07 side panel bracket.

5. Slide 2 x ST02 door stops onto the rail, one at either end, followed by the ST01 wall bracket sleeve and ST07 side panel bracket sleeve.

6. Install the rail onto the fixed panel using the 2 x ST05 button fixings (remove extra nylon washer for 10mm glass). Slide the ST01 wall bracket sleeve and ST07 side panel bracket sleeve over the mounting blocks and tighten grubscrews.

7. Install the ST04 rollers to the door and hang door on the rail.

8. Install the ST04 guides to the door and adjust in conjunction with the rollers.

9. Slide the ST02 door stops into position and tighten grub screws.

10. Install ST03 floor guide onto bottom of fixed panel and under door.

![ELITE GLASS SOLUTIONS logo]

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HARDWARE

SHOWER KITS

F003

F003 - Elite slider trio

L
P   LF
LM
← 60mm
→

Glass 1   Glass 2

L = 1,150mm to 1,650mm   P = L/2   LM = P + 60mm   LF = L - P

100mm   LM-200   100mm
50 mm   Ø20   58mm
H-8
Glass 1

(LF-450)/2   450mm   (LF-450)/2
84mm
Ø15
H
Glass 2

20.5mm
84mm
Ø15
H
Glass 3

20.5mm
84mm
Ø15
H
Glass 4

INSTALLATION GUIDE F003

1. Install fixed and side panels using your preferred method (brackets, channel, etc.).

2. Install the mounting blocks from the ST07 bracket on the side panels.

3. Cut the rail to length allowing clearance either end for the mounting blocks inside the ST07 side panel brackets.

4. Slide 2 x ST02 door stops onto the rail, one at either end, followed by the ST07 side panel bracket sleeves.

5. Install the rail onto the fixed panel using the 2 x ST05 button fixings (remove extra nylon washer for 10mm glass). Slide the ST07 side panel bracket sleeves over the mounting blocks and tighten the grubscrews.

6. Install the ST04 rollers to the door and hang door on the rail.

7. Install the ST04 guides to the door and adjust in conjunction with the rollers.

8. Slide the ST02 door stops into position and tighten grub screws.

9. Install ST03 floor guide onto bottom of fixed panel and under door.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SLIDING SHOWER KIT

Item number	SS30
Description	• sliding shower kit • manufactured in stainless steel • can be fixed to glass or solid walls • maximum hanger load 45kg per door • rail is a rectangular hollow section, height 50mm and thickness 10mm • custom kits available upon request
Suitable for	• 10mm toughened glass thickness • both inline and square showers
Material finish	• polished or satin stainless steel

SS30

SS30

ELITE GLASS SOLUTIONS

SHOWER HARDWARE

SHOWER KITS

SLIDING SHOWER KIT A

Item number	SS30 - KIT A
Description	• sliding shower kit A • door opening 600mm • rail length 1.35 meters
Kit includes	• SS30.H - 2 x hangers • SS30.WM - 1 x glass/wall mount • SS30.SM - 1 x side panel mount/stop • SS30.EP - 1 x rail end plug • SSG10 - 1 x floor guide • SS30RAIL - 1 x rail • DS4 - 1 x door seal (3 meters)

SS30 KIT A

GLASS CUTOUT DETAIL KIT A

Overlap 43mm

Minimum 1,375mm

SS30 KIT A

STANDARD SHOWER CONFIGURATIONS

SS30 KIT A — Inline (wall-to-side panel)

SS30 KIT A — Square (wall-to-side panel)

SS30 KIT A — Square (return-to-side panel)

96mm

Overhang 72mm

Door opening width

KIT A COMPONENTS

SS30H
2 x hangers

SS30WM
1 x glass/wall mount

SS30SM
1 x side panel mount/stop
Rail fastener

SS30EP
1 x rail end plug

SSG10
1 x floor guide

SS30RAIL
1 x rail

DS4
1 x door seal (3m length)

71mm
Ø15
663mm

Side panel
10mm glass thickness

75mm 75mm
31mm
Ø22
2 places
40mm
Ø10
2 places
715mm

Door
10mm glass thickness

42mm
73mm
Ø15

Return panel
(if applicable)
10mm glass thickness

SLIDING SHOWER KIT B

Item number	SS30 - KIT B
Description	• sliding shower kit B • specify tight opening size upon ordering (maximum opening width 1.4 meters)
Kit includes	• SS30.H - 2 x hangers • SS30.WM - 2 x glass/wall mounts • SS30.AS - 1 x adjustable stop • SSG10 - 1 x floor guide • SS30RAIL - 1 x rail • DS4 - 1 x door seal (3 meters)

SS30
KIT B

GLASS CUTOUT DETAIL KIT B

96mm

Maximum 1,400mm

SS30
KIT B

STANDARD SHOWER CONFIGURATIONS

SS30
KIT B

Inline (wall-to-wall)

SS30
KIT B

Square (wall-to-return panel)

75mm   75mm   42mm

31 mm

Ø22 2 places

73 mm

Ø15

40 mm

Ø10 2 places

Side panel
10mm glass
thickness

Door
10mm glass
thickness

Return panel
(if applicable)
10mm glass
thickness

KIT B COMPONENTS

SS30H
2 x hangers

SS30WM
2 x glass/wall mounts

SS30AS
1 x adjustable stop

SSG10
1 x floor guide

SS30RAIL
1 X rail

DS4
1 x door seal (3m length)

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TENZA ULTRA SPAN SLIDING DOOR SYSTEM

RG40

Item number	RG40

Description	• Tenza sliding door system
	• sliding door track is mounted between two walls
	• track is unsupported, ceiling fixings are not required
	• maximum span of 2 meters from wall to wall
	• side panels are easily glazed into the top track and floor channel
	• floor guide and floor stop is inserted into the side panel floor channel, screwing through the floor is not required
	• supplied as a complete set, each Tenza track pack contains:
	  – 2 meter track
	  – 2 meter track cover
	  – 2 meter floor channel
	  – 2 meter top track in fill
	  – 2 x wheel assemblies
	  – 2 x top track door stops
	  – 1 x floor channel door guide
	  – 1 x floor channel door stop
	  – 3 x 2 meter clips on door bump seals and
	  – 2 x track wall mounting brackets
	• Elite Glass offer a specialist Tenza which spans up to 3 meters (lead time applies)

Suitable for	• 8mm and 10mm glass thickness • any door width of a weight no greater than 40kg • shower enclosures • interior home and office doors
Material finish	• satin anodised aluminium

41 mm

60mm

COMMON CONFIGURATIONS

Side panel with door (standard TENZA track pack)

RG40

Double side panel with door
(additional bottom track stop required)

Centre panel with double do (additional fittings required)

JULY 2016

RG40

GLASS DETAIL

52mm
31 mm
8-10 mm
6 mm
H - 58mm
H-37mm
H
6mm
1.5 mm

RG40

L
P

75mm

5.5mm

P = L - 5mm (maximum 2 meters)

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

SHOWER BRACKETS

SHOWER
BRACKETS

SHOWER BRACKET GLASS TO WALL FIXED

Item number	• SB50 - round edge • SB50.SQ - square edge • SB50.B - with button
Description	• shower bracket wall fix • manufactured in solid brass • 90° glass panel to wall fixing • stud fixing recommended for all glass to wall applications
Suitable for	• 10mm glass thickness • adaptable for 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB50/SQ/B

45mm
50mm
50 mm
SB50
44mm

45mm
50mm
50mm
SB50.SQ

SB50.B

GLASS CUT OUT DETAIL

Wall
Glass
5 mm
Ø18
29mm

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER BRACKET ADJUSTABLE WALL FIX

Item number	• SB50.CAB - round edge • SB50.CAB.SQ - square edge • SB50.CAB.B - with button
Description	• shower bracket adjustable wall fix • manufactured in solid brass • 240˚ glass panel to wall fixing • adaptable to suit any non-square walls by loosening allen key screw
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SHOWER BRACKET WITH HORIZONTAL LEG

Item number	SB50.SQ.NH
Description	• shower bracket with horizontal leg
Suitable for	• when fixing point is away form edge of tile and/or wall
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SB50.
SQ.NH

SB50.SQ.NH

SB50.CAB/
SQ/B

SB50.CAB.SQ

SB50.CAB

2 - M8 x 7mm

11.8mm

M5 x 40mm

GLASS CUT OUT DETAIL

Wall

Glass

5 mm

Ø18

29mm

SHOWER HARDWARE

SHOWER BRACKETS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

SHOWER BRACKETS

SHOWER BRACKET GLASS TO GLASS FIXED DOUBLE SIDED

Item number	• SBD50 - round edge • SBD50.SQ - square edge • SBD50.B - with button
Description	• shower bracket glass to glass fixed double sided • manufactured in solid brass • 90˚ glass panel to glass panel fixing
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SBD50/SQ/B

45mm

50 mm

SBD50

44mm

45mm 50mm

50 mm

SBD50.SQ

44mm

SBD50.B

GLASS CUT OUT DETAIL

2mm silicone joint

46 mm

Ø18   Ø18

34 mm

SHOWER BRACKET GLASS TO WALL FIXED CUSTOM 1

Item number	• SB50.C1 - round edge • SB50.C1.SQ - square edge • SB50.C1.B - with button
Description	• shower bracket glass to wall fixed custom 1 • manufactured in solid brass • provides mechanical fixing of glass panel to wall at 90˚ to floor or wall
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request • when fixing area is restricted or where the bracket fixing point is lower than the glass edge
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB50.C1/SQ/B

30mm

SB50.C1

25mm

SB50.C1.SQ

SB50.C1.B

5mm

30mm

50mm

50mm

25mm

SHOWER BRACKET GLASS TO WALL FIXED CUSTOM 2

Item number	• SB50.C2 - round edge • SB50.C2.SQ - square edge • SB50.C2.B - with button
Description	• shower bracket glass to wall fixed custom 2 • manufactured in solid brass • provides mechanical fixing of glass panel to wall at 90° to floor or wall
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request • when fixing area is restricted
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB50.C2/SQ/B

SB50.C2
45mm
25mm

SB50.C2.SQ

SB50.C2.B

45mm 5mm 50mm 25mm 50mm

SHOWER BRACKET GLASS TO WALL FIXED CUSTOM 3

Item number	• SB50.C3 - round edge • SB50.C3.SQ - square edge • SB50.C3.B - with button
Description	• shower bracket glass to wall fixed custom 3 • manufactured in solid brass • provides mechanical fixing of glass panel to wall at 90° to floor or wall
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request • when the bracket fixing point is lower than the glass edge
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB50.C3/SQ/B

SB50.C3
30mm
50mm

SB50.C3.SQ

SB50.C3.B

30mm 5mm 50mm 50mm 50mm

SHOWER HARDWARE
SHOWER BRACKETS

JULY 2016

SHOWER HARDWARE

SHOWER BRACKETS

SHOWER BRACKET 135° GLASS TO WALL FIXED

Item number	• SB135 - round edge • SB135.SQ - square edge • SB135.B - with button
Description	• shower bracket 135° glass to wall fixed • manufactured in solid brass • 135° glass panel to wall fixing
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB135/
SQ/B

SB135

SB135.SQ

SB135.B

GLASS CUT OUT DETAIL

SHOWER BRACKET 135° GLASS TO GLASS FIXED

Item number	• SBD135 - round edge • SBD135.SQ - square edge • SBD135.B - with button
Description	• shower bracket 135° glass to glass fixed • manufactured in solid brass • 135° glass panel to glass panel
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SBD135/
SQ/B

SBD135

SBD135.SQ

SBD135.B

GLASS PREPARATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SHOWER BRACKET 180° GLASS TO WALL FLAT FIXED

| Item number	• SB180 - round edge • SB180.SQ - square edge • SB180.B - with button
Description	• shower bracket 180° glass to wall flat fixed • manufactured in solid brass • 180° glass panel to wall fixing
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SHOWER BRACKET 135° GLASS TO GLASS DOUBLE SIDED FLAT FIXED

Item number	• SBD180 - round edge • SBD180.SQ - square edge • SBD180.B - with button
Description	• shower bracket 180° glass to glass double sided flat fixed • manufactured in solid brass • fixing of two glass panels at 180°
Suitable for	• 10mm glass thickness • adaptable for 6mm, 8mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish • bracket type (round, square, button)

SB180/ SQ/B

SB180

45mm

50mm

100mm

SB180.SQ

100mm

SB180.B

SBD180/ SQ/B

SBD180

45mm

50mm

100mm

SBD180.SQ

SBD180.B

GLASS CUT OUT DETAIL

Wall

Glass

5 mm

Ø18

29mm

GLASS PREPARATION

33mm   33mm

2mm

SHOWER HARDWARE

SHOWER BRACKETS

JULY 2016

SHOWER BRACKETS

SHOWER BRACKET 180°/ 90° GLASS TO GLASS

Item number	• SBT180 - round edge • SBT180.SQ - square edge
Description	• shower bracket 180°/ 90° glass to glass
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin chrome
Order	• bracket type (round, square)

SBT180/SQ

SBT180

SBT180.SQ

GLASS PREPARATION

5mm

37.5mm   Ø18

Ø18   5mm

Ø18   30mm

10mm

112mm

SHOWER GLASS SHELF BRACKETS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

GLASS SHELF BRACKET ROUND EDGE

| Item number	• SB6 - suits 6mm glass thickness • SB8 - suits 8mm glass thickness • SB10 - suits 10mm glass thickness • SB12 - suits 12mm glass thickness
Description	• glass shelf bracket round edge • manufactured in solid brass • provides friction fixing of shelves and panels at 90° to floor and wall • fixing to glass by teflon tipped grub screw • fixing to wall by counter sunk hole through bracket
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB (SB6 and SB10 only) • special finishes on request, lead time applies
Order	• material finish

GLASS SHELF BRACKET SQUARE EDGE

Item number	• SB6.SQ - suits 6mm glass thickness • SB8.SQ - suits 8mm glass thickness • SB10.SQ - 10mm glass thickness • SB12.SQ - suits 12mm glass thickness
Description	• glass shelf bracket square edge • manufactured in solid brass • provides friction fixing of shelves and panels at 90° to floor and wall • fixing to glass by teflon tipped grub screw • fixing to wall by counter sunk hole through bracket
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness on request
Material finish	• polished or satin chrome • ORB (SB6.SQ and SB10.SQ only) • special finishes on request, lead time applies
Order	• material finish

SB6/8/10/12

SB6/SB8/SB10/SB12

50mm
4mm
4mm

2.5mm
25mm

24mm
Dimension
SB6 = 6.2mm
SB8 = 8.2mm
SB10 = 10.2mm
SB12 = 12.2mm

SB6/8/10/12.SQ

SB6.SQ/SB8.SQ/SB10.SQ/SB12.SQ

50mm
4mm
4mm

2.5mm

24mm
Dimension
SB6.SQ = 6.2mm
SB8.SQ = 8.2mm
SB10.SQ = 10.2mm
 SB12.SQ = 12.2mm

ELITE GLASS SOLUTIONS

GLASS SHELF BRACKET WITH GRUB SCREW

Item number	• SB10.GF - round edge • SB10.GF.SQ - square edge
Description	• glass shelf bracket with grub screw • manufactured in solid brass • facilitates fixing of glass shelves through glass panels
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• material finish • bracket type (round, square)

SB10.GF/SQ

SB10.GF

SB10.GF.SQ

GLASS PREPARATION

4mm   25mm
18mm
Ø10
4mm
60mm

GLASS SHELF BRACKET WITH HORIZONTAL LEG

Item number	• SB10.HL - round edge • SB10.HL.SQ - square edge
Description	• glass shelf bracket with horizontal leg • manufactured in solid brass • for use in SB10 applications where desired fixing point is away from edge of tile and/or wall • fixing to glass by teflon tipped grub screw • fixing to wall by counter sunk hole through bracket
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• material finish • bracket type (round, square)

SB10.HL/SQ

SB10.HL

SB10.HL.SQ

24mm
50mm   43mm

GLASS PREPARATION

43mm
24mm
28mm

R26
51mm


ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

GLASS SHELF BRACKET WITH VERTICAL LEG

Item number	• SB10.VL - round edge • SB10.VL.SQ - square edge
Description	• glass shelf bracket with horizontal leg • manufactured in solid brass • for use in SB10 applications where desired fixing point is away from edge of tile and/or wall
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• material finish • bracket type (round, square)

SB10.VL/SQ

SB10.VL

SB10.VL.SQ

50mm   69mm   18mm

GLASS PREPARATION

2mm
30mm
69mm
51mm

GLASS SHELF BRACKET

Item number	SB500
Description	• glass shelf bracket • friction fit with grub screw
Suitable for	• 10mm glass thickness • 6mm and 8mm glass thickness when gasket is added
Material finish	• polished or satin chrome

SB500

SB500

35mm
20mm   45mm

GLASS SHELF BRACKET

Item number	SB41
Description	• glass shelf bracket
Suitable for	• 6mm up to 15mm glass thickness
Material finish	• polished or satin chrome

SB41

SB41

SEC1
39

SHOWER HARDWARE

SHOWER GLASS SHELF BRACKETS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER DOOR STOPS

SHOWER DOOR STOPS

SHOWER DOOR STOP

Item number	• SB10.STOP - round profile • SB10.STOP.SQ - square profile
Description	• shower door stop • manufactured in solid brass • fixing to glass by teflon tipped grub screw • glass stops against the rubber gasket shown
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies
Order	• material finish

SB10. STOP/SQ

24mm
18mm
2mm

SB10.STOP

18mm

SB10.STOP.SQ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SHOWER DOOR STOP

Item number	DSP.25
Description	• shower door stop • manufactured in solid brass
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • oil rubbed bronze • special finishes on request, lead time applies
Order	• material finish

DSP.25

45mm
25mm
13mm

DSP.25

SHOWER DOOR STOP

Item number	DSP.27
Description	• shower door stop • manufactured in solid brass
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • oil rubbed bronze • special finishes on request, lead time applies
Order	• material finish

DSP.27

25mm
25mm
39mm
13mm

DSP.27

SHOWER DOOR STOP

Item number	DSP.26
Description	• shower door stop • manufactured in solid brass
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome • oil rubbed bronze • special finishes on request, lead time applies
Order	• material finish

DSP.26

30mm
25mm
25mm

DSP.26

SHOWER HARDWARE

SHOWER DOOR STOPS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER FIXED BRACKETS

SHOWER
FIXED BRACKETS

FIXED BRACKET GLASS TO WALL 90°
CONCEALED FIXING

Item number	MB45
Description	• fixed bracket glass to wall 90° concealed fixing • 90° glass panel to wall fixing
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MB45

44mm

44mm

MB45

GLASS PREPARATION

5mm

16mm diameter hole in glass

19mm

4mm

Ø16

19mm

2mm

17mm

20mm

13mm

JULY 2016

FIXED BRACKET GLASS TO WALL 90°

Item number	MB50
Description	• fixed bracket glass to wall 90° • 90° glass panel to wall fixing
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MB50

41mm
44mm
45mm

MB50

FIXED BRACKET GLASS TO GLASS 90° DOUBLE SIDED

Item number	MBD.50
Description	• fixed bracket glass to glass 90° double sided • 90° glass panel to glass panel
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MBD.50

41mm
44mm
45mm

MBD.50

GLASS PREPARATION

Ø16
23mm
2mm
16mm diameter hole in glass
23mm
2mm

GLASS PREPARATION 6MM GLASS THICKNESS

16mm diameter holes in glass
32mm
32mm
2mm

16mm diameter holes in glass
33mm
23mm
2mm

JULY 2016

FIXED BRACKET GLASS TO GLASS 135°
DOUBLE SIDED

Item number	MBD.135
Description	• fixed bracket glass to glass 135° double sided • 135° glass panel to glass panel
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MBD.135

MBD.135

GLASS PREPARATION 10MM GLASS THICKNESS

4mm

16mm diameter holes in glass

27mm   27mm

2mm

FIXED BRACKET GLASS TO WALL 180°
FLAT

Item number	MB.180
Description	• fixed bracket glass to wall 180° flat • 180° glass panel to wall panel
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MB.180

44mm
44mm
90mm
MB.180

GLASS PREPARATION

16mm diameter holes in glass

23mm

2mm

FIXED BRACKET GLASS TO GLASS 180°
DOUBLE SIDED FLAT

Item number	MBD.180
Description	• fixed bracket glass to glass 180° double sided flat • 180° glass panel to glass panel
Suitable for	• 6mm glass thickness • adaptable for 8mm and 10mm glass thickness on request
Material finish	• polished or satin chrome • special finishes on request, lead time applies
Order	• specify glass thickness • material finish

MBD.180

44mm
44mm
44mm
MBD.180
90mm

GLASS PREPARATION

16mm diameter
holes in glass
4mm
24mm   24mm
1mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

SHOWER PULL KNOBS

SHOWER
PULL KNOBS

PULL KNOB FINGER SET

Item number	MH20
Description	• pull knob finger set • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

MH20

25mm

30mm

MH20

GLASS CUT OUT DETAIL

Ø12

80mm

INSITU APPLICATION

JULY 2016

SHOWER PULL KNOBS

PULL KNOB DOUBLE 25MM DIAMETER

Item number	MH40
Description	• pull knob double 25mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

MH40

R1
Ø25
30mm
8mm
5mm
MH40

PULL KNOB DOUBLE 32MM DIAMETER

Item number	SK25
Description	• pull knob double 32mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK25

Ø32
40mm
SK25
40mm

GLASS CUT OUT DETAIL

Ø12
80mm

INSITU APPLICATION

GLASS CUT OUT DETAIL

Ø12
80mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

PULL KNOB DOUBLE 32MM DIAMETER

Item number	SK30
Description	• pull knob double 32mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK30

Ø32   40mm

SK30   40mm

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø12

80mm

PULL KNOB DOUBLE 32MM DIAMETER

Item number	SK35
Description	• pull knob double 32mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK35

25mm

Ø32   12mm

SK35   23mm

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø12

80mm

ELITE GLASS SOLUTIONS

JULY 2016

PULL KNOB DOUBLE SQUARE 38MM DIAMETER

Item number	SK38
Description	• pull knob double square 38mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK38

38mm

38mm   43mm

SK38

PULL KNOB DOUBLE 25MM DIAMETER

Item number	• SK40 - round edge • SKB40 - round edge with button • SK40.SQ - square edge
Description	• pull knob double 25mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

SK40/SQ
SKB40

Ø25   43mm

43mm

SK40

SKB40

SKB40.SQ

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø10

80mm

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø12

80mm

SHOWER PULL KNOBS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PULL KNOB DOUBLE 32MM DIAMETER

Item number	SK45
Description	• pull knob double 32mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK45

32mm

SK45   40mm

PULL KNOB DOUBLE 24MM DIAMETER

Item number	SK50
Description	• pull knob double 24mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • ORB • special finishes on request, lead time applies

SK50

70mm

50mm

24mm   SK50

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø12

80mm

GLASS CUT OUT DETAIL   INSITU APPLICATION

Ø12

60mm   26mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PULL KNOB DOUBLE 38MM DIAMETER

Item number	SK60
Description	• pull knob double 38mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK60

38mm

44mm

SK60

## PULL KNOB DOUBLE 27MM DIAMETER

Item number	SK70
Description	• pull knob double 27mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK70

33mm

27mm

SK70

GLASS CUT OUT DETAIL

Ø12

80mm

INSITU APPLICATION

GLASS CUT OUT DETAIL

Ø12

80mm

INSITU APPLICATION

SHOWER HARDWARE

SHOWER PULL KNOBS

ELITE GLASS SOLUTIONS

JULY 2016

PULL KNOB DOUBLE 38MM DIAMETER

Item number	SK80
Description	• pull knob double 38mm diameter • solid brass • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SK80

Ø38
50mm
SK80

GLASS CUT OUT DETAIL

Ø12
80mm

INSITU APPLICATION

PULL KNOB DOUBLE ROUND

Item number	EGSH50
Description	• pull knob double round • supplied as a pair
Material finish	• polished or satin chrome • special finishes on request, lead time applies

EGSH50

74mm (10mm glass)
50mm
60mm
EGSH50

GLASS CUT OUT DETAIL

Ø12
80mm
26mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SLIDING DOOR FINGER PULL

| Item number	SS.9
Description	• sliding door finger pull • glass hole size 48mm • 58mm overall diameter
Suitable for	• 8mm and 10mm glass thickness
Material finish	• satin stainless steel

SS.9

58mm

48mm

SS.9

GLASS CUT OUT DETAIL

Ø48

SHOWER PULL KNOBS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

SHOWER PULL HANDLES

SHOWER
PULL HANDLES

PULL HANDLE DOUBLE D

Item number	• SH210 210mm overall length hole centres 210mm apart • SH250 250mm overall length hole centres 250mm apart • SH300 300mm overall length hole centres 300mm apart • SH400 300mm overall length hole centres 400mm apart • SH450 300mm overall length hole centres 450mm apart • SH500 300mm overall length hole centres 500mm apart
Description	• pull handle double d • 25mm diameter • 10mm hole diameter • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • special finishes on request, lead time applies

SH

SH210 - 210mm
SH250 - 250mm
SH300 - 300mm
SH400 - 400mm
SH450 - 450mm
SH500 - 500mm

Ø25

SH
210/250/300/
400/450/500

72mm

GLASS CUT OUT DETAIL

100mm

SH210 - 210mm
SH250 - 250mm
SH300 - 300mm
SH400 - 400mm
SH450 - 450mm
SH500 - 500mm

Ø10

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PULL HANDLE TOWEL HANDLE

Item number	• TRK210 210mm overall length hole centres 210mm apart • TRK250 250mm overall length hole centres 250mm apart • TRK300 300mm overall length hole centres 300mm apart • TRK400 300mm overall length hole centres 400mm apart • TRK450 300mm overall length hole centres 450mm apart • TRK500 300mm overall length hole centres 500mm apart
Description	• pull handle towel handle • 25mm diameter • 10mm hole diameter • brass tube
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • special finishes on request, lead time applies

PULL HANDLE DOUBLE 25MM WIDTH

Item number	CUBIX.25
Description	• pull handle double 25mm width • supplied as a pair
Material finish	• polished or satin stainless steel • special finishes on request, lead time applies

CUBIX.25

CUBIX.25

25mm
230mm
40mm

GLASS CUT OUT DETAIL

100mm
210mm
Ø10

INSITU APPLICATION

TRK

TRK
210/250/300/
400/450/500

Ø25

TRK210 - 210mm
TRK250 - 250mm
TRK300 - 300mm
TRK400 - 400mm
TRK450 - 450mm
TRK500 - 500mm

72mm

GLASS CUT OUT DETAIL

Ø10

80mm

TRK210 - 210mm
TRK250 - 250mm
TRK300 - 300mm
TRK400 - 400mm
TRK450 - 450mm
TRK500 - 500mm

INSITU APPLICATION

SHOWER HARDWARE

SHOWER PULL HANDLES

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

PULL HANDLE DOUBLE 50MM WIDTH

Item number	CUBIX.50
Description	• pull handle double 50mm width • supplied as a pair
Material finish	• polished or satin stainless steel • special finishes on request, lead time applies

CUBIX.50

50mm
230mm
CUBIX.50
40mm

GLASS CUT OUT DETAIL

100mm
210mm
Ø10

INSITU APPLICATION

PULL HANDLE MATISSE DOUBLE

Item number	• HO.1 210mm overall length hole centres 210mm apart • HO.2 250mm overall length hole centres 250mm apart
Description	• pull handle matisse double • 19mm diameter • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished stainless steel

**HO.1
HO.2**

Ø19
H0.1 - 210mm
H0.2 - 250mm
H0.1
H0.2
60mm

GLASS CUT OUT DETAIL

100mm
H0.1 - 210mm
H0.2 - 250mm
Ø10

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

PULL HANDLE WAVE DOUBLE

Item number	WAVE210
Description	• pull handle wave 210 double • solid brass • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

WAVE210

230mm

WAVE210

70mm

GLASS CUT OUT DETAIL

INSITU APPLICATION

100mm

210mm

Ø10

PULL HANDLE CREST DOUBLE

Item number	CREST210
Description	• pull handle crest 210 double • stainless steel tube • 25mm diameter • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

CREST210

Ø25

230mm

CREST210

55mm

GLASS CUT OUT DETAIL

INSITU APPLICATION

100mm

210mm

Ø10

ELITE GLASS SOLUTIONS

JULY 2016

SHOWER HARDWARE

SHOWER PULL HANDLES

PULL HANDLE TUSK DOUBLE

Item number	TUSK150
Description	• pull handle tusk 150 double • solid brass • 22mm diameter with taper • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

TUSK150

70mm
Ø22
360mm
TUSK150

GLASS CUT OUT DETAIL

100mm
150mm
Ø10

INSITU APPLICATION

PULL HANDLE MARSH

Item number	• HM.150 - round 250mm overall length hole centres 150mm apart • HM.210 - round 300mm overall length hole centres 210mm apart • HM.210.SQ - square 300mm overall length hole centres 210mm apart • HM.300 - round 400mm overall length hole centres 300mm apart
Description	• pull handle marsh • solid brass • 19mm diameter • supplied as a pair
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin chrome • special finishes on request, lead time applies

HM

Ø19
17.5mm square

HM.150 - 250mm
HM.210 - 300mm
HM.300 - 400mm

HM.210.SQ
300mm

55mm

HM
150/210/300

55mm

HM
210.SQ

GLASS CUT OUT DETAIL

100mm
HM.150 - 150mm
HM.210 - 210mm
HM.210.SQ - 210mm
HM.300 - 300mm
Ø10

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BRACING BARS

BRACING BAR GLASS TO WALL CORNER

Item number	WB240
Description	• bracing bar glass to wall corner • aligns from the corner of the shower 45° • attaches to glass with grub screws • can be retrofit fixed to stabilise any extra deflection in the glass • with the 45° angle it provides a less obtrusive option for fixed panels of glass
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

WB240

18mm   25mm

13mm

240mm - 400mm

WB240

INSITU APPLICATION

Glass   Wall

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

BRACING BARS

BRACING BAR ADJUSTABLE GLASS TO WALL

Item number	GWB90
Description	• bracing bar glass to wall • adjustable length up to 1.1 meters • attaches to glass with grub screws
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

GWB90

GWB90

INSITU APPLICATION

Glass | Wall

BRACING BAR ADJUSTABLE GLASS TO GLASS

Item number	GGB135
Description	• bracing bar glass to glass • adjustable length up to 1.1 meters • attaches to glass with grub screws
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

GGB135

GGB135

INSITU APPLICATION

Glass | Glass

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BRACING BAR ADJUSTABLE GLASS TO WALL

Item number	• WB700 - round profile • WB700.SQ - square profile
Description	• bracing bar adjustable glass to wall • available in round and square profile • telescopic extendable for precise fit adjusting from 725mm minimum to 1180mm maximum • 25mm diameter outer rod • 19mm diameter inner rod • complete retrofit bracing system • attaches to glass with grub screws • swivel glass attachment for variable angles
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

WB700/ SQ

WB700

INSITU APPLICATION

Wall

725mm to 1180mm

Glass

Glass

BRACING BAR ADJUSTABLE GLASS TO GLASS

Item number	GGB700
Description	• bracing bar adjustable glass to glass • telescopic extendable for precise fit adjusting from 725mm minimum to 995mm maximum at 135° • 25mm diameter outer rod • 19mm diameter inner rod • complete retrofit bracing system • attaches to glass with grub screws • swivel glass attachment for variable angles
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

GGB700

GGB700

INSITU APPLICATION

725mm to 995mm

Glass

Glass

Glass

JULY 2016

BRACING BAR TRIM TO FIT
GLASS TO WALL

Item number	GWB1200.OPF
Description	• bracing bar trim to fit glass to wall • provides bracing of glass panels to walls • can be trimmed to size on site
Suitable for	• fitting on top of the fixed panel
Material finish	• polished or satin chrome

GWB1200.OPF

1.2 meters - can be trimmed to size

GWB1200.OPF

INSITU APPLICATION

Wall

Glass

BRACING BAR TRIM TO FIT
GLASS TO WALL 25MM DIAMETER

Item number	GWB1200
Description	• bracing bar trim to fit glass to wall • 25mm diameter • provides bracing of glass panels to walls • button fix to glass • can be trimmed to size on site • on site bracing of fixed shower panels at time of installation
Suitable for	• 10mm glass thickness
Material finish	• polished or satin chrome

GWB1200

Trim to size

GWB1200

INSITU APPLICATION

Wall

Glass

Ø14
required
in glass

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BRACING BAR GLASS TO WALL CORNER

Item number	• WB300L - 300mm • WB450L - 450mm
Description	• bracing bar glass to wall corner • aligns from the corner of the shower 45° • attaches to glass with grub screws • can be retrofit fixed to stabilise any extra deflection in the glass • with the 45° angle it provides a less obtrusive option for fixed panels of glass
Suitable for	• 6mm, 8mm and 10mm glass thickness • fix, swing bath applications
Material finish	• polished chrome

WB300L/ WB450L

WB300L - 300mm
WB450L - 450mm

36mm
6-12mm

INSITU APPLICATION

Glass   Wall

ELITE GLASS SOLUTIONS

JULY 2016

BRACING BAR CUSTOM SIZE

Description	• a bracing bar across the top of the enclosure can stabilise an oversized panel • custom lengths and angles available on request, lead time applies
Material finish	• polished or satin chrome • special finishes on request, lead time applies

Item number	BAR A
Description	• bracing bar custom size side panel to return • 16mm square pole • mounted on glass

Item number	BAR B
Description	• bracing bar custom size wall to return • 25mm round diameter pole • 12mm diameter hole in glass • mounted through glass

Item number	BAR C
Description	• bracing bar custom size side panel to side panel - quad • 16mm square pole • mounted on glass

Item number	BAR D
Description	• bracing bar custom size side panel to side panel • 16mm square pole • mounted on glass

Item number	BAR E
Description	• bracing bar custom size wall to side panel • 16mm square pole • mounted on glass

Item number	BAR F
Description	• bracing bar custom size wall to return panel • 25mm round pole • mounted on glass

BARS

BAR A
BAR B
BAR C
BAR D
BAR E
BAR F

OVERPANEL FITTINGS

Item number	• OPF1 - round profile
	• OPF1.SQ - square profile
	• OPF2 - round profile
	• OPF2.SQ - square profile
Description	• overpanel fittings
	• fixed to glass by teflon tipped grub screws
Suitable for	• 10mm fixed panel with 6mm overpanel (OPF1)
	• 10mm fixed panel with 10mm overpanel (OPF2)
Material finish	• polished or satin chrome
	• ORB

OVERPANEL 90° FITTING

Item number	SF.M003
Description	• overpanel 90° fitting
Material finish	• polished or satin chrome
	• oil rubbed bronze

SF.M003

SF.M003

OPF1/SQ OPF2/SQ

OPF1

OPF1.SQ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

HEADER SYSTEM ALUMINIUM PROFILE

| Item number	HS1000
Description	• header system aluminium profile • 3.2 meter lengths • complete header for bracing of inline 90° and 135° shower configurations • manufactured in aluminium
Material finish	• bright silver and gold anodised • white powdercoat

HS1000

HS1000

14mm
25mm
12mm
20mm

HEADER SYSTEM ALUMINIUM GLASS DEDUCTIONS AND CLEARANCES

HS1000

18mm
Sidepanel   Door   12mm   Sidepanel

Top of aluminium header to top of fixed side panels = 18mm

Deduction off door from sidepanel to swing under aluminium header = 12mm

18mm   18mm   18mm
              7mm   7mm

6mm glass   8mm glass   10mm glass

A spacer of less than 7mm can be used in 8mm and 10mm glass applications, however, the deduction to the door (12mm as shown) will need to be increased when measured from the sidepanels to compensate for the smaller spacer

WALL BRACKET DETAIL

2mm

14mm

![Elite Glass Solutions logo] ELITE GLASS SOLUTIONS

HEADER SYSTEM ALUMINIUM
FIXING BRACKETS

Item number	• HS1010 - wall bracket • HS1020 - 135° bracket • HS1030 - 90° bracket
Description	• header system aluminium fixing brackets • sold per piece
Material finish	• bright silver and gold anodised • white powdercoat

HS10/10 /20/30

HS1010

27mm

5mm

17mm

17mm

10mm

100mm

10mm

HS1020

36mm

HS1030

9.3mm

HEADER SYSTEM ALUMINIUM
GLAZING WEDGE AND INFILLS

Item number	• HS1040 - glazing vinyl • HS1050 - infill strip
Description	• header system aluminium glazing wedge and infill • comes in 10 meter rolls

HS1040 HS1050

HS1040

HS1050

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105

sales@eliteglasssolutions.com.au

www.eliteglasssolutions.com.au

DOOR SEALS, WATER SEALS AND CHANNELS

DOOR SEALS, WATER SEALS AND CHANNELS

DOOR SEAL D SHAPED

Item number	DS4
Description	• door seal D shaped • rigid back PVC with flexible PVC seal • 2 meter length
Material finish	• clear PVC

DS4

7mm
7.5mm
DS4

7mm
Rigid PVC   Flexible PVC

DOOR SEAL CLEAR

Item number	DS5
Description	• door seal clear • 2.2 meter length
Suitable for	• 10mm glass thickness
Material finish	• clear plastic

DS5

10mm
12mm
10mm
DS5

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

DOOR SEAL U CHANNEL

Item number	DS10
Description	• door seal U channel • 2 meter length
Suitable for	• 10mm glass thickness
Material finish	• clear plastic

DS10

10mm

13mm

DS10

DOOR SEAL T SHAPED

Item number	TS1
Description	• door seal T shaped • 2 meter length • rigid back PVC with flexible PVC seal
Material finish	• clear PVC

TS1

4.5mm

7mm

TS1

DOOR SEAL L SHAPED

Item number	LS1
Description	• door seal L shaped • 2 meter length • rigid back PVC with flexible PVC seal
Material finish	• clear PVC

LS1

3mm

7mm

LS1

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

WATER SEAL WITH FELT INSERT

Item number	WS1
Description	• water seal with felt insert • 2 meter length
Material finish	• satin or polished silver anodised • special finishes on request, lead time applies

WS1

8mm

9mm

WS1

9mm

WATER SEAL ALUMINIUM

Item number	HR1
Description	• water seal aluminium • 1.5 meter length
Material finish	• satin or polished silver anodised • special finishes on request, lead time applies

HR1

4.8mm

12mm

HR1

WATER SEAL WATERBAR SECTION

Item number	WS3
Description	• water seal waterbar section • 3 meter length
Material finish	• satin or polished silver anodised • special finishes on request, lead time applies

WS3

10mm

10mm

WS3

WATER SEAL CLEAR ACRYLIC

Item number	HR2
Description	• water seal clear • 1.5 meter length
Material finish	• clear acrylic

HR2

4.8mm

12mm

HR2

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

WATERBAR OFFSET ROUND

| Item number	MWB10
Description	• waterbar offset • 2.1 meter length
Material finish	• polished silver and gold and matt silver

MWB10

10mm

20mm

MWB10

WATER SEAL RIGID CLEAR PVC

Item number	WS10.01
Description	• water seal rigid clear PVC • 2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.01

WS10.01

4mm

WATER SEAL ANGLE SECTION 18MM HEIGHT

Item number	AS18
Description	• water seal angle section 18mm x 18mm • aluminium extrusion • 3 meter length
Material finish	• polished silver anodised • powdercoat

AS18

18mm

18mm

AS18

WATER SEAL RIGID CLEAR PVC WITH REMOVABLE FLEXIBLE FIN

Item number	WS10.02
Description	• water seal rigid clear PVC with removable flexible fin • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.02

WS10.02

12mm

SHOWER HARDWARE

DOOR SEALS, WATER SEALS AND CHANNELS

ELITE GLASS SOLUTIONS

JULY 2016

WATER SEAL RIGID/FLEXIBLE CLEAR PVC 180° DOOR/SIDELIGHT APPLICATION

Item number	WS10.03
Description	• water seal rigid/flexible clear pvc 180° door/sidelight application • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.03

WS10.03

5mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC 90° DOOR TO WALL APPLICATION

Item number	WS10.05
Description	• water seal rigid/flexible clear pvc 90° door to wall application • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.05

WS10.05

5mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC 90° DOOR/SIDELIGHT APPLICATION

Item number	WS10.04
Description	• water seal rigid/flexible clear pvc 90° door/sidelight application • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.04

WS10.04

5mm

WATER SEAL RIGID CLEAR PVC CLIP WITH FLEXIBLE FIN

Item number	WS10.06
Description	• water seal rigid clear pvc clip with flexible fin • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.06

WS10.06

6mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

WATER SEAL RIGID CLEAR PVC WITH FLEXIBLE ROUND BULB SECTION FOR DOOR TO WALL OR DOOR TO SIDELIGHT APPLICATION

Item number	WS10.07
Description	• water seal rigid clear pvc with flexible round bulb section for door to wall or door to sidelight application • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.07

WS10.07

5mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC SUITABLE FOR 135° APPLICATIONS

Item number	WS10.09
Description	• water seal rigid/flexible clear pvc suitable for 135° door/sidelight applications • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.09

WS10.09

7mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC SUITABLE FOR 90° APPLICATIONS

Item number	WS10.08
Description	• water seal rigid/flexible clear pvc suitable for 90° applications • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.08

WS10.08

5mm

WATER SEAL RIGID CLEAR PVC CLIP WITH DUAL FLEXIBLE FINS

Item number	WS10.10
Description	• water seal rigid clear pvc clip with dual flexible fins for sealing underneath doors • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.10

WS10.10

6mm

SHOWER HARDWARE

DOOR SEALS, WATER SEALS AND CHANNELS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

WATER SEAL RIGID CLEAR PVC CLIP WITH PVC FIN FOR 180° APPLICATIONS

Item number	WS10.11
Description	• water seal rigid clear pvc clip with pvc fin for 180° applications • 2.2 meter length
Suitable for	• 8mm and 10mm glass thickness
Material finish	• clear PVC

WS10.11

WS10.11

5mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC FOR 135° DOOR TO SIDEPANEL APPLICATION

Item number	WS06.09
Description	• water seal rigid/flexible clear pvc for 135° door to sidepanel application • 2.2 meter length
Suitable for	• 6mm glass thickness
Material finish	• clear PVC

WS06.09

WS06.09

7mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC FOR 135° DOOR TO SIDEPANEL APPLICATION

Item number	WS06.06
Description	• water seal rigid/flexible clear pvc for 135° door to sidepanel application • 2.2 meter length
Suitable for	• 6mm glass thickness
Material finish	• clear PVC

WS06.06

WS06.06

6mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC FOR 135° DOOR TO SIDEPANEL APPLICATION

Item number	WS06.10
Description	• water seal rigid/flexible clear pvc for 135° door to sidepanel application • 2.2 meter length
Suitable for	• 6mm glass thickness
Material finish	• clear PVC

WS06.10

WS06.10

8mm

WATER SEAL RIGID/FLEXIBLE CLEAR PVC FOR BOTH 180° GLASS TO GLASS AND UNDERNEATH DOORS

Item number	WS06.11
Description	• water seal rigid/flexible clear pvc for both 180° glass to glass and underneath doors • 2.5 meter length
Suitable for	• 6mm glass thickness
Material finish	• clear PVC

WS06.11

WS06.11

5mm

CHANNEL ALUMINIUM SHOWER GLAZING CHANNEL 15MM

Item number	CH15
Description	• channel aluminium shower glazing channel 15mm • extruded aluminium • 3 meter lengths
Suitable for	• 10mm glass thickness
Material finish	• polished or satin anodised • special finishes on request, lead time applies

CH15

CH15

1.6mm
16mm
10.4mm
14mm

CHANNEL ALUMINIUM SHOWER GLAZING CHANNEL 18MM

Item number	HS18
Description	• channel aluminium shower glazing channel 18mm • 2.1 and 3 meter lengths
Suitable for	• 12mm glass thickness
Material finish	• polished or satin anodised • special finishes on request, lead time applies

HS18

1.8mm
10mm
28mm
HS18
18mm
18mm

CHANNEL ALUMINIUM LOW PROFILE 16MM

Item number	CH16
Description	• channel aluminium low profile 16mm • extruded aluminium • 2.5 meter lengths
Suitable for	• 12mm glass thickness
Material finish	• polished or satin anodised • special finishes on request, lead time applies

CH16

1.6mm
8mm
12.8mm
CH16
16mm

SHOWER HARDWARE

DOOR SEALS, WATER SEALS AND CHANNELS

ELITE GLASS SOLUTIONS

JULY 2016

CHANNEL ALUMINIUM SHOWER GLAZING CHANNEL 18MM

Item number	CH18
Description	• channel aluminium shower glazing channel 18mm • 2.1 and 3 meter lengths
Suitable for	• 12mm glass thickness
Material finish	• polished or satin anodised • special finishes on request, lead time applies

CH18

CH18

1.8mm
14mm
18.4mm
17.7mm

END CAPS

Item number	• EC1 • EC45
Description	• end caps • extruded aluminium
Suitable for	• CH18 (EC1) • 45° mitre CH18/CH25 (EC45)
Material finish	• polished or satin anodised • special finishes on request, lead time applies

EC1
EC45

EC1
1mm
18.4mm
17.4mm

EC45
1mm
18.4mm
24.5mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

ACCESSORIES

ROBE HOOK

Item number	RH1
Description	• robe hook • manufactured in solid brass • 38mm diameter
Material finish	• polished or satin chrome

RH1

65mm

Ø38

RH1

TOILET ROLL HOLDER

Item number	TRH1

Description	• toilet roll holder
	• manufactured in solid brass
	  with 134mm x 25mm diameter
	  glass rod
	• can be glue fixed

Material finish	• polished chrome

TRH1

75mm

30mm

TRH1

134mm

38mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SHOWER HARDWARE

ACCESSORIES

MEASURING PACKERS

| Item number	• PP1.5 - 1.5mm blue packer • PP2 - 2mm red packer • PP3 - 3mm orange packer • PP4 - 4mm green packer • PP5 - 5mm grey packer • PP6 - 6mm black packer
Description	• measuring packers • available in 1.5mm, 2mm, 3mm, 4mm, 5mm and 6mm thicknesses
Material finish	• polished chrome

PP

37.5mm
96mm
12mm

PP1.5 = 1.5mm
PP2 = 2mm
PP3 = 3mm
PP4 = 4mm
PP5 = 5mm
PP6 = 6mm

SILICONE SPATULA

Item number	SS1
Description	• polyurethane silicone spatulas for finishing off silicone butt joins

SS1

85mm
77mm
SS1

SILICONE SPATULA

Item number	SS2
Description	• polyurethane silicone spatulas for finishing off silicone butt joins

SS2

SS2

SHOWER SUPPORT BRACKET

Item number	SSB100
Description	• shower support bracket • supplied standard at 100mm to FFL • custom sizes made to order
Suitable for	• installing fixed panels
Material finish	• polished or satin chrome • special finishes on request, lead time applies

SSB100

SSB100

19mm
19mm
100mm
Ø50

JULY 2016

WASHERS

Item number	• W25 - 25mm diameter • W30 - 30mm diameter • W37 - 37mm diameter • W43 - 43mm diameter
Description	• washers available in 25mm, 30mm, 37mm and 43mm diameter • 2mm thickness • manufactured in solid brass
Suitable for	• SK60 knob (W25) • SK40 knob, SH and TRK handles (W30) • modern handle (W37) • SK80 knob and classic handle (W43)
Material finish	• polished or satin chrome • special finishes on request, lead time applies

W25/30/37/43

43mm

W43

37mm

W37

30mm

W30

25mm

W25

SCREWS

Item number	• WS2.25 - wood screw 25mm length • WS2.38 - wood screw 38mm length • WS2.50 - wood screw 50mm length • MS612.304 - machine screw • HS612.304 - hex screw
Description	• wood screws available in 25mm, 39mm and 50mm lengths • machine and hex screws
Suitable for	• ES hinges (machine and hex screws)
Material finish	• polished stainless • satin chrome • special finishes on request, lead time applies

WS/MS/HS

WS2.25 = 25mm length
WS2.38 = 38mm length
WS2.50 = 50mm length

MS612.304

HS612.304

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS SHELVES

GLASS SHELF CORNER 150MM RADIUS

Item number	GS150
Description	• glass shelf corner • 150mm radius
Material finish	• 10mm toughened clear glass

GS150

GS150

GLASS SHELF CORNER 200MM RADIUS

Item number	• GS200.CFL - clear glass • GS200.LOW - low iron glass
Description	• glass shelf corner • 200mm radius
Material finish	• 10mm toughened clear glass • 10mm toughened diamant low iron glass

GS200

GS200

GLASS SHELF CORNER 250MM RADIUS

Item number	• GS250.CFL - clear glass • GS250.LOW - low iron glass
Description	• glass shelf corner • 250mm radius
Material finish	• 10mm toughened clear glass • 10mm toughened diamant low iron glass

GS250

GS250

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS SHELF CORNER 300MM RADIUS

Item number	GS300
Description	• glass shelf corner • 300mm radius
Material finish	• 10mm toughened clear glass

GS300

GS300

GLASS SHELF CORNER 200MM ANGLED

Item number	GSA200
Description	• glass shelf corner angled • 200mm angled
Material finish	• 10mm toughened clear glass

GSA200

GSA200

GLASS SHELF CORNER 250MM ANGLED

Item number	GSA250
Description	• glass shelf corner angled • 250mm angled
Material finish	• 10mm toughened clear glass

GSA250

GSA250

GLASS SHELF CORNER WITH SOAP AREA 200MM RADIUS

Item number	• GSS200.CFL - clear glass • GSS200.LOW - low iron glass
Description	• glass shelf corner with soap area • 200mm radius • polished recessed are for soap with drainage hole
Material finish	• 10mm toughened clear glass • 10mm toughened diamant low iron glass

GSS200

GSS200

GLASS SHELF CORNER WITH SOAP AREA 250MM RADIUS

Item number	• GSS250.CFL - clear glass • GSS250.LOW - low iron glass
Description	• glass shelf corner with soap area • 250mm radius • polished recessed are for soap with drainage hole
Material finish	• 10mm toughened clear glass • 10mm toughened diamant low iron glass

GSS250

GSS250

SHOWER HARDWARE

GLASS SHELVES

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS SHELF CURVED WAVE

| Item number	GS.WAVE
Description	• glass shelf curved wave • 100mm radius x 100mm length • available in 500mm and 600mm length
Material finish	• 10mm toughened clear glass

GS.WAVE

GS.WAVE

GLASS SHELF HALF CIRCLE

Item number	GS.CIRCO
Description	• glass shelf half circle • 150mm radius x 300mm length
Material finish	• 10mm toughened clear glass

GS.CIRCO

GS.CIRCO

GLASS SHELF RECTANGLE

Item number	• GS.RECTO.300 - 300mm length • GS.RECTO.600 - 600mm length • GS.RECTO.900 - 900mm length
Description	• glass shelf rectangle • width 150mm • available in 300mm, 600mm and 900mm lengths
Material finish	• 10mm toughened clear glass

GS.RECTO

GS.RECTO.300
GS.RECTO.600
GS.RECTO.900

GLASS SHELF CRESCENT

Item number	GS.CRESCENT
Description	• glass shelf crescent • 150mm radius x 500mm length
Material finish	• 10mm toughened clear glass

GS.
CRESCENT

GS.CRESCENT

INSPIRED VISION
FOR FRAMELESS GLASS

EUROGLASS WARRANTY INFORMATION

dated: 01 Mar 2015

Shower Hardware

Euroglass guarantee our product against faulty workmanship or defective materials for a period of ten (10) years from the date of purchase. They will be replaced at no charge to the purchaser once the defect has been inspected and confirmed.

This warranty does not apply in respect of defects arising from the following:

1. If the product has been altered in any way.
2. The product has been subject to incorrect mechanical fixing techniques.
3. The product has been installed outside of the specifications of its use.
4. The product has been subject to abnormal stresses from loading, heat, building or foundation movement.
5. Faulty workmanship of any person in the installation of the product.
6. Defect in any framework or substrate to which the product has been installed supporting the product.

The replacement is solely for the product only, and Euroglass will not be liable for the dismantling at site, return or reassembly at site of the product, or to any structure to which it is affixed.

Repairs or replacements under this warranty do not extend the warranty period and do not initiate a new warranty period and the warranty period for any replacement parts ends together with the warranty for the entire product.

65 CARR ROAD, MT ROSKILL, AUCKLAND   CALL **09 624 1180**

FAX   09 624 2280
EMAIL hardware@euroglass.co.nz
WEB   www.euroglass.co.nz

BALUSTRADE & GLASS FIXINGS

ELITE GLASS
SOLUTIONS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CONTENTS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

BALUSTRADE & GLASS FIXINGS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BALUSTRADE CHANNELS

BALUSTRADE CHANNEL

Item number	• BACH • BAEC - end cap
Description	• balustrade channel • 6 meter stock length • handrail options available • for installation use Tecgrout C (NG.20KG)
Suitable for	• 12mm and 15mm glass thickness
Material finish	• mill • silver pearl powdercoat • selected powdercoat (lead time applies)

BACH BAEC

BACH

BAEC

AUSTRALIAN MADE

SIDE VIEW

S2217
60.30 ± 1.50
85.00 ± 0.60
20.00CTRS
5°
R8.80
3.8CTRS (2)
18.7CTRS
26.00 I.P
4 mm
3mm
1.2 mm
8.00 ± 0.20
15mm
35LPS
78.30mm

ELITE GLASS SOLUTIONS

MEDIUM DUTY GLAZING CHANNEL

Item number	EZM
Description	• medium duty glazing channel • designed for use on parapets, and if correctly installed, the creation of toeholds may be avoided • it may also be used for some full height balustrades, (*subject to relative design criteria) • internal recess of 74mm high x 41mm wide • utilises Axiom glazing rubbers SRB retained back seal and SWZ9 wedge rubber when using 12mm glass thickness • for installation use Tecgrout C (NG.20KG) • end caps available on request
Suitable for	• supporting free standing glass balustrade • parapets • some full height balustrades • 10mm, 12mm and 15mm glass thickness
Material finish	• mill • powdercoat

EZM

EZM

AUSTRALIAN MADE

SIDE VIEW

32mm
84mm
60mm

TECGROUT C NON SHRINK

Item number	NG.20KG
Description	• Tecgrout C is a flowable, non shrink type C grout based on ordinary Portland cement, specially graded aggregates and admixtures to produce a flowable grout at a low water cement ratio
Suitable for	• for installation of Balustrade Channel (BACH) and Medium Duty Glazing Channel (EZM)

NG.20KG

NON SHRINK GROUT

NG.20KG

RESIGROUT LV TWO PART

Item number	RESIGROUT LV
Description	• Resigrout LV is a low viscosity epoxy grout for the repair of cracks in concrete pavement

RESIGROUT LV

RESIGROUT LV TWO PART PART A

HARDENER PART B

JULY 2016

SMART-RAIL TILT-LOCK BASE RAIL SYSTEM

BR

TILT AND LOCK
Tightening

Item number	BR (available in 5.85 meter lengths)
Description	The Smart-Rail Tilt-lock base rail system is a revolution in design and ease of installation. Never before has a base rail system been so simple to install for expert and the DIY installer. It greatly reduces the issues of uneven sites making the channel installation so much faster, on most sites just tilt the glass to resolve site issues simply and quickly. With modern design architects seeking clean clear lines the Smart-Rail meets the design demands of today and the future. Featuring three models to suit a range of glass from 12mm to 32.67mm and up to 3kn applications the system provides an unprecedented range of installation and glass options to meet the ever increasing demand for better frameless glass systems.

Whether you require top, rebated or side fixed option the system provides every thing you need in a simple and strong solution. The grub screw system is design to use full length covers for one or both sides and the internal clamping system can use either long or short covers. The recess model is designed to be installed in situations where the base rail is required to not be seen, this model is also suitable for use with curved glass.

The Smart-Rail system can be easily used for grout filled applications if this option is specified, although with the ease of the Tilt-lock system the need is unlikely. |
| **Suitable for** | • 12mm to 25mm glass thickness with the three available models
• top or side fixed applications
• indoor and outdoor installations |
| **Material finish** | • sections and covers are fully anodised for durability and come standard in a unique brushed anodised finish which give a "stainless steel effect"
• other aluminium finishes are available on request |

GLASS TILT

UPPER SCREW

GLASS TILT

LOWER SCREW

Adjustment

30mm   30mm

1 meter

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BALUSTRADE & GLASS FIXINGS

BALUSTRADE CHANNELS

BR

INTERNAL CLAMPING MOUNTING SYSTEM

GRUB SCREW MOUNTING SYSTEM

SMART-RAIL TILT-LOCK
BASE CHANNEL MODEL

Item number	BR68
Description	• smart-rail tilt-lock base channel model
Suitable for	• 12mm to 19mm glass thickness (internal clamping system) • 12mm to 25mm glass thickness (grub screw mounting system)
Material finish	• duplex 2205 polished or satin stainless steel

BR68

BR68

SMART-RAIL TILT-LOCK
COVER PLATES

Item number	• BR68.SCP square style full cover model • BR68.CPS square style top cover model
Description	• smart-rail tilt-lock cover plates
Suitable for	• BR68 and BR78
Material finish	• duplex 2205 polished or satin stainless steel

BR68.SCP/ CPS

BR68.SCP   BR68.CPS

SMART-RAIL TILT-LOCK
HIGH STRENGTH MODEL

Item number	BR78
Description	• smart-rail tilt-lock high strength model
Suitable for	• 12mm to 25mm glass thickness (internal clamping system) • 12mm to 32.67mm glass thickness (grub screw mounting system)
Material finish	• duplex 2205 polished or satin stainless steel

BR78

BR78

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

POSIGLAZE BALUSTRADE SYSTEM

Item number

- PG120.B - base fix system
  120mm high x 72mm wide x 3 meter lengths
- PG120.S - side fix system
  120mm high x 74mm wide x 3 meter lengths
- PG180.S - side fix system
  180mm high x 74mm wide x 3 meter lengths

Description

The PosiGlaze Glass Balustrade System was developed for cantilevered structural balustrades to cope with the transition from monolithic toughened safety glass to toughened laminated safety glass.

The unique design uses a special high strength hollow core aluminium extrusion and special glass clamp kits that clamp the glass and locate into the section. This means the system can be used on 12, 15, and 19mm toughened safety glass and 13.5, 17.5 and 21.5 laminated safety glass without holes in the glass. Holes can make the systems more complex and often the holes are the point of failure.

The other key to PosiGlaze is its clever locating and adjusting technique which allows the installers to adjust the glass panels once in place, with a turn of a spanner, saving on installation time.

Suitable for

The PosiGlaze Glass Balustrade System can be base fixed or side fixed for top or side (face) mounted balustrade applications.

The 120mm high x 72mm wide extrusion comes in 3 meter lengths all pre drilled ready for fixing and once the section is fitted the glass is easily dropped in and located. The systems also makes re-glazing easy, or the glass type or thickness can be easily changed at a later date.

A top seal strip section and gasket are installed after the glass has been adjusted to give a clean top edge look and matching end caps complete the system.

For the side fixed systems an additional clip on side cladding and tapered base cladding section is used for aesthetics and to cover the fixing holes.

Material finish

The sections and covers are fully anodized for durability and come standard in a unique brushed anodized finish which give a "Stainless Steel Effect"

Other aluminium finishes are available on request.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

Design and testing

The PosiGlaze Glass Balustrade System has been designed and tested to New Zealand and British Standards, which use similar occupancy types and loading requirements.

The UK testing to BS 6180:2011, involved base and side fixed systems to concrete and steel and a range of glass types and thicknesses from 15mm - 21mm including TLSG with EVA and SG inter layer.

The NZ testing is to AS/NZS 1170 loadings in accordance with B1/VM1 Amend 8, for Occupancy A, B, E, C3 and the higher C1, C2 and D loadings.

Therefore the systems can be used for all residential applications and commercial applications, except for C5 (over-crowding).

Installation

The Posiglrade Glass Balustrade System can be glazed with Toughened, Heat soaked, Screen printed, Digital printed, Toughened Safety Glass (TSG) or SafeLite Toughened Laminated Safety Glass (TLSG), using either, PVB, CIP, EVA or SGP interlayer. Note that the breakage characteristic can alter with different interlayer's.

(Refer to Glass Manufacturer for more details).

Compliance

The PosiGlaze Glass Balustrade System can be used for compliance with NZ Building Code Clause F4 – Safety from falling, with barrier heights to suit the design application, normally 1 meter.

The maximum glass height is a function of the glass type, thickness, occupancy loading, and wind loading and a design table or specific design is available from Elite Structural Glass Fittings.

Test data and independent engineered and certified Producer Statements (PS1) are available for compliance with the NZ Building Code.

Heat Soaked TSG is recommended for barriers with interlinking handrails or top rails

PG120.B

PG120.B

PG120.S

PG120.S

PG180.S

PG180S

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BALUSTRADE & GLASS FIXINGS

BALUSTRADE CHANNELS

INFINITY SIDEFIX GLASS BALUSTRADE SYSTEM

BA124

Item number	BA124
Description	• Infinity sidefix glass balustrade system • no holes are required in the glass panels, they are simple to install, align and adjust • Residential A, C3 and pool fencing require 12mm toughened glass, clamps at 500mm centres with a maximum overhang of 250mm • Commercial B, E and C3 require 15mm toughened glass, clamps at 400mm centres with a maximum overhang of 200mm • PS1 and system manual with full set out details are available on request
Suitable for	• side fix frameless glass balustrades • pool fencing and the following balustrade occupancy types – Residential A and C3, Commercial B, E and C3
Material finish	• natural anodised aluminium with mill finish • standard colour powder coat options also available
Order	• specify lengths of front and rear covers, plus the required number of glass clamps. All system components can be selected on pages to follow

BA124

BA124

124mm

64mm

clamp kit

Fixing

rear cover

front cover

Residential A, C3 and Pool Fence

1.5 meters

Height 1.2 meters maximum

250mm overhang

500mm   500mm

Commercial B, E and C3

1.2 meters

Height 1.3 meters maximum

200mm overhang

400mm   400mm

ELITE GLASS SOLUTIONS

BA124

Timber Deck - M12 coach screw
Occupancy
Residential A and C3 only

53mm wide Lumberlok Multibrace stainless steel straps to top and bottom of joists. 6 x 45 x 3.3mm annular grooved nails to each end of straps, top and bottom

Decking

12mm toughened glass

10 suggested

60
75
+5,-5

Minimum joist size ex 200mm x 50mm

EPDM layer

Nails, 20 off - 90 x 3.4mm diameter through joists

BA124

1 - Coachscrews 90mm minimum thread engagement into joists
2 - Bond all coachscrews with SIKA Supergrip to full depth
3 - A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Waterproof timber deck - M12 coach screw
Occupancy
Residential A and C3 only

53mm wide Lumberlok Multibrace stainless steel straps to top and bottom of joists. 6 x 45 x 3.3mm annular grooved nails to each end of straps, top and bottom

Decking + Membrane

12mm toughened glass

30

60
75
+5,-5

Minimum joist size ex 200mm x 50mm

Rear spacer +EPDM layer

Optional 15mm spacer plate shown

Nails, 20 off - 90 x 3.4mm diameter through joists

1 - Coachscrews 90mm minimum thread engagement into joists
2 - Bond all coachscrews with SIKA Supergrip to full depth
3 - A Rubber, EPDM or foam tape layer must be installed between the clamp and timber

Infinity glass clamps height options

'Normal' height say 10mm below deck

Clamp flush with deck

Clamp below deck

Clamp flush with deck 15mm spacer

BA124

Concrete Deck - M12 Stud
Occupancy
Residential A & C3 = 12mm toughened glass
Commercial B, E & C3 = 15mm toughened glass

15mm toughened glass

Concrete Slab

10 suggested

110mm minimum

150mm minimum

60
75
+5,-5

EPDM layer

BA124

1 - All fixings must engage into the structural slab
2 - A Rubber, EPDM or foam tape layer must be installed between the clamp and concrete

Steel structure - M12 bolt
Occupancy
Residential A and C3 = 12mm glass
Commercial B, E or C3 = 15mm glass

15mm toughened glass

Decking

10 suggested

60
75
+5,-5

EPDM layer

1 - A Rubber, EPDM or foam tape layer must be installed between the clamp and steel

Infinity glass clamps height options

'Normal' height say 10mm below deck

Clamp flush with deck

Clamp below deck

Clamp flush with deck 15mm spacer

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE & GLASS FIXINGS

BALUSTRADE CHANNELS

INFINITY TYPICAL INSTALLATION EXAMPLES

BA124

Waterproof timber deck
Occupancy
Commercial B, E or C3

53mm wide Lumberlok Multibrace
stainless steel straps to top and
bottom of joists. 6 x 45 x 3.3mm
annular grooved nails to each
end of straps, top and bottom

Decking + Membrane

15mm toughened glass

30

60 75
+5,-5

Minimum joist size
ex 200mm x 50mm

Nails, 20 off - 100 x 4mm
diameter through joists

BA124

1 - Coachscrews 120mm minimum thread engagement into joists
2 - Bond all coachscrews with SIKA Supergrip to full depth
3 - A Rubber, EPDM or foam tape layer must be installed
   between the clamp and timber

Timber deck - M12 coach screw
Occupancy
Commercial B, E or C3

15mm toughened glass

Decking

10 suggested
60 80
+5,-5

Bottom of glass

Minimum joist size
ex 200mm x 50mm

Rear spacer +EPDM layer

Nails, 20 off - 110 x 4mm
diameter through joists

1 - Coachscrews 90mm minimum thread engagement into joists
2 - Bond all coachscrews with SIKA Supergrip to full depth
3 - A Rubber, EPDM or foam tape layer must be installed
   between the clamp and timber

Infinity glass clamps height options

'Normal' height say 10mm below deck | Clamp flush with deck | Clamp below deck | Clamp flush with deck 15mm spacer

INFINITY HEAVY DUTY CLAMP EXTRUSION

Item number	CKI.1
Description	• Infinity heavy duty clamp extrusion • the infinity balustrade clamp comes as a kit - clamp extrusion, front and rear gasket extrusions gaskets, glass bottom packer and all adjusting screws (M12 fastener not included)
Suitable for	• 12mm, 13.52mm, 15mm, 17.52mm, 19mm and 21.52mm glass thickness
Material finish	• aluminium

CKI.1

CKI.1
150mm
Top clamp screws
Access hole to M12 bolt / coachscrew head
Rear side
Front side
Bottom clamp screws
Access holes to horizontal adjustment screw

M12 Bolt/ Coachscrew (rear side)

Vertical adjustment screw (in base)

Front side deleted, showing bolt hole in rear side and height adjusting screw

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

INFINITY REAR COVER/CLAMP BASE
WITH BULB SEAL

Item number	• RCI.118.N.5000 118mm height natural anodised 5 meter length • RCI.118.N.2500 118mm height natural anodised 2.5 meter length • RCI.118.M.5000 118mm height mill aluminium 5 meter length • RCI.118.M.2500 118mm height mill aluminium 2.5 meter length
Description	• Infinity rear cover/clamp base with bulb seal • acts as a template
Suitable for	• Infinity system
Material finish	• natural anodised • mill aluminium • standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A.

RCI.118

118mm   RCI.118

INFINITY FRONT COVER
WITH BULB SEAL

Item number	• FCI.124.N.5000 124mm height natural anodised 5 meter length • FCI.124.N.2500 124mm height natural anodised 2.5 meter length • FCI.124.M.5000 124mm height mill aluminium 5 meter length • FCI.124.M.2500 124mm height mill aluminium 2.5 meter length
Description	• Infinity front cover with bulb seal
Suitable for	• Infinity system
Material finish	• natural anodised • mill aluminium • standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A.

FCI.124

124mm   FCI.124

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

INFINITY CLAMP KIT
SUITABLE FOR 12MM GLASS THICKNESS

Item number	CKI.12
Description	• Infinity clamp kit
Suitable for	• Infinity system • 12mm glass thickness
Material finish	• matt black

CKI.12

CKI

INFINITY REAR COVER SPACER PLATE

| Item number	RSI.1
Description	• Infinity rear cover spacer plate • 1mm to align rear cover if structure is not straight • use only if required
Suitable for	• Infinity system
Material finish	• silver frost • mill

RSI.1

RSI.1

94mm

100mm

1mm

INFINITY CLAMP KIT
SUITABLE FOR 15MM GLASS THICKNESS

Item number	CKI.15
Description	• Infinity clamp kit
Suitable for	• Infinity system • 15mm glass thickness
Material finish	• matt black

CKI.15

CKI

INFINITY STAND OFF PLATE

Item number	SOI.15
Description	• Infinity stand off plate • will stand the infinity system 15mm off the structure • use only if required
Suitable for	• Infinity system
Material finish	• silver frost • mill

SOI.15

SOI.15

94mm

100mm

15mm

INFINITY EXTRUSION END CAP

Item number	• ECI.124.6 no.6 plastic plug + 6g x 25 SS CS screw • ECI.124.7 no.7 plastic plug + z x 25 SS CS screw
Description	• infinity extrusion end cap complete with plugs and screws
Suitable for	• Infinity system
Material finish	• natural anodised • mill

ECI.124.6
ECI.124.7

ECI.124

INFINITY GLASS GASKET SET
FRONT AND REAR

Item number	• GGSI.F - front • GGSI.R - rear
Description	• Infinity glass gasket set front and rear
Suitable for	• Infinity system

GGSI.F
GGSI.R

Rear
150mm

100mm

GGSI

Front

INFINITY GLASS GASKET
SUITABLE FOR 12/15MM GLASS THICKNESS

Item number	12mm glass thickness • GGI.12F front - 2mm thick x 100mm wide • GGI.12R rear - 2mm thick x 150mm wide 15mm glass thickness • GGI.15F front - 1mm thick x 100mm wide • GGI.15R rear - 1mm thick x 150mm wide
Description	• Infinity glass gasket
Suitable for	• Infinity system • 12mm and 15mm glass thickness

GGI.12F
GGI.12R

GGI

INFINITY GLASS BULB SEAL

Item number	GBS.124
Description	• Infinity glass bulb seal
Suitable for	• Infinity system

GBS.124

GBS.124

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

RESIDENTIAL FLOOR MOUNT CHANNEL MONTREUX

EDC

EDC

EDCEND

AUSTRALIAN MADE

Item number	• EDC • EDCEND - end cap

Description	• residential floor mount channel Montreux
	• 1.25 meter, 2.5 meter and 5 meter stock lengths
	• supplied complete with clamping kits and cover plates
	• vertical adjustment up to 15mm
	• Out of plumb adjustment:
	  +/- 50mm @ 1 meter high
	  +/- 60mm @ 1.2 meters high
	• M10 coach screw at 200mm centres fixing in timber
	• M10 s/s epoxy bolts at 400mm centres fixing in concrete and steel
	• clamping kits no greater than 400mm centres
	• supporting base channel is anotec powder coated with 10 year warranty
	• PS1 available for use with Viridian 'Balustrade 100' toughened safety glass based on barrier loads from AS/NZS1170.1
	• very high wind zone 1.76 kPa or less
	• maximum heights above floor level are for residential occupancies A & C3 of Table 3.3 AS/NZS1170.1
	  – 1.1 meters from finish floor level
	  – 1.2 meter with glass corners at the top connected by elite glass balustrade clamps, or an interlinking handrail at 900mm to 1 meter, end panels must be connected to the building by clamps or interlinking rail

Suitable for	• 12mm or 13.52mm glass thickness • pool fencing protecting a fall of 1 meter or more
Material finish	• mill • silver pearl powdercoat • selected powdercoat (lead time applies)
Order	• specify glass thickness

GLASS CUT OUT DETAIL

R12.5

60mm

25mm

SIDE VIEW

100mm

12mm

89mm

25mm glass clearance

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

EDC

FIXING DETAIL - CONCRETE

EDC

90mm

90

M10 s.s. threaded rod in Ramset Epcon C6 anchor @ 400mm crs

50mm

FIXING DETAIL - TIMBER

Hard decking material

M10 s.s. coach screws at 200mm crs with minimum 120mm wood thread penetration

120mm

FIXING DETAIL - STEEL

Nylon washer and bush in hole

M10 s.s. bolts @ 400mm crs

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL FLOOR MOUNT CLAMP
GENOA

EYB

Item number	EYB
Description	• commercial floor mount clamp Genoa • stock lengths available in 1.2 meter, 2.4 meter and 4.8 meter • fixing options (concrete and steel) • end caps available • glass cut out required • 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass • based on design loads from AS/NZS 1170.1 and a maximum uls wind pressure of 2.13 kPa (extra high wind zone), minimum glass thicknesses are: – for commercial occupancies B, E and C3 of table 3.3 AS/NZS 1170.1, up to 1.1 meter high balustrade measured from floor level Viridian 'Balustrade 100' 15mm toughened safety glass or 17.5mm laminated toughened glass
Suitable for	• 15mm toughened and 17.5mm laminated glass
Material finish	• mill • silver pearl powdercoat • selected powdercoat (lead time applies)

EYB

GLASS CUT OUT DETAIL

Ø30

55mm

30mm

ELITE GLASS SOLUTIONS

JULY 2016

EYB

FIXING DETAIL - STEEL

EYB

powdercoated aluminium cover

M10 grade 316 stainless bolts @ 400mm centres

aluminium support

6mm thick setting block

stainless steel and nylon insulating washers

nylon insulating bush in hole

grade 316 stainless steel M10 bolts @ 400mm centres with nylon insulating bush in hole

stainless steel washer, spring washer and nylon insulating washer

69mm

grade 316 stainless steel M10 threaded rod @ 400mm centres

FIXING DETAIL - CONCRETE

SS316 M10 bolts @ 400mm centres

Powdercoated aluminium cover

6mm thick setting block

Aluminium support

SS316 shim/washer

50mm   69mm

SS316 M10 threaded rod in Ramset Epcon C6 anchor @ 400mm crs

FIXING DETAIL - STEEL CONCRETE FIXING PLATE

Grade 316 100x100x12 base plate @ 400mm crs

316 M12 bolt

Hilti HIS-RN M12 internally threaded sleeve in Ramset Epcon C6 anchor

Fixing to wall

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

RESIDENTIAL FACE FIX CHANNEL LUGANO

EFC

| Item number	EFC
Description	• residential face fix channel Lugano • stock lengths available in 1.2 meter, 2.4 meter or 4.8 meter • fixing options (concrete, steel, bolt through timber and lag screw) • recommended installation tools available • end, internal and external corner caps available • no glass cut outs or holes required • 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass • based on barrier loads from AS/NZS 1170.1, Viridian 12mm 'Balustrade 100' toughened safety glass or 13.5mm toughened laminated safety glass, maximum height above the channel is: – for residential occupancy A, B, C3 of Table 3.3 AS/NZS 1170.1, very high wind zone 1.76 kPa or less: 1.2 meters high with glass corners at top edge connected by elite glass balustrade clamps or with an interlinking rail at 900mm to 1 meter • end panels must be connected to the building by clamps or interlinking rail • extra high wind zone 2.13 kPa or less - 1.1 meter high without balustrade corner clamps or interlinking rail
Suitable for	• 12mm toughened and 13.5mm laminated glass • suitable for pool fencing protecting a fall of 1 meter or more
Material finish	• mill • silver pearl powdercoat • selected powdercoat (lead time applies)

EFC

FIXING DETAIL - CONCRETE

EFC

15 | 12 | 35mm | 10-20 | 90mm
100mm
52mm
166mm
50mm
M10 s.s. threaded rod in Ramset Epcon C6 anchor @ 600mm crs
90mm
25-35 mm
56mm
50mm
90mm

FIXING DETAIL - TIMBER SLATTED DECK BOLT THROUGH FIXING

40mm
M10 s.s. threaded rod at 600mm crs
90mm
40 x 40 x 3 s.s. front washers
40 x 40 x 3 s.s. back washers

FIXING DETAIL - TIMBER SLATTED DECK LAG SCREW FIXING

10-20 mm
35mm
100mm
52mm
40mm
25-35 mm
M10 s.s. @ 600mm crs maximum
90mm
40x40x3 front washers
130mm minimum penetration

FIXING DETAIL - TIMBER ENCLOSED DECK LAG SCREW FIXING

EFC

40 x 40 x 3 s.s. washer and EPDM gasket
40mm
M10 s.s. lag screws at 600mm crs maximum
90mm
Rigid cladding
20mm
90mm minimum penetration

FIXING DETAIL - STEEL (EXTERNAL & INTERNAL)

25mm
Hole and s.s. nut welded by others at 600mm crs maximum or nut with s.s and EPDM washer
90mm
Nylon bush in hole
steel structure by others
s.s. and EPDM washers

FIXING DETAIL - STEEL (INTERNAL)

25mm
M10 s.s. threaded rods at 600mm crs maximum. All holes drilled and tapped M10 by others
90mm
steel structure by others minimum 10mm thick

BALUSTRADE & GLASS FIXINGS

BALUSTRADE CHANNELS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL FACE FIX CLAMP
MONACO

Item number	EGL
Description	• commercial face fix clamp Monaco • stock lengths available in 1.2 meter, 2.4 meter and 4.8 meter • fixing options (concrete, steel and bolt through timber) • recommended installation tools available • end, internal and external corner caps available • glass cut out required • 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass • based on design loads from table 3.3 of AS/NZS 1170.1 and a maximum uls wind pressure of 3.0 kPa, minimum glass thicknesses and maximum balustrade heights measured from top of clamp are: – Occupancy B, E & C3 'Viridian Balustrade 100' 15mm toughened safety glass or 17.5mm toughened laminated safety glass up to 1.2 meters – Occupancy C1/C2 & D: Viridian 'Balustrade 100' 15mm toughened safety glass up to 1.1 meter with corner connectors, or Viridian 'Balustrade 100' 19mm toughened safety glass or 21.5mm laminated toughened glass up to 1.2 meter
Suitable for	• 15mm and 19mm toughened and 17.5mm and 21.5mm laminated glass
Material finish	• mill • silver pearl powdercoat • selected powdercoat (lead time applies)

EGL

GLASS CUT OUT DETAIL

Ø30

55mm

30mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

EGL

FIXING DETAIL - CONCRETE

EGL

15mm
30mm
10-20mm
90mm
50mm
166mm
25-35 mm

Grade 316 M10 stainless steel threaded rod in Ramset Epcon C6 anchor @ 400mm crs

FIXING DETAIL - TIMBER SLATTED DECK

15 mm
30 mm
10-20 mm
166mm
25-35 mm
90mm

40x40x3 s.s. back washers
M10 s.s. threaded rod at 400mm crs
40x40x3 s.s. front washers
40x40x3 s.s. back washers

FIXING DETAIL - STEEL

15 mm
30 mm
10-20 mm
166mm
25-35 mm
25mm
90mm

M10 s.s. thread rods/bolts @ 400mm crs maximum

Nylon bush in hole
EPDM and s.s. washers

BONDING AND SEALING
QUICK CEMENT FIXIT AND RAPID

Item number	BTI
Description	• bonding and sealing quick cement fixit and rapid • no corrosion enhancing effect with metals apart from lead • the appropriate quick cement for every application • quickly hardening • free from chlorides • high pressure and flexural strength • waterproof and free of cracks • fixit is pasty and can be poured for processing flowingly
Suitable for	• bonding and sealing • for quick interior and exterior anchoring and fixing of steel and plastic parts; for fixing cable ducts, switching units, pipes, gratings, consoles, protective edges, etc • anchoring door frames and windows • filling in gaps and holes • cement/concrete, chalk cement grout and cement attics • masonry and stone

BTI

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

BALUSTRADE & GLASS FIXINGS

MINI POSTS

MINI POSTS

MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST

Item number	ERP
Description	• milano post semi-frameless residential balustrade post • based on design loads from AS/NZS 1170.1 and a maximum uls wind pressure of 1.76 kPa (very high wind zone) • fixed at 1.65 meters centres • maximum height 1.1 meter • maximum glass overhang 500mm • PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• Viridian 'Balustrade 100' 10mm toughened safety glass or 11.5mm toughened laminate glass • residential occupancy A and C3
Material finish	• silver pearl powdercoat • selected powdercoat

ERP

ERP

Apply Simson ISR 70-08 sealant to post before placing glass

6 x 3mm thick PD169 tape

2 x 50mm long x 6mm thick single-sided tape stuck to edge of glass

No glass joint

EPL25031 backing rubber

Glass joint

Dow corning 580 silicon to gap, both sides of glazing bar

500mm maximum

500mm maximum

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

MILANO POST SEMI-FRAMELESS
RESIDENTIAL BALUSTRADE POST TOP FIXED

Item number	ERPT
Description	• milano post semi-frameless residential balustrade post top fixed • concrete or steel • supplied complete with fixing to suit substrate • four fixings per post • minimum edge distance for fixings is 50mm
Suitable for	• residential
Material finish	• mill finish • natural anodised

ERPT

ERPT

Optional handrail

1-1.1 meter

130mm

20mm 20mm

20mm

100mm

20mm

80mm

M8 csk bolt. Installer to apply
Duralac DTD269B to bolt,
cap and bar before fixing

Stainless
steel cap

2mm

Duralloy
powdercoated
aluminium post

10mm
toughened
or 11.5mm
toughened
laminated glass

M10xT316
s.s dome
nut, washer,
spring
washer,
insulating
nylon bush
and gasket

Ramset Epcon
C6 anchor with
M10 T316
threaded rod

90mm

50mm

MILANO POST SEMI-FRAMELESS
RESIDENTIAL BALUSTRADE POST FACE FIXED

| Item number	ERPF
Description	• milano post semi-frameless residential balustrade post face fixed • minimum edge distance for fixings is 60mm • two fixings per post
Suitable for	• concrete, steel or bolt through timber • residential
Material finish	• mill finish • natural anodised

ERPF

ERPF

Optional handrail

1-1.1 meter

100mm maximum

M8 csk bolt. Installer
to apply Duralac
DTD369B to bolt, cap
and bar before fitting

Stainless
steel cap

2mm

10mm
toughened
or 11.5mm
toughened
laminated glass

Duralloy
powdercoated
aluminium post

Ramset Epcon C6
anchor with M10 T316
s.s. threaded rod,
50x50x3 washer and
insulating nylon bush
and gasket

M10xT316 s.s
dome nut, washer,
spring washer,
insulating nylon
bush and gasket

60mm

150mm

270mm

150mm

60mm

110mm

Aluminium cap

MILANO POST SEMI-FRAMELESS RESIDENTIAL BALUSTRADE POST

Item number	ERPH
Description	• milano post semi-frameless residential balustrade post • concealed face fixed • minimum edge distance for fixings is 30mm • two fixings per post
Suitable for	• steel or bolt through timber • residential
Material finish	• mill finish • natural anodised

ERPH

ERPH

Optional handrail

1-1.1 meter

M8 csk bolt. Installer to apply Duralac DTD369B to bolt, cap and bar before fitting

Stainless steel cap

2mm

10mm toughened or 11.5mm toughened laminated glass

Duralloy powder coated aluminium post

100mm maximum

50x50x3 s.s washer with nylon insulating washer and gasket to separate stainless steel and aluminium

M12 x T316 s.s. bolt, washer, spring washer, insulating nylon bush and gasket

T316 s.s. nut and 50x50x3 washer

30mm

150mm

25mm

Aluminium cap

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST CONCRETE OR BOLT THROUGH TIMBER

Item number	ECP
Description	• milano post semi-frameless commercial balustrade post • concrete or bolt through timber • fixed at 1.1 meter centres • maximum height 1.1 meter • maximum glass overhang 500mm • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• Virdian 'Balustrade 100' 10mm toughened safety glass or 11.5mm toughened laminated glass • commercial occupancy B, E and C3
Material finish	• silver pearl powdercoat • selected powdercoat

ECP

Apply Simson ISR 70-08 sealant to post before placing glass

6 x 3mm thick PD169 tape

Dow corning 580 silicone to gap, both sides of glazing bar

EPL 25031 backing rubber

NO GLASS JOINT

GLASS JOINT

ECP

2x50mm long x 6mm thick single-sided tape stuck to edge of glass

500mm maximum

500mm maximum

JULY 2016

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO CONCRETE SUBSTRATE

Item number	ECPFC
Description	• milano post semi-frameless commercial balustrade post • face fixed to concrete substrate
Suitable for	• commercial occupancy B, E and C3
Material finish	• mill finish • natural anodised

ECPFC

ECPFC

Handrail as required

Commercial buildings and common areas of multi-unit dwellings

1.1 meter

Installer to apply Duralac DTD269B to bolts, cap and aluminium before fixing

2mm

Duralloy powdercoated aluminium post

Ramset Epcon C6 anchor with T316 s.s. threaded rod, 50x50x3 s.s. washer, nylon bush and gasket to separate stainless steel and aluminium

M12xT316 s.s. dome nut, s.s. washer, s.s. spring washer, nylon bush and gasket to separate aluminium and stainless steel

60
270mm   150mm   150mm
60
110mm

aluminium cap

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST FACE FIXED TO TIMBER SUBSTRATE

Item number	ECPFBT
Description	• milano post semi-frameless commercial balustrade post • face fixed to timber substrate
Suitable for	• commercial occupancy B, E and C3
Material finish	• mill finish • natural anodised

ECPFBT

ECPFBT

Handrail as required

All other buildings, and common areas of multi-unit dwellings

1.1 meter

80mm

2mm

10mm toughened or 11.5mm toughened laminated glass

Duralloy powdercoated aluminium post

50x50x3 s.s. washer with nylon insulating washer and gasket to separate stainless steel and aluminium

M12xT316 s.s. dome nut, s.s. washer, s.s. spring washer, nylon bush and gasket to separate aluminium and stainless steel

M12 x T316 bolt and 50x50x3 s.s. washer

150mm

aluminium cap

BALUSTRADE & GLASS FIXINGS

MINI POSTS

ELITE GLASS SOLUTIONS

JULY 2016

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST TOP FIXED TO CONCRETE SUBSTRATE

Item number	ECPTC
Description	• milano post semi-frameless commercial balustrade post • top fixed to concrete substrate
Suitable for	• commercial occupancy B, E and C3
Material finish	• mill finish • natural anodised

ECPTC

ECPTC

Handrail as requested

1.1 meter

Commercial buildings and common areas of multi-unit dwellings

130mm

20mm

100 mm

60mm

20mm

90mm

20mm

Installer to apply Duralac DTD269B to bolts, cap and aluminium before fixing

2mm

10mm toughened or 11.5mm toughened laminated glass

Duralloy powdercoated aluminium post

M10xT316 s.s dome nut, s.s. washer, s.s. spring washer, nylon bush and gasket to separate aluminium and stainless steel

Ramset Epcon C6 anchor with M10 T316 threaded rod

90mm

50mm

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5)

Item number	ECPR
Description	• milano post semi-frameless commercial balustrade post (C5) • two fixings per post • fixed at 1.1 meter centres • maximum height 1.1 meter • maximum glass overhang 300mm • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• concrete, steel or bolt through timber • commercial occupancy C1, C2, D and C5 • Viridian 'Balustrade 100' 15mm toughened safety glass or 17.2mm toughened laminated glass
Material finish	• silver pearl powdercoat • selected powdercoat

ECPR

Apply Simson ISR 70-08 sealant to post before placing glass

6 x 3mm thick PD169 tape

2 x 50mm long x 6mm thick single-sided tape stuck to edge of glass

EPL25031 backing rubber

No glass joint

Glass joint

Dow Corning 580 silicon to gap, both sides of glazing bar

300mm maximum

ECPR

MILANO POST SEMI-FRAMELESS
COMMERCIAL BALUSTRADE POST (C5)
SUITABLE FOR TIMBER

Item number	ECPRBT
Description	• milano post semi-frameless commercial balustrade post (C5) • substrate fixings are concealed
Suitable for	• commercial occupancy C1, C2, D and C5 • face fixed to timber substrate
Material finish	• mill finish • natural anodised

ECPRBT

ECPRBT

- Milano Europost
- s.s. bar insert
- Viridian 15mm toughened or 17.5mm toughened laminated safety glass
- M12 s.s. threaded rod, washer and spring washer, nylon bush and gasket

800mm
80mm
45mm
200mm
45mm

MILANO POST SEMI-FRAMELESS
COMMERCIAL BALUSTRADE POST (C5)
SUITABLE FOR STEEL

Item number	ECPRS
Description	• milano post semi-frameless commercial balustrade post (C5) • substrate fixings are concealed
Suitable for	• face fixed to steel substrate • commercial occupancy C1, C2, D and C5
Material finish	• mill finish • natural anodised

ECPRS

ECPRS

- Milano Europost
- s.s. bar insert
- Viridian 15mm toughened or 17.5mm toughened laminated safety glass
- M12 s.s. threaded rod, washer and spring washer, nylon bush and gasket

800mm
80mm
50mm
200mm
50mm

BALUSTRADE & GLASS FIXINGS

MINI POSTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

MILANO POST SEMI-FRAMELESS COMMERCIAL BALUSTRADE POST (C5)

Item number	ECPRC
Description	• milano post semi-frameless commercial balustrade post (C5) • substrate fixings are concealed
Suitable for	• face fixed to concrete substrate • commercial occupancy C1, C2, D and C5
Material finish	• mill finish • natural anodised

ECPRC

ECPRC

Milano Europost

s.s. bar insert

Viridian 15mm toughened or 17.5mm toughened laminated safety glass

800mm

80mm

60mm

200mm

M12 s.s. threaded rod in Ramset Epcon C6 anchor

60mm

320 x 125 x 12mm thick s.s. plate

110mm

CORE DRILLED FRICTION FIT MINI POST ROUND

Item number	EMP250.CD.FF.RD
Description	• core drilled friction fit mini post round • no holes in glass required • 285mm overall height • supplied with dress ring to conceal core drilling and M16 threaded rod for height adjustment
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP250.CD.FF.RD

EMP250.CD.FF.RD

19.25mm
90mm
40mm
M10-2X
78.5mm
19.25mm
10mm
30.5mm

5mm
10mm
160mm
Ø41.2

90°
16mm
100mm
185mm
285mm
Ø49
39.5mm
100mm
35.99mm

CORE DRILLED FRICTION FIT MINI POST SQUARE

Item number	EMP250.CD.FF.SQ
Description	• core drilled friction fit mini post square • no holes in glass required • 285mm overall height • supplied with dress ring to conceal core drilling and M16 threaded rod for height adjustment
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP250.CD.FF.SQ

EMP250.CD.FF.SQ

BASE MOUNTED FRICTION FIT MINI POST ROUND

Item number	EMP350.BM.FF.RD
Description	• base mounted friction fit mini post round • no holes in glass required • 156mm overall height • supplied with dress ring to conceal structural fittings
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP350.BM.FF.RD

EMP350.BM.FF.RD

BASE MOUNTED FRICTION FIT MINI POST ROUND

Item number	EMP350.BM.FF.RD
Description	• base mounted friction fit mini post round • 156mm overall height • no holes in glass required • supplied with dress ring to conceal structural fittings
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP350.BM.FF.RD

17mm
40mm
156mm

EMP350.BM.FF.RD

M8*2
48 mm
100mm
48 mm
100mm

BASE MOUNTED FRICTION FIT MINI POST SQUARE

Item number	EMP450.BM.FF.SQ
Description	• base mounted friction fit mini post square • 175mm height • no holes in glass required • supplied with dress ring to conceal structural fittings
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP450.BM.FF.SQ

R1 34mm
44.8mm
99mm M10
55mm
17.2mm
21.75mm
R2
Ø37.6
37.75mm
R1

EMP450.BM.FF.SQ

Ø82.22
Ø11
72.4mm
50 mm
50 mm
21.4mm
11mm
72.4mm

30mm
16 mm
42°
121mm
176.5mm
C1
C1
6.2 mm
R2
R3
6.5mm R1 R1 3.25mm
Ø105.3

BASE MOUNTED FRICTION FIT MINI POST ROUND

Item number	EMP450.BM.FF.RD
Description	• base mounted friction fit mini post round • 175mm height • no holes in glass required • supplied with dress ring to conceal structural fittings
Suitable for	• 10mm and 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

EMP450.
BM.FF.RD

EMP450.BM.FF.RD

EUROBRACE MINI POST ROUND

Item number	EB1
Description	• Eurobrace mini post round • posts are set into concrete (Ø50 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) • 26mm diameter holes in glass • 45mm typical clearance from ground surface • distance from inside face of glass and post centre is 40mm • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

EB1

EB1

GLASS CUT OUT DETAIL

JULY 2016

BALUSTRADE & GLASS FIXINGS

MINI POSTS

EUROBRACE MINI POST SQUARE

Item number	EB2
Description	• Eurobrace mini post square • posts are set into concrete (Ø50 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) • 26mm diameter holes in glass • 45mm typical clearance from ground surface • distance from inside face of glass and post centre is 32mm • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

EB2

EB2

GLASS CUT OUT DETAIL

CORE DRILLED MINI POST ROUND

Item number	FMP250
Description	• core drilled mini post round • set 85mm into concrete (Ø60 hole) and affixed using Sika or Rockite grout (to manufacturer's specifications) • 26mm diameter holes in glass • 45/50mm typical clearance from ground surface • PS1 available on request • optional ring (FMP205.R) and cover (FMP250.C) available
Suitable for	• 12mm and 15mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

FMP250

FMP250

GLASS CUT OUT DETAIL

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105

✉ sales@eliteglasssolutions.com.au

🌐 www.eliteglasssolutions.com.au

MINI POST RING

Item number	FMP205.R
Description	• mini post ring (optional)
Suitable for	• FMP250

FMP250.R

FMP250.R

51mm

80mm

MINI POST COVER

Item number	FMP250.C
Description	• optional post cover
Suitable for	• FMP250

FMP250.C

FMP250.C

51mm

125mm

BASE MOUNTED MINI POST ROUND

Item number	FMP350
Description	• based mounted mini post round • 26mm diameter holes in glass • 45mm - 50mm typical clearance from ground surface • posts can be fastened to concrete or wooden surfaces using two M10 bolts/screws • PS1 available on request.
Suitable for	• 12mm and 15mm glass thickness • concrete or wooden surfaces
Material finish	• 316 grade polished or satin stainless steel

FMP350

50mm

187mm

FMP350

Ø125

Ø90 PCD
4 holes

14

GLASS CUT OUT DETAIL

Ø26

77mm

45 mm

FFL

BALUSTRADE & GLASS FIXINGS

MINI POSTS

ELITE GLASS SOLUTIONS

JULY 2016

TILT-LOCK MINI POST
HEAVY DUTY RANGE

TL

Item number	TL
Description	• tilt-lock mini post heavy duty range
	• tilt-lock adjustable mounting systems are designed to support glass from 12mm to 25.52mm thickness using a vast range of fixing solutions
	• range of six models including top, side and edge mounting options provide installation answers to almost every mounting issue imaginable
	• without holes in the glass the system offers great flexibility, lower cost and fast installation
	• the tilt-lock feature of the mounting systems offers a unique and simple levelling method by tilting the glass vertical and locking the grub screws ensuring a perfect result in half the time
	• fully engineered tested
Suitable for	• 12mm to 25.52mm glass thickness
	• use with SGP
Material finish	• duplex 2205 polished or satin stainless steel

TILT AND LOCK
Tightening

GLASS TILT

LOWER SCREW

GLASS TILT

UPPER SCREW

Adjustment

30mm   30mm

1 meter

TILT-LOCK means "tilt and lock" a simple process that allows you to simply tilt the glass in the spigot to the correct alignment and lock the grub screws, for the perfect finish in half the time. **TILT-LOCK** is the only answer!

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

TILT-LOCK CORE DRILLED MINI POST

Item number	TL9642G
Description	• tilt-lock core drilled mini post
Suitable for	• 12mm through to 25.52mm glass thickness • no holes in glass required
Material finish	• duplex 2205 polished or satin stainless steel

TL9642G

32 mm
55mm
275mm
TL9642G
92mm
42mm

TILT-LOCK BASE MOUNTED MINI POST

Item number	TL9642B
Description	• tilt-lock base mounted mini post
Suitable for	• 12mm through to 25.52mm glass thickness • no holes in glass required
Material finish	• duplex 2205 polished or satin stainless steel

TL9642B

TL9642B
32 mm
55 mm
155mm
150mm
96mm
42mm
65mm

TILT-LOCK CORE DRILLED MINI POST COVER PLATE

Item number	• TL9642G.SCP - square • TL9642G.CP - round
Description	• tilt-lock core drilled mini post cover plate
Suitable for	• TL9642G mini post
Material finish	• duplex 2205 polished or satin stainless steel

TL9642G.
SCP/CP

TL9642G.CP
TL9642G.SCP

TILT-LOCK BASE MOUNTED MINI POST COVER PLATE

Item number	TL9642B.CP
Description	• tilt-lock base mounted mini post cover plate
Suitable for	• TL9642B mini post
Material finish	• duplex 2205 polished or satin stainless steel

TL9642B.
CP

TL9642B.CP

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TILT-LOCK BASE MOUNTED MINI POST
SQUARE BASE PLATE

Item number	STL9642B
Description	• tilt-lock base mounted mini post square base plate
Suitable for	• 12mm through to 25.52mm glass thickness • no holes in glass required
Material finish	• duplex 2205 polished or satin stainless steel

STL9642B

STL9642B

32 mm

55 mm

155mm

106mm

42mm

106mm

96mm

TILT-LOCK BASE MOUNTED MINI POST
SQUARE BASE PLATE COVER PLATE

Item number	STL9642B.CP
Description	• tilt-lock base mounted mini post square base plate cover plate
Suitable for	• STL9642B mini post
Material finish	• duplex 2205 polished or satin stainless steel

STL9642B.CP

STL9642B.CP

ELITE GLASS SOLUTIONS

TILT-LOCK SIDE FIX MINI POST

Item number	EDGE92
Description	• tilt-lock side fix mini post
Suitable for	• 12mm through to 25.52mm glass thickness • no holes in glass required
Material finish	• duplex 2205 polished or satin stainless steel

EDGE92

EDGE92

TILT-LOCK SIDE FIX CLAMP

| Item number	TLSF96
Description	• tilt-lock side fix clamp
Suitable for	• 12mm through to 25.52mm glass thickness • no holes in glass required
Material finish	• duplex 2205 polished or satin stainless steel

TLSF96

TLSF96

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

NAUTECH STRUT POST BASE FIX

NBF168

Item number	NBF168 (Patent NZP561106)
Description	• NauTech strut post - base fix • the system is a unique strut post design which is unobtrusive, strong and durable • the system features horizontal and vertical adjustment for the glass • the vertical adjustment is attained by the use of a patented clamping and adjustment technique which is the heart of the fitting, it clamps the glass without the need for holes and this saves on glass processing costs and installation time • the strut post is 168mm high and provides a 50mm clearance between the top of the deck and underside of the glass pane • the NauTech system has been tested in NZ to AS/NZS 1170 barrier loadings in accordance with B1/VM1 Amendment 8
Suitable for	• 12mm glass thickness (no holes or cutouts required) • domestic and commercial balustrades and pool fences • base fixing to masonry, timber and steel structures
Material finish	• 16mm thick 316 grade polished or satin stainless steel • bead blast

Ø11 20mm 12mm 70mm 100mm 16mm 168mm 50mm 8mm

NBF168

FIXING DETAIL - DOMESTIC WOOD FIX (CSW100)

50mm 60mm

FIXING DETAIL - DOMESTIC CONCRETE FIX (MF43)

50mm 60mm

BALUSTRADE & GLASS FIXINGS

MINI POSTS

NBF168

FIXING DETAIL - COMMERCIAL AND DOMESTIC STEEL FIX (SF25)

NBF168 — 50mm

FIXING DETAIL - COMMERCIAL AND DOMESTIC WOOD FIX (SBW120 OR DBW140)

50mm

60mm

FIXING DETAIL - COMMERCIAL CONCRETE FIX (DF100)

60mm

NAUTECH TWO STRUT POSTS PER PANEL SET OUT DETAILS

Domestic and residential occupancy A & A other (C3)			
H = 1 meter	X = 1 meter C = 200mm W = 1.4 meter	OR	X = 700mm C = 350mm W = 1.4 meter

Commercial occupancy C3, B and E	
H = 1.1 meter	X = 700mm, C = 150mm, W = 1 meter

Pool fence	
H = 1.2 meter	X = 1 meter, C = 500mm, W = 2 meters

TWO STRUTS

W, H, C, X, C

NAUTECH THREE STRUT POSTS PER PANEL SET OUT DETAILS

Domestic and residential occupancy A & A other (C3)			
H = 1 meter	X = 1 meter C = 200mm W = 2.4 meter	OR	X = 700mm C = 350mm W = 2.1 meter

Commercial occupancy C3, B and E	
H = 1.1 meter	X = 700mm, C = 150mm, W = 1.7 meters

Pool fence	
H = 1.2 meter	X = 1 meter, C = 500mm, W = 3 meters

THREE STRUTS

W, H, C, X, X, C

Note: Larger panels can be used by applying the above spacings.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

NAUTECH STRUT POST FACE FIX

NSF315

| Item number	NSF315 (Patent NZP561106)
Description	• NauTech strut post - face fix • the system is a unique strut post design which is unobtrusive, strong and durable • the system features horizontal and vertical adjustment for the glass • the vertical adjustment is attained by the use of a patented clamping and adjustment technique which is the heart of the fitting, it clamps the glass without the need for holes and this saves on glass processing costs and installation time • 315mm high in total (168 above FFL) and provides a 50mm clearance between the top of the deck and underside of the glass pane • the NauTech system has been tested in NZ to AS/NZS 1170 barrier loadings in accordance with B1/VM1 Amendment 8
Suitable for	• 12mm glass thickness (no holes or cutouts required) • domestic and commercial balustrades and pool fences • base fixing to masonry, timber and steel structures
Material finish	• 16mm thick 316 grade polished or satin stainless steel • bead blast

FIXING DETAIL - DOMESTIC WOOD FIX (CSW100)

FIXING DETAIL - DOMESTIC CONCRETE FIX (MF43)

ELITE GLASS SOLUTIONS

NSF315

FIXING DETAIL - COMMERCIAL AND DOMESTIC
STEEL FIX (SF25)

NSF315   50mm

minimum
100mm
thick steel

FIXING DETAIL - COMMERCIAL AND DOMESTIC
WOOD FIX (SBW120 OR DBW140)

50mm

20mm

FIXING DETAIL - COMMERCIAL CONCRETE FIX
(DF100)

NAUTECH TWO STRUT POSTS PER PANEL
SET OUT DETAILS

Domestic and residential occupancy A & A other (C3)			
H = 1 meter	X = 1 meter C = 200mm W = 1.4 meter	OR	X = 700mm C = 350mm W = 1.4 meter

Commercial occupancy C3, B and E	
H = 1.1 meter	X = 700mm, C = 150mm, W = 1 meter

Pool fence	
H = 1.2 meter	X = 1 meter, C = 500mm, W = 2 meters

TWO STRUTS

NAUTECH THREE STRUT POSTS PER PANEL
SET OUT DETAILS

Domestic and residential occupancy A & A other (C3)			
H = 1 meter	X = 1 meter C = 200mm W = 2.4 meter	OR	X = 700mm C = 350mm W = 2.1 meter

Commercial occupancy C3, B and E	
H = 1.1 meter	X = 700mm, C = 150mm, W = 1.7 meters

Pool fence	
H = 1.2 meter	X = 1 meter, C = 500mm, W = 3 meters

THREE STRUTS

Note: Larger panels can be used by applying the above spacings.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

STRUT POST BASE FIX

PL200

Item number	• PL200
	  silver frost powder coat
	• PL200.1
	  selected powder coat colour
	  one to five units
	• PL200.6
	  selected powder coat colour
	  six plus units

Description	• strut post base fix • compliant to AS/NZS1170 • adjustable for glass alignment • concealed fixings
Suitable for	• 12mm toughened glass • occupancy A, B, E and C3 • use in balustrades and pool fences
Material finish	• standard silver frost powder coat • available in special colours on request • powder coated aluminium

Stub post

PL200

Hidden fixing
cover plates

MAIN FEATURES FOR A BASE FIX BRACKET

65mm

12mm glass minimum
strength 100mpa

M8 x 20mm grub screws
(x3 off) clamp and tilt
adjustment torque to 5Nm

SP cover panels (x2 off)

clamp panels 3mm s.s.
and gasket material
(x2 off)

200mm

bottom gasket

M10 x 45mm hex bolt
and nut + washer (x 2
off) torque to 100Nm

82mm

M10 x 25mm s.s. screws
(x2 off) use thread lock when
attaching to base plate

12mm

selected base plate

ELITE GLASS SOLUTIONS

JULY 2016

STRUT POST FACE FIX

Item number	• PL400
	  silver frost powder coat
	• PL400.1
	  selected powder coat colour
	  one to five units
	• PL400.6
	  selected powder coat colour
	  six plus units

Description	• strut post face fix • compliant to AS/NZS1170 • adjustable for glass alignment • concealed fixings
Suitable for	• 12mm toughened glass • occupancy A, B, E and C3 • use in balustrades and pool fences
Material finish	• standard silver frost powder coat • available in special colours on request • powder coated aluminium

PL400

Stub Post   Stub Post

PL400

MAIN FEATURES FOR A SIDE FIX BRACKET

65mm

12mm glass minimum
strength 100mpa

M8 x 20 grub screws
(x 3 off) clamp and tilt
adjustment torque to Nm

SP cover panels (x 3 off)

clamp panels, 3mm s.s. and
gasket material (x 2 off)

bottom gasket

70mm

M10 x 45 s.s. hex bolt
and nut + washer (x 2 off)
torque to 100Nm

57
mm

400mm

suitable for M10 bolts or
coachscrews for face fixing

100
mm

screw cover panel

BALUSTRADE & GLASS FIXINGS

MINI POSTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

STRUT POST BASE FIX

Item number	SP155
Description	• strut post base fix • 155mm high and comes with drop on covers to hide the fixings
Suitable for	• 12mm toughened safety glass balustrades (no holes or cutouts required) • base fixing on top of masonry or other solid structures • occupancy A, B, C3, E and pool fences
Material finish	• 2205 duplex grade polished or satin stainless steel

SP155

155mm

SP155

TWO STRUT POST RESIDENTIAL SET OUT

1.4 meters

1 meter

200mm   1 meter   200mm

JULY 2016

GLASS CLAMPS

GLASS CLAMP ROUND PROFILE ROUND BACK
SUITABLE FOR 6/8MM GLASS THICKNESS

Item number	BCRD6
Description	• glass clamp - round profile • round back to suit 50mm tubular post
Suitable for	• 6mm and 8mm glass thickness • post mount
Material finish	• polished or satin stainless steel

BCRD6

BCRD6

38mm

53mm

14mm

6-8mm glass

24mm

GLASS CLAMP ROUND PROFILE FLAT BACK
SUITABLE FOR 6/8MM GLASS THICKNESS

Item number	BCFD6
Description	• glass clamp - round profile • flat back for fixing to square section and wall mounting
Suitable for	• 6mm and 8mm glass thickness • wall mount
Material finish	• polished or satin stainless steel

BCFD6

BCFD6

38mm

49mm

6-8mm glass

24mm

14mm

ELITE GLASS SOLUTIONS

JULY 2016

GLASS CLAMP ROUND PROFILE ROUND BACK
SUITABLE FOR 10/12MM GLASS THICKNESS

Item number	BCRD10
Description	• glass clamp - round profile • round back to suit 50mm tubular post
Suitable for	• 10mm and 12mm glass thickness • post mount
Material finish	• polished or satin stainless steel

BCRD10

GLASS CLAMP SQUARE PROFILE ROUND BACK
SUITABLE FOR 8/10MM GLASS THICKNESS

Item number	BCRS8
Description	• glass clamp - square profile • round back to suit 50mm tubular post
Suitable for	• 8mm and 10mm glass thickness • post mount
Material finish	• polished or satin stainless steel

BCRS8

GLASS CLAMP ROUND PROFILE FLAT BACK
SUITABLE FOR 10/12MM GLASS THICKNESS

Item number	BCFD10
Description	• glass clamp - round profile • flat back for fixing to square section and wall mounting
Suitable for	• 10mm and 12mm glass thickness • wall mount
Material finish	• polished or satin stainless steel

BCFD10

GLASS CLAMP SQUARE PROFILE FLAT BACK
SUITABLE FOR 8/10MM GLASS THICKNESS

| Item number	BCFS8
Description	• glass clamp - square profile • flat back for fixing to square section and wall mounting
Suitable for	• 8mm and 10mm glass thickness • wall mount
Material finish	• polished or satin stainless steel

BCFS8

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

## GLASS CLAMP SQUARE PROFILE ROUND BACK
SUITABLE FOR 10/12MM GLASS THICKNESS

Item number	BCRS10
Description	• glass clamp - square profile • round back to suit 50mm tubular post
Suitable for	• 10mm and 12mm glass thickness • post mount
Material finish	• polished or satin stainless steel

BCRS10

BCRS10

55mm
60mm
19mm
10-12mm glass
27mm

GLASS CLAMP SQUARE PROFILE FLAT BACK
SUITABLE FOR 10/12MM GLASS THICKNESS

Item number	BCFS10
Description	• glass clamp - square profile • flat back for fixing to square section and wall mounting
Suitable for	• 10mm and 12mm glass thickness • wall mount
Material finish	• polished or satin stainless steel

BCFS10

BCFS10

55mm
56mm
17mm
10-12mm glass
31mm

BALUSTRADE CLAMP GLASS TO GLASS

Item number	BCI
Description	• balustrade clamp - glass to glass • supplied with rubber gasket inserts
Suitable for	• 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BCI

BCI

typical height 25mm
70mm
12mm glass
12mm

BALUSTRADE CLAMP 90° CORNER

Item number	BC90
Description	• balustrade clamp - 90° corner • supplied with rubber gasket inserts
Suitable for	• 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BC90

BC90

12mm glass
13mm
70mm
12mm glass
80mm

BALUSTRADE CLAMP GLASS TO GLASS

Item number	BC135
Description	• balustrade clamp - 135° corner glass to glass
Suitable for	• 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

BC135

BC135

50mm
13.5mm
50mm
13.5mm

BALUSTRADE CLAMP WALL MOUNT

Item number	BCWM
Description	• balustrade clamp - wall mount • supplied with rubber gasket inserts
Suitable for	• 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BCWM

BCWM

70mm
12mm glass
24mm
18mm

BALUSTRADE CLAMP RECTANGLE
WALL MOUNT WITH LEG

Item number	BCWML
Description	• balustrade clamp wall mount with leg
Suitable for	• 12mm glass thickness
Material finish	• duplex 2205 polished or satin stainless steel

BCWML

BCWML

65mm
25mm
13.5mm
65mm

BALUSTRADE & GLASS FIXINGS

GLASS CLAMPS

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE BRACKET ROUND
WALL MOUNT

Item number	BB70
Description	• balustrade bracket round - wall mount
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BB70

BB70

10mm or 12mm glass

45mm   Ø8.4

70mm

54mm

5mm

50mm

35mm

GLASS CUT OUT DETAIL

Wall

Glass

Ø18

20 mm

34mm

BALUSTRADE BRACKET SQUARE
WALL MOUNT

Item number	BB70.SQ
Description	• balustrade bracket square - wall mount
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BB70.SQ

BB70.SQ

10mm or 12mm glass

45mm   Ø8.4

70mm

54mm

5mm

50mm

35mm

GLASS CUT OUT DETAIL

Wall

Glass

Ø18

20 mm

34mm

ELITE GLASS SOLUTIONS

BALUSTRADE BRACKET ROUND
GLASS TO GLASS

Item number	BBD70
Description	• balustrade bracket round - glass to glass
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BBD70

BBD70

33 mm 20 mm

Ø18 hole
in glass

45 mm

BALUSTRADE BRACKET SQUARE
GLASS TO GLASS

Item number	BBD70.SQ
Description	• balustrade bracket square - glass to glass
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

BBD70.SQ

BBD70.SQ

33 mm 20 mm

Ø18 hole
in glass

45 mm

BALUSTRADE & GLASS FIXINGS

GLASS CLAMPS

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

GLASS ANCHORS

GLASS ANCHOR BUTTON HEAD
WITH THREADED ROD OR LAG SCREW

Item number	• B19.M6 - 19mm button diameter • B25.M6 - 25mm button diameter • B32.M6 - 32mm button diameter • B32.M10 - 32mm button diameter
Description	• glass anchor button head, 10mm button thickness • threaded rod 30mm in length or lag screw 50mm in length • complete with plastic washer/spacer • select fixing (included - threaded rod or wood fix lag screw)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel (lead time applies - except B32.M10

B19/25/32

19mm, 25mm
or 32mm button
diameter

B19/25/32

FIXING OPTIONS
THREADED ROD OR WOOD FIX LAG SCREW

M6 and M10
30mm

10mm   Threaded rod

10mm

M6 50mm
M10 100mm

Wood fix lag screw

GLASS CUT OUT DETAIL

Ø10mm

B19/B25

Ø14mm

B32

JULY 2016

GLASS ANCHOR DOUBLE BUTTON HEAD

Item number	• BB19.M6 - 19mm button diameter • BB25.M6 - 25mm button diameter • BB32.M6 - 32mm button diameter • BB32.M10 - 32mm button diameter
Description	• glass anchor double button head, 10mm button thickness • complete with plastic washer/spacer
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel (lead time applies - except BB32.M10

BB19/25/32

19mm, 25mm or 32mm button diameter

10mm   10mm

BB19/25/32

please specify glass thickness

GLASS CUT OUT DETAIL

Ø10mm   Ø14mm

BB19/BB25   BB32

GLASS ANCHOR BUTTON HEAD AND BODY FIXING OPTIONS

Item number	BSOM
Description	• glass anchor button head and body fixing options – threaded rod – wood fix lag screw – hallow wall – timber insert – masonry

FIXING OPTIONS

Threaded rod

Wood fix lag screw

Hollow wall

Timber insert

Masonry

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

ELITE GLASS SOLUTIONS

JULY 2016

GLASS ANCHOR 19MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING

Item number	19mm button head diameter
	• BSOM6.19.10 19mm button diameter 10mm body length M6 thread 10mm hole in glass • BSOM6.19.20 19mm button diameter 20mm body length M6 thread 10mm hole in glass • BSOM6.19.30 19mm button diameter 30mm body length M6 thread 10mm hole in glass • BSOM6.19.50 19mm button diameter 50mm body length M6 thread 10mm hole in glass
Description	• glass anchor 19mm button head and body, M6 thread • 10mm button thickness • body length available in 10mm, 20mm, 30mm or 50mm • 10mm hole in glass required • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

BSOM6.19
BSOM6.19

Optional body length
10mm, 20mm, 30mm or 50mm

19mm button diameter

M6 thread

10mm button thickness

Optional fixing

GLASS CUT OUT DETAIL

Ø10mm

GLASS ANCHOR 25MM BUTTON HEAD AND BODY M6 THREAD WITH OPTIONAL FIXING

Item number	25mm button head diameter
	• BSOM6.25.10 25mm button diameter 10mm body length M6 thread 10mm hole in glass • BSOM6.25.20 25mm button diameter 20mm body length M6 thread 10mm hole in glass • BSOM6.25.30 25mm button diameter 30mm body length M6 thread 10mm hole in glass • BSOM6.25.50 25mm button diameter 50mm body length M6 thread 10mm hole in glass
Description	• glass anchor 25mm button head and body, M6 thread • 10mm button thickness • body length available in 10mm, 20mm, 30mm or 50mm • 10mm hole in glass required • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

BSOM6.25
BSOM6.25

Optional body length
10mm, 20mm, 30mm or 50mm

25mm button diameter

M6 thread

10mm button thickness

Optional fixing

GLASS CUT OUT DETAIL

Ø10mm

ELITE GLASS SOLUTIONS

GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING

Item number	32mm button head diameter

	• BSOM6.32.10
	  32mm button diameter
	  10mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM6.32.20
	  32mm button diameter
	  20mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM6.32.30
	  32mm button diameter
	  30mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM6.32.50
	  32mm button diameter
	  50mm body length
	  M10 thread
	  10mm hole in glass

Description	• glass anchor 32mm button and body, M10 thread • 10mm button thickness • body length available in 10mm, 20mm, 30mm or 50mm • 10mm hole in glass required • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

BSOM6.32

BSOM6.32

Optional body length
10mm, 20mm, 30mm or 50mm

32mm button diameter

M6 thread

Optional fixing

10mm button thickness

GLASS CUT OUT DETAIL

Ø14mm

GLASS ANCHOR 32MM BUTTON HEAD AND BODY M10 THREAD WITH OPTIONAL FIXING

Item number	32mm button head diameter

	• BSOM10.32.10
	  32mm button diameter
	  10mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM10.32.20
	  32mm button diameter
	  20mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM10.32.30
	  32mm button diameter
	  30mm body length
	  M10 thread
	  10mm hole in glass
	• BSOM10.32.50
	  32mm button diameter
	  50mm body length
	  M10 thread
	  10mm hole in glass

Description	• glass anchor 32mm button and body, M10 thread • 10mm button thickness • body length available in 10mm, 20mm, 30mm or 50mm • 10mm hole in glass required • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

BSOM10.32

BSOM10.32

Optional body length
10mm, 20mm, 30mm or 50mm

32mm button diameter

M10 thread

Optional fixing

10mm button thickness

GLASS CUT OUT DETAIL

Ø14mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105

sales@eliteglasssolutions.com.au

www.eliteglasssolutions.com.au

JULY 2016

GLASS ANCHOR COUNTER SUNK HEAD AND BODY FIXING OPTIONS

Item number	CBMSO
Description	• glass anchor counter sunk head and body fixing options – threaded rod – wood fix lag screw – hallow wall – timber insert – masonry

FIXING OPTIONS

Threaded rod

Wood fix lag screw

Hollow wall

Timber insert

Masonry

GLASS ANCHOR 18MM COUNTER SUNK HEAD 19MM BODY DIAMETER WITH OPTIONAL FIXING

| Item number	19mm body diameter

	• CBM6SO.19.10
	  19mm body diameter
	  10mm body length
	  M6 thread
	  18mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CBM6SO.19.20
	  19mm body diameter
	  20mm body length
	  M6 thread
	  18mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CBM6SO.19.30
	  19mm body diameter
	  30mm body length
	  M6 thread
	  18mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CBM6SO.19.50
	  19mm body diameter
	  50mm body length
	  M6 thread
	  18mm counter sunk head diameter
	  10mm counter sunk base diameter

Description	• glass anchor 18mm counter sunk head 19mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M6 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

CBM6 SO.19

CBM6SO.19

Optional body length
10mm, 20mm, 30mm or 50mm

M6 thread

Counter sunk head diameter 18mm

Optional fixing

Body diameter 19mm

Counter sunk base diameter 10mm

Glass hole preparation
A diameter = 18mm
B diameter = 10mm

90°
AØ
Head
BØ

ELITE GLASS SOLUTIONS

JULY 2016

GLASS ANCHOR 18MM COUNTER SUNK HEAD 25MM BODY DIAMETER WITH OPTIONAL FIXING

| Item number	25mm body diameter
	• CBM6SO.25.10 25mm body diameter 10mm body length M6 thread 18mm counter sunk head diameter 10mm counter sunk base diameter • CBM6SO.25.20 25mm body diameter 20mm body length M6 thread 18mm counter sunk head diameter 10mm counter sunk base diameter • CBM6SO.25.30 25mm body diameter 30mm body length M6 thread 18mm counter sunk head diameter 10mm counter sunk base diameter • CBM6SO.25.50 25mm body diameter 50mm body length M6 thread 18mm counter sunk head diameter 10mm counter sunk base diameter
Description	• glass anchor 18mm counter sunk head 25mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M6 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	32mm body diameter
	• CBM6SO.32.10 32mm body diameter 10mm body length M6 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM6SO.32.20 32mm body diameter 20mm body length M6 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM6SO.32.30 32mm body diameter 30mm body length M6 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM6SO.32.50 32mm body diameter 50mm body length M6 thread 24mm counter sunk head diameter 16mm counter sunk base diameter
Description	• glass anchor 24mm counter sunk head 32mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M6 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

CBM6SO.25

CBM6SO.25

Optional body length 10mm, 20mm, 30mm or 50mm

M6 thread

Counter sunk head diameter 18mm

Optional fixing

Body diameter 25mm

Counter sunk base diameter 10mm

Glass hole preparation
A diameter = 18mm
B diameter = 10mm

90°
AØ
Head
BØ

CBM6SO.32

CBM6SO.32

Optional body length 10mm, 20mm, 30mm or 50mm

M6 thread

Counter sunk head diameter 18mm

Optional fixing

Body diameter 32mm

Counter sunk base diameter 10mm

Glass hole preparation
A diameter = 18mm
B diameter = 10mm

90°
AØ
Head
BØ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

GLASS ANCHOR 24MM COUNTER SUNK HEAD 32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	32mm body diameter
	• CBM10SO.32.10 32mm body diameter 10mm body length M10 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM10SO.32.20 32mm body diameter 20mm body length M10 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM10SO.32.30 32mm body diameter 30mm body length M10 thread 24mm counter sunk head diameter 16mm counter sunk base diameter • CBM10SO.32.50 32mm body diameter 50mm body length M10 thread 24mm counter sunk head diameter 16mm counter sunk base diameter
Description	• glass anchor 24mm counter sunk head 32mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M10 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

GLASS ANCHOR 22MM COUNTER SUNK HEAD WITH CAP 19MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	19mm body diameter
	• CCBM6SO.19.10 19mm body diameter 10mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter • CCBM6SO.19.20 19mm body diameter 20mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter • CCBM6SO.19.30 19mm body diameter 30mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter • CCBM6SO.19.50 19mm body diameter 50mm body length M6 thread 22mm counter sunk head diameter 10mm counter sunk base diameter
Description	• glass anchor counter sunk head with cap 19mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M6 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

CBM10 SO.32

CBM10SO.32

Optional body length 10mm, 20mm, 30mm or 50mm

M10 thread

Counter sunk head diameter 24mm

Optional fixing

Body diameter 32mm

Counter sunk base diameter 16mm

Glass hole preparation
A diameter = 24mm
B diameter = 16mm

90°
AØ
Head
BØ

CCBM6 SO.19

CCBM6SO.19

Optional body length 10mm, 20mm, 30mm or 50mm

M6 thread

Counter sunk head diameter 22mm

Optional fixing

Body diameter 19mm

Counter sunk base diameter 10mm

Glass hole preparation
A diameter = 22mm
B diameter = 10mm

90°
AØ
Head
BØ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

GLASS ANCHOR COUNTER SUNK HEAD WITH CAP
25MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	25mm body diameter

	• CCBM6SO.25.10
	  25mm body diameter
	  10mm body length
	  M6 thread
	  22mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CCBM6SO.25.20
	  25mm body diameter
	  20mm body length
	  M6 thread
	  22mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CCBM6SO.25.30
	  25mm body diameter
	  30mm body length
	  M6 thread
	  22mm counter sunk head diameter
	  10mm counter sunk base diameter
	• CCBM6SO.25.50
	  25mm body diameter
	  50mm body length
	  M6 thread
	  22mm counter sunk head diameter
	  10mm counter sunk base diameter

Description	• glass anchor counter sunk head with cap 25mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M6 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

GLASS ANCHOR COUNTER SUNK HEAD WITH CAP
32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	32mm body diameter

	• CCBM6SO.32.10
	  32mm body diameter
	  10mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM6SO.32.20
	  32mm body diameter
	  20mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM6SO.32.30
	  32mm body diameter
	  30mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM6SO.32.50
	  32mm body diameter
	  50mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter

Description	• glass anchor counter sunk head with cap 32mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M10 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

CCBM6 SO.25

Optional body length
10mm, 20mm, 30mm or 50mm

CCBM6SO.25

Counter sunk head diameter 22mm

M6 thread

Optional fixing

Body diameter 25mm

Counter sunk base diameter 10mm

90°
AØ
Head

Glass hole preparation
A diameter = 22mm
B diameter = 10mm

BØ

CCBM6 SO.32

Optional body length
10mm, 20mm, 30mm or 50mm

CCBM6SO.32

Counter sunk head diameter 30mm

M6 thread

Optional fixing

Body diameter 32mm

Counter sunk base diameter 18mm

90°
AØ
Head

Glass hole preparation
A diameter = 22mm
B diameter = 10mm

BØ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

GLASS ANCHOR COUNTER SUNK HEAD WITH CAP
32MM BODY DIAMETER WITH OPTIONAL FIXING

Item number	32mm body diameter

	• CCBM10SO.32.10
	  32mm body diameter
	  10mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM10SO.32.20
	  32mm body diameter
	  20mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM10SO.32.30
	  32mm body diameter
	  30mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter
	• CCBM10SO.32.50
	  32mm body diameter
	  50mm body length
	  M10 thread
	  30mm counter sunk head diameter
	  18mm counter sunk base diameter

Description	• glass anchor counter sunk head with cap 32mm body diameter • body length available in 10mm, 20mm, 30mm or 50mm • M10 thread • select fixing (threaded rod, wood fix lag screw, hallow wall, timber insert or masonry)
Suitable for	• 6mm, 8mm, 10mm and 12mm glass thickness
Material finish	• 304 grade polished or satin stainless steel

CCBM10 SO.32

CCBM10SO.32

Optional body length
10mm, 20mm, 30mm or 50mm

M10 thread

Counter sunk head diameter 30mm

Optional fixing

Counter sunk base diameter 18mm

Body diameter 32mm

90°
AØ
Head

Glass hole preparation
A diameter = 30mm
B diameter = 18mm

BØ

EUROANCHOR 38MM DIAMETER
STEPPED DISC

Item number	EUBFSD38
Description	• euroanchor 38mm stepped disc • anodised to over 20um • 20mm spacer, M8 • includes washer, PVC sleeve and fixing (threaded rod only) • glass fixing hole 20mm diameter • fixing centres are set as per PS1 • PS1 available on request
Suitable for	• concrete, steel and timber
Material finish	• satin silver anodised • 316 grade polished or satin stainless steel

EUBFSD38

10mm   20mm

38mm

EUBFSD38

GLASS CUT OUT DETAIL

Ø20

EUROANCHOR 50MM DIAMETER STEPPED DISC

Item number	• EUBFSD50
	  includes 25mm thick spacer
	• EUBFSD51
	  includes 10mm thick spacer

Description	• euroanchor 50mm stepped disc • anodised to over 20um • includes washer, PVC sleeve and fixing (threaded rod or lag screw) • glass fixing hole 26mm diameter • 25mm spacer can be threaded M10 or 10.5mm through hole • fixing centres as per PS1 • PS1 available on request
Suitable for	• concrete, steel and timber
Material finish	• satin silver anodised • 316 grade polished or satin stainless steel

EUBFSD50

12mm 25mm

50mm

EUBFSD50

GLASS CUT OUT DETAIL

Ø26

EUROANCHOR 50MM DIAMETER COUNTER SUNK STEPPED DISC

Item number	EUBFCS
Description	• euroanchor 50mm counter sunk stepped disc • spacers available in 10mm or 25mm • includes washer, PVC sleeve and fixing (threaded rod or lag screw) • glass fixing hole 22mm diameter • 25mm spacer threaded M10 • M10 counter sunk hex bolt 35mm • fixing centres as per PS1 • PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• concrete, steel and timber
Material finish	• 316 grade polished or satin stainless steel

EUBFCS

50mm

EUBFCS

GLASS CUT OUT DETAIL

Ø22

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

EUROANCHOR 50MM DIAMETER SQUARE STEPPED DISC

Item number	EUBFSQ
Description	• euroanchor 50mm square stepped disc • includes washer, PVC sleeve and fixing (threaded rod or lag screw) • glass fixing hole 26mm diameter • fixing centres as per PS1 • PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• concrete, steel and timber
Material finish	• 316 grade polished or satin stainless steel

EUBFSQ

12mm 25mm
50mm

EUBFSQ

GLASS CUT OUT DETAIL

Ø26

EUROANCHOR RECTANGULAR STEPPED DISC

Item number	EUBFSQD
Description	• euroanchor rectangular stepped disc • double 25mm spacer 10.5mm through hole • includes washer, PVC sleeve and fixing (threaded rod or lag screw) • glass fixing hole 22mm diameter • fixing centres as per PS1 • PS1 available on request for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• concrete, steel and timber
Material finish	• satin silver anodised • 316 grade polished or satin stainless steel

EUBFSQD

11mm 27mm
90mm minimum embedment
164 mm
110mm

EUBFSQD

GLASS CUT OUT DETAIL

Ø22

ELITE GLASS SOLUTIONS

GLASS ANCHOR ADJUSTABLE

MB50

MB50 INNOVATIVE AND SUPERIOR FEATURES

1. Cap with snake eyes and chamfered edge to match mounting body. Square edge cap with countersunk machine screw fixing also available.

2. Step in cap allows correct penetration of M10 threaded rod.

3. 49mm x 1mm acetal plastic cap washer.

4. M10 threaded rod to suit 12mm toughened glass, other lengths available on request.

5. 49mm x 1mm acetal plastic mounting body washer with integrated bush.

6. Step in mounting body in conjunction with washer/bush aids in supporting the glass panel while the caps are being installed and during adjustment.

7. Mounting body is adjustable for a wall clearance between 40mm and 50mm via the use of an allen key through the centre before and after installation of the glass panels.

8. Recessed mark in mounting body indicates maximum recommended adjustment of 10mm.

9. Recess for rubber O-Ring.

10. Rubber O-Ring creates friction for finer adjustment, restricts movement prior to glass panels being installed and also helps to prevent foreign matter entering the inside of the anchor.

11. Allen key recess at centre of the base body allows tightening onto M10 threaded rods and helps with insertion of lagscrews into timber with the use of a battery drill and allen key bit.

12. Base body.

13. Recess in base body allows for tightening hard against concrete slab after excess epoxy may have emerged around the M10 threaded rod.

14. 115mm x M10 threaded rod. Other fixing methods including lagscrews available on request.

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS ANCHOR 50MM DIAMETER
## ADJUSTABLE

Item number	• MB50.AS.T45.40 40mm length • MB50.AS.T45.50 50mm length • MB50.CS.AS.T45 counter sunk
Description	• glass anchor 50mm diameter adjustable anchor • adjustable with allen key before and after installation • passed AS/NZS1170 testing loads due to a 20mm diameter glass hole preparation and 50mm diameter mounting body/cap • telescopic body hides the thread for a seamless appearance
Suitable for	• 12mm toughened glass thickness
Material finish	• polished or satin stainless steel

MB50. AS.T45

MB50.AS.T45

MB50. CS.AS.T45

MB50.CS.AS.T45

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

PLATEFIX SINGLE ANCHOR

Item number	PF150
Description	• the PlateFix PF150 was born from the double disc fixings by joining the discs into a single piece profile base plate with a outer clamping plate for a stronger multipurpose balustrade fixing. This enables the PF150 to be used with single or double fixings and it can be used vertically, horizontally, angled or a combination of the above
Suitable for	• concrete, steel and timber
Material finish	• 316 grade polished or satin stainless steel • bead blast

PF150

PF150

150mm
50 mm
6mm
20mm
20 mm
100 mm

TYPICAL SET OUT 400MM MAXIMUM CENTRES

H
50 mm
400 mm
400 mm
400 mm
400 mm
400 mm
400 mm 150 mm 150 mm
150 150 mm mm
400 mm
150 400 mm mm

Domestic installation H = 550mm 10mm toughened glass
Domestic installation H = 1,050mm 12mm toughened glass
Commercial installation H = 1,250mm 15mm toughened glass
Pool fence installation H = 1,250mm 12mm toughened glass
Note: X is from centre of top fixing to top edge of glass

PF150

INSTALLATION
COMMERCIAL GLASS THICKNESS 15MM
DOMESTIC GLASS THICKNESS 12MM

Typical PF150 fixing details to comply with AS/NZS1170. Full details available on request.

TIMBER SINGLE POINT FIX - WOOD FIX CBW - 130

STEEL SINGLE POINT FIX - METAL FIX SF50 - 12

CONCRETE SINGLE POINT FIX - HILTI 12MM MF125

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PF150

INSTALLATION
COMMERCIAL GLASS THICKNESS 15MM
DOMESTIC GLASS THICKNESS 12MM

Typical PF150 fixing details to comply with AS/NZS1170. Full details available on request.

TIMBER DOUBLE POINT FIX - WOOD FIX CBW - 120

STEEL DOUBLE POINT FIX - METAL FIX SF50 - 10

### CONCRETE DOUBLE POINT FIX - HILTI 10MM MF110

PF150

DESIGN OPTIONS
BALUSTRADE SYSTEM VARIATIONS

Fitting variations shown relate to design table PF150. Full details available on request.

minimum 1 meter

H

Option A

45°   X   maximum 200mm
minimum 50mm

minimum 1 meter

H

Option B

45°   X   maximum 200mm
minimum 50mm

minimum 1 meter

H

Option C

X   maximum 200mm
minimum 50mm

minimum 1 meter

H

Option D

X   maximum 200mm
minimum 50mm   minimum 100mm

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

PRADIS RESIDENTIAL BALUSTRADE SYSTEM

Item number	PRADIS
Description	• Pradis residential balustrade system • the system complies with New Zealand Building Code Clauses B1 Structure, F2 Hazardous Building Materials and F4 Safety from falling third edition, subject to: – all products meeting the required performance specification – site installation carried out in accordance with intent of this drawing – minimum balustrade height of 1 meter from finished floor level • based on 12mm Viridian "Balustrade 100" toughened safety glass, maximum height of glass above the top of the clamp for residential occupancies A and C3 of Table 3.3 AS/NZS 1170.1 and clamp spacings are: – very high wind zone 1.76 kPa - maximum height 1.1 meter – Pradis clamps @ 800mm crs for steel, concrete and bolt through with timber – Pradis clamps @ 600mm crs for timber with lagscrew • the design of the concrete, steel or timber support for the balustrade is the responsibility of others. • a handrail of 32mm - 50mm diameter is required for stairs and ramps exceeding 1:20 slope. Refer NZBC D1/AS1. • the guidance on narrier design published by the Department of Building and Housing states that if any part of the balustrade panel is 5 meters or higher than the ground or floor below, an interlinking handrail or laminated toughened glass with a top rail or capping to protect the edge should be provided. Fit handrail 900mm above floor level.

Description	• minimum width of glass panel is 1 meter unless connected by interlinking handrail or mechanical connector to adjacent panels • maximum distance from side edge of glass to fixings - 200mm for both occupancies. • this system is not suitable for balustrades in areas susceptible to overcrowding such as theatres, cinemas, assembly halls, stadiums etc.
Suitable for	• concrete, internal, wet exposed SG8 timber and dry concealed SG8 timber
Material finish	• satin • anodised aluminium

GLASS CUT OUT DETAIL

Ø30mm

PRADIS

PRADIS BALUSTRADE SYSTEM - RESIDENTIAL

- Handrail as required
- 1.1 meter maximum to top of clamp
- Viridian 12mm "Balustrade 100" toughened safety glass
- Pradis clamps
- Support structure by others. Refer note 3 and fixing details. Face of support must be plumb.

FIXING DETAIL - CONCRETE

- Elite satin anodised Pradis clamp @ 800crs
- 40mm
- 110mm
- 150mm
- Solid packing if required
- SS316 M12 threaded rod in Ramset Epcon C6 anchor
- Minimum 25 MPA concrete

FIXING DETAIL - DRY CONCEALED SG8 TIMBER

- Elite satin anodised Pradis clamp @ 600 crs
- 40mm
- SS 316, M12 lags crews at 600mm crs maximum with Sika anchor fix 3 or Hilti RE-500 epoxy to be installed strictly in accordance with Elite instructions
- 150mm
- Solid packing if required
- 90mm minimum penetration

PRADIS

FOR INTERNAL INSTALLATION ONLY

- Elite satin anodised Pradis clamp @ 800crs
- 40mm
- Flooring
- Steel structure by others
- SS316 M12 threaded rod. All holes drilled and tapped M12 by others
- 150mm
- Minimum 12mm thick steel
- Solid packing if required

FOR INTERNAL INSTALLATION ONLY

- Elite satin anodised Pradis clamp @ 800crs
- 40mm
- Flooring
- Steel structure by others
- M12 stainless steel 316 threaded rod, hole and stainless nut welded by others
- 150mm
- minimum 12mm thick steel
- Solid packing if required

FIXING DETAIL - WET EXPOSED SG8 TIMBER

- SS 316, M12 lags crews at 600mm crs maximum with Sika Anchor fix 3 or Hilti RE-500 epoxy to be installed strictly in accordance with Elite instructions
- Elite satin anodised Pradis clamp @ 600crs
- 40mm
- 150mm
- Solid packing if required
- 135mm minimum penetration

FIXING DETAIL - SG8 TIMBER (BOLT THROUGH)

- Elite satin anodised Pradis clamp @ 600crs
- 40mm
- M12, S.S 316 threaded rod
- 150mm
- 50x50x3mm stainless steel washer
- Solid packing if required

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

JULY 2016

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

## PRADIS COMMERCIAL BALUSTRADE SYSTEM

Item number	PRADIS
Description	• this system complies with New Zealand Building Code Clauses B1 Structure, F2 Hazardous building materials and F4 Safety from falling third edition, subject to: – all products meeting the required performance specification – site installation carried out in accordance with intent of this drawing – minimum balustrade height of 1.1 meters from finished floor level. • based on 15mm Viridian toughened safety glass, maximum heights of glass above the top of the clamps for commercial occupancies B, E and C3 of table 3.3 AS/NZS 1170.1 and clamp spacings are: – extra high wind zone 2.13 kPa - maximum height 1.2 meters – Pradis clamps @ 800mm crs for all occupancies. • a handrail of 32-50mm diameter is required for stairs and ramps exceeding 1:20 slope. Refer NZBC D1/AS1. • the Guidance on Barrier Design published by the Department of Building and Housing states that if any part of the balustrade panel is 5 meters or higher than the ground or floor below, an interlinking handrail or laminated toughened glass with a top rail or capping to protect the edge should be provided. Fit handrail 900mm above floor level. • minimum width of glass panel is 1 meter unless connected by interlinking handrail or mechanical connector to adjacent panels • maximum distance from side edge of glass to fixings - 200mm for both occupancies. • this system is not suitable for balustrades in areas susceptible to overcrowding such as theatres, cinemas, assembly halls, stadiums etc.

PRADIS

PRADIS BALUSTRADE SYSTEM - COMMERCIAL

Handrail as required

1.2 meters maximum to top of clamp

Viridian 15mm toughened safety glass

Pradis clamps @ 800mm crs

FIXING DETAIL - CONCRETE

Elite satin anodised Pradis clamp @ 800 crs

40mm

110mm

150mm

Minimum 25 MPA concrete

Solid packing if required

SS316 M12 threaded rod in Ramset Epcon C6 anchor

FIXING DETAIL - SG8 TIMBER BOLT THROUGH

Elite satin anodised Pradis clamp @ 800 crs

40mm

150mm

M12, stainless steel 316 threaded rod with nut

50x50x3mm stainless steel washer

Solid packing if required

JULY 2016

PRADIS

FOR INTERNAL INSTALLATION ONLY

Elite satin
anodised
Pradis clamp
@ 800 crs

40mm

SS316 M12
threaded rod.
All holes drilled
and tapped M12
by others

150mm

Minimum
12mm thick steel

Solid packing if required

FOR INTERNAL INSTALLATION ONLY

Elite satin
anodised
Pradis clamp
@ 800 crs

40mm

M12, stainless
steel 316 threaded
rod, hole and
stainless steel nut
welded by others

150mm

Minimum
12mm thick steel

Solid packing
if required

GLASS CUT OUT DETAIL

Ø30mm

ELITE GLASS
SOLUTIONS

JULY 2016

EUROANCHOR BALUSTRADE SYSTEM
RESIDENTIAL INSTALLATION EXAMPLES

EUBFSD

Examples using these item numbers	• EUBFSD.50 includes 25mm thick spacer • EUBFSD.51 includes 10mm thick spacer • EUBFSQ • EUBFCS • EUBFSQD
Description	• maximum distance from side edge of glass to fixings is 300mm for occupancy A and 200mm for occupancy C3 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• residential occupancies A, B, C3 of Table 3.3 AS/NZS 1170.1 based on 12mm Viridian 'Balustrade 100' toughened safety glass, maximum heights of glass above top anchors for residential occupancies A and C3 of Table 3.3 AS/NZS 1170.1 are: – very high wind zone 1.76 kPa - 1.1 meters – high wind zone 1.36 kPa - 1.2 meters with corner connectors or interlinking handrail
Material finish	• 316 grade polished or satin stainless steel

BALUSTRADE SYSTEM - RESIDENTIAL

Viridian 12mm "Balustrade 100" toughened safety glass

EUBFSD

Optional handrail

High wind zone 1.36 kPa 1.2 maximum with corner connectors or interlinking handrail. Very high wind zones 1.76 kPa - 1.1 meter maximum

1 meter minimum for private dwelling of residential buildings

FIXING DETAIL - CONCRETE

Euroglass EUBFSD50 @ 600mm crs for occupancy A 400mm crs for occupancy C3

50mm minimum

110mm

50mm minimum

25mm   90mm

FIXING DETAIL - TIMBER SLATTED DECK BOLT THROUGH

Euroglass EUBFSD50 @ 600mm crs for occupancy A 400mm crs for occupancy C3

40mm

110mm

40mm

M10 grade 316 s.s. bolt and 50mm x 50mm x 3mm s.s. washer

25mm

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

EUBFSD

FIXING DETAIL - TAPPED STEEL INTERNAL ONLY

EUBFSD

Euroglass EUBFSD50 @
600mm crs for occupancy A
400mm crs for occupancy C3

25mm minimum

All holes drilled and tapped M10 by others

Neoprene or EPDM gasket

110mm

Steel structure by others. Minimum 10mm thick

25mm minimum

FIXING DETAIL - STEEL

Flooring

Euroglass EUBFSD50 @
600mm crs for occupancy A
400mm crs for occupancy C3

25mm minimum

Nylon insulating bush

Neoprene or EPDM gasket

110mm

Steel structure by others

Stainless steel nut welded to PFC by others

25mm minimum

25mm

FIXING DETAIL - TIMBER LEG SCREW INTERNAL ONLY

Euroglass EUBFSD50 with threaded spacer @ 600mm crs for occupancy A

Flooring

40mm

110mm

M10 s.s. lag screws

40mm

90mm minimum penetration

EUBFSD

FIXING DETAIL - WEATHERED, ANGLE SPACER ENCLOSED DECK ONLY

EUBFSD

190mm

Waterproofing and flashing by others

Sealant in hole

20mm minimum

M10 s.s. lag screws

110mm minimum

20mm minimum

s.s. shim and EPDM gasket

90mm minimum penetration

Weatherboard

45mm wide radiata cavity batten fixed directly behind each anchor

FIXING DETAIL - TIMBER, CAVITY CLADDING ENCLOSED DECK

175mm

Waterproofing and flashing design by others

Euroglass EUBFSD50 @ 400mm crs for occupancy C3

5mm minimum

40mm

Neoprene or EPDM gasket

Sealant in hole

110mm

M10 s.s. lag screw

40mm

Use threaded spacer for non-rigid cladding to avoid crushing

25mm

90mm minimum penetration

Rigid wall cladding

45mm wide radiata cavity batten fixed directly behind each anchor

FIXING DETAIL - TIMBER LEG SCREW SLATTED DECK

Euroglass EUBFSD50 @ 400mm crs for occupancy C3

175mm

40mm

110mm

M10 s.s. lag screw

40mm

25mm

130mm minimum penetration

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

EUROANCHOR BALUSTRADE SYSTEM COMMERCIAL INSTALLATION EXAMPLES

EUBFSD

Item number	• EUBFSD.50 includes 25mm thick spacer • EUBFSD.51 includes 10mm thick spacer • EUBFSQ • EUBFCS • EUBFSQD
Description	• 10 year warranty • PS1 available for use with Viridian 'Balustrade 100' toughened safety glass
Suitable for	• commercial occupancies B, E, C3 of Table 3.3 AS/NZS 1170.1 based on 15mm Viridian 'Balustrade 100' toughened safety glass, maximum heights of glass above top anchors for commercial occupancies B, E, C3 of Table 3.3 AS/NZS 1170.1 are: – extra high wind zone 2.13 kPa - 1.2 meters
Material finish	• 316 grade polished or satin stainless steel

BALUSTRADE SYSTEM - COMMERCIAL

Viridian 15mm toughened safety glass

Optional handrail

EUBFSD

1.2 meters maximum

1.1 meter minimum for other buildings and public areas of residential buildings

Structural concrete (25 mPa minimum)

FIXING DETAIL - CONCRETE

Euroglass EUBFSD50 @ 400mm crs

90mm

50mm

150mm minimum

60mm

30mm, 40mm or 50mm

Grade 316 s.s. M10 threaded rod in Ramset
1. Epcon C6 anchor, or
2. SS316 TCM threaded cast in anchor


ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

EUBFSD

FIXING DETAIL - TIMBER SLATTED DECK BOLT-THROUGH

EUBFSD

Euroglass EUBFSD50 @ 400mm crs

30mm

150mm minimum

M10 grade 316 s.s. bolt and 50 x 50 x 3mm s.s. washer

Floor joist/nog to building code

30mm, 40mm or 50mm

Boundary joist strapped to floor joist/nog by others to building code

FIXING DETAIL - STEEL

Flooring

Euroglass EUBFSD50 @ 400mm crs

25mm minimum

Nylon insulating bush

Neoprene or EPDM gasket

Steel structure by others

110mm

Stainless steel nut welded to PFC by others

25mm minimum

25mm

BALUSTRADE ANCHOR HEAVY WEIGHT 50MM SQUARE EDGE HEAD

Item number	MB50.S
Description	• balustrade anchor heavy weight 50mm square edge head • 6mm standoff • glass to cleat fixing
Suitable for	• 10mm, 12mm and 15mm toughened glass
Material finish	• 316 grade machined, polished or satin stainless steel

MB50.S

MB50.S

BALUSTRADE ANCHOR HEAVY WEIGHT 50MM ROUND EDGE HEAD

Item number	MB50.R
Description	• balustrade anchor heavy weight 50mm round edge head • 6mm standoff • glass to cleat fixing
Suitable for	• 10mm 12mm and 15mm toughened glass
Material finish	• 316 grade machined, polished or satin stainless steel

MB50.R

MB50.R

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE ANCHOR HEAVY WEIGHT
50MM ROUND EDGE HEAD OPTIONAL FIXING

Item number	MB50.R.T30
Description	• Balustrade anchor heavy weight 50mm round edge head • 6mm standoff • glass to cleat fixing • optional fixings ordered separately (threaded rod or stainless steel/ zinc plated lag screw)
Suitable for	• 10mm, 12mm and 15mm toughened glass
Material finish	• 316 grade machined, polished or satin stainless steel

MB50.R.T30

MB50.R.T30

MB50.R.T30

FIXING DETAIL - DOMESTIC AND COMMERCIAL CONCRETE INSTALLATION WITH M10-R115 STAINLESS STEEL ROD FIXING

MB50.R.T30

FIXING DETAIL - DOMESTIC AND COMMERCIAL STEEL INSTALLATION WITH M10-R50 ROD, WASHER AND NUT IN STAINLESS STEEL

FIXING DETAIL - COMMERCIAL TIMBER INSTALLATION WITH M10-R140 ROD, WASHER AND NUT IN STAINLESS STEEL

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

MB50.R.T30

FIXING DETAIL - DOMESTIC ONLY
INSTALLATION WITH M10-100SL STAINLESS
STEEL LAG SCREW FIXING

MB50.R.T30

TYPICAL BALUSTRADE PANEL LAYOUT
AT 400MM CENTRES

FFL
50mm   50mm
H
400mm 400mm 400mm 400mm
100mm   100mm
1.8 meters

H = Commercial = 100mm minimum
H= Domestic = 75mm minimum

TYPICAL STAIR LAYOUT

BALUSTRADE ANCHOR HEAVY WEIGHT
75MM SINGLE DISC

Item number	MB75.T.T30
Description	• Balustrade anchor heavy weight 75mm single disc • fitting suitable for single line • fixings at 400mm maximum centres • 30mm standoff • optional fixings ordered separately (threaded rod - 60mm, 120mm or 150mm)
Suitable for	• 12mm and 15mm toughened glass
Material finish	• 316 grade polished or satin stainless steel

MB75.T.T30

GLASS CUT OUT DETAIL
Ø18mm

MB75.T.T30

SQUARE COVER KIT CONVERT MB75.T.T30

Item number	MB75.SQ
Description	• square cover kit to convert MB75.T.T30 to square fitting
Suitable for	• MB75.T.T30
Material finish	• 316 grade polished or satin stainless steel

MB75.SQ

GLASS CUT OUT DETAIL
Ø18mm

MB75.SQ

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

BALUSTRADE ANCHOR HEAVY WEIGHT
100MM SINGLE DISC

Item number	MB100.S.T30
Description	• Balustrade anchor heavy weight 100mm single disc • fitting suitable for single line • compliant to NZS1170 for use in domestic and commercial installations • maximum 400mm centres • optional fixings ordered separately (threaded rod - 60mm, 120mm or 150mm)
Suitable for	• 12mm and 15mm toughened glass
Material finish	• 316 grade polished or satin stainless steel

**MB100.S.
T30**

MB100.S.T30

**TYPICAL SETOUT FOR MB100.S.T30
AND MB75.T.T30 FITTINGS**

FFL

150mm   400mm   400mm   400mm   400mm   150mm

GLASS CUT OUT DETAIL

Ø18mm

**MB100.S.
T30**

FIXING DETAIL - CONCRETE

12mm - 15mm glass
30mm
MB100.S.T30

FIXING DETAIL - STEEL

12mm - 15mm glass
30mm
50mm

FIXING DETAIL - TIMBER

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

MB100.S.T30

FIXING DETAIL - CONCRETE

MB100.S.T30

FIXING DETAIL - STEEL

FIXING DETAIL - TIMBER

GLASS ANCHOR   38MM DIAMETER
FLAT BUTTON HEAD

| Item number	38mm diameter

	• EGSBF1000.38.10
	  38mm diameter
	  10mm spacer
	• EGSBF1000.38.15
	  38mm diameter
	  15mm spacer
	• EGSBF1000.38.20
	  38mm diameter
	  20mm spacer
	• EGSBF1000.38.30
	  38mm diameter
	  30mm spacer
	• EGSBF1000.38.50
	  38mm diameter
	  50mm spacer

Description	• glass anchor 38mm flat button head • spacer length available in 10mm, 15mm, 20mm, 30mm or 50mm • M12 threaded rod standard 150mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1000.38

Optional spacer body length
10mm, 15mm, 20mm, 30mm or 50mm

38mm
flat button
diameter

M12 threaded rod
150mm

21.6mm

EGSBF1000.38

GLASS CUT OUT DETAIL

Ø18mm

ELITE GLASS SOLUTIONS

JULY 2016

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

GLASS ANCHOR 50MM DIAMETER
FLAT BUTTON HEAD

| Item number	50mm diameter
	• EGSBF1000.50.10
	  50mm diameter
	  10mm spacer
	• EGSBF1000.50.15
	  50mm diameter
	  15mm spacer
	• EGSBF1000.50.20
	  50mm diameter
	  20mm spacer
	• EGSBF1000.50.30
	  50mm diameter
	  30mm spacer
	• EGSBF1000.50.50
	  50mm diameter
	  50mm spacer

Description	• glass anchor 50mm flat button head • spacer length available in 10mm, 15mm, 20mm, 30mm or 50mm • M12 threaded rod standard 150mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1000
.50

Optional spacer body length
10mm, 15mm, 20mm, 30mm or 50mm

50mm
flat button
diameter

M12 threaded rod
150mm

21.6mm

EGSBF1000.50

GLASS CUT OUT DETAIL

Ø18mm

GLASS ANCHOR 38MM DIAMETER
CONCAVE BUTTON HEAD

Item number	38mm diameter
	• EGSBF1100.38.10
	  38mm diameter
	  10mm spacer
	• EGSBF1100.38.15
	  38mm diameter
	  15mm spacer
	• EGSBF1100.38.20
	  38mm diameter
	  20mm spacer
	• EGSBF1100.38.30
	  38mm diameter
	  30mm spacer
	• EGSBF1100.38.50
	  38mm diameter
	  50mm spacer

Description	• glass anchor 38mm concave button head • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1100
.38

Optional body length
10mm, 15mm, 20mm, 30mm or 50mm

8mm

38mm
button
diameter

M12 thread

Optional fixing

21.6mm

EGSBF1100.38

GLASS CUT OUT DETAIL

Ø18mm

ELITE GLASS SOLUTIONS

JULY 2016

GLASS ANCHOR 50MM DIAMETER
CONCAVE BUTTON HEAD

Item number	50mm diameter

	• EGSBF1100.50.10
	  50mm diameter
	  10mm spacer
	• EGSBF1100.50.15
	  50mm diameter
	  15mm spacer
	• EGSBF1100.50.20
	  50mm diameter
	  20mm spacer
	• EGSBF1100.50.30
	  50mm diameter
	  30mm spacer
	• EGSBF1100.50.50
	  50mm diameter
	  50mm spacer

Description	• glass anchor 50mm concave button head • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) • other body sizes available on request
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1100 .50

Optional body length
10mm, 15mm, 20mm, 30mm or 50mm

8mm

50mm button diameter

M12 thread

Optional fixing

21.6mm

EGSBF1100.50

GLASS CUT OUT DETAIL

Ø18mm

GLASS ANCHOR 38MM DIAMETER
FLAT BUTTON HEAD

Item number	38mm diameter

	• EGSBF1150.38.10
	  38mm diameter
	  10mm spacer
	• EGSBF1150.38.15
	  38mm diameter
	  5mm spacer
	• EGSBF1150.38.20
	  38mm diameter
	  20mm spacer
	• EGSBF1150.38.30
	  38mm diameter
	  30mm spacer
	• EGSBF1150.38.50
	  38mm diameter
	  50mm spacer

Description	• glass anchor 38mm flat button head • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry) other body sizes available on request
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1150 .38

Optional body length
10mm, 15mm, 20mm, 30mm or 50mm

38mm button diameter

M12 thread

Optional fixing

8mm button thickness

EGSBF1150.38

GLASS CUT OUT DETAIL

Ø24mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS ANCHOR 50MM DIAMETER
## FLAT BUTTON HEAD

Item number	50mm diameter
	• EGSBF1150.50.10
	  50mm diameter
	  10mm spacer
	• EGSBF1150.50.15
	  50mm diameter
	  15mm spacer
	• EGSBF1150.50.20
	  50mm diameter
	  20mm spacer
	• EGSBF1150.50.30
	  50mm diameter
	  30mm spacer
	• EGSBF1150.50.50
	  50mm diameter
	  50mm spacer

Description	• glass anchor 50mm flat button head • spacer available in 10mm, 15mm, 20mm, 30mm or 50mm • fixings available (threaded rod, wood fix lag screw, timber insert or masonry)
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF1150 .50

EGSBF1150.50

GLASS CUT OUT DETAIL

Ø24mm

HANDRAIL FIXING GLASS OPTION
FLAT BUTTON HEAD

Item number	• EGSBF1200.38
	  38mm diameter
	• EGSBF1200.50
	  50mm diameter

Description	• handrail fixing glass option flat button head • diameter available in 38mm or 50mm • saddle - flat or curved (loose or welded)
Suitable for	• mounting handrails to glass panels • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel finish

EGSBF1200

EGSBF1200

GLASS CUT OUT DETAIL

Ø18mm

JULY 2016

HANDRAIL FIXING GLASS OPTION
FLAT BUTTON HEAD

Item number	• EGSBF1250.38
	  38mm diameter
	• EGSBF1250.50
	  50mm diameter

Description	• handrail fixing glass option
	  flat button head
	• diameter available in 38mm or 50mm
	• saddles for easy mounting to
	  handrails included
	• three saddles supplied with
	  every fitting
	  – saddles to suit 38mm diameter
	    and 50mm diameter round tube
	  – one flat saddle to this flat tube

Suitable for	• mounting handrails to glass panels • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel finish

EGSBF1250

EGSBF1250

Kit includes three saddles

Suits 38mm
diameter handrail

Suits 50.8mm
diameter handrail

Flat handrail

GLASS CUT OUT DETAIL

Ø24mm

HANDRAIL FIXING GLASS OPTION
CONCAVE BUTTON HEAD

Item number	• EGSBF1300.38
	  38mm diameter
	• EGSBF1300.50
	  50mm diameter

Description	• handrail fixing glass option
	  concave button head
	• diameter available in 38mm or 50mm
	• saddle - flat or curved
	  (loose or welded)

Suitable for	• mounting handrails • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel finish

EGSBF1300


EGSBF1300

GLASS CUT OUT DETAIL

Ø18mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POST ATTACHMENT GLASS PANEL
FLAT BUTTON HEAD

Item number	• EGSBF1400.38 38mm diameter • EGSBF1400.50 50mm diameter
Description	• post attachment glass panel flat button head • diameter available in 38mm or 50mm • saddle - flat or curved (loose or welded)
Suitable for	• welding to a vertical post to attach glass panels • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel finish

EGSBF1400

EGSBF1400

GLASS CUT OUT DETAIL

Ø18mm

POST ATTACHMENT GLASS PANEL
CONCAVE BUTTON HEAD

Item number	• EGSBF1500.38 38mm diameter • EGSBF1500.50 50mm diameter
Description	• post attachment glass panel concave button head • diameter available in 38mm or 50mm • saddle - flat or curved (loose or welded)
Suitable for	• welding to a vertical post to attach glass panels • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel finish

EGSBF1500

EGSBF1500

GLASS CUT OUT DETAIL

Ø18mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

HANDRAIL BRACKET ROUND

Item number	EUHB.50
Description	• handrail bracket round • supplied 150mm high for on-site trimming
Suitable for	• mounting handrails • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

EUHB.50

Ø12

75mm 150mm

50mm diameter

6mm EUHB.50

GLASS CUT OUT DETAIL

Ø26mm

HANDRAIL BRACKET SQUARE

Item number	EUHB.50.SQ
Description	• handrail bracket square • supplied 150mm high for on-site trimming
Suitable for	• mounting handrails • 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

EUHB.50. SQ

Ø12

75mm 150mm

51mm

8mm EUHB.50.SQ

GLASS CUT OUT DETAIL

Ø26mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

HANDRAIL BRACKET ROUND
SUITABLE FOR TIMBER FIX

Item number	EUHBTF50
Description	• handrail bracket round • supplied 150mm high for on-site trimming
Suitable for	• timber fix
Material finish	• 316 grade polished or satin stainless steel

EUHBTF50

Ø12
75mm
150mm
11.5mm
EUHBTF50

GLASS CUT OUT DETAIL

Ø26mm

HANDRAIL SQUARE
SUITABLE FOR TIMBER FIX

Item number	EUHBTF50.SQ
Description	• handrail bracket square • supplied 150mm high for on-site trimming
Suitable for	• timber fix
Material finish	• 316 grade polished or satin stainless steel

EUHBTF50.SQ

Ø12
75mm
150mm
51mm
9mm
EUHBTF50.SQ

GLASS CUT OUT DETAIL

Ø26mm

ELITE GLASS SOLUTIONS

POST ATTACHMENT GLASS PANEL
FLAT BUTTON HEAD - LONG FIXING LEG

Item number	EGSBF1600
Description	• post attachment glass panel flat button head - long fixing leg • fixing leg can be cut to size as required • available in long leg (150mm length) or short leg (80mm length)
Suitable for	• any application, including staircases
Material finish	• 316 grade satin stainless steel

EGSBF1600

43.4mm
12 mm
6.2mm
50mm flat button diameter
21.6mm
1.8 mm
1.8 mm

EGSBF1600

LONG LEG - BACK

50mm diameter
150mm

LONG LEG

150mm

SHORT LEG

80mm

GLASS CUT OUT DETAIL

Ø18mm

POST ATTACHMENT GLASS PANEL
CONCAVE BUTTON HEAD - LONG FIXING LEG

Item number	EGSBF1700
Description	• post attachment glass panel concave button head - long fixing leg • fixing leg can be cut to size as required • available in long leg (150mm length) or short leg (80mm length) • spacer available in 10mm or 15mm
Suitable for	• any application, including staircases
Material finish	• 316 grade satin stainless steel

EGSBF1700

53.4mm
12 mm
10mm
6.2mm
50mm flat button diameter
21.6mm
1.8 mm
1.8 mm

EGSBF1700

LONG LEG - BACK

50mm diameter
150mm

LONG LEG

150mm

SHORT LEG

80mm

GLASS CUT OUT DETAIL

Ø18mm

BALUSTRADE & GLASS FIXINGS

GLASS ANCHORS

JULY 2016

COMPONENTS AND PARTS

COMPONENTS AND PARTS

SPACER 38MM DIAMETER

Item number	38mm diameter
	• EGSBF600.38.10 38mm diameter 10mm length • EGSBF600.38.15 38mm diameter 15mm length • EGSBF600.38.20 38mm diameter 20mm length • EGSBF600.38.30 38mm diameter 30mm length • EGSBF600.38.50 38mm diameter 50mm length
Description	• spacer 38mm diameter • length available in 10mm, 15mm, 20mm, 30mm or 50mm • custom sizes are available on order
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF600
.38

38mm diameter

10mm

38mm diameter

15mm

38mm diameter

20mm

EGSBF600.38

38mm diameter

30mm

38mm diameter

50mm

ELITE GLASS
SOLUTIONS

JULY 2016

SPACER 38MM DIAMETER 20MM LENGTH

Item number	SP3820
Description	• spacer 38mm diameter • 20mm length • 8.5mm diameter through hole
Material finish	• satin silver anodised • polished or satin stainless steel

SP3820

SP3820

SPACER 50MM DIAMETER 25MM LENGTH

Item number	• SP5025
	  10.5mm diameter through hole
	• SP5025.T
	  threaded M10 hole

Description	• spacer 50mm diameter • 25mm length
Material finish	• satin silver anodised • polished or satin stainless steel

**SP5025
SP5025.T**

SP5025

SPACER 50MM DIAMETER

Item number	50mm diameter
	• EGSBF600.50.10
	  50mm diameter
	  10mm length
	• EGSBF600.50.15
	  50mm diameter
	  15mm length
	• EGSBF600.50.20
	  50mm diameter
	  20mm length
	• EGSBF600.50.30
	  50mm diameter
	  30mm length
	• EGSBF600.50.50
	  50mm diameter
	  50mm length

Description	• spacer 50mm diameter • length available in 10mm, 15mm, 20mm, 30mm or 50mm • other sizes available on request (lead time applies)
Suitable for	• 10mm, 12mm, 15mm and 19mm glass thickness
Material finish	• 316 grade satin stainless steel

EGSBF600 .50

EGSBF600.50

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

BALUSTRADE & GLASS FIXINGS

COMPONENTS AND PARTS

JULY 2016

SPACER COUNTERSUNK FIXING DISC

Item number	SPC5010
Description	• spacer or countersunk fixing disc • 50mm diameter • 10mm length • drilled and counter sunk
Suitable for	• M10 counter sunk hex bolt
Material finish	• polished or satin stainless steel

SPC5010

SPC5010

TAPERED NUT

| Item number	• EGSBF610.38
	  38mm diameter
	• EGSBF610.50
	  50mm diameter

Description	• tapered nut • diameter available in 38mm or 50mm
Material finish	• 316 grade satin stainless steel

EGSBF610

EGSBF610

GIB SPACER

Item number	• SPG32.10
	  32mm diameter
	  10mm length
	• SPG32.12
	  32mm diameter
	  12mm length

Description	• gib spacer • length available in 10mm and 12mm
Material finish	• plastic • aluminium

SPG32

SPG32.10

SPG32.12

FLANGE TAPERED RANGE

Item number	• EGSBF620.38
	  38mm diameter
	• EGSBF620.50
	  50mm diameter

Description	• flange tapered range • diameter available in 38mm or 50mm
Material finish	• 316 grade satin stainless steel

EGSBF620

EGSBF620

ELITE GLASS SOLUTIONS

STEPPED DISC
50MM DIAMETER

Item number	SD50M10
Description	• stepped disc 50mm diameter • M10 threaded blind hole
Material finish	• satin silver anodised • polished or satin stainless steel

SD50M10

50mm
diameter

SD50M10

12mm

STEPPED DISC
38MM DIAMETER

Item number	SD38M8
Description	• stepped disc 38mm diameter • M8 threaded blind hole
Material finish	• satin silver anodised • polished or satin stainless steel

SD38M8

38mm
diameter

SD38M8

10mm

COVERED FLANGE PLATE

Item number	• EGSBF630.38
	  38mm diameter
	• EGSBF630.50
	  50mm diameter

Description	• covered flange plate • diameter available in 38mm or 50mm
Material finish	• 316 grade satin stainless steel

EGSBF630

38mm
or 50mm
diameter

9mm 4
mm

EGSBF630

NUT

Item number	• EGSBF640.38
	  38mm diameter
	• EGSBF640.50
	  50mm diameter

Description	• nut • diameter available in 38mm or 50mm
Material finish	• 316 grade satin stainless steel

EGSBF640

38mm
or 50mm
diameter

21.6mm   EGSBF640

ELITE GLASS SOLUTIONS

BALUSTRADE & GLASS FIXINGS

COMPONENTS AND PARTS

COVER RANGE

Item number	• EGSBF650.38 38mm diameter • EGSBF650.50 50mm diameter
Description	• cover range • diameter available in 38mm or 50mm
Material finish	• 316 grade satin stainless steel

EGSBF650

38mm or 50mm diameter

EGSBF650

18mm
11mm

SHORT PLATE WITH THREADED ROD

Item number	EGSBF670
Description	• short plate with threaded rod • 50mm diameter • 80mm length
Suitable for	• EGSBF1600 • EGSBF1700
Material finish	• 316 grade satin stainless steel

EGSBF670

55mm / 50mm / 80mm / 6mm / 40mm / 50mm

EGSBF670

LONG PLATE WITH THREADED ROD

Item number	EGSBF660
Description	• long plate with threaded rod
Suitable for	• EGSBF1600 • EGSBF1700
Material finish	• 316 grade satin stainless steel

EGSBF660

125mm / 50mm / 150mm / 6mm / 40mm / 50mm

EGSBF660

WALL BRACKET 75MM OFFSET

Item number	EGSBF700
Description	• wall bracket 75mm offset
Material finish	• 316 grade satin stainless steel

EGSBF700

50mm / 66mm / 35mm / 12mm

EGSBF700

JULY 2016

WALL BRACKET 80MM OFFSET

Item number	EGSBF710
Description	• wall bracket 80mm offset
Material finish	• 316 grade satin stainless steel

EGSBF710

EGSBF710

60mm

12mm

85mm

MASONRY WALL BRACKET

Item number	EGSBF730
Description	• masonry wall bracket
Material finish	• 316 grade satin stainless steel

EGSBF730

EGSBF730

12mm

60mm

80mm

75mm

POST BRACKET M12 OFFSET

Item number	EGSBF720
Description	• post bracket M12 offset
Material finish	• 316 grade satin stainless steel

EGSBF720

90mm

EGSBF720

12mm

62mm

35mm

ROD THREAD STRAIGHT

Item number	EGSBF740
Description	• rod thread straight • 210mm length
Material finish	• 316 grade satin stainless steel

EGSBF740

EGSBF740

12mm

35mm

185mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

ROD THREAD 150MM

Item number	EGSBF750
Description	• rod thread • 150mm length
Material finish	• 304 grade satin stainless steel

EGSBF750

EGSBF750

150mm

WASHER COLLARED BLACK NYLON

Item number	EGSBF830
Description	• washer collared • 1.6mm
Suitable for	• M12 threaded rod
Material finish	• black nylon

EGSBF830

EGSBF830

LAG SCREW

Item number	• EGSBF750.LS.M6
	  6mm diameter
	  90mm length
	• EGSBF750.LS.M10
	  10mm diameter
	  135mm length
	• EGSBF750.LS.M12.135
	  12mm diameter
	  135mm length
	• EGSBF750.LS.M12.165
	  12mm diameter
	  165mm length

Description	• lag screw
Material finish	• 304 grade satin stainless steel

EGSBF750.LS

EGSBF750.LS

WASHER BLACK NYLON

Item number	• EGSBF800.06
	  0.6mm thickness
	• EGSBF800.10
	  1.0mm thickness
	• EGSBF800.16
	  1.6mm thickness
	• EGSBF820
	  1.6mm thickness*

Description	• washer
Suitable for	• M12 threaded rod • EGSBF650 (*EGSBF820 only)
Material finish	• black nylon

EGSBF800

EGSBF800

ELITE GLASS SOLUTIONS

PROTECTIVE SLEEVE CLEAR

Item number	EGSBF810
Description	• protective sleeve clear
Suitable for	• EGSBF750 head • M12 threaded rod

EGSBF810

EGSBF810

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BALUSTRADE & GLASS FIXINGS

TOP RAILS

TOP RAILS

FRAMELESS GLASS TOP RAIL
SQUARE ULTRA SLIM

Item number	EH.TOPRAIL.SQ
Description	• frameless glass top rail square ultra slim • weld free installation • precision manufactured in 5.8 meter lengths • supplied complete with high strength u shaped rubber extrusion that provides a tight fit between the glass and top rail, standard is 12mm with an optional rubber to suit 10mm glass • complies with Australian and NZ standards AS/NZS 1170.1.2002 • compact shape ensures minimum disruption to the view • all joints are weld free - assemble using Soudal T Rex Crystal or equal
Suitable for	• 10mm and 12mm glass thickness • indoor and outdoor applications
Material finish	• 2205 duplex satin or polished stainless

EH.TOPRAIL
.SQ

EH.TOPRAIL.SQ

14mm

21mm

14mm

25mm

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

WALL BRACKET
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.WB.SQ
Description	• wall bracket
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ • fastening lug suits 6 or 12 o'clock installation
Material finish	• 2205 duplex satin or polished stainless

EH.WB.SQ

EH.WB.SQ

STRAIGHT 180° JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.180.SQ.JOINER
Description	• straight joiner
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ • slides into the top rail for a neat join
Material finish	• 2205 duplex satin or polished stainless

EH.180.SQ .JOINER

EH.180.SQ.JOINER

END CAP
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.ENDCAP.SQ
Description	• end cap
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ • fastening lug can be rotated to suit each installation
Material finish	• 2205 duplex satin or polished stainless

EH.ENDCAP .SQ

EH.ENDCAP.SQ

FIXED 90° CORNER JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.90.SQ.JOINER
Description	• fixed 90° corner joiner • slides into the top rail and ensures an accurate corner joint
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ
Material finish	• 2205 duplex satin or polished stainless

EH.90.SQ .JOINER

EH.90.SQ.JOINER

ELITE GLASS SOLUTIONS

JULY 2016

HORIZONTAL VARIABLE JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.HOR.VAR.SQ.JOINER
Description	• horizontal variable joiner
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ
Material finish	• 2205 duplex satin or polished stainless

EH.HOR.VAR .SQ. JOINER

EH.HOR.VAR.SQ.JOINER

ADJUSTABLE JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.ADJ.JOINER
Description	• adjustable joiner
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ
Material finish	• 2205 duplex satin or polished stainless

EH.ADJ .JOINER

EH.ADJ.JOINER

22mm 28mm 22mm
22mm
75mm

HINGE VERTICAL JOINER
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.VER.SQ.JOINER
Description	• hinge vertical joiner • multi adjustable component for negotiating hand rail bends up and down stair wells. No more cutting and welding, just slide inside TBHR400 rail and glue with silicone
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ
Material finish	• 2205 duplex satin or polished stainless

EH.VER.SQ. JOINER

EH.VER.SQ.JOINER

INLINE JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.INLINE.JOINER
Description	• inline joiner
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ
Material finish	• 2205 duplex satin or polished stainless

EH.INLINE .JOINER

EH.INLINE.JOINER

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLEEVE JOINER
SUITABLE FOR TOP RAIL SQUARE ULTRA SLIM

Item number	EH.SLEEVE.JOINER
Description	• sleeve joiner
Suitable for	• top rail square ultra slim EH.TOPRAIL.SQ • connects wall bracket to adjustable joiner
Material finish	• 2205 duplex satin or polished stainless

EH.SLEEVE .JOINER

EH.SLEEVE.JOINER

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FRAMELESS GLASS TOP RAIL
ROUND ULTRA SLIM

Item number	EH.TOPRAIL.RD
Description	• frameless glass top rail round ultra slim • 25mm round diameter • precision manufactured in 5.8 meter lengths • supplied complete with high strength u shaped rubber extrusion that provides a tight fit between the glass and top rail, standard is 12mm with an optional rubber to suit 10mm glass • complies with Australian and NZ standards AS/NZS 1170.1.2002 • compact shape ensures minimum disruption to the view • all joints are weld free - assemble using Soudal T Rex Crystal or equal
Suitable for	• 10mm and 12mm glass thickness • indoor and outdoor applications
Material finish	• 2205 duplex satin or polished stainless

EH.TOPRAIL .RD

EH.TOPRAIL.RD

38mm diameter

WALL BRACKET
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.WB.RD
Description	• wall bracket
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD • fastening lug can be rotated to suit each installation
Material finish	• 2205 duplex satin or polished stainless

EH.WB.RD

EH.WB.RD

END CAP
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.ENDCAP.RD
Description	• end cap
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD
Material finish	• 2205 duplex satin or polished stainless

EH.ENDCAP .RD

EH.ENDCAP.RD

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

STRAIGHT 180° JOINER
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.180.RD.JOINER
Description	• straight joiner • slides into the top rail for a neat join
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD
Material finish	• 2205 duplex satin or polished stainless

EH.180.RD .JOINER

EH.180.RD.JOINER

HORIZONTAL VARIABLE JOINER
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.HOR.VAR.RD.JOINER
Description	• horizontal variable joiner
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD
Material finish	• 2205 duplex satin or polished stainless

EH.HOR.VAR. RD. JOINER

EH.HOR.VAR.RD.JOINER

FIXED 90° CORNER JOINER
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.90.RD.JOINER
Description	• fixed 90° corner joiner • slides into the top rail and ensures an accurate corner joint
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD
Material finish	• 2205 duplex satin or polished stainless

EH.90.RD. JOINER

EH.90.RD.JOINER

HINGE VERTICAL JOINER
SUITABLE FOR TOP RAIL ROUND ULTRA SLIM

Item number	EH.VER.RD.JOINER
Description	• hinge vertical joiner • multi adjustable component for negotiating hand rail bends up and down stair wells. No more cutting and welding, just slide inside TBHR400 rail and glue with silicone
Suitable for	• top rail round ultra slim EH.TOPRAIL.RD
Material finish	• 2205 duplex satin or polished stainless

EH.VER.RD. JOINER

EH.VER.RD.JOINER

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

HANDRAIL SLIMLINE
WITH END CAP

Item number	• BH1
	• BH2 - end cap
Description	• handrail slimline with end cap
	• meets AS1288-2006 for hand railing for glass balustrades that are over 1 meter in height and only fixed to the base
	• complies with NZS4203:1992 for handrails
	• designed for easy fitting, clips directly over the glass:
	– no welding required and can be installed after glass is fitted
	• optional stainless steel cover and fixtures manufactured in marine grade 316 (lead time applies)
Suitable for	• 10mm and 12mm glass thickness
	• interior and exterior applications
Material finish	• mill or silver pearl
	• special finishes available on request (lead time applies)

BH1

BH1

30 mm

24 mm

BH2

HANDRAIL FLAT TUBE

Item number	SOLO
Description	• handrail flat tube
	• 50mm width x 10mm height
	• available in 2.5 meter and 5 meter lengths
	• available uncapped or with 1 or 2 fully welded end caps
Material finish	• 2205 duplex satin or polished stainless

SOLO

10mm

50mm

SOLO

WALL BRACKET
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• SOLO.WB
Description	• wall bracket
Suitable for	• handrail flat tube SOLO
Material finish	• 2205 duplex satin or polished stainless

SOLO.WB

SOLO.WB

ELITE GLASS
SOLUTIONS

END CAP
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• SOLO.ENDCAP
Description	• end cap
Suitable for	• handrail flat tube SOLO
Material finish	• 2205 duplex satin or polished stainless

SOLO.ENDCAP

SOLO.ENDCAP

FIXED 90° CORNER JOINER
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	SOLO.90°.JOINER
Description	• fixed 90° corner joiner
Suitable for	• handrail flat tube SOLO
Material finish	• 2205 duplex satin or polished stainless

SOLO.90°.JOINER

SOLO.90°.JOINER

STRAIGHT 180° JOINER
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• SOLO.180°.JOINER
Description	• straight 180° joiner
Suitable for	• handrail flat tube SOLO
Material finish	• 2205 duplex satin or polished stainless

SOLO.180°.JOINER

SOLO.180°.JOINER

HORIZONTAL VARIABLE JOINER
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• SOLO.VAR.JOINER
Description	• HORIZONTAL VARIABLE JOINER
Suitable for	• handrail flat tube SOLO
Material finish	• 2205 duplex satin or polished stainless

SOLO.VAR.JOINER

SOLO.VAR.JOINER

BALUSTRADE & GLASS FIXINGS

TOP RAILS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CLAMP WALL TO FLAT HANDRAIL
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• HRB.HB.25 25mm diameter • HRB.HB.38 38mm diameter
Description	• wall to flat handrail clamp • diameter available in 25mm or 38mm • 50mm slotted body • CNC machined body allows for various fixing options
Suitable for	• handrail flat tube SOLO
Material finish	• 316 grade polished or satin stainless steel

HRB.HB

HRB.HB

AUSTRALIAN MADE

CLAMP GLASS TO FLAT HANDRAIL
SUITABLE FOR HANDRAIL FLAT TUBE

Item number	• HRB.25 25mm diameter • HRB.38 38mm diameter
Description	• glass to flat handrail clamp • diameter available in 25mm or 38mm • 50mm slotted body
Suitable for	• 8mm, 10mm and 12mm glass thickness (can be supplied with longer studs to suit other glass thicknesses) • handrail flat tube SOLO
Material finish	• 316 grade polished or satin stainless steel

HRB

HRB

AUSTRALIAN MADE

JULY 2016

POOL HARDWARE

ELITE GLASS SOLUTIONS

POOL HARDWARE

CONTENTS

CONTENTS


ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

FLOOR SPRINGS

SEALING COMPOUND

Item number	FS.RESIN
Description	• sealing compound • two component resin is poured around the body of the closer in the cement box to improve waterproofing Download the "Material Safety Data" flyer from our website for further information
Suitable for	• preventing the likelihood of water entering the cement box

FS.RESIN

FS.RESIN

ELITE GLASS
SOLUTIONS

FLOOR SPRING SEALING COMPOUND PART A

ELITE GLASS
SOLUTIONS

PART B HARDENER COMPOUND

DOUBLE ACTION FLOOR SPRING

Item number	EF820
Description	• for further information see Section 4 - page 6 (EFS840)

EF820

EF820

130mm
324mm
40 mm
306mm
108mm

SELF CLOSING PATCH FITTING

SELF CLOSING
PATCH FITTING

OZONE HYDRAULIC PATCH FITTING
SELF CLOSING

| Item number	EHP100.NHO - non-hold open
Description	• Ozone hydraulic patch fitting self closing non-hold open • applicable for door width of 750mm to 1 meter and weight up to 100kg • bottom patch fitting for internal doors • used in conjunction with a standard top patch fitting and floor stop • multiple adjustments and settings for closing and breaking speed • 5 year warranty
Suitable for	• single or double doors • residential and commercial internal use only • mounting to timber, steel or concrete • 8mm, 10mm and 12mm toughened safety glass
Material finish	• 316 polished or satin stainless steel

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

EHP100. NHO

EHP100.NHO

28mm

86mm

16mm
material

Hold open at 90°

150°

No.1

10°
No.2
0°
No.2
10°

150°

No.1

Hold open at 90°

Maximum opening angle 150°
Hold open at 90°
Non-hold open, by request

Two speed adjustment:
Closing speed (150° down to 10°)
Breaking speed (10° down to 0°)

Speed adjustment

Fast
Slow

No.2 Braking speed

No.1 Closing speed

EHP100. NHO

GLASS CUT OUT DETAIL

R12

56mm

49mm

173mm

180mm

EHP100.NHO

POST TO POST GATE

FPF8

HP20

PL1

10mm
20mm

F.F.L
12mm

EHP100.NHO

GLASS TO GLASS GATE

FPF6

PL2

6mm
6mm

F.F.L.
12mm

EHP100.NHO

WALL TO GLASS GATE

FPF5

HP20

PL2

6mm
15mm

F.F.L.
12mm

EHP100.NHO

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

HINGES

SELF-CLOSING SAFETY HINGE
GLASS TO GLASS

| Item number	PGG
Description	• self-closing safety hinge - glass to glass • single, soft close action • non-hold open • door up to 950mm x 1.25 meters • maximum door weight 50kg • suitable for weather -10°c and +50°c • hinge opening angle 90° • to be used with child resistant safety latch • complies with Australian standards for pool gate hardware AS2820 and AS1926 • National Association of Testing Authorities, Australia accredited and independently tested to 10,000 cycles or 10 years normal use • endorsed by Royal Life Saving Society, Australia
Suitable for	• glass pool fencing • 10mm and 12mm glass thickness
Material finish	• 316 grade mirror, polished or satin stainless steel

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PGG

PGG

FRONT VIEW

2mm

90 mm

SIDE VIEW

35mm

REAR VIEW

114mm

BASE VIEW

45°

2 mm

12 mm

GLASS CUT OUT DETAIL

5mm

41mm   41mm

37mm   37mm

2-R10   2-R10

2.5mm   2.5mm

58mm   63mm   63mm   58mm

2.5mm   2.5mm

ELITE GLASS SOLUTIONS

JULY 2016

POOL HARDWARE

HINGES

SELF-CLOSING SAFETY HINGE
## GLASS TO WALL

PGW

| Item number	PGW

Description	• self-closing safety hinge
	  - glass to wall
	• single, soft close action
	• non-hold open
	• door up to 950mm x 1.25 meters
	• maximum door weight 50kg
	• suitable for weather -10˚c and
	  +50˚c
	• hinge opening angle 90˚
	• to be used with child resistant
	  safety latch
	• complies with Australian standards
	  for pool gate hardware AS2820
	  and AS1926
	• National Association of Testing
	  Authorities, Australia accredited
	  and independently tested to 10,000
	  cycles or 10 years normal use
	• endorsed by Royal Life Saving
	  Society, Australia

Suitable for	• glass pool fencing • 10mm and 12mm glass thickness
Material finish	• 316 grade mirror, polished or satin stainless steel

PGW

FRONT VIEW

2mm

90 mm

SIDE VIEW

75mm

REAR VIEW

82mm

BASE VIEW

45˚

35 mm

12 mm

2mm

GLASS CUT OUT DETAIL

8mm

61mm

57mm

2-R10

3.5mm

65mm

58mm

3.5mm

GLASS CUT OUT TOP AND BOTTOM

SELF-CLOSING SAFETY HINGE
GLASS TO OFFSET WALL PLATE

POW

Item number	POW

Description	• self-closing safety hinge
	  - glass to offset wall plate
	• single, hydraulic soft close
	• non-hold open
	• door up to 950mm x 1.25 meters
	• maximum door weight 50kg
	• suitable for weather -10˚c and
	  +50˚c
	• hinge opening angle 90˚
	• auto close from any angle
	• cycle tested

Suitable for	• glass pool fencing • 10mm and 12mm glass thickness
Material finish	• 316 grade mirror, polished or satin stainless steel

POW

FRONT VIEW

2mm

90 mm

SIDE VIEW

75mm

REAR VIEW

82mm

BASE VIEW

45˚

35 mm

12 mm

2mm

GLASS CUT OUT DETAIL

8mm

61mm

57mm

2-R10

3.5mm

65mm

58mm

3.5mm

GLASS CUT OUT TOP AND BOTTOM

POOL HARDWARE

HINGES

ELITE GLASS SOLUTIONS

JULY 2016

POOL HARDWARE

HINGES

SELF-CLOSING SAFETY HINGE
## GLASS TO SQUARE POST

PSP

| Item number	PSP

Description	• self-closing safety hinge
	  - glass to square post
	• single, soft close action
	• non-hold open
	• door up to 950mm x 1.25 meters
	• maximum door weight 50kg
	• suitable for weather -10˚c and
	  +50˚c
	• hinge opening angle 90˚
	• to be used with child resistant
	  safety latch
	• complies with Australian standards
	  for pool gate hardware AS2820
	  and AS1926
	• National Association of Testing
	  Authorities, Australia accredited
	  and independently tested to 10,000
	  cycles or 10 years normal use
	• endorsed by Royal Life Saving
	  Society, Australia

Suitable for	• glass pool fencing • 10mm and 12mm glass thickness
Material finish	• 316 grade mirror, polished or satin stainless steel

PSP

FRONT VIEW

2mm

125 mm

SIDE VIEW

45mm

REAR VIEW

82mm

BASE VIEW

45˚

35 mm

12 mm

2mm

GLASS CUT OUT DETAIL

8mm

61mm

57mm

2-R10

3.5mm

65mm

58mm

3.5mm

GLASS CUT OUT TOP AND BOTTOM

ELITE GLASS SOLUTIONS

JULY 2016

SELF-CLOSING SAFETY HINGE
GLASS TO ROUND POST

PRP

Item number	PRP
Description	• self-closing safety hinge - glass to round post • single, soft close action • non-hold open • door up to 950mm x 1.25 meters • maximum door weight 50kg • suitable for weather -10˚c and +50˚c • hinge opening angle 90˚ • to be used with child resistant safety latch • complies with Australian standards for pool gate hardware AS2820 and AS1926 • National Association of Testing Authorities, Australia accredited and independently tested to 10,000 cycles or 10 years normal use • endorsed by Royal Life Saving Society, Australia
Suitable for	• glass pool fencing • 10mm and 12mm glass thickness
Material finish	• 316 grade mirror, polished or satin stainless steel

PRP

FRONT VIEW 2mm 90mm

SIDE VIEW 55mm

REAR VIEW 105mm

BASE VIEW 45˚ 35mm 12mm 2mm R25

GLASS CUT OUT DETAIL
8mm 61mm 57mm 2-R10 3.5mm 65mm 58mm 3.5mm

GLASS CUT OUT TOP AND BOTTOM

POOL HARDWARE

HINGES

JULY 2016

POOL HARDWARE

POOL GATE LATCHES

POOL
GATE LATCHES

POOL GATE LATCH AND STRIKE
GLASS TO POST

Item number	PL1
Description	• pool gate latch and strike - glass to post • designed for a frameless glass pool gate that closes to a post or wall • self latching using "Magna" latch • minimum door height 1.2 meters
Suitable for	• 10mm and 12mm glass thickness, can be adapted for other sizes
Material finish	• 316 grade polished or satin stainless steel

PL1

50mm
100mm
PL1

GLASS CUT OUT DETAIL

33mm
150mm minimum
66mm
Ø16
5mm
Gate Panel
Return/Post

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POOL GATE LATCH AND STRIKE
GLASS TO ROUND POST

Item number	PL1RP
Description	• pool gate latch strike - glass to round post • designed for a frameless glass pool gate • 50mm diameter post mount • self latching using "Magna" latch • minimum door height 1.2 meters
Suitable for	• 10mm and 12mm glass thickness, can be adapted for other sizes
Material finish	• 316 grade polished or satin stainless steel

PL1RP

50mm

100mm

PL1RP

GLASS CUT OUT DETAIL

33mm

150mm minimum

66mm

Ø16

Gate Panel

Return/Post

5mm

POOL GATE LATCH AND KEEPER
GLASS TO GLASS

| Item number	PL2
Description	• pool gate latch and keeper - glass to glass • designed for a frameless glass pool gate and side panel • self latching using "Magna" latch • minimum door height 1.2 meters
Suitable for	• 10mm and 12mm glass thickness, can be adapted for other sizes
Material finish	• 316 grade polished or satin stainless steel

PL2

105mm

100mm

PL2

GLASS CUT OUT DETAIL

33mm 33mm

150mm minimum

66mm

Ø16   Ø16

Gate Panel

5mm

ELITE GLASS SOLUTIONS

JULY 2016

POOL GATE LATCHES

POOL GATE LATCH AND KEEPER GLASS TO GLASS 90˚

Item number	PL290
Description	• pool gate latch and keeper - glass to glass 90˚ • designed for a frameless glass pool gate that closes to a side panel at 90˚ • self latching using "Magna" latch • minimum door height 1.2 meters
Suitable for	• 10mm and 12mm glass thickness, can be adapted for other sizes
Material finish	• 316 grade polished or satin stainless steel

PL290

PL290

GLASS CUT OUT DETAIL

SIDE VIEW

Ø16

66mm

TOP VIEW

88mm

Door

4mm
32mm

Side panel

POOL GATE LATCH AND KEEPER GLASS TO GLASS 90˚

Item number	PL290.R
Description	• pool gate latch and keeper - glass to glass 90˚ • designed for a frameless glass pool gate that closes to a side panel at 90˚ • self latching using "Magna" latch • minimum door height 1.2 meters
Suitable for	• 10mm and 12mm glass thickness, can be adapted for other sizes
Material finish	• 316 grade polished or satin stainless steel

PL290.R

PL290.R

40mm

56mm

5 mm

10mm

GLASS CUT OUT DETAIL

33mm

Ø16

66mm

ELITE GLASS SOLUTIONS

JULY 2016

POOL GATE LATCH
GLASS TO GLASS FRICTION FIT 180˚

| Item number	PL2.FF
Description	• pool gate latch - glass to glass friction fit 180˚ • no holes required for a strike/latch panel and can be installed with any fixed (blank) panel to latch to
Suitable for	• 12mm glass thickness
Material finish	• 316 grade polished or satin stainless steel

PL2.FF

PL2.FF

GLASS CUT OUT DETAIL

36mm

66mm

Gate Panel

8/10mm strike panel

POOL GATE LATCH KIT
GLASS TO WALL SQUARE POST

Item number	• PG1 • PG1.R - hook plate - external fit
Description	• pool gate latch kit - glass to wall square post application • stainless steel backing plates plus D&D side pull polymer latch
Suitable for	• 8mm, 10mm and 12mm glass gates
Material finish	• 316 grade polished or satin stainless steel

PG1

PG1

9mm

glass gate

30mm

wall or square post

PG1

hook plate

PG1.R

GLASS CUT OUT DETAIL

900mm

200mm

209mm

42mm

20mm

1.2 meters

200mm

POOL HARDWARE

POOL GATE LATCHES

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POOL HARDWARE

POOL GATE LATCHES

POOL GATE LATCH KIT
GLASS TO GLASS 90° EXTERNAL

| Item number	PG90R
Description	• pool gate latch kit - glass to glass 90° - external corner fit • stainless steel backing plates plus D&D side pull polymer latch • latch panel must be 12mm thick - no latch holes required
Suitable for	• 8mm, 10mm and 12mm glass gates
Material finish	• 316 grade polished or satin stainless steel

PG90R

PG90R

9mm

glass gate

12mm panel

GLASS CUT OUT DETAIL

900mm

200mm

209mm

42mm

20mm

1.2 meters

200mm

POOL GATE LATCH KIT
GLASS TO GLASS 90° INTERNAL

Item number	PG90
Description	• pool gate latch kit - glass to glass 90° - internal corner fit • stainless steel backing plates plus D&D side pull polymer latch • latch panel must be 12mm thick - no latch holes required
Suitable for	• 8mm, 10mm and 12mm glass gates • internal 90° configuration
Material finish	• 316 grade polished or satin stainless steel

PG90

PG90

Gate swing

Latch panel

9mm gap

Gate

20mm gate offset

Locking clasp mechanism

GLASS CUT OUT DETAIL

900mm

200mm

209mm

42mm

20mm

1.2 meters

200mm

ELITE GLASS SOLUTIONS

POOL GATE LATCH ONLY
FACE MOUNT

| Item number	• MLSPS2 - non-locking • MLSPS2.L - locking
Description	• pool gate latch only - face mount • black polymer nylon D&D latch
Suitable for	• 10mm and 12mm glass gates
Material finish	• 316 grade polished or satin stainless steel

MLSPS2

MLSPS2

GLASS CUT OUT DETAIL

900mm
200mm
209mm
42mm
20mm
1.2 meters
200mm

POOL GATE LATCH KIT
GLASS TO GLASS

Item number	PG2
Description	• pool gate latch kit - glass to glass • friction latch for glass to glass 180˚ application • stainless steel backing plates plus D&D side pull polymer latch • latch panel must be 12mm thick - no latch holes required
Suitable for	• 8mm, 10mm and 12mm glass gates
Material finish	• 316 grade polished or satin stainless steel backing plates

PG2

PG2

9mm
glass gate
12mm panel

GLASS CUT OUT DETAIL

900mm
200mm
209mm
42mm
20mm
1.2 meters
200mm

POOL HARDWARE

POOL GATE LATCHES

ELITE GLASS SOLUTIONS

JULY 2016

POOL HARDWARE

PIVOTS

PIVOTS

PIVOT ARM TOP
GLASS TO GLASS

| Item number	FPF6
Description	• pivot arm top - glass to glass • use in conjunction with elite glass standard patch fittings and floor springs
Suitable for	• mounting a glass gate to a glass balustrade
Material finish	• 316 grade polished or satin stainless steel

FPF6

24mm
140mm
75mm
19mm
FPF6

GLASS CUT OUT DETAIL

44mm
Ø16
38mm

INSITU APPLICATION

FPF6
HP20.PG
HP10
Non-hold open floor spring

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PIVOT ARM TOP
GLASS TO SOLID WALL

| Item number	FPF8
Description	• pivot arm top - glass to solid wall • use in conjunction with elite glass standard patch fittings and floor springs
Suitable for	• mounting a glass gate to a solid wall
Material finish	• 316 grade polished or satin stainless steel

FPF8

30mm
80mm
5mm
60mm
FPF8

INSITU APPLICATION

FPF8
HP20.PG
HP10
Non-hold open floor spring

PIVOT ARM TOP
GLASS TO WALL

Item number	FPF5
Description	• pivot arm top - glass to wall • use in conjunction with SBC42400 top patch to allow the gate to pivot from a wall or post
Suitable for	• walls posts 60mm and wider
Material finish	• 316 grade polished or satin stainless steel

FPF5

FPF5
12mm
20mm
15mm
19mm

GLASS CUT OUT DETAIL

60mm
R5
R10
60mm
20mm
80mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PIVOT TOP ARM
GLASS TO ROUND POST

| Item number	FPF5.P
Description	• pivot top arm - glass to wall • use in conjunction with SBC42400 top patch to allow the gate to pivot from 50mm diameter post
Suitable for	• 50mm diameter posts
Material finish	• 316 grade polished or satin stainless steel

FPF5.P

FPF5.P

GLASS CUT OUT DETAIL

59mm R10
3mm
R25 20mm
3.5mm

INSITU APPLICATION

PIVOT TOP
BRACKET

Item number	FPF7
Description	• pivot top - bracket • use in conjunction with HP20/HP10 top patch fittings that allow them to work as a top pivot set
Suitable for	• mounting a glass gate to a glass balustrade
Material finish	• 316 grade polished or satin stainless steel

FPF7

30mm 240mm
6mm
FPF7

INSITU APPLICATION

Pool Gate Arm

HP10/20   HP20.PG

FPF7

HP10

Non-hold open floor spring

Base channel

ELITE GLASS SOLUTIONS

**HEAD OFFICE**
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PIVOT TOP
SET KIT

Item number	FPF7.KIT

Description	• pivot top set
	• kit includes:
	  – two HP20,
	  – one HP10, and
	  – one FPFT

Suitable for	• complete glass to glass setup application
Material finish	• 316 grade polished or satin stainless steel

FPF7.KIT

FPF7

HP20

HP20

HP10

FPF7.KIT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POOL HARDWARE

PIVOTS

EUROPOOL PIVOT ARM TOP 90˚

| Item number	• FPF790.L - left hand • FPF790.R - right hand
Description	• Europool pivot arm top 90˚ • use in conjunction with HP20/HP10 top patch fittings that allows them to work as a top pivot set
Suitable for	• mounting a glass gate to a glass balustrade • frameless glass mounting
Material finish	• 316 grade polished or satin stainless steel

FPF790

FPF790

FPF790.L
(left hand)

106mm
91mm
167mm
30mm

FPF790.R
(right hand)

167mm
106mm
91mm
30mm

GLASS DETAIL - RETURN PANEL

151mm
37mm
R80
R55
36mm
148mm
Ø20

FPF790

GLASS DETAIL - DOOR

60mm
37mm
R80
R55
36mm
R10
158mm
Ø20
10mm
158mm
171mm

ASSEMBLY (RIGHT HAND SIDE)

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PATCHES

BOTTOM PATCH FITTING
FOR 10/12MM GLASS THICKNESS

Item number	HP10 - for further details see Section 4 page 20

HP10

31mm

166mm

52mm

HP10

TOP PIVOT PATCH FITTING
FOR 10/12MM GLASS THICKNESS

Item number	HP20 - for further details see Section 4 page 24 (HP22)

HP20

31mm

166mm

52mm

HP20

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POOL HARDWARE

PATCHES

TOP PATCH FITTING
SUITABLE FOR POOL GATE PIVOTS

Item number	HP20.PG
Description	• top patch fitting suitable for pool gate pivots • adjustable pivot insert • features concealing cover plates
Suitable for	• Eliteglass pool gate fittings - FPF5/FPF6/FPF7 and Δ/FPF8
Material finish	• polished or satin stainless steel

HP20.PG

HP20.PG

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SECTION FOUR - COMMERCIAL HARDWARE

COMMERCIAL HARDWARE

ELITE GLASS
SOLUTIONS

COMMERCIAL HARDWARE

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CONTENTS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

CONTENTS

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CLEARANCES

Top patch	• 4-5mm clearance required

Top rail	• clearance required
	  top rail 57mm +
	  head clearance 4mm - 6mm

Bottom patch	• 10mm clearance required with supplied 0mm spindle

Bottom rail	• clearance required
	  bottom rail 57mm +
	  floor clearance 8mm - 10mm

Double door clearance	• 3mm - 5mm clearance required
Side clearance	• 4mm clearance required

EXTENDED SPINDLES

0mm	• 10mm floor clearance required

5mm	• 15mm floor clearance required
	  • additional 5mm required with
	    a bottom patch or bottom rail

10mm	• 20mm floor clearance required
	  • additional 10mm required with
	    a bottom patch or bottom rail

15mm	• 25mm floor clearance required
	  • additional 15mm required with
	    a bottom patch or bottom rail

20mm	• 30mm floor clearance required
	  • additional 20mm required with
	    a bottom patch or bottom rail

25mm	• 35mm floor clearance required
	  • additional 25mm required with
	    a bottom patch or bottom rail

30mm	• 40mm floor clearance required
	  • additional 30mm required with
	    a bottom patch or bottom rail

Top rail 57mm
+ head clearance
4mm - 6mm

Top patch
clearance
4-5mm

Double door
clearance
3-5mm

Side clearance
4mm

Side clearance
4mm

Bottom rail 57mm
+ floor clearance
8mm - 10mm

Bottom patch
clearance
10mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

FLOOR SPRINGS

FLOOR
SPRINGS

DOUBLE ACTION FLOOR SPRING

Item number	• EFS840.HO - 90° hold open standard 25NM spring force • EFS840.HOW - 90° hold open weak 16NM spring force • EFS840.NHO - non-hold open standard 25NM spring force • EF S840.NHOW - non-hold open weak 16NM spring force
Description	• double action floor spring including stainless steel cover plate • maximum door weight 100kg • maximum door width 1.1 meter standard and 800mm weak • two speed hydraulic control; closing adjustment 130°-15° • latching adjustment 15°-0° • spindle heights from STD to 50mm extension (5mm increments)
Suitable for	• frameless patch fittings and rail
Material finish	• stainless steel cover plate

EFS840

130mm

324mm

EFS840

40 mm

306mm

108mm

*S.T.D. spindle clearance 8mm
* 5mm extended clearance 13mm

40 mm

108mm

55(65)mm   324mm

2mm

108 mm   130 mm

51-58mm

306mm

cover plate

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FULLY ADJUSTABLE COMPACT FLOOR SPRING
HEAVY DUTY - CASMA

SBCM60

Item number	• SBCM60.HO - 90˚ hold open • SBCM60.NHO - non-hold open

Description	• fully adjustable compact floor spring with standard spindle heavy duty - CASMA
	• interchangeable extended spindles available in the following sizes 5mm, 10mm, 15mm 20mm and 25mm
	• maximum door weight 160kg
	• maximum door width
	  – exterior 1 meter
	  – interior 1.2 meters
	• available 90˚ in hold open and non-hold open

Suitable for	• patch fittings and rail
Material finish	• polished or satin stainless steel • polished brass

SBCM60

65mm

24 mm

56 mm

5 mn

8mm

242mm

14 mn

CASMA

3 mm

45mm

15°-0°
+ −

96 mm

86 mm

2 mm

6 mm

10 mm

3 mm

267mm

130°-15
+ −

286mm

123mm

speedy
by casma

L

L > 1000   X = 4
L 600-1000 X = 6
L < 600   X = 8

X

COMMERCIAL HARDWARE

FLOOR SPRINGS

JULY 2016

STANDARD FLOOR SPRING
CASMA

SBCM68

Item number	• SBCM68.HO - 90˚ hold open • SBCM68.NHO - non-hold open
Description	• floor spring - CASMA • maximum door weight 100kg • maximum door width – exterior 950mm • available 90˚ in hold open, and non-hold open • highly reliable mechanics proven by more than 4 million units installed. Yield greater than 65%. Lasts more than a decade • can be regulated inside the cement case, above all longitudinally to consent use even were the hinges axes are very different • quick and effective fixing in the cement case with seven screws • two completely independent oil circuits for programming the desired closing speed with two regulating valves: – one from 120° to 15° ca, and – the other from 15° to 0° ca • the rear cover (matching the cover) snaps into place once the door and cover are assembled. If this has been forgotten, it does not imply dismounting the door.
Material finish	• polished or satin stainless steel

SBCM68

71mm
8mm
9,5
40 mm

CASMA

+ ↔ −
0°
15°   15°
110 mm
280mm
+ ↔ −
15°
120°   120°

299mm
135mm

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FULLY ADJUSTABLE COMPACT FLOOR SPRING
HEAVY DUTY - CASMA

SBCM25

Item number	• SBCM25.HO - 90˚ hold open • SBCM25.NHO - non-hold open

Description	• fully adjustable compact floor spring heavy duty - CASMA
	• maximum door weight 120kg
	• maximum door width
	  – exterior 1 meter
	  – interior 1.2 meters
	• available 90˚ in hold open, and non-hold open
	• highly reliable mechanics proven by more than 4 million units installed. Yield greater than 65%. Lasts more than a decade
	• can be moved inside the cement case, above all longitudinally to allow use even where the hinge axes are very different
	• quick and effective fixing in the cement case with just four screws
	• two completely independent oil circuits for programming the desired closing speed with two regulating valves:
	  – one from 115° to 15° ca, and
	  – the other from 15° to 0° ca
	• the rear cover (matching the cover) snaps into place once the door and cover are assembled. If this has been forgotten, it does not necessitate dismantling the door

Material finish	• polished or satin stainless steel

SBCM25

67+3

15 mm

65mm

10mm   283mm   12mm

CASMA

15°-0°
+   −

130 mm 118.5 mm

9 mm

264mm

283mm

115°-15°
+   −

155mm

305mm

COMMERCIAL HARDWARE

FLOOR SPRINGS

MEDIUM DUTY FLOOR SPRING
SUITABLE FOR DOORS UP TO 120KG - DORMA

Item number	• BTS75V.HO - 90˚ hold open • BTS75V.NHO - non-hold open
Description	• medium duty floor spring - DORMA • complete with stainless steel cover plate and screw pack (option available for brass cover plate) • double action • maximum door width 1.1 meters • maximum door weight 120kg • maximum opening angle 175˚ • variable closing force from 10-30NM • optional 5mm, 10mm and 15mm extended spindles
Suitable for	• single and double-action doors
Material finish	• stainless steel or brass cover plate

BTS75V

BTS75V

DORMA

*S.T.D. spindle clearance
8mm to 50mm
extended clearance 58mm

50mm

78mm

55(65)mm   308mm

2 mm

78 mm

105 mm

51-58mm   291mm

cover plate

HEAVY DUTY FLOOR SPRING
SUITABLE FOR DOORS UP TO 300KG - DORMA

Item number	• BTS80.HO - 90˚ hold open • BTS80.NHO - non-hold open
Description	• heavy duty floor spring - DORMA • double action • selective multi-point hold open adjustable between approximately 75˚ and 175˚ • mechanical back check at approximately 85˚ and 165˚ • stainless steel cover plate (option available for brass cover plate) • maximum door weight 300kg • maximum door width 1.4 meters • maximum opening angle 180˚ • variable closing force 53NM • optional 5mm, 10mm and 15mm extended spindles
Suitable for	• single and double-action doors
Material finish	• stainless steel or brass cover plate

BTS80

BTS80

DORMA

*S.T.D. spindle clearance
8mm to 50mm
extended clearance 58mm

60mm

78mm

55(65)mm   358mm

2 mm

78 mm

105 mm

51-58mm   341mm

cover plate

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

STANDARD FLOOR SPRING DORMA

Item number	• BTS84.HO - 90˚ hold open standard • BTS84.HOW - 90˚ hold open weak spring force • BTS84.NHO - non-hold open standard
Description	• standard floor spring - DORMA • low profile 40mm depth • stainless steel cover plate (option available for brass cover plate) • maximum door weight 100kg • maximum door width 1.1 meter • maximum opening angle 130˚ • variable closing force from 25NM • optional 5mm, 10mm and 15mm extended spindles • optional 15NM weak spring force
Suitable for	• double-action doors
Material finish	• stainless steel or brass cover plate

BTS84

BTS84

DORMA

*S.T.D. spindle clearance
8mm to 50mm
extended clearance 58mm

40mm

108mm

55(65)mm   324mm

2 mm

108 mm

130 mm

51-58mm   306mm

cover plate

FLOOR SPRING SUITABLE FOR ONE LEAF SINGLE AND DOUBLE DOOR ACTION

Item number	TS500NV
Description	• floor spring suitable for one leaf single and double door action up to 1.1 meter leaf width • overall height 42mm • closing force adjustable size 1-4 according to EN1154 (TA 500 NV) • back check • closing speed adjustable • latching action adjustable • safety valve preventing deliberate overloading • closing range from approximately 170˚ • large adjustment range – height 6mm, lateral 10mm, length 10mm • galvanised cement box • floor spring complete with flat-tapered spindle, cement box and installation instructions. Without hold-open mechanism (cover plate not included)
Suitable for	• for internal right and left closing • single-action doors • for internal double-action doors
Material finish	• cover plate • stainless steel, LM - dark bronze and satin brass

TS500NV

TS500NV

42 mm

278mm

298mm

51-61mm

36-46 mm

36-46 mm

82 mm   105 mm

COMMERCIAL HARDWARE

FLOOR SPRINGS

ELITE GLASS SOLUTIONS

COMMERCIAL HARDWARE

FLOOR SPRINGS

FLOOR SPRING SUITABLE FOR ONE LEAF SINGLE AND DOUBLE DOOR ACTION

TS550NV

Item number	TS550NV
Description	• floor spring suitable for one leaf single and double door action • overall height 54mm • closing force adjustable size 3-6 according to EN1154 (TS 550 NV) • Infinitely variable hydraulic hold-open (80° - 165°), can be enabled/disabled • delayed closing instead of hold-open is possible • closing speed and latching action adjustable • fixed back check, integrated • safety valve preventing deliberate overloading • all settings can be adjusted from the top (when installed) • closing range from approx. 170° • large adjustment range – height 6mm, lateral 10mm, length 9mm • galvanised cement box • floor spring complete with flat-tapered spindle, cement box and installation instructions (cover plate not included) • maximum door width 1.4 meters • maximum door weight 300kg
Suitable for	• highly frequented doors • right and left hand closing • single-action doors

TS550NV

54 mm

1.5mm

342mm

362mm

51-60mm

82 mm

105 mm

B-B

A

A

54mm

36 mm

82mm

OZONE HYDRAULIC PATCH FITTING
SELF CLOSING

FH100

Item number	• FH100.HO - 90˚ hold open • FH100.NHO - non-hold open
Description	• Ozone hydraulic patch fitting self closing 90° hold open • floor mounted patch fitting for internal Frameless Glass doors up to 1 meter wide • maximum door width 1 meter (12mm clearance to floor) • maximum door weight 100kg • simple installation with four screw fixings into any floor • adjustable base plate for easy alignment of the door in either direction (as shown in diagram) • use in conjunction with standard HP20 top patch fitting (two speed closing adjustment as shown)
Suitable for	• single or double action doors • toughened frameless glass doors from 8mm - 12mm glass thickness
Material finish	• 316 polished or satin stainless steel

FH100

Hold open at 90°

150° No.1 10°
No.2 0°
No.2 10°
150° No.1

Hold open at 90°

Speed adjustment
Fast Slow

No.2 Braking speed
No.1 Closing speed

GLASS CUT OUT DETAIL

R12
49 mm
56 mm
173mm
180mm

HPT20
3mm gap
5mm gap
Maximum door width
1 meter
12mm gap
EPC

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

FLOOR SPRINGS

OZONE HYDRAULIC PATCH FITTING
HIGH STRENGTH SELF CLOSING

FH105

Item number	• FH105.HO - 90˚ hold open • FH105.NHO - non-hold open

Description	• Ozone hydraulic patch fitting high strength self closing
	• maximum door width
	  – internal 1.25 meters
	  – external 1 meter
	    (12mm clearance to floor)
	• maximum door weight 100kg
	• simple installation with four screw fixings into any floor
	• adjustable base plate for easy alignment of the door in either direction
	• used in conjunction with standard HP20 top patch fitting (two speed closing adjustment as shown)

Suitable for	• internal and external • single or double action doors • toughened frameless glass doors from 10mm - 15mm thick
Material finish	• 316 polished or satin stainless steel

36mm

186mm

68mm

FH.105

48mm

110mm

9mm

Hold open at 90˚

150˚

No.1

10˚

No.2

0˚

No.2

10˚

150˚

No.1

Hold open at 90˚

Speed adjustment

Fast   Slow

No.2 Braking speed

No.1 Closing speed

GLASS CUT OUT DETAIL

R12

179mm

59mm

67mm

187mm

12mm clearance
to floor level

The edges of the radius
should tipped or R5

ELITE GLASS SOLUTIONS

JULY 2016

EXTENDED SPINDLE
SUITABLE FOR FLOOR SPRING

Item number	EX.5
Description	• spindle extended by 5mm
Suitable for	• patch fittings and door rails

Item number	EX.10
Description	• spindle extended by 10mm
Suitable for	• patch fittings and door rails

Item number	EX.15
Description	• spindle extended by 15mm
Suitable for	• patch fittings and door rails

Item number	EX.20
Description	• spindle extended by 20mm
Suitable for	• patch fittings and door rails

Item number	EX.25
Description	• spindle extended by 25mm
Suitable for	• patch fittings and door rails

EX

EX.5   EX.10   EX.15

EX.20   EX.25

FLOOR SPRING COMPONENTS

Item number	MFX840
Description	• body only
Suitable for	• patch fittings and door rails

Item number	MFX.B
Description	• box only
Suitable for	• patch fittings and door rails
Material finish	• steel powder coated

Item number	MFX.BSS
Description	• box only
Suitable for	• patch fittings and door rails
Material finish	• stainless steel powder coated

Item number	MFX.CP
Description	• cover plate only
Suitable for	• patch fittings and door rails
Material finish	• 316 stainless steel

Item number	MFX.SP
Description	• cover plate screw pack
Suitable for	• patch fittings and door rails

MFX

MFX840

MFX.B

MFX.CP

COMMERCIAL HARDWARE

FLOOR SPRINGS

ELITE GLASS SOLUTIONS

COMMERCIAL HARDWARE

HYDRAULIC DOOR HINGES

HYDRAULIC
DOOR HINGES

HYDRAULIC DOOR HINGE MALIBU
GLASS TO GLASS

Item number	• HH180.HO - 90˚ hold open • HH180.NHO - non-hold open
Description	• hydraulic door hinge Malibu glass to glass • adjustable closing speed and position • maximum door width 900mm • maximum door height 2.4 meters • maximum door weight 65kg
Suitable for	• 10mm and 12mm glass thickness • double or single action applications
Material finish	• 316 polished or satin stainless steel

HH180

HH180

GLASS CUT OUT DETAIL - GLASS TO GLASS

R10   39mm   39mm   R10

70mm   78mm   78mm   70mm

49mm   49mm

7mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

COMMERCIAL HARDWARE

DOOR CLOSERS

DOOR CLOSERS

CONCEALED OVERHEAD DOOR CLOSER
STANDARD STRENGTH 25NM

Item number	• ECOC90.SNHO - non hold open 90˚ • ECOC90.SHO - hold open 90˚ • ECOC105.SHO - hold open 105˚
Description	• concealed overhead closer standard strength 25NM • available in non hold 90˚, hold open 90˚ or hold open 105˚ • supplied with closer arm and bottom pivot assembly • maximum door width 1 meter • maximum door weight 100kg

CONCEALED OVERHEAD DOOR CLOSER
HEAVY STRENGTH 35NM

Item number	ECOC90.HHO
Description	• concealed overhead closer heavy strength 35NM hold open 90˚ • supplied with closer arm and bottom pivot assembly • maximum door width 1.1 meter • maximum door weight 100kg

ECOC90

ECOC

Closer arm

Bottom pivot

ELITE GLASS SOLUTIONS

TRANSOM CONCEALED DOOR CLOSER
DORMA

Item number	• RTS85.HO - 90˚ hold open • RTS85.NHO - non-hold open
Description	• transom concealed door closer - DORMA • double action • maximum door width 1 meter • offers a solution for installations where door control must be provided without disturbing the aesthetic appearance of the door. The majority of preparation can be accomplished by the fabricator prior to installation, leaving minimal on-site work
Suitable for	• shop fitting - for both double and single action doors
Material finish	• stainless steel cover plate (aluminium or wood fix)

RTS85

RTS85

56mm
12mm
38mm
42mm

DORMA

323mm
20 mm
10 mm
Ø32

68 mm
M6
14.3mm
14mm 7mm
90 mm
84mm
52
80 mm
58mm
250mm
65mm
258.5mm

COMMERCIAL HARDWARE

DOOR CLOSERS

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

PATCH FITTINGS
10/12/15MM GLASS THICKNESS

BOTTOM PATCH FITTING
FOR 10/12MM GLASS THICKNESS

Item number	HP10
Description	• bottom patch fitting • maximum door weight 100kg • pivot set at 55mm • adjustable pivot insert
Suitable for	• 10mm and 12mm glass thickness • elite glass floor spring range • MP26 free swing pivot
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP10

31mm
166mm
52mm
HP10

GLASS CUT OUT DETAIL

161mm
148mm
20 mm
36mm
55mm
R80
68mm
37 mm

INSITU APPLICATION

JULY 2016

BOTTOM PATCH FITTING
FOR 10/12/15MM GLASS THICKNESS - CASMA

Item number	SBC41400
Description	• bottom patch fitting - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC41400

SBC41400

CASMA

GLASS CUT OUT DETAIL

165mm
148mm
ø18
50 mm
36 mm
68mm
R 73
36mm

INSITU APPLICATION

BOTTOM PIVOT PATCH FITTING
CENTRE MOUNT - CASMA

Item number	SBC41400.CM
Description	• bottom pivot patch fitting centre mount - CASMA • maximum door weight 100kg • maximum glass hold 300kg
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC41400.
CM

SBC41400.CM

CASMA

GLASS CUT OUT DETAIL

165mm
ø18
50 mm
36 mm
R6
R73
36 mm
98mm
145mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

TOP PIVOT PATCH FITTING
CENTRE MOUNT - CASMA

Item number	SBC42400.CM
Description	• top pivot patch fitting, centre mount - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm • adjustable +/- 3mm
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42400.CM

SBC42400.CM

CASMA

GLASS CUT OUT DETAIL

98mm minimum · 145mm · 36mm · R6 · R73 · 36 mm · 50 mm · Ø18 · 165mm

INSITU APPLICATION

TOP PATCH FITTING CENTRE MOUNT
FOR CONCEALED CLOSER - CASMA

Item number	SBC42420.CM
Description	• top patch fitting centre mount for concealed closer - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 65mm
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42420.CM

SBC42420.CM

CASMA

GLASS CUT OUT DETAIL

98mm minimum · 145mm · 36mm · R6 · R73 · 36 mm · 50 mm · Ø18 · 165mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TOP PIVOT PATCH FITTING
FOR 10/12/15MM GLASS THICKNESS - CASMA

| Item number	SBC42400
Description	• top pivot patch fitting - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42400

SBC42400

CASMA

GLASS CUT OUT DETAIL

131mm
36 mm
68mm
R73
36 mm
50 mm
ø18
148mm
165mm

INSITU APPLICATION

TOP PIVOT PATCH FITTING
FOR 10/12MM GLASS THICKNESS

Item number	HP20
Description	• top pivot patch fitting • maximum door weight 100kg • maximum glass hold 300kg • adjustable pivot insert
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP20

31mm
166mm
52mm
HP20

GLASS CUT OUT DETAIL

36mm
55mm
R80
68mm
37 mm
20 mm
148mm
161mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS


ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

TOP PATCH FITTING FOR OVERHEAD TRANSOM CLOSER

Item number	HP22
Description	• top patch fitting for overhead transom closer • maximum door weight 100kg • pivot set at 55mm • reversible to 65mm • adjustable pivot insert
Suitable for	• 10mm and 12mm glass thickness • overhead transom close
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP22

31mm
166mm
52mm
HP22

GLASS CUT OUT DETAIL

36mm 55mm R80 68mm 37mm
20mm
148mm
161mm

INSITU APPLICATION

TOP PATCH FITTING FOR CONCEALED CLOSER - CASMA

| Item number	SBC42420
Description	• top patch fitting for concealed closer - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 65mm
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42420


CASMA

GLASS CUT OUT DETAIL

36mm R73 36mm 50mm Ø18
148mm
165mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

OVERPANEL TRANSOM
PATCH FITTING WITH PIVOT
FOR 10/12MM GLASS THICKNESS

| Item number	• HP34 - includes fixing plate • HP30 - patch only
Description	• overpanel transom patch fitting with pivot • maximum door weight 100kg • pivot set at 55mm • adjustable pivot insert
Suitable for	• HP20 • 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP34

52mm · 164mm · 15mm · HP34 · 32mm · 60mm

GLASS CUT OUT DETAIL

161mm · 148mm · 20mm · 55mm · 36mm · R80 · 68mm · 37mm

INSITU APPLICATION

OVERPANEL TRANSOM
PATCH FITTING WITH PIVOT
FOR 10/12/15MM GLASS THICKNESS - CASMA

Item number	SBC43400
Description	• overpanel transom patch fitting with pivot - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• SBC42400 • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • side fixing to masonry, timber or aluminium jamb
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC43400

SBC43400 · CASMA

GLASS CUT OUT DETAIL

165mm · 148mm · ø18 · 50mm · 36mm · 68mm · R 73 · 36mm · 131mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

OVERPANEL PATCH FITTING
WITH PIVOT CENTRE MOUNT - CASMA

Item number	SBC43400.CM
Description	• overpanel patch fitting with pivot centre mount - CASMA • maximum door weight 100kg • maximum glass hold 300kg
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC43400.CM

SBC43400.CM

### GLASS CUT OUT DETAIL

165mm
148mm
ø18
50mm
36mm
68mm
36mm
R73
131mm

INSITU APPLICATION

OVERPANEL TO SIDE PANEL 90˚
PATCH FITTING WITH PIVOT - CASMA

Item number	• SBC43400.90˚.R - right hand • SBC43400.90˚.L - left hand
Description	• overpanel to side panel 90˚ patch fitting with pivot - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• SBC42400 top door pivot patch • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC43400.90˚.R

SBC43400.90°.R

GLASS CUT OUT DETAIL

50mm
35mm
165mm
148mm
18mm
20mm
36mm
68mm
25mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

OVERPANEL TO SIDE PANEL 135˚
PATCH FITTING WITH PIVOT - CASMA

Item number	• SBC43400.135˚.R - right hand • SBC43400.135˚.L - left hand
Description	• overpanel to side panel 135˚ patch fitting with pivot - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm • adjustable +/- 3mm
Suitable for	• SBC42400 • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC43400.
135˚.R

SBC43400.135°.R

CASMA

GLASS CUT OUT DETAIL

INSITU APPLICATION

OVERPANEL TO SIDE PANEL PATCH FITTING
WITH PIVOT FOR 10/12MM GLASS THICKNESS

| Item number	HP40
Description	• overpanel to side panel patch fitting with pivot • maximum door weight 100kg • adjustable pivot insert • pivot pin can be removed and replaced with a stop for single action door when this patch fitting is used for an overpanel/side panel
Suitable for	• HP20 • 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP40

HP40

**GLASS CUT OUT DETAIL**

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

JULY 2016

OVERPANEL TO SIDE PANEL PATCH FITTING WITH PIVOT FOR 10/12/15MM GLASS THICKNESS - CASMA

| Item number	SBC44400
Description	• overpanel to side panel patch fitting with pivot - CASMA • maximum door weight 100kg • maximum glass hold 150kg • pivot can be set at 55mm or 65mm
Suitable for	• SBC42400 • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC44400


SBC44400

GLASS CUT OUT DETAIL


INSITU APPLICATION

OFFSET PATCH FITTING WITH PIVOT - CASMA

Item number	SBC12790
Description	• offset patch fitting with pivot - CASMA • maximum door weight 60kg • maximum door width 1 meter • maximum glass hold 160kg • comes in a set (top and bottom) • single action only
Suitable for	• 10 or 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC12790

TOP

BOTTOM

SBC12790

GLASS CUT OUT DETAIL

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

OFFSET PATCH FITTING
BOTTOM LEFT HAND SIDE - CASMA

Item number	SBC41881
Description	• offset patch fitting bottom left hand side - CASMA • maximum door weight 100kg • maximum glass hold 150kg • offset knuckle cover - available in satin silver anodised or polished or satin stainless steel
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC41881

SBC41881

GLASS CUT OUT DETAIL

165mm
148mm
ø18
50 mm
36 mm
68mm
R73
36 mm
131mm

INSITU APPLICATION

OFFSET PATCH FITTING
BOTTOM RIGHT HAND SIDE - CASMA

| Item number	SBC41882
Description	• offset patch fitting bottom right hand side - CASMA • maximum door weight 100kg • maximum glass hold 150kg • offset knuckle cover - available in satin silver anodised or polished or satin stainless steel
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC41882

SBC41882

GLASS CUT OUT DETAIL

165mm
148mm
50 mm
36 mm
55mm
R73
68mm
36 mm
131mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

OFFSET PATCH FITTING TOP LEFT HAND SIDE - CASMA

Item number	SBC42881
Description	• offset patch fitting top left hand side - CASMA • maximum door weight 100kg • maximum glass hold 150kg • offset knuckle cover - available in satin silver anodised or polished or satin stainless steel
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42881

SBC42881

GLASS CUT OUT DETAIL

131mm, 36mm, 68mm, R73, 36mm, 50mm, ø18, 148mm, 165mm

INSITU APPLICATION

OFFSET PATCH FITTING TOP RIGHT HAND SIDE - CASMA

| Item number	SBC42882
Description	• offset patch fitting top right hand side - CASMA • maximum door weight 100kg • maximum glass hold 150kg • offset knuckle cover - available in satin silver anodised or polished or satin stainless steel
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42882



SBC42882

GLASS CUT OUT DETAIL

131mm, 36mm, 50mm, R73, 68mm, 36mm, ø18, 148mm, 165mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

OVERPANEL TO SIDE PANEL PATCH FITTING

Item number	HP60
Description	• overpanel to side panel patch fitting
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP60

106mm

HP60

106mm

52mm

GLASS CUT OUT DETAIL

20 mm

20 mm

36 mm

36 mm

73mm

34mm

20 mm

3mm 36mm

INSITU APPLICATION

OVERPANEL TO SIDE PANEL PATCH FITTING WITH DOOR STOP

Item number	HP61
Description	• overpanel to side panel patch fitting with removable single action door stop
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP61

106mm

HP61

106mm

52mm

GLASS CUT OUT DETAIL

20 mm

20 mm

36 mm

36 mm

73mm

34mm

20 mm

3mm 36mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

JULY 2016

OVERPANEL TO SIDE PANEL PATCH FITTING WITH DOOR STOP - CASMA

| Item number	SBC44710
Description	• overpanel to side panel patch fitting with door stop - CASMA • maximum glass hold 200kg
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC44710

SBC44710

CASMA

GLASS CUT OUT DETAIL

104mm
ø18
50mm
104mm
50mm

INSITU APPLICATION

OVERPANEL PATCH FITTING FOUR CORNER CONNECTING - CASMA

| Item number	SBC46500
Description	• overpanel patch fitting four corner connecting - CASMA • maximum glass hold 300kg • to connect two or four glass panels
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC46500

SBC46500

CASMA

GLASS CUT OUT DETAIL

104mm
ø18
104mm
75mm
75mm

INSITU APPLICATION

OVERPANEL PATCH FITTING WITH DOOR STOP

Item number	HP70
Description	• overpanel patch fitting incorporating stops for single action double doors • stops are removable and reversible
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP70

116mm

HP70

52mm

26mm

GLASS CUT OUT DETAIL

20 mm   20 mm

30 mm   73mm   30 mm

INSITU APPLICATION

OVERPANEL PATCH FITTING WITH DOOR STOP - CASMA

Item number	SBC47210
Description	• overpanel patch fitting with door stop - CASMA • maximum glass hold 150kg • comes with door stop plate
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC47210

SBC47210

CASMA

GLASS CUT OUT DETAIL

104mm

ø16/18   50mm

36mm   73mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

HEAD/JAMB FITTING ANGLE - CASMA

Item number	SBC46700
Description	• head/jamb fitting angle - CASMA • maximum glass hold 300kg • recommended torque 14 - 16
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC46700

SBC46700

GLASS CUT OUT DETAIL

104mm

73mm

52mm

36mm

ø16/18

INSITU APPLICATION

OVERPANEL TO SIDE PANEL PATCH FITTING WITH FIN - CASMA

Item number	• SBC44706 - right hand • SBC44707 - left hand
Description	• overpanel to side panel patch fitting with fin • maximum glass hold 200kg • to connect two or four glass panels • optional door stop can be fitted
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • 12mm or 15mm glass fin
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC44706
SBC44707

SBC44706

GLASS CUT OUT DETAIL

73mm

ø18

75 mm

36 mm

36 mm

36mm

GLASS FIN DETAIL

91mm

ø18

ø18

36mm

R9

39 mm

42mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

OVERPANEL TO SIDE PANEL PATCH FITTING WITH PIVOT AND 90° FIN

| Item number	• HP41.R - right hand • HP41.L - left hand
Description	• overpanel to side panel patch fitting with pivot and 90° fin • adjustable pivot insert
Suitable for	• HP20 • 10mm and 12mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coat

HP41

GLASS CUT OUT DETAIL

INSITU APPLICATION

Looking from outside

OVERPANEL TO SIDE PANEL PATCH FITTING WITH PIVOT AND 90° FIN - CASMA

Item number	• SBC45051 - right hand • SBC45052 - left hand
Description	• overpanel to side panel patch fitting with pivot and 90° fin - CASMA • maximum door weight 100kg • maximum glass hold 150kg • pivot point set at 55mm or 65mm
Suitable for	• SBC42400 • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • 12mm or 15mm glass fin
Material finish	• natural anodised • polished or satin stainless steel • polished brass

SBC45051
SBC45052

CASMA

GLASS CUT OUT DETAIL

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

COMMERCIAL HARDWARE

PATCH FITTINGS - 10/12/15MM GLASS THICKNESS

FOUR CORNER CONNECTING PATCH FITTING WITH FIN - CASMA

Item number	SBC46550
Description	• four corner connecting patch fitting with fin - CASMA • maximum glass hold 300kg
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • 12mm or 15mm glass fin
Material finish	• natural anodised • polished or satin stainless steel • polished brass

SBC46550

SBC46550

GLASS CUT OUT DETAIL

104mm
33mm
ø18
104mm
73/75mm
36 mm
36 mm
73/75mm

INSITU APPLICATION

DOUBLE DOOR FIN WITH BRACKET AND DOOR STOPS - CASMA

Item number	SBC47260
Description	• double door fin with bracket and door stops - CASMA • maximum glass hold 150kg
Suitable for	• 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • 12mm or 15mm glass fin
Material finish	• natural anodised • polished or satin stainless steel • polished brass

SBC47260

SBC47260

GLASS CUT OUT DETAIL

73mm
ø18
36 mm
91mm
ø18
39 mm
R9
36 mm
42mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

TRANSOM FIN
WITH DOUBLE PIVOT - CASMA

Item number	SBC47750
Description	• transom fin with double pivot - CASMA • maximum glass hold 350kg • pivot point set at 55mm or 65mm
Suitable for	• SBC42400 (provides pivot point) • 12mm glass thickness • 10mm or 15mm glass thickness can be adjusted to fit • 12mm or 15mm glass fin
Material finish	• natural anodised • polished or satin stainless steel • polished brass

SBC47750

SBC47750

CASMA

GLASS CUT OUT DETAIL

333mm
33mm
299mm
50 mm
36 mm
36mm
Ø16/18
36 mm
R73
10/12
77mm
33mm
15mm
113mm
271mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 15/19MM GLASS THICKNESS

PATCH FITTINGS
15/19MM GLASS THICKNESS

BOTTOM PATCH FITTING
FOR 15/19MM GLASS THICKNESS - CASMA

| Item number	SBC41020
Description	• bottom patch fitting - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC41020

SBC41020

CASMA

GLASS CUT OUT DETAIL

165mm
128mm
ø30
50 mm
26 mm
38 mm
136mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TOP PIVOT PATCH FITTING
FOR 19MM GLASS THICKNESS - CASMA

| Item number	SBC42020
Description	• top pivot patch fitting - CASMA • maximum door weight 100kg • maximum glass hold 300kg • pivot set at 55mm or 65mm • adjustable +/- 3mm
Suitable for	• 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC42020

SBC42020

GLASS CUT OUT DETAIL

38 mm | 138mm | 22 mm | 50 mm
126mm | ø38
165mm

INSITU APPLICATION

OVERPANEL TRANSOM PATCH FITTING WITH
PIVOT FOR 15/19MM GLASS THICKNESS - CASMA

Item number	SBC43020
Description	• overpanel transom patch fitting with pivot - CASMA • maximum door weight 125kg • maximum glass hold 300kg • pivot set at 55mm or 65mm
Suitable for	• SBC42400 • 15mm or 19mm glass thickness • side fixing to masonry, timber or aluminium jamb
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC43020

SBC43020

GLASS CUT OUT DETAIL

165mm | ø38 | 50 mm
126mm
38 mm | 138mm | 22 mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PATCH FITTINGS - 15/19MM GLASS THICKNESS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PATCH FITTINGS - 15/19MM GLASS THICKNESS

OVERPANEL TO SIDE PANEL
PATCH FITTING WITH PIVOT
FOR 15/19MM GLASS THICKNESS - CASMA

Item number	SBC44020
Description	• overpanel to side panel patch fitting with pivot - CASMA • maximum door weight 125kg • maximum glass hold 300kg • pivot can be set at 55mm or 65mm
Suitable for	• SBC42400 - provides pivot point • 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • polished brass

SBC44020

SBC44020

CASMA

GLASS CUT OUT DETAIL

220mm
128mm
2mm
26mm
50 mm
ø38
38 mm
ø38
ø15
78mm
70mm
105 mm
26mm
50mm

INSITU APPLICATION

JULY 2016

DOOR RAILS

BOTTOM DOOR RAIL NON-LOCKING

Item number	RL1
Description	• bottom door rail - non-locking • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps • adjustable pivot strap function
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• please specify glass width

RL1

RL1

Total door width

32mm

SIDE VIEW

59mm

84mm

INSITU APPLICATION

COMMERCIAL HARDWARE

DOOR RAILS

BOTTOM DOOR RAIL NON-LOCKING
FOR SLIDING DOORS

Item number	RL5.B
Description	• bottom door rail - non-locking • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • floor guide (FGR) • roller attachments • sliding doors
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• please specify glass width

RL5.B

Total door width

32mm

SIDE VIEW

59mm   84mm

INSITU APPLICATION

BOTTOM DOOR RAIL LOCKING
FOR SLIDING DOORS

Item number	RL6.B
Description	• bottom door rail - locking • complete with 590 lock • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • floor guide (FGR) • sliding doors
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• specify cylinder combination - double cylinder, cylinder/turn, single cylinder or single turn • please specify glass width

RL6.B

Total door width

32mm

SIDE VIEW

59mm   84mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BOTTOM DOOR RAIL LOCKING

| Item number	RL3
Description	• bottom door rail - locking • complete with 590 lock • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps • adjustable pivot strap function
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• specify cylinder combination - double cylinder, cylinder/turn, single cylinder or single turn • please specify glass width

TOP DOOR RAIL NON-LOCKING

Item number	RL2
Description	• top door rail - non-locking • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps • adjustable pivot strap function
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• please specify glass width

RL3

RL3

Total door width

32mm

SIDE VIEW

59mm   84mm

INSITU APPLICATION

RL2

RL2

Total door width

32mm

SIDE VIEW

84mm   59mm

INSITU APPLICATION

TOP DOOR RAIL NON-LOCKING
FOR CONCEALED OVERHEAD CLOSER

Item number	RL2.COC
Description	• top door rail - non-locking for concealed overhead closer • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • concealed overhead closer
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• please specify glass width

RL2.COC

RL2.COC

Total door width

SIDE VIEW

84mm   59mm   32mm

INSITU APPLICATION

TOP DOOR RAIL NON-LOCKING
FOR SLIDING DOORS

Item number	RL5.T
Description	• top door rail - non-locking supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • sliding doors • floor guide (FGR) • roller attachments
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• please specify glass width

RL5.T

RL5.T

Total door width

SIDE VIEW

84mm   59mm   32mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TOP DOOR RAIL LOCKING
FOR SLIDING DOORS

Item number	RL6.T
Description	• top door rail - locking • complete with 590 lock • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • sliding doors • floor guide (FGR)
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• specify cylinder combination - double cylinder, cylinder/turn, single cylinder or single turn • please specify glass width

RL6.T

RL6.T

Total door width

32mm

SIDE VIEW

84mm   59mm

INSITU APPLICATION

TOP DOOR RAIL LOCKING

| Item number	RL4
Description	• top door rail - locking • complete with 590 lock • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps • adjustable pivot strap function
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• specify cylinder combination - double cylinder, cylinder/turn, single cylinder or single turn • please specify glass width

RL4

RL4

Total door width

32mm

SIDE VIEW

84mm   59mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

TOP DOOR RAIL LOCKING
FOR CONCEALED OVERHEAD CLOSER

Item number	RL4.C0C
Description	• top door rail - locking • complete with 590 lock • supplied in custom lengths with cover plates and end caps • rail length needs to 9mm less than your glass to allow for end caps
Suitable for	• 10mm, 12mm, 15mm or 19mm glass thickness • concealed overhead closer
Material finish	• satin silver anodised • polished or satin stainless steel • selected powder coated
Order	• specify cylinder combination - double v/turn, single cylinder or single turn • please specify glass width

FLOOR GUIDE RAIL

Item number	FGR
Description	• floor guide rail
Suitable for	• elite glass sliding rail
Material finish	• black nylon

FGR

FGR

6mm

25mm

46mm

100mm

RL4.COC

RL4.COC

Total door width

32mm

SIDE VIEW

84mm

59mm

INSITU APPLICATION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PIVOTS, BEARINGS AND DOOR STOPS

PIVOTS, BEARINGS AND DOOR STOPS

TOP PIVOT WITH PLATE MOUNTING

Item number	HP24
Description	• top pivot with plate mounting
Suitable for	• HP20 patch fitting • RL2 and RL4 top rails
Material finish	• stainless steel

HP24

HP24

105mm
2mm
28mm

TOP PIVOT PIN WITH WASHER

Item number	HP25
Description	• top pivot pin with washer • 8mm metric thread • 44mm diameter face washer
Suitable for	• HP20 patch fitting • RL2 and RL4 top rails
Material finish	• plated steel

HP25

HP25

60mm
22mm
50mm

ELITE GLASS SOLUTIONS

JULY 2016

TOP PIVOT WITH PLATE MOUNTING - CASMA

Item number	• SBC10180 maximum door weight 100kg maximum door width 1.1 meter • SBC10180.3 - heavy duty maximum door weight 150kg • SBC10180.6 - heavy duty maximum door weight 250kg
Description	• top pivot with plate mounting - CASMA • option of polished or satin stainless steel covers can be added
Material finish	• raw stainless steel (standard)

TOP PIVOT COVER - CASMA

Item number	• SBC10180.SSS satin stainless steel • SBC10180.PSS polished stainless steel
Description	• top pivot cover - CASMA
Suitable for	• SBC10180 body
Material finish	• polished or satin stainless steel

SBC10180

GLASS CUT OUT DETAIL

INSITU APPLICATION

COMMERCIAL HARDWARE

PIVOTS, BEARINGS AND DOOR STOPS

JULY 2016

TOP PIVOT CENTRE

Item number	FFF210
Description	• top centre pivot • provides top pivot point in aluminium or timber transoms • transom fitting, cover plate and door component included (if using glass door with patch fitting, disregard door component)
Suitable for	• SBC4240 and top rails

FFF210

25mm
164mm
5mm
31mm
Ø15
177mm
1mm
FFF210

TOP PIVOT RIGHT AND LEFT HAND

Item number	• SBC10481 - left hand • SBC10482 - right hand
Description	• top pivot right and left hand • maximum door weight 100kg • maximum door width 1.1 meter
Suitable for	• casma offset patch fittings • door rails
Material finish	• natural anodised • polished or satin stainless steel • polished brass

SBC10481
SBC10482

SBC10481

CASMA

DETAIL

118.5mm
30mm
37.5mm
37.5mm
13.5 mm
5 mm
3.5 mm
22mm
15mm

INSITU APPLICATION

BOTTOM DOOR STRAP

Item number	FFF212
Description	• bottom door strap
Suitable for	• bottom of timber or aluminium door to provide connection to floor bearing pivot HP26 or floor spring

FFF212

FFF212

FLOOR PIVOT BEARING

Item number	SBC11720
Description	• floor pivot bearing • maximum door weight 80kg
Suitable for	• SBC41400 patch fitting for free grout point • door rails on showcases • lightweight doors • runs on bearing mechanism for ease of use

SBC11720

SBC11720

CASMA

DETAIL

INSITU APPLICATION

COMMERCIAL HARDWARE

PIVOTS, BEARINGS AND DOOR STOPS

ELITE GLASS SOLUTIONS

JULY 2016

FLOOR PIVOT BEARING

Item number	MP26
Description	• floor pivot bearing • free swing
Suitable for	• HP10 • RL1 and RL3 bottom rails • 10mm and 12mm glass thickness
Material finish	• satin silver anodised

MP26

4mm

100mm   45mm

MP26

ALUMINIUM PACKING PLATES

Item number	• MP26.P5 - 5mm thickness • MP26.P10 - 10mm thickness
Description	• aluminium packing plates available in 5mm and 10mm thickness
Suitable for	• standard floor pivot
Material finish	• mill aluminiumj

MP26.P5
MP26.P10

MP26.P5
MP26.P10

FLOOR PIVOT BEARING EXTENDED SPINDLE

Item number	MP26.EXT5
Description	• floor pivot bearing extended spindle • 5mm extended spindle • free swing
Suitable for	• HP10 • RL1 and RL3 bottom rails • 10mm and 12mm glass thickness
Material finish	• satin silver anodised

MP26.EXT5

4mm

100mm   45mm

MP26.EXT5

ELITE GLASS SOLUTIONS

FLOOR FERULE
SUIT 10/12/13 DIAMETER PIN

Item number	• SBC15501 - 10mm diameter • SBC15502 - 12mm diameter • SBC15503 - 13mm diameter
Description	• floor ferule • to be used in flooring or structure with pin locks
Suitable for	• use with 10mm, 12mm and 13mm diameter pin style locks in show cases
Material finish	• natural anodised

SBC15501
/02/03

SBC15501   SBC15502
Ø10   Ø12

SBC15503
Ø13

DETAIL

24.5mm
2mm
20 mm
4mm
16mm

INSITU APPLICATION

FLOOR FERULE
ELONGATED HOLE

Item number	SBC15519
Description	• floor ferule - elongated hole for adjustment with lock on site • to be used in flooring or structure with pin locks
Suitable for	• eurostyle pin locks in floor
Material finish	• stainless steel satin

SBC15519

SBC15519

DETAIL

30mm
2.5mm
32.5mm   35mm
30mm
16mm   13mm
19.5mm

INSITU APPLICATION

COMMERCIAL HARDWARE

PIVOTS, BEARINGS AND DOOR STOPS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

© Copyright 2016. Theses drawings must not be copied or used by others without the written consent of Elite Glass Solutions.   JULY 2016

PIVOT WITH THREADED ROD

| Item number	SBC10200
Description	• pivot with threaded rod • pivot 15mm diameter • threaded rod M8
Suitable for	• fixing a pivot point to a steel or concrete head

SBC10200

SBC10200

CASMA

DETAIL

18mm 39mm 20mm
15 mm M8 5mm
3mm
60mm

INSITU APPLICATION

GROUND KEEPER

Item number	MK590
Description	• ground keeper
Suitable for	• lockwood 590
Material finish	• polished or satin stainless steel

MK590

28mm 142mm
38mm MK590 2mm

LOCK KEEPER

Item number	LK590
Description	• lock keeper
Suitable for	• ground keeper
Material finish	• polished or satin stainless steel

LK590

2mm 142mm
LK590 28mm

FLOOR MOUNT STOP
QUARTER SPHERE 21MM

Item number	HP32.2
Description	• floor mount stop • 21mm high • quarter sphere shape
Material finish	• polished or satin stainless steel

HP32.2

HP32.2

FLOOR MOUNT STOP
TRIANGLE

Item number	HP32.4
Description	• floor mount stop • triangle shape
Material finish	• polished or satin stainless steel

HP32.4

HP32.4

FLOOR MOUNT STOP
QUARTER SPHERE 33MM

Item number	HP32.3
Description	• floor mount stop • 33mm high • quarter sphere shape
Material finish	• polished or satin stainless steel

HP32.3

HP32.3

FLOOR MOUNT STOP
CYLINDER

Item number	HP32
Description	• floor mount stop • cylinder shape
Material finish	• satin silver anodised • chrome plate • polished brass • selected powder coat

HP32

HP32

**ELITE GLASS SOLUTIONS**

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FLOOR MOUNT STOP SPACER

Item number	HP32.2S
Description	• floor mount stop spacer
Suitable for	• HP32.2
Material finish	• polished or satin stainless steel

HP32.2S

ø45

10mm

HP32.2S

WALL MOUNT STOP 76MM

Item number	HP33
Description	• wall mount stop • 76mm length
Suitable for	• concealed fixings
Material finish	• satin silver anodised • polished or satin stainless steel • powder coated

HP33

76mm

HP33

WALL MOUNT STOP CYLINDER 52MM

Item number	HP32.5
Description	• wall mount stop • 52mm length • cylinder shape
Suitable for	• concealed fixings
Material finish	• polished or satin stainless steel

HP32.5

ø35

HP32.5

52mm

22mm

TRANSOM HEAD DOOR STOP

Item number	HP6
Description	• transom head door stop with 3mm rubber buffer
Material finish	• natural anodised • polished or satin stainless steel

HP6

30mm

100mm

15mm

HP6

12.5mm   75mm   12.5mm

15mm

ELITE GLASS SOLUTIONS

TRANSOM MOUNT STOP
FOR SINGLE DOOR INSTALLATION

Item number	HP28
Description	• transom mount stop • rubber in fill stop
Suitable for	• single door 50mm installation
Material finish	• satin silver anodised • chrome plate • polished brass • selected powder coat

HP28

HP28

16mm
50mm
16mm

TRANSOM MOUNT STOP
FOR DOUBLE DOOR INSTALLATION

Item number	HP28.D
Description	• transom mount stop • rubber in fill stop
Suitable for	• double door installation
Material finish	• satin silver anodised • chrome plate • polished brass • selected powder coat

HP28.D

HP28.D

16mm
100mm
16mm

SEALING COMPOUND

Item number	FS.RESIN
Description	• sealing compound • two component resin is poured around the body of the closer in the cement box to improve waterproofing
Suitable for	• preventing the likelihood of water entering the cement box

FS.RESIN

FS.RESIN

ELITE GLASS SOLUTIONS

FLOOR SPRING SEALING COMPOUND PART A

ELITE GLASS SOLUTIONS

PART B HARDENER COMPOUND

COMMERCIAL HARDWARE

PIVOTS, BEARINGS AND DOOR STOPS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

DOOR PIVOTS

DOOR PIVOTS

TOP TRANSOM SPIDER DOOR PIVOT

Item number	483
Description	• top transom spider door pivot
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

483

86mm

483

97mm

451
Spider fitting

TOP SPIDER DOOR PIVOT

Item number	452
Description	• top spider door pivot
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

452

451
Spider fitting

97mm

452

86mm

ELITE GLASS SOLUTIONS

JULY 2016

BOTTOM SPIDER DOOR PIVOT

Item number	451
Description	• bottom spider door pivot
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

451

86mm

451

451
Spider fitting

97mm

SHORT TOP POLE DOOR PIVOT

Item number	652
Description	• short top pole door pivot • maximum door weight 80kg • maximum door height 2.5 meters • maximum door width 1.2 meters
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

652

652

SHORT BOTTOM DOOR PIVOT

Item number	651
Description	• fits to floor spring • maximum door weight 80kg • maximum door height 2.5 meters • maximum door width 1.2 meters
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

651

651

PIVOT POLE SECTION JOINER

Item number	65S
Description	• intermediate pivot pole section to join top and bottom pole pieces
Suitable for	• 10mm and 12mm glass thickness
Material finish	• 316 stainless steel satin

COMMERCIAL HARDWARE

OFFSET JAMB HINGE

OFFSET JAMB HINGE

OFFSET JAMB HINGE - CASMA

Item number	SBC13100
Description	• maximum door weight 50kg • maximum door width 1 meter
Suitable for	• 8mm or 10mm glass thickness • floor guide (FGR)
Material finish	• natural anodised • polished or satin stainless steel

SBC13100

SBC13100

CASMA

GLASS CUT OUT DETAIL

30 mm
55mm
50mm
Ø16/20

INSITU APPLICATION

ELITE GLASS SOLUTIONS

JULY 2016

DOOR SEALS

ANODISED ALUMINIUM DOOR SEAL
FOR 12MM GLASS THICKNESS

Item number	DS180.12
Description	• anodised aluminium door seal with polypropylene grey pile • includes double sided adhesive foam tape • 3 meter stock length
Material finish	• silver anodised
Suitable for	• 12mm glass thickness

DS180.12

8mm
12mm
10.5mm

DS180.12

ANODISED ALUMINIUM DOOR SEAL
FOR 10MM GLASS THICKNESS

Item number	DS180.10
Description	• anodised aluminium door seal with polypropylene grey pile • includes double sided adhesive foam tape • 3 meter stock length
Material finish	• silver anodised
Suitable for	• 10mm glass thickness

DS180.10

8mm
10mm
DS180.10
10.5mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

CLEAR POLY CARBONATE DOOR SEAL FOR 10MM GLASS THICKNESS

Item number	RP103
Description	• clear poly carbonate door seal with black polypropylene pile • 3 meter stock length
Material finish	• clear poly
Suitable for	• 10mm glass thickness

RP103

CLEAR POLY CARBONATE DOOR SEAL FOR 12MM GLASS THICKNESS

Item number	RP104
Description	• clear poly carbonate section with polypropylene pile • 3 meter stock length
Material finish	• clear poly
Suitable for	• 12mm glass thickness

RP104

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

ANODISED ALUMINIUM DOOR SEAL 90º
FOR SLIDING DOOR

| Item number	DSS90
Description	• anodised aluminium door seal 90º with polypropylene grey woolpile • slim profile • will reduce draughts • will assist with noise reduction • includes double sided adhesive tape • seal fitted to back edge of door to create seal back to side panel or wall • profile designed to match DS180 edge seal • available with different woolpile lengths • 3 meter stock length
Material finish	• silver anodised with grey woolpile
Suitable	• between frameless glass sliding door panels, sidelights or walls • suitable for manual or automatic doors
Order	• specify 'Y' dimension as per selection chart to the right

Item number	DSS90.12.Y
Suitable for	• 12mm glass thickness

Item number	DSS90.10.Y
Suitable for	• 10mm glass thickness

DSS90

SELECTION CHART FOR DSS90
FOR 10MM GLASS THICKNESS

X = glass thickness 10mm Y = wool pile (just touching side panel)	
When X = 10mm glass thickness	Y = 18mm order DSS90.10.18 Y = 20mm order DSS90.10.20 Y = 23mm order DSS90.10.23 Y = 26mm order DSS90.10.26 Y = 28mm order DSS90.10.28 Y = 32mm order DSS90.10.32

SELECTION CHART FOR DSS90
FOR 12MM GLASS THICKNESS

| X = glass thickness 12mm Y = wool pile (just touching side panel)	
When X = 12mm glass thickness	Y = 18mm order DSS90.12.18 Y = 20mm order DSS90.12.20 Y = 23mm order DSS90.12.23 Y = 26mm order DSS90.12.26 Y = 28mm order DSS90.12.28 Y = 32mm order DSS90.12.32

COMMERCIAL HARDWARE

DOOR SEALS

ELITE GLASS SOLUTIONS

JULY 2016

PVC SEALS

PVC SEALS

PVC SEAL SUITABLE FOR 180° APPLICATION

Item number	DS12.1
Description	• PVC seal • available in 2.4 meter lengths
Suitable for	• 12mm glass thickness • 180° door/sidelight application
Material finish	• clear PVC

DS12.1

DS12.1

10mm

Fixed panel   Glass door

PVC SEAL SUITABLE FOR 135° APPLICATION

Item number	DS12.2
Description	• PVC seal • available in 3 meter lengths
Suitable for	• 12mm glass thickness • 135° door application
Material finish	• clear PVC

DS12.2

DS12.2

135°
15 mm

Glass door

Fixed panel

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

PVC SEAL WITH FIN

Item number	DS12.3
Description	• PVC seal with fin • available in 3 meter lengths
Suitable for	• 12mm glass thickness
Material finish	• clear PVC

DS12.3

DS12.3

PVC SEAL SUITABLE FOR 180° APPLICATION

Item number	DS12.11
Description	• PVC seal • available in 3 meter lengths
Suitable for	• 12mm glass thickness • 180° door application
Material finish	• clear PVC

DS12.11

DS12.11

PVC SEAL WITH FIN

Item number	DS12.4
Description	• PVC seal with fin • available in 3 meter lengths
Suitable for	• 12mm glass thickness
Material finish	• clear PVC

DS12.4

DS12.4

PVC SEAL SUITABLE FOR 135° APPLICATION FIXED PANEL

Item number	DS12.14
Description	• PVC seal • available in 3 meter lengths
Suitable for	• 12mm glass thickness • 135° door/sidelight application • fixed panel
Material finish	• clear PVC

DS12.14

DS12.14

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

PVC SEALS

PVC SEAL SUITABLE FOR 180° APPLICATION FIXED PANEL

Item number	DS12.18
Description	• PVC seal • available in 3 meter lengths
Suitable for	• 12mm glass thickness • 180° door application • fixed panel
Material finish	• clear PVC

DS12.18

DS12.18

15mm

Fixed panel   Glass door

PVC SEAL WITH ROUND TUBE SECTION

Item number	DS12.19
Description	• PVC seal with round tube section • available in 2.2 meter lengths
Suitable for	• 12mm glass thickness • door to wall application • door to sidelight application
Material finish	• clear PVC

DS12.19

DS12.19

6 mm

Glass or Wall

Glass door

Glass door

Floor

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

CHANNELLING

## COMMERCIAL HARDWARE

CHANNELLING

CHANNELLING 25MM HIGH

Item number	CU25
Description	• 25mm high channel • 5 meter stock length • 2.6mm thickness
Suitable for	• 10mm and 12mm glass thickness
Material finish	• mill finish • stain silver anodised

CU25

25mm
20mm
5 metres
CU25

CHANNELLING 45MM HIGH

Item number	CU45
Description	• 45mm high channel • 5 meter stock length • 2.6mm thickness
Suitable for	• 10mm and 12mm glass thickness
Material finish	• mill finish • stain silver anodised

CU45

45mm
20mm
5 metres
CU45

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

CHANNELLING

CHANNELLING ONE PIECE
FOR 10 TO 15MM GLASS THICKNESS

Item number	CS134
Description	• channeling one piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• heavy weight toughened and laminated glass 10mm to 15mm
Material finish	• natural anodised • mill finish

CS134

CS134

19
40mm
30mm

CHANNELLING ONE PIECE
FOR 27 TO 34MM GLASS THICKNESS

Item number	CS155
Description	• channeling one piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• double glazed units from 27mm to 34mm
Material finish	• natural anodised • mill finish

CS155

50mm
38mm
CS155
50mm

CHANNELLING ONE PIECE
FOR 18MM TO 25MM GLASS

Item number	CS144
Description	• channeling one piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• heavy weight toughened glass and double glazed units from 18mm to 25mm
Material finish	• natural anodised • mill finish

CS144

40mm
29mm
40mm
CS144

CHANNELLING ONE PIECE
TAPERED PROFILE

Item number	TC143
Description	• channeling one piece with tapered profile • 5 meter stock length only
Suitable for	
Material finish	• natural anodised • mill finish • bright silver anodised

TC143

40mm
30mm
TC143

JULY 2016

CHANNELLING TWO PIECE
TAPERED PROFILE

Item number	TC243
Description	• channeling two piece with tapered profile • 5 meter stock length only
Suitable for	• 10mm and 15mm glass thickness
Material finish	• natural anodised • mill finish • bright silver anodised

TC243

TC243

40mm

30mm

CHANNELLING TWO PIECE
FOR 10MM TO 15MM GLASS THICKNESS

Item number	CS234
Description	• channeling two piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• heavy weight toughened and laminated glass 10mm to 15mm
Material finish	• natural anodised • mill finish

CS234

CS234

40mm

CHANNELLING TWO PIECE
FOR 18MM TO 25MM GLASS THICKNESS

Item number	CS244
Description	• channeling two piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• heavy weight toughened glass and double glazed units from 18mm to 25mm
Material finish	• natural anodised • mill finish

CS244

40mm

40mm

CS244

CHANNELLING TWO PIECE
FOR 27MM TO 34MM GLASS THICKNESS

Item number	CS255
Description	• channeling two piece • 5 meter stock length only • anodised to 20 microns
Suitable for	• double glazed units from 27mm to 34mm
Material finish	• natural anodised • mill finish

CS255

CS255

50mm

SEC4
69

COMMERCIAL HARDWARE

CHANNELLING

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

COMMERCIAL HARDWARE

CHANNELLING

COMMERCIAL GLAZING U CHANNELLING BOTTOM

Item number	COM1
Description	• heavy duty one or two piece architectural commercial channel section
Suitable for	• bottom • interior and exterior applications • 10mm, 12mm, or 15mm glass thickness • 19mm glass thickness if wet glazed
Material finish	• mill finish • stain silver anodised

COM1

32mm
20.4mm
COM1
39mm 45mm

COMMERCIAL GLAZING U CHANNELLING HEAD/SIDE

Item number	COM2
Description	• heavy duty one or two piece architectural commercial channel section
Suitable for	• head and side • interior and exterior applications • 10mm, 12mm, or 15mm glass thickness • 19mm glass thickness if wet glazed
Material finish	• mill finish • stain silver anodised

COM2

32mm
20.4mm
COM2
33mm 45mm

COMMERCIAL GLAZING END CAP

Item number	COM3
Description	• end cap for channelling
Suitable for	• COM1 and COM2
Material finish	• mill finish • stain silver anodised

COM3

COM3

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

LOCKING SYSTEMS

**ELITE GLASS SOLUTIONS**

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

DIGITAL LOCKS

SMART TOUCH DIGITAL LOCK

| Item number	YDG313L
Description	• introducing a very smart glass door lock... the preferred solution to secure your home or office • sleek silver mirror finish - the numbered keypad appears on the mirror screen when touched • a simple solution for locking pivot doors • quick and easy installation • smartpad touch screen with optional card key • multi-featured • battery operated, including a 9 volt emergency battery back-up • automatic locking • no hole or glass cut out required • dual access, either by card or by smart pad screen (multiple cards can be enabled) • 4AA batteries will last up to one year • used in conjunction with standard elite glass pivot door fittings • strike plate for door jambs available on request
Suitable for	• for internal and external doors • residential and commercial applications • suits both single and double doors • 10mm and 12mm toughened safety glass
Material finish	• silver polished mirror

YDG313L

FRONT

YDG313L

BACK

DIGITAL LOCK GLASS KEEPER

Item number	YDG313K
Description	• digital lock glass keeper • no holes or notches required in glass • fits existing doors with minimum 3mm clearance • fitted with high bond tape
Suitable for	• 10mm and 12 single or double action glass doors

YDG313K

YDG313K

FRONT   BACK

REMOTE ACCESS RECEIVER MODULE

Item number	RCM100
Description	• remote access receiver module • required component if remote access is required
Suitable for	• smart touch lock YDG313L

RCM100

RCM100

WALL MOUNTABLE REMOTE

Item number	WRC100
Description	• wall mountable remote • lock and unlock function • operating range up to 30 meters
Suitable for	• use with RCM100 to operate

WRC100

WRC100

KEY FOB REMOTE

Item number	PRC100
Description	• key fob remote • unlock function, • operating range up to 30 meters
Suitable for	• smart touch lock YDG313L

PRC100

PRC100

ALUMINIUM / TIMBER STRIKE PLATE

Item number	ATS100
Description	• aluminium / timber strike plate
Suitable for	• smart touch lock YDG313L
Material finish	• 316 stainless steel satin

ATS100

ATS100

LOCKING SYSTEMS

DIGITAL LOCKS

ELITE GLASS SOLUTIONS

JULY 2016

PATCH LOCKS

BOTTOM OR TOP PATCH LOCK

Item number	PL590
Description	• bottom or top patch lock • complete with lock and cylinders
Suitable for	• 10mm and 12mm glass thickness • keeper LK590/GK590
Material finish	• polished or satin stainless steel • selected powdercoat (lead time applies)

Order	• specify cylinder combination
	  - double cylinder, cylinder/turn,
	    single cylinder or single turn
	• please specify glass width

PL590

PL590

235mm

50mm

37mm

GLASS CUT OUT DETAIL

40mm

R10

222mm

CENTRE PATCH LOCK

Item number	CPL590
Description	• centre patch lock • complete with lock and cylinders
Suitable for	• 10mm and 12mm glass thickness • keeper CPK590/LK590
Material finish	• polished or satin stainless steel • selected powdercoat (lead time applies)

Order	• specify cylinder combination
	  - double cylinder, cylinder/turn,
	    single cylinder or single turn

CPL590

CPL590

233mm

37mm   50mm

GLASS CUT OUT DETAIL

R10

212mm

40mm

CENTRE PATCH KEEPER

Item number	CPK590
Description	• centre patch keeper • complete with lock and cylinders
Suitable for	• 10mm and 12mm glass thickness • CPL590
Material finish	• polished or satin stainless steel • selected powdercoat (lead time applies)

CPK590

CPK590

233mm

37mm   50mm

GLASS CUT OUT DETAIL

R10

212mm

40mm

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BOTTOM OR CENTRE PATCH LOCK

Item number	MP300
Description	• bottom or centre patch lock • includes cylinders and long throw mortice lock • 210mm H x 64mm W with throw centre of 112.5mm
Suitable for	• 10mm and 12mm glass thickness • keeper MP320
Material finish	• polished or satin stainless steel

MP300

64mm

MP300

210mm

GLASS CUT OUT DETAIL

R10
198mm
48mm
80mm minimum

CENTRE PATCH KEEPER

Item number	MP320
Description	• centre patch keeper • 210mm H x 64mm W
Suitable for	• 10mm and 12mm glass thickness • MP300 and MP300L
Material finish	• polished or satin stainless steel

MP320

MP320

GLASS CUT OUT DETAIL

R10
198mm
48mm
80mm minimum

EXIT LEVER CENTRE PATCH LOCK

Item number	MP300.L
Description	• exit lever centre patch lock • Includes cylinders and mortice lock
Suitable for	• MP300
Material finish	• polished or satin stainless steel
Order	• specify handing and glass thickness

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

TOP OR BOTTOM PATCH LOCK

Item number	• EL10.PL.CT
	  cylinder/turn knob
	• EL10.PL.DC
	  double cylinder

Description	• top or bottom patch lock • vertical belt projection 20mm • eurotype cylinders
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • selected powdercoat (lead time applies)

Order	• specify cylinder combination
	  - double cylinder, cylinder/turn,
	    single cylinder or single turn

EL10.PL

EL10.PL

52mm
166mm
31mm

GLASS CUT OUT DETAIL

43mm
R10
150mm

CENTRE PATCH FITTING

Item number	• EL10.CPL.CT
	  cylinder/turn knob
	• EL10.CPL.DC
	  double cylinder

Description	• centre patch fitting • vertical belt projection 20mm • eurotype cylinders
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • selected powdercoat (lead time applies)

Order	• specify cylinder combination
	  - double cylinder, cylinder/turn,
	    single cylinder or single turn

EL10.CPL

EL10.CPL

29mm
51mm
162.5mm

GLASS CUT OUT DETAIL

R10
132mm
43mm

LOCKING SYSTEMS

PATCH LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

CENTRE PATCH STRIKER BOX

Item number	EL10.CPK
Description	• centre patch striker patch
Suitable for	• EL10
Material finish	• polished or satin stainless steel

EL10.CPK

EL10.CPK

GROUND KEEPER

Item number	GK10
Description	• ground keeper
Suitable for	• EL10
Material finish	• satin stainless steel

GK10

GK10

LOCK KEEPER

Item number	LK10
Description	• lock keeper
Suitable for	• EL10
Material finish	• satin stainless steel

LK10

LK10

CYLINDER DOUBLE

Item number	DC88
Description	• cylinder double • eurostyle cylinder
Suitable for	• EL10
Material finish	• chrome plate or satin chrome

DC88

DC88

ELITE GLASS SOLUTIONS

JULY 2016

CYLINDER TURN

Item number	CT88
Description	• cylinder turn • eurostyle cylinder
Suitable for	• EL10
Material finish	• chrome plate or satin chrome

CT88

CT88

LOCK KEEPER

Item number	GK590
Description	• lock keeper
Suitable for	• PL590 and CPL590 locks and rails
Material finish	• polished or satin stainless steel

GK590

GK590

LOCKWOOD 590 GROUND KEEPER

Item number	LK590
Description	• lockwood 590 ground keeper
Suitable for	• rail locks and PL590
Material finish	• polished or satin stainless steel

LK590

LK590

FLOOR GUIDE FOR SLIDING RAILS

Item number	MRG
Description	• floor guide for sliding rails
Suitable for	• 10mm and 12mm glass thickness
Material finish	• black nylon

MRG

MRG

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FLOOR GUIDE FOR GLASS DOORS SCP

Item number	MDG
Description	• floor guide for glass doors SCP
Suitable for	• 8mm to 12mm glass thickness
Material finish	• stain chrome

MDG

MDG

TURN KNOB LOCKWOOD 590 CYLINDER

Item number	TK90
Description	• turn knob lockwood 590 cylinder
Suitable for	• rail locks
Material finish	• satin silver anodised

TK90

TK90

CYLINDER SINGLE
LOCKWOOD 590 ACCESSORY

Item number	SC90
Description	• cylinder single • lockwood 590 accessory
Suitable for	• rail locks
Material finish	• satin silver anodised

SC90

SC90

ESCUTCHEON ROSE
LOCKWOOD 590 ACCESSORY

Item number	ER90
Description	• escutcheon rose • lockwood 590 accessory
Suitable for	• rail locks
Material finish	• satin silver anodised

ER90

ER90

RETAINING SCREW
LOCKWOOD 590 ACCESSORY

Item number	RS90
Description	• retaining screw lockwood 590 accessory
Suitable for	• rail locks
Material finish	• satin silver anodised

RS90

RS90

PATCH LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLIDING
DOOR LOCKS

SLIDING DOOR PATCH LOCK

Item number	MP300.H
Description	• sliding door patch lock • includes cylinders and hook mortice lock
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

MP300.H

64mm

MP300.H

210mm

GLASS CUT OUT DETAIL

R10   198mm

SLIDING DOOR PATCH KEEPER

Item number	MP320.H
Description	• sliding door patch keeper
Suitable for	• MP300.H
Material finish	• polished or satin stainless steel

MP320.H

MP320.H

GLASS CUT OUT DETAIL

R10
198mm

SLIDING DOOR PARROT BEAK PATCH

Item number	CPL590.P
Description	• sliding door parrot beak patch • includes lock and cylinders
Suitable for	• 10mm and 12mm glass thickness • sliding doors • use with keeper CPK590.P
Material finish	• polished or satin stainless steel

Order	• specify cylinder combination
	  - double cylinder, cylinder/turn,
	    single cylinder or single turn

CPL590.P

CPL590.P

GLASS CUT OUT DETAIL

R10
212mm
40mm

LOCKING SYSTEMS

SLIDING DOOR LOCKS

ELITE GLASS SOLUTIONS

PARROT BEAK KEEPER
SUITABLE FOR SLIDING DOOR

Item number	• CPK590.P beak keeper • WK590.P spring-loaded wall keeper
Description	• parrot beak keeper
Suitable for	• 10mm and 12mm glass thickness • sliding doors • use with keeper CPL590.P
Material finish	• polished or satin stainless steel

CPK590.P
WK590.P

CPK590.P

WK590.P

GLASS CUT OUT DETAIL

R10
212mm
40mm

SLIDING DOOR PRIVACY LATCH
SNIB BOTH SIDES

| Item number	MSL.1
Description	• sliding door privacy latch • snib both sides
Suitable for	• 8mm and 10mm glass thickness
Material finish	• satin silver
Order	• left or right hand • inside or outside

MSL.1

MSL.1

GLASS CUT OUT DETAIL

116mm
52mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLIDING DOOR PRIVACY LATCH SET SNIB ONE SIDE

Item number	MSL.2
Description	• sliding door privacy latch set • snib one side • with emergency access screw
Suitable for	• 8mm and 10mm glass thickness
Material finish	• satin silver
Order	• left or right hand • inside or outside

MSL.2

MSL.2

GLASS CUT OUT DETAIL

116mm

52mm

SLIDING DOOR LOCK

Item number	MSL.3
Description	• sliding door lock
Suitable for	• 8mm and 10mm glass thickness
Material finish	• satin silver
Order	• left or right hand • inside or outside

MSL.3

MSL.3

GLASS CUT OUT DETAIL

116mm

52mm

LOCKING SYSTEMS

SLIDING DOOR LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLIDING DOOR DEADLOCK HEAVY DUTY

Item number	MS590
Description	• sliding door deadlock heavy duty • can be master keyed • locking options - cylinder/turn, cylinder/cylinder
Suitable for	• internal or external applications • 10mm and 12mm glass thickness
Material finish	• satin silver
Order	• specify cylinder combination - cylinder/turn or cylinder/cylinder

SLIDING DOOR JAMB FIX STRIKE

Item number	MJ590
Description	• sliding door jamb fix strike
Suitable for	• MS590 lock
Material finish	• satin silver

MS590
MJ590

MS590

MJ590

GLASS CUT OUT DETAIL

203mm

R10

42mm

SLIDING DOOR GLASS MOUNT STRIKE BOX

Item number	MG590
Description	• sliding door glass mount strike box
Suitable for	• MS590 lock • 10mm and 12mm glass thickness
Material finish	• satin silver

MG590

MG590

GLASS CUT OUT DETAIL

203mm

R10

42mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SLIDING DOOR FINGER PULL
50MM DIAMETER

Item number	FP50
Description	• sliding door finger pull • 50mm diameter • 40mm diameter hole for glass preparation
Suitable for	• 10mm and 12mm glass thickness
Material finish	• stainless steel

FP50

50mm

FP50

SLIDING DOOR FINGER PULL
70MM DIAMETER

Item number	SDFP70
Description	• sliding door finger pull • 70mm diameter • 55mm diameter hole for glass preparation
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

SDFP70

70mm

SDFP70

GLASS CUT OUT DETAIL

Ø40

GLASS CUT OUT DETAIL

Ø55

LOCKING SYSTEMS

SLIDING DOOR LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

LOCKING SYSTEMS

SLIDING DOOR LOCKS

SLIDING DOOR FLUSH

Item number	FP150
Description	• sliding door flush • handle with ring pull for cavity installation • 150mm H x 70mm W x 36mm D
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin stainless steel

FP150

150mm

70mm

36mm

FP150

GLASS CUT OUT DETAIL

134mm

60mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

LOCKING SYSTEMS

SECURITY PATCH AND LEVER LOCKS

SECURITY PATCH LOCK
HANDLES BOTH SIDES

Item number	MP358.2A
Description	• security patch lock • handles both sides • cylinder outside • snib inside
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP358.2A

43mm

Lockwood cylinder outside

Turn snib inside

63mm

248mm

MP358.2A

GLASS CUT OUT DETAIL

46mm   Ø24

227mm   217mm

48mm

To specify handing of door state RH or LH and direction of opening eg. in or out.
See guide below

Right hand door

RH-In Opening in	RH-Out Opening Out
Outside	Outside

Left hand door

LH-In Opening in	LH-Out Opening Out
Outside	Outside

SECURITY PATCH
AND LEVER LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SECURITY PATCH LOCK
HANDLE INSIDE

Item number	MP358.2B
Description	• security patch lock • handle inside • cylinder outside
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP358.2B

MP358.2B

GLASS CUT OUT DETAIL

To specify handing of
door state RH or LH
and direction of opening
eg. in or out.
See guide below

Right hand door	
RH-In Opening in	RH-Out Opening Out
Outside	Outside

Left hand door	
LH-In Opening in	LH-Out Opening Out
Outside	Outside

SECURITY PATCH LOCK
NO HANDLES

Item number	MP358.2C
Description	• security patch lock • no handles • cylinder outside • snib inside
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP358.2C

MP358.2C

GLASS CUT OUT DETAIL

To specify handing of
door state RH or LH
and direction of opening
eg. in or out.
See guide below

Right hand door	
RH-In Opening in	RH-Out Opening Out
Outside	Outside

Left hand door	
LH-In Opening in	LH-Out Opening Out
Outside	Outside

ELITE GLASS SOLUTIONS

SECURITY PATCH LOCK HANDLES BOTH SIDES CYLINDER INSIDE AND OUTSIDE

Item number	MP358.2D
Description	• security patch lock • handles both sides • cylinder inside and outside
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP358.2D

43mm

63mm

Lockwood cylinder outside

Lockwood cylinder inside

248mm

MP358.2D

GLASS CUT OUT DETAIL

46mm   Ø24

227mm   217mm

48mm

To specify handing of door state RH or LH and direction of opening eg. in or out.
See guide below

Right hand door

RH-In Opening in	RH-Out Opening Out
Outside	Outside

Left hand door

LH-In Opening in	LH-Out Opening Out
Outside	Outside

SECURITY PATCH LOCK HANDLES BOTH SIDES CYLINDER OUTSIDE

Item number	MP358.2E
Description	• security patch lock • handles both sides • cylinder outside
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP358.2E

43mm

63mm

Lockwood cylinder outside

248mm

MP358.2E

GLASS CUT OUT DETAIL

46mm   Ø24

227mm   217mm

48mm

To specify handing of door state RH or LH and direction of opening eg. in or out.
See guide below

Right hand door

RH-In Opening in	RH-Out Opening Out
Outside	Outside

Left hand door

LH-In Opening in	LH-Out Opening Out
Outside	Outside

LOCKING SYSTEMS

SECURITY PATCH AND LEVER LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

SECURITY PATCH LOCK KEEPER

Item number	MP358.2K
Description	• security patch lock keeper
Suitable for	• strike patch for glass side light application
Material finish	• polished or satin stainless steel
Order	• specify sidelight glass thickness

STRIKE PLATE PATCH LOCK

Item number	MP358.2SP
Description	• strike plate patch lock
Suitable for	• striker plate for attaching to aluminium or timber frame
Material finish	• polished or satin stainless steel

MP358.2K
MP358.2SP

43mm

109mm

MP358.2K

100mm

WALL MOUNT STRIKE BOX PATCH LOCK

Item number	MK590.H
Description	• wall mount strike box patch lock
Suitable for	• striker patch unit for sliding door application
Material finish	• polished or satin stainless steel

MK590.H

3mm
26mm   25mm
146mm   124mm

MK590.H

GLASS CUT OUT DETAIL

63mm

248mm

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

LEVER LOCKSET
SUITABLE FOR TIMBER OR ALUMINIUM JAMB

Item number	LLJ.01
Description	• lever lockset
Suitable for	• locking to timber or aluminium jamb
Material finish	• polished or satin stainless steel

LLJ.01

LLJ.01

LEVER LATCHSET
SUITABLE FOR TIMBER OR ALUMINIUM JAMB

Item number	LLJ.03
Description	• lever latchset
Suitable for	• latching to timber or aluminium jamb
Material finish	• polished or satin stainless steel

LLJ.03

LLJ.03

LEVER LOCKSET
SUITABLE FOR GLASS SIDELITE

Item number	LLG.02
Description	• lever lockset
Suitable for	• locking to glass sidelite
Material finish	• polished or satin stainless steel

LLG.02

LLG.02

GLASS CUT OUT DETAIL
LLJ.01, LLG.02, LLJ.03

Ø45 (2 holes)

62mm   60mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

LEVER LATCHSET
SUITABLE FOR GLASS SIDELITE

Item number	LLG.04
Description	• lever latchset
Suitable for	• latching to glass sidelite
Material finish	• polished or satin stainless steel

LLG.04

LLG.04

STRIKE PLATE
SUITABLE FOR ALUMINIUM OR TIMBER JAMBS

Item number	LSJ.09
Description	• strike plate
Suitable for	• aluminium or timber jambs
Material finish	• polished or satin stainless steel

LSJ.09

LSJ.09

STRIKE BOX
SUITABLE FOR GLASS SIDELITE

Item number	LSG.08
Description	• strike box
Suitable for	• glass sidelite
Material finish	• polished or satin stainless steel

LSG.08

LSG.08

GLASS CUT OUT DETAIL LLG.04, LSG.08

Ø45 (2 holes)

62mm   60mm

ELITE GLASS SOLUTIONS

JULY 2016

SECURITY PATCH LOCK

Item number	MP100.F
Description	• security patch lock • handle both sides
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel
Order	• left or right hand • open in or out

MP100.F

MP100.F

GLASS CUT OUT DETAIL

Ø16
177mm
92mm

CENTRE PATCH KEEPER

Item number	MP100.K
Description	• centre patch keeper
Suitable for	• MP100.F
Material finish	• polished or satin stainless steel

MP100.K

MP100.K

STRIKE PLATE

Item number	MP100.SP
Description	• strike plate
Suitable for	• MP100.F
Material finish	• polished or satin stainless steel

MP100.SP

120mm   25mm

MP100.SP

LOCKING SYSTEMS

SECURITY PATCH AND LEVER LOCKS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

© Copyright 2016. Theses drawings must not be copied or used by others without the written consent of Elite Glass Solutions.   JULY 2016

INDICATOR LOCKS
FOR SWING DOORS

GLASS SWING DOOR INDICATOR LOCK
DOOR TO WALL

Item number	IL700C
Description	• glass swing door indicator lock • door to wall • with emergency access
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

IL700C

IL700C

GLASS CUT OUT DETAIL

R7.5x2

36.5mm

59mm

59mm

Lock

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

GLASS SWING DOOR INDICATOR LOCK
DOOR TO SIDEPANEL

Item number	IL701C
Description	• glass swing door indicator lock • door to sidepanel
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

IL701C

IL701C

GLASS SWING DOOR INDICATOR LOCK
DOOR TO WALL

Item number	IL600C
Description	• glass swing door indicator lock • door to wall • no glass cut out required
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

IL600C

IL600C

GLASS CUT OUT DETAIL

R7.5x2   36.5mm   36.5mm   R7.5x2

59 mm   59 mm   59 mm

Lock   3mm   Keeper

NO GLASS CUT OUT REQUIRED

LOCKING SYSTEMS

INDICATOR LOCKS FOR SWING DOORS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS SWING DOOR INDICATOR LOCK
DOOR TO SIDE PANEL

Item number	IL601C
Description	• glass swing door indicator lock • door to side panel • no glass cut out required
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

IL601C

IL601C

NO GLASS CUT OUT REQUIRED

GLASS SLIDING DOOR INDICATOR LOCK
DOOR TO WALL

Item number	IL700C.H
Description	• glass sliding door indicator lock • door to wall – glass cut out required
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• satin chrome

IL700C.H

IL700C.H

GLASS CUT OUT DETAIL

R7.5x2   36.5mm

59mm

Lock

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

GLASS SLIDING DOOR INDICATOR LOCK DOOR TO SIDE PANEL

| Item number	IL701C.H
Description	• glass sliding door indicator lock • door to side panel – glass cut out required
Suitable for	• toilet and bathroom doors • 8mm and 10mm glass thickness
Material finish	• satin chrome

IL701C.H

IL701C.H

GLASS CUT OUT DETAIL

R7.5x2
36.5mm
59mm
Lock

RIVIERA BOAT LATCH

Item number	• FF930.6
	  suits 6mm glass thickness
	• FF930.6K
	  glass keeper to suit latch
	• FF930.10
	  suits 10mm glass thickness
	• FF93.10K
	  glass keeper to suit latch

Description	• Riviera boat latch • manufactured in brass • sliding bolt spring action • non-locking
Suitable for	• use in conjunction with ES hinge range for boat showers
Material finish	• polished chrome

FF930

FF930

GLASS CUT OUT DETAIL

Door and keeper
glass cutout detail
55mm
R10
40mm

LOCKING SYSTEMS

INDICATOR LOCKS FOR SWING DOORS

ELITE GLASS SOLUTIONS

LOCKING SYSTEMS

PRIVACY PATCH LOCKS AND LATCHES

PRIVACY
PATCH LOCKS
AND LATCHES

PRIVACY PATCH LOCK SLIDE-ON
GLASS TO WALL - FLOOR LOCK

Item number	MP65
Description	• patch lock slide-on • glass to wall - floor lock • complete with wall keeper plate • 5mm-6mm clearance between glass and wall • no glass cut out required
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

MP65

MP 65

NO GLASS CUT OUT REQUIRED

ELITE GLASS SOLUTIONS

PRIVACY LATCH AND LOCK
SLIDE-ON GLASS TO WALL

Item number	MPL.1
Description	• privacy latch and lock • slide-on glass to wall • complete with wall keeper plate • 5mm-6mm clearance between glass and wall • no glass cut out required
Suitable for	• 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

MPL.1

MPL.1

Inside - snib

Outside - indicator

NO GLASS CUT OUT REQUIRED

PRIVACY LATCH AND LOCK
SLIDE-ON GLASS TO GLASS

Item number	MPL.2
Description	• privacy latch and lock • slide-on glass to glass • complete with glass keeper • 7mm-8mm clearance between glass and wall • no glass cut out required
Suitable for	• 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

MPL.2

MPL.2

NO GLASS CUT OUT REQUIRED

LOCKING SYSTEMS

PRIVACY PATCH LOCKS AND LATCHES

ELITE GLASS SOLUTIONS

JULY 2016

PIVOT AND SLIDING DOOR PRIVACY LATCH GLASS TO WALL

Item number	• MFPL1 - square profile • CPL1 - round profile
Description	• pivot and sliding door privacy latch • glass to wall • complete with keeper plate • available in square or round profile
Suitable for	• 8mm and 10mm glass thickness
Material finish	• polished or satin chrome

MFPL1 CPL1

MFPL1

CPL1

GLASS CUT OUT DETAIL

Door

36.5mm Ø20

63.5 mm   59 mm

46.5mm

3mm to 5mm

PATCH BOLT LOCK SLIDE-ON

Item number	374
Description	• patch bolt lock slide-on • no glass cut out required
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural silver anodised

374

Slide option

50mm

20 mm

40mm

28mm

Glue-on option

12mm

374

NO GLASS CUT OUT REQUIRED

PATCH LOCK SLIDE-ON

Item number	343.1
Description	• patch lock slide-on • complete with single sided key cylinder • no glass cut out required
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural silver anodised

343.1

43mm   70mm

110mm

343.1

20mm

NO GLASS CUT OUT REQUIRED

PATCH LOCK

Item number	342.1
Description	• patch lock • complete with cylinder/snib and keeper plate • glass cut out required
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural silver anodised

342.1

70mm
43mm
110mm
342.1
20mm

GLASS CUT OUT DETAIL

Ø55
65mm
65mm

PROFILE PLUNGER LOCK

Item number	456
Description	• profile plunger lock • glass cut out required • non-stock item available with lead-time
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

456

80mm
456
15mm
110mm
12mm
34mm

GLASS CUT OUT DETAIL

68mm
53mm
70mm
60mm minimum

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

LOCKING SYSTEMS

CASMA LOCKS

CASMA LOCKS

BOTTOM PIN LOCK
CASMA

Item number	SBC14600
Description	• bottom pin lock - CASMA • internal single cylinder lock • maximum glass hold 90kg
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

SBC14600

SBC14600

53mm
65mm
10.5mm
Ø11
26mm

GLASS CUT OUT DETAIL

55mm
39mm
32mm

BOTTOM PIN LOCK WITH THUMBTURN
CASMA

Item number	SBC14700
Description	• bottom pin lock with thumbturn - CASMA • internal single snib lock • maximum glass hold 90kg
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel

SBC14700

SBC14700

53mm
65mm
18mm
14mm
Ø13
26mm

GLASS CUT OUT DETAIL

55mm
39mm
32mm

CENTRE OR BOTTOM DOOR LOCK
CASMA

Item number	SBC16000
Description	• centre or bottom door lock - CASMA • euro-style cylinder • maximum glass hold 100kg
Suitable for	• doors in cabinets, showcases or similar • 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • natural anodised • polished brass (lead time applies)

SBC16000

SBC16000

77mm
14mm
110mm
17mm
32mm

GLASS CUT OUT DETAIL

54mm
79mm
63mm
59mm

ELITE GLASS SOLUTIONS

LOCK STRIKE KEEPER
CASMA

Item number	SBC16100
Description	• lock strike keeper - CASMA • maximum glass hold 150kg
Suitable for	• SBC16000 • 8mm, 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel • natural anodised • polished brass

SBC16100

SBC16100

77mm

110mm

17mm

32mm

GLASS CUT OUT DETAIL

54mm

79mm   63mm

59mm   Ø18

CORNER PIN LOCK
CASMA

Item number	SBC48700
Description	• corner pin lock - CASMA • maximum glass hold 150kg • recommended torque for fixing screws Nm 14-16 • euro style cylinder
Suitable for	• SBC16000 • 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel • natural anodised • polished brass

SBC48700

SBC48700

165mm

50 mm

38 mm   33 mm

1 mm

20 mm

12 mm

33 mm

GLASS CUT OUT DETAIL

Ø16/18   148mm

36 mm

R73   68mm

33 mm

LOCKING SYSTEMS

CASMA LOCKS

CORNER PIN LOCK - CASMA
SUITABLE FOR 19MM GLASS THICKNESS

Item number	SBC48720
Description	• corner pin lock - CASMA • maximum glass hold 250kg • recommended torque for fixing screws Nm 14-16 • euro style cylinder
Suitable for	• 19mm glass thickness
Material finish	• polished or satin stainless steel • natural anodised • polished brass

SBC48720

SBC48720

165mm
50 mm
1 mm
38 mm
33 mm
20 mm
12 mm
33 mm

GLASS CUT OUT DETAIL

Ø30
128mm
26 mm
38 mm
136mm

SLIDING, BI-FOLDING & STACKING

ELITE GLASS SOLUTIONS

SLIDING, BI-FOLDING & STACKING

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLIDING
SYSTEMS

VITRIS 120 SOFT CLOSE SLIDING DOOR KIT
WALL, CEILING AND GLASS MOUNTED

Item number	Wall mounted
	• EVW.2SD - single door 2 meter track
	• EVW.4SD - single door 4 meter track
	• EVW.4DD - double door 4 meter track
	Ceiling mounted
	• EVC.2SD - single door 2 meter track
	• EVC.4SD - single door 4 meter track
	• EVC.4DD - double door 4 meter track
	Glass mounted
	• EVG.1SD - single door threshold opening 1 meter
	• EVG.12SD - single door threshold opening 1.2 meter
Description	• VITRIS soft close sliding door
	• maximum door weight 120kg
	• easy installation and no glass cutout required
	• comfort stop - prevents door from banging, eliminates the associated noise and vibration
	• removes risk of trapped fingers
	• modular construction means it can be adapted to customer requirements
	• kit includes
	– 1 x soft close mechanism
	– 1 x track
	– end caps and cover
	– wheel assembly kit
	– door stops
	– floor guide
	• available with softstop close action maximum door weight 80kg
Suitable for	• 8mm, 10mm and 12mm toughened glass thickness
	• 8.76mm, 10.76mm and 12.76mm toughened laminated glass thickness
	• ceiling, wall-fixed installation or to a glass overlite
Material finish	• satin anodised aluminium

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

VITRIS 120   DETERMINATION OF GLASS HEIGHT AND WIDTH

Glass height	H = R - 43mm
Glass width	A = LW + 70mm (single door) A = LW/2 + 33mm (double door)

VITRIS 120   KEY

A =	glass width of sliding sash
H1 /H2=	glass height of sliding/fixed sash
LH =	clear height
LW =	clear width (opening)
R =	room height

EVW, EVC, EVG

WALL MOUNTED

EVW

70mm

R

22.5   12mm
23.5   10mm
24.5   8mm

H1 = R-43mm

56.7mm

10mm

CEILING MOUNTED

56.7mm

EVC

70 mm

R

H1 = R - 43mm

10mm

GLASS MOUNTED

56.7mm

EVG

70 mm

LH

23mm   12mm
24mm   10mm
25mm   8mm

10/ 12mm

H1 = LH + 28mm

10mm

Roller assembly

Driver Fork

Cushioning system with frictional damper

Endstop with cushion

Activator arm with activator catch

SLIDING, BI-FOLDING & STACKING

SLIDING SYSTEMS

JULY 2016

PERLAN CEILING FIX KIT

Item number	• GPC2450 • GPC2450.SS - softstop

Description	• perlan ceiling fix kit
	• maximum door weight 140kg
	• kit includes
	  – 1 x 2.45 meter track
	  – 2 x double roller carriages
	  – 2 x black plastic track end caps
	  – 2 x tube buffers
	  – 1 x hold open spring
	  – 2 x glass clamping plates with
	    individual covers and black
	    plastic end caps
	  – 1 x adjustable glass floorguide
	  – **please note** no handle included
	• available with softstop close
	  action maximum door weight 80kg
	• no glass cut out required

Suitable for	• 8mm, 10mm and 12mm glass thickness • ceiling mounting
Material finish	• anodised stainless steel

GPC2450

GPC2450

45mm
ø5.2
40mm
119mm±4
29mm±4
59mm±4
GH
SH = GH - 106
7mm

NO GLASS CUT OUT REQUIRED

JULY 2016

PERLAN WALL FIX KIT

Item number	• GPW2450 • GPW2450.SS - softstop

Description	• perlan wall fix kit
	• maximum door weight 140kg
	• kit includes
	   – 1 x 2.45 meter track
	   – 1 x concealed wall bracket
	   – 2 x end caps for concealed
	      wall bracket and track
	   – 2 x double roller carriages
	   – 2 x tube buffers
	   – 1 x hold open spring
	   – 2 x glass clamping plates with
	      individual covers and black
	      plastic end caps
	   – 1 x adjustable glass floorguide
	   – **please note** no handle included
	• available with softstop close
	  action maximum door weight 80kg

Suitable for	• 8mm, 10mm and 12mm glass thickness • wall mounting
Material finish	• anodised stainless steel

GPW2450

GPW2450

28mm
23mm
6mm
14mm
40mm
29mm±4
59mm±4
119mm±4
GH
SH = GH - 126mm
7mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

LEVOLAN CEILING FIX KIT

Item number	GLC2450

Description	• levolan ceiling fix kit
	• maximum door weight 150kg
	• kit includes
	  – 1 x 2.45 meter track and
	    cover profile
	  – 2 x roller carriages
	  – 2 x buffers
	  – 2 x end covers
	  – 1 x brush seal
	  – 1 x adjustable floorguide
	  – **please note** no handle included
	• available with softstop close
	  action maximum door weight 80kg
	• no glass cut out required

Suitable for	• 8mm, 10mm and 12mm glass thickness • ceiling mounting
Material finish	• anodised stainless steel

GLC2450

GLC2450

Cover profile for ceiling mounting

60mm

34mm

Profile for ceiling mounting

63mm

33mm ±5

Attachment pane

Seal brush

40mm

Overall height

Pane height = overall height - 40mm ±5

Glass thickness 8/10/12mm

ca. 7

NO GLASS CUT OUT REQUIRED

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

LEVOLAN WALL FIX KIT

Item number	• GLW2450
	  maximum door weight 1,500kg
	• GL602450
	  maximum door weight 60kg

Description	• levolan wall fix kit
	• kit includes
	  – 1 x 2.45 meter track and
	    wall bracket profile
	  – 2 x roller carriages
	  – 2 x buffers
	  – 2 x end covers
	  – 1 x brush seal
	  – 1 x adjustable floorguide
	  – **please note** no handle included
	• available with softstop close
	  action maximum door weight 80kg
	• no glass cut out required

Suitable for	• 8mm, 10mm and 12mm glass thickness • wall mounting
Material finish	• anodised stainless steel

GLW2450
GL602450

Profile for ceiling mounting

GLW2450

Profile for wall mounting

60mm

57mm

63mm

33mm$^{\pm5}$

37mm

Seal brush

20mm

Overall height
= clear height
+ 63mm

Pane height
= overall height
- 40mm $^{\pm5}$

Glass thickness
8/10/12mm

ca. 7

NO GLASS CUT OUT REQUIRED

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

PICO SLIDING SYSTEM

| Description	• one of our smallest sliding door system PICO runs with enormous precision, as the upper track is reduced to a minimum special rollers guarantee for smooth sliding at all times. With the three weight options a suitable system is available for every application. The maintenance-free units allow for a gentle and quiet movement of the sliding panels. By means of the integrated height-adjusting mechanisms the panels can be easily adjusted. The upper tracks can be fixed to walls as well as ceilings which allows for a great flexibility in design. • one or two panel sliding door system with/without fix panel

PICO SLIDING SYSTEM
MAXIMUM WEIGHT PER PANEL 150KG

Item number	MS150
Description	• PICO sliding system maximum weight per panel 150kg • maximum dimensions 1.5 meters x 3 meters • minimum width of panel 500mm • kit includes – two trolleys, length 160mm each – two limit stop buffers – one bottom floor guide
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• two different kinds of upper tracks are available in anodised aluminium in various colours: with or without side fixed panels

MS150

MS150

DETAIL GLASS PREPARATION

15mm

Ø14

GLASS PREPARATION

130mm   130mm
100mm   100mm
15 mm

Boreholes Ø14mm (slitting)

X - trimmed or polished edges

JULY 2016

PICO SLIDING SYSTEM
MAXIMUM WEIGHT PER PANEL 75KG

Item number	MS75
Description	• PICO sliding system maximum weight per panel 75kg • maximum dimensions 1.2 meters x 2.5 meters • minimum width of panel 380mm • kit includes – two trolleys, length 115mm each – two limit stop buffers – one bottom floor guide
Suitable for	• 8mm and 10mm glass thickness
Material finish	• two different kinds of upper tracks are available in anodised aluminium in various colours: with or without side fixed panels

PICO SLIDING SYSTEM
MAXIMUM WEIGHT PER PANEL 50KG

Item number	MS50
Description	• PICO sliding system maximum weight per panel 50kg • maximum dimensions 1.0 meter x 2 meters • minimum width of panel 250mm • kit includes – two trolleys, length 60mm each – two limit stop buffers – one bottom floor guide
Suitable for	• 8mm and 10mm glass thickness
Material finish	• two different kinds of upper tracks are available in anodised aluminium in various colours: with or without side fixed panels

SLIDING, BI-FOLDING & STACKING

SLIDING SYSTEMS

MS75

MS75

DETAIL GLASS PREPARATION

15mm

Ø14

GLASS PREPARATION

85mm 85mm
80mm 80mm
15 mm

Boreholes Ø14mm (slitting)
X - trimmed or polished edges

MS50

MS50

DETAIL GLASS PREPARATION

15mm

Ø14

GLASS PREPARATION

80mm 80mm
15 mm

Boreholes Ø14mm (slitting)
X - trimmed or polished edges

ELITE GLASS SOLUTIONS

JULY 2016

GLASS GLIDE SLIDING DOOR KIT

Item number	• GG.CW2000 - suitable for door up to 1 meter wide • GG.CW3000 - suitable for door up to 1.5 meter wide • GG.CW5000 - suitable for door up to 2.5 meters wide

Description	• glass glide sliding door kit
	• maximum door weight 150kg
	• slim profile track
	• top hung system
	• no glass cutout required
	• kit includes
	  – track
	  – pelmet
	  – hangers
	  – stops
	  – end caps
	  – floor guides

Suitable for	• 8mm, 10mm and 12mm glass thickness • ceiling or wall fix installations
Material finish	• natural anodized finish

GLASS GLIDE KIT FOR ADDITIONAL DOOR

Item number	GG.DK
Description	• glass glide kit for additional door • kit includes – hangers, stops and floor guides

TO DETERMINE DOOR HEIGHT AND WIDTH

Door height Wall Mounted	TH = Opening height to underside of transom DH = Glass door height DH = TH plus 25mm
Door height Ceiling Mounted	H = Overall opening height DH = Glass door height DH = H less 37mm
Door width	COW = Clear opening width DW = Door width Doors typically overlap the clear opening by 35mm each side Eg. DW = COW + 70mm Track length is 2 x door width

GG.CW

WALL MOUNTED

GG.CW

CEILING MOUNTED

TO DETERMINE DOOR WIDTH

GLASS GLIDE CEILING MOUNT
WITH SIDELIGHT CARRIER KIT

Item number	• GG.SP2000 - door set to suit opening up to 2 meters wide • GG.SP3000 - door set to suit opening up to 3 meters wide • GG.SP5000 - door set to suit opening up to 5 meters wide
Description	• glass glide ceiling mount with sidelight carrier • maximum door weight 150kg • slim profile track with sidelight • carrier section • top hung system • no glass cutout required • kit includes – track – sidelight carrier section – infill channel for carrier – hangers – stops – end caps – floor guides
Suitable for	• 8mm, 10mm and 12mm glass thickness • ceiling fix
Material finish	• natural anodized finish

GLASS GLIDE KIT FOR ADDITIONAL DOOR

Item number	GG.DK
Description	• glass glide kit for additional door • kit includes – hangers, stops and floor guides

TO DETERMINE THE HEIGHT OF GLASS
DOORS AND SIDELIGHTS

Height	H = Overall opening height DH = Glass door height DH = H less 37mm SL = Glass sidelight height SL = H less 47mm

With the Glass Glide sliding door and sidelight system there are numerous set out options. To the right are two of the more common options.

Note: It is recommended that the door and sidelight overlap be 35mm each side. When glazing side lights specify CS25 channel.

GG.SP

WITH SIDE LIGHT

Sidelight glass = H - 47mm

WITH INFILL CHANNEL

GG.SP

Door height = H - 37mm

SIDELIGHT CARRIER INFILL

Door height = H - 37mm

SIDELIGHT CARRIER

Sidelight glass = H - 47mm

TO DETERMINE THE HEIGHT OF
GLASS DOORS & SIDELIGHTS

Clear opening

D   SL

Clear opening

SL   D   SL

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

EUROROLLER SLIDING SYSTEM KIT

RS10

Item number	• RS10.2SD - includes 2 meter track for single door
	• RS10.4SD - includes 4 meter track for single door
	• RS10.4DD - includes 4 meter track for double door
Description	• euroroller sliding system
	• kit includes
	– bottom track
	– rollers and stops
	– felt brush seal (for channel)
	– COM1 top channel guide
	– 2 x COM3 end caps
	• maximum load 150kg per door, two rollers and two stops supplied per door
Suitable for	• 10mm and 12mm glass thickness
Material finish	• polished or satin stainless steel - rollers
	• satin stainless steel - track

2m or 4m

RS10

4m

EUROROLLER COMPONENTS

Item number	• RS10.R - roller
	• RS10.2T - 2 meter track
	• RS10.4T - 4 meter track
	• RS10.4DD - double door 4 meter track
Description	• euroroller components
	• maximum load per roller 75kg
Suitable for	• euroroller systems

RS10.R

RS10

Ø90

RS10.R
Roller detail

72mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105

sales@eliteglasssolutions.com.au

www.eliteglasssolutions.com.au

RS10

GLASS DETAIL

A

Glass height
= Aperture
- 24mm

B

ROLLER - GLASS CUTOUT DETAIL

Ø72
115mm
53mm
17mm
R5
79mm

STOP - GLASS CUTOUT DETAIL

70mm
17mm
R5

RS10 CROSS SECTION DETAIL

32mm
45mm
10mm
Aperture
9mm
31mm

ELBA SLIDING SYSTEM

Item number	ELBA
Description	• elba sliding system • maximum wing weight 100kg • born as an alternative solution to the numberless so-called "naked" sliding systems, featuring point fixed solution to the glass • its upper track is made of two parallel steel rods kept together by rounded clamps, used to reinforce and fix the two rods and the whole system to the walls or glass panels • glass panel require two cut outs • sliding door dimensions vary according to the distance between the fixing points Download the ELBA flyer from our website for further information
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• stainless steel

SLIDING, BI-FOLDING & STACKING

SLIDING SYSTEMS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 **1300 4 ELITE** | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

　　　　　　JULY 2016

LINEAR 100 SLIDING DOOR KIT

L100

| Item number	• L100.1000 - suitable for one door up to 1 meter wide track and channel 2 meters • L100.1500 - suitable for one door up to 1.5 meter wide track and channel 3 meters • L100.2000 - suitable for one door up to 2 meters wide track and channel 4 meters

Description	• linear 100 sliding door kit
	• maximum door weight 170kg
	• bottom rolling sliding door system
	• kit includes
	  – 2 x 100 wheels
	  – 2 x top channel stops
	  – 2 x top channel
	  – 1 x bottom channel

Suitable for	• 10mm and 12mm glass thickness • floor and ceiling fix installations
Material finish	• satin stainless steel (wheels) • natural anodised (channels) • aluminium (floor track)

LINEAR 100 COMPONENTS

Item number	• L153.T40 - bottom track • L153.C50 - top channel
Description	• linear 100 components • side mount channel fittings available on request • system can be used with multiple lines of track for several doors opening in the same direction and biparting applications
Suitable for	• linear 100 systems

KEY

X =	height of door which is finished opening height less 35mm
T =	glass thickness

Note: Allow for selected handle glass preparation.

L100

25mm
50mm
20mm
Top channel
Stop
Woolpile
2.5mm
10/12mm glass thickness

L100
100mm
Wheel
15mm
10mm
40mm

TYPICAL GLASS SET OUT

63mm
63mm
15mm
R5
R5
15mm
X
R35 R35
40mm
40mm
70mm
70mm
15mm

LINEAR 153 SLIDING DOOR KIT

L153

Item number	• L153.1000 - suitable for one door up to 1 meter wide track and channel 2 meters • L153.1500 - suitable for one door up to 1.5 meter wide track and channel 3 meters • L153.2000 - suitable for one door up to 2 meters wide track and channel 4 meters
Description	• linear 153 sliding door kit • maximum door weight 250kg • bottom rolling sliding door system • kit includes – 2 x 153 wheels – 2 x top channel stops – 2 x top channel – 1 x bottom channel • system can be used with multiple lines of track for several doors opening in the same direction and biparting applications
Suitable for	• 10mm and 12mm glass thickness
Material finish	• satin stainless steel (wheels) • natural anodised (channels) • aluminium (floor track)

LINEAR 153 COMPONENTS

Item number	• L153.T40 - bottom track • L153.C50 - top channel
Description	• linear 153 components • side mount channel fittings available on request
Suitable for	• linear 153 systems

KEY

X =	height of door which is finished opening height less 35mm
T =	glass thickness

Note: Allow for selected handle glass preparation.

25mm
20mm
50mm
Top Channel
Stop
Woolpile
2.5mm
10/12mm glass

L153

153mm
Wheel
15mm
10mm
40mm

TYPICAL GLASS SET OUT

63mm   63mm
15mm   15mm
X
Ø70   Ø70
67mm   67mm
150mm   150mm

SLIDING, BI-FOLDING & STACKING

SLIDING SYSTEMS

JULY 2016

PRAKTICA VARIANT SINGLE AND MULTIPLE SLIDING SYSTEM

Item number	PRAKTICA
Description	• Praktica variant single and multiple sliding system • maximum wing weight 90kg • minimum wing width 680mm • hanging fittings and rollers are concealed inside the upper track, thus giving the opening a "total glass" look even with fixed side panels, as the upper track features a special groove for them. • kit includes – 2 x hanging fittings 280mm wide – one floor guiding patch Download the Praktica flyer from our website for further information
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• silver anodised aluminium or painted aluminium in different colours (upper track)

SLIDING RAIL KIT METRO

Item number	• MRS90.1250 - suitable to slide one door up to 1.25 meters wide • MRS90.000 - custom door kit can be designed with multiple lines of track for several doors opening in the same direction and biparting applications • MRS90.L - bottom lock with keeper
Description	• sliding rail kit - metro • maximum door weight 180kg • bottom rail sliding system • kit includes – bottom sliding rail – bottom track – top channel – 2 x channel stops
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural anodised

MRS90

MRS90

T = Glass thickness

Top of Door

Details of top of door notch setout to accommodate top channel stops

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SLIDING DOOR KIT METRO

MF250

| Item number	• MF250.1000 - suitable for one door up to 1 meter wide track 2 meters • MF250.1500 - suitable for one door up to 1.5 meter wide track 3 meters • MF250.2000 - suitable for one door up to 2 meters wide track 4 meters
Description	• sliding door kit - metro • maximum door weight 250kg • top hung system with standard top rail • no cutout in glass required • kit includes – 1 x top track – 1 x top rail – 2 x hangers – 2 x track steps – 1 x floor guide • system can be used in single, biparting and multiple lines of sliding doors • bottom rails and in ground channel guide systems available on request
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural anodised (track and rail)

METRO MF250 COMPONENTS

Item number	• MF250.2000 - custom door set • MF250.T50 - additional track per meter
Description	• metro MF250 components
Suitable for	• metro MF250 systems

MF250

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

POINT FIX SLIDING SYSTEM

SS

POINT FIX SLIDING SYSTEM TUBE TOP RAIL

| Item number	SS.1
Description	• point fix sliding system tube top rail • cut to size per 1 meter, includes two ends caps
Material finish	• satin stainless steel

SS.1

SS.1

GLASS DETAIL

700mm maximum

100mm   100mm

55mm

120mm

4 x Ø27

Door

600mm maximum   50mm

65mm

Ø27

Fixed Panel

POINT FIX SLIDING SYSTEM
GLASS HANGER BAR

Item number	• SS.3R - round bar • SS.3F - flat bar
Description	• point fix sliding system glass hanger bar • two required per door
Suitable for	• adjusting to suit 10mm and 12mm glass thickness
Material finish	• satin stainless steel

SS.3R
SS.3F

SS.3R   SS.3F

ELITE GLASS SOLUTIONS

POINT FIX SLIDING SYSTEM WALL ANCHOR

Item number	SS.4
Description	• point fix sliding system wall anchor
Suitable for	• SS.1 tube top rail
Material finish	• satin stainless steel

SS.4

SS.4

POINT FIX SLIDING SYSTEM STOP

Item number	• SS.7R - round with spring stop • SS.7FL - flat stop - left hand • SS.7FR - flat stop - right hand
Description	• point fix sliding system stop
Material finish	• satin stainless steel

SS.7R

SS.7R

**SS.7FL
SS.7FR**

SS.7FL
SS.7FR

POINT FIX SLIDING SYSTEM
GLASS MOUNT CLAMP

Item number	SS.5
Description	• point fix sliding system glass mount clamp
Material finish	• satin stainless steel

SS.5

SS.5

POINT FIX SLIDING SYSTEM
WALL MOUNT CLAMP

Item number	SS.6
Description	• point fix sliding system wall mount clamp
Material finish	• satin stainless steel

SS.6

SS.6

STACKING, BI-FOLD & SLIDING SYSTEMS

SLIDING SYSTEMS

ELITE GLASS SOLUTIONS

JULY 2016

POINT FIX SLIDING SYSTEM FLOOR GUIDE

Item number	SS.G10
Description	• point fix sliding system floor guide • clips on to the channel • no fixings required
Suitable for	• 10mm glass thickness
Material finish	• satin stainless steel

SS.G10

SS.G10

POINT FIX SLIDING SYSTEM FLOOR GUIDE

Item number	SS.8
Description	• point fix sliding system floor guide • base thickness is 6mm
Suitable for	• adjusting to suit 8mm, 10mm and 12mm glass thickness
Material finish	• satin stainless steel

SS.8

SS.8

POINT FIX SLIDING SYSTEM
SLIDING DOOR FINGER PULL

Item number	SS.9
Description	• point fix sliding system sliding door finger pull • glass hole size 48mm • 58mm overall diameter
Suitable for	• 8mm and 10mm glass thickness
Material finish	• satin stainless steel

SS.9

58mm

48mm

SS.9

GLASS CUT OUT DETAIL

Ø48

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SLIDING, BI-FOLDING & STACKING

SLIDING SYSTEMS

FRAMELESS GLASS SLIDING DOOR CEILING FIX KIT - GCC

Item number	RS150

Description	• frameless glass sliding door system - ceiling fix kit - GCC
	• maximum door weight 150kg
	• kit includes:
	  – 1 x 3 meters sliding door track
	  – 2 x roller carriages
	  – 2 x end stop and holder
	  – 1 x 1.5 meter top sliding door rail non-locking
	  – 2 x 1.5 meters brush door seals
	  – 1 x bottom guider roller
	  – 1 x glass or door rail bottom guide
	  – **please note** no handle included

Suitable for	• 10mm and 12mm glass thickness

RS150

39.5mm
49.5mm
20mm (±4)
100mm
22mm
10mm-12mm
10mm

88 mm
10 mm

Optional bottom rail with or without lock

RS150

GCC FRAMELESS GLASS SLIDING DOOR SIDE MOUNT BRACKET - GCC

Item number	SM15
Description	• GCC frameless glass sliding door side mount bracket

SM15

SM15

GCC FRAMELESS GLASS SLIDING DOOR TOP MOUNT BRACKET - GCC

Item number	TM15
Description	• GCC frameless glass sliding door top mount bracket

TM15

TM15

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

GCC FRAMELESS GLASS SLIDING DOOR
END CAP - GCC

Item number	TEC48
Description	• GCC frameless glass sliding door end cap

TEC48

TEC48

GCC FRAMELESS GLASS SLIDING DOOR
BOTTOM SLIDING DOOR RAIL - GCC

Item number	• GR50 - non-locking
	• GR70 - locking
Description	• GCC frameless glass sliding door 1.5 meters bottom sliding door rail

GR50
GR70

GR70

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

BI-FOLDING SYSTEMS

BI-FOLDING SYSTEMS

FRAMELESS GLASS FOLDING DOOR WITH DOOR RAILS - OFFSET ROLLER TYPE - GCC

Item number	SFW.DR.O
Description	• frameless glass folding door system with door rails - GCC • offset roller type • custom designed • maximum panel height 3 meters • maximum panel width 850mm • maximum panel weight 80kg
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural anodised

SFW.DR.O

GCC®

65mm glass center to glass center
35mm between the door rails
Open   Indoor   Open
Outdoor
55mm between glass panels   55mm between glass panels

SFW.DR.0

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FRAMELESS GLASS FOLDING DOOR WITH DOOR RAILS - CENTRE ROLLER TYPE - GCC

Item number	SFW.DR.C
Description	• frameless glass folding door system with door rails - GCC • centre roller type • custom designed • maximum panel height 3 meters • maximum panel width 1 meter • maximum panel weight 80kg
Suitable for	• 10mm and 12mm glass thickness
Material finish	• natural anodised

SFW.DR.C

GCC®

SFW.DR.C

Adjustable suspension bracket

20~33mm

Top rubber seal/weather strip

DR-102

100mm

22mm

SFW.DR.C

DR-102

Bottom rubber seal/weather strip

10~15mm

SFW.DR.C

GCC®

SFW.DR.C

65mm glass center to glass center
35mm between the door rails

← Open   Indoor   Open →

55mm between glass panels   Outdoor   55mm between glass panels

SLIDING, BI-FOLDING & STACKING

BI-FOLDING SYSTEMS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

JULY 2016

SLIDING, BI-FOLDING & STACKING

BI-FOLDING SYSTEMS

SLYDSTAK GLASS BI-FOLDING DOOR
AUSTVISION

BFS
BFR

AUSTVISION

Item number	• BFS - top spider hanger and bottom patch lock • BFR - top and bottom door rail
Description	• Slydstak glass bi-folding door - AUSTVISION • heavy duty top track extrusion • hidden fixing system • smooth nylon radial suspension roller system • rollers rated to 110kg each (typically two per door) • good corrosion resistance • special track covers to support ceiling panels • range of hardware options • easy to measure, install and maintain
Suitable for	• 10mm, 12mm and 15mm glass thickness • steel, concrete or timber
Material finish	• extruded aluminium in natural anodised aluminium finish (overhead track) • extruded aluminium standard in 316 stainless steel cover, 25 micron natural anodised aluminium and powder coated (door rails) • natural anodised aluminium finish or powder coated (cover plates for the overhead track) • 316 grade polished or satin stainless steel (spider hangers and patch locks)

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

INVISIBLE CONNECTION - CASMA

Item number	Invisible
Description	• invisible connection - CASMA • an innovative hardware system for frameless glass-folding doors exclusively equipped with patch fittings • the system hangs and slides in a top-mounted track and the wings are aligned in a „U" brass profile hidden in the floor • maximum size of each wing is 900mm x 3 meters x 10mm • maximum number of wings is 10 for a total opening of 900mm e.g. 6 wings on each side Download the Invisible flyer from our website for further information
Suitable for	• 8mm and 10mm glass thickness • steel, concrete or timber
Material finish	• aluminium

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SLIDING, BI-FOLDING & STACKING

STACKING SYSTEMS

STACKING
SYSTEMS

FRAMELESS GLASS STACKING DOOR WITH DOOR RAILS - GCC

Item number	SWS.DR
Description	• frameless glass stacking door with door rails - GCC • custom designed • maximum panel height 4 meters • maximum panel width 1.25 meters • maximum panel weight 150kg
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• natural anodised

SWS.DR

GCC®

SWS.DR

Indoor

← Outdoor

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

© Copyright 2016. Theses drawings must not be copied or used by others without the written consent of Elite Glass Solutions.   JULY 2016

SWS.DR
SWS.PF

GCC®

SWS.DR   .PF

FRAMELESS GLASS STACKING DOOR
WITH PATCH FITTING - GCC

Item number	SWS.PF
Description	• frameless glass stacking door with patch fitting - GCC • custom designed • maximum panel height 3 meters • maximum panel width 1 meter • maximum panel weight 85kg Download flyer from our website for set out and fixing details
Suitable for	• 10mm, 12mm and 15mm glass thickness
Material finish	• polished or satin stainless steel

SWS.PF

GCC®

SWS.PF

Indoor

← Outdoor

ELITE GLASS
SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

📞 1300 4 ELITE | 03 9314 6105
✉ sales@eliteglasssolutions.com.au
🌐 www.eliteglasssolutions.com.au

SLYDSTAK GLASS FOLDING STACKING DOOR AUSTVISION

| Item number	• FSR - top and/or bottom door rail with locking and latching • FSS - top spider hanger and bottom patch lock
Description	• Slydstak glass folding stacking door - AUSTVISION • heavy duty top track extrusion • hidden fixing system • smooth nylon radial suspension roller system • rollers rated to 110kg each (typically two per door) • good corrosion resistance • a range of parking bag options to stack doors • special track covers to support ceiling panels • range of hardware options • easy to measure, install and maintain
Suitable for	• 10mm, 12mm and 15mm glass thickness • steel, concrete and timber
Material finish	• extruded aluminium in natural anodised aluminium finish (overhead track) • extruded aluminium standard in 316 stainless steel cover, 25 micron natural anodised aluminium and powder coated (door rails) • natural anodised aluminium finish or powder coated (cover plates for the overhead track) • 316 grade polished or satin stainless steel (spider hangers and patch locks)

JUNIOR STACKING SYSTEM CASMA

Item number	Junior
Description	• Junior stacking system - CASMA • maximum wing dimensions 1 meter W x 3 meters H • maximum wing weight 80kg • the independent wing system slides inside a top mounted track • the wings can be stacked away in specifically designed parking bays, which can be either parallel or perpendicular to the sliding track • the system allows an unlimited number of wings and segmented installations, with very low bending radius • thanks to the use of patch fittings system with small interchangeable covers, extremely light glass surfaces can be created Download the Junior flyer from our website for further information
Suitable for	• 8mm, 10mm and 12mm glass thickness
Material finish	• aluminium and stainless steel

DOOR HANDLES

ELITE GLASS SOLUTIONS

DOOR HANDLES

**CONTENTS**

CONTENTS

# PULL HANDLES

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

D PULL HANDLE
32MM DIAMETER

Item number	• DH10.300 300mm overall length hole centres 300mm apart • DH10.500 500mm overall length hole centres 500mm apart • DH10.600 600mm overall length hole centres 600mm apart
Description	• D pull handle • 32mm diameter • lengths available in 300mm, 500mm or 600mm • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH10

32mm

DH10.300 - 300mm
DH10.550 - 500mm
DD.600 - 600mm

DH10
300/500/600

GLASS CUT OUT DETAIL

minimum
80mm

DH10.300 - 300mm
DH10.500 - 500mm
DH10.600 - 600mm

Ø14

OFFSET D PULL HANDLE
32MM DIAMETER

Item number	DH20.300
Description	• offset D pull handle • 32mm diameter • 300mm overall length • hole centres 300mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH20.300

32mm

300mm

DH20.300

GLASS CUT OUT DETAIL

80mm

300mm

Ø14

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

ROUND DOUBLE PULL HANDLE
32MM DIAMETER

Item number	DH30.300
Description	• round double pull handle • 32mm diameter • 300mm overall length • hole centres 300mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH30.300

300mm
32mm
DH30.300

GLASS CUT OUT DETAIL

80mm
300mm
Ø14

HALF CIRCLE HANDLE
32MM DIAMETER

Item number	DH40.300
Description	• half circle handle • 32mm diameter • 300mm overall length • hole centres 300mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH40.300

300mm
32mm
DH40.300

GLASS CUT OUT DETAIL

80mm
300mm
Ø14

ELITE GLASS SOLUTIONS

JULY 2016

BOW HANDLE
32MM DIAMETER

Item number	DH50.450
Description	• bow handle • 32mm diameter • 450mm overall length • hole centres 450mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH50.450

450mm   32mm

DH50.450

GLASS CUT OUT DETAIL

80mm

450mm   Ø14

ARCH D PULL HANDLE
40MM DIAMETER

Item number	• AR.500 580mm overall length hole centres 500mm apart • AR.750 830mm overall length hole centres 750mm apart
Description	• arch D pull handle • 40mm diameter • lengths available in 500mm or 830mm • hole diameter 12mm
Suitable for	• swing or sliding doors
Material finish	• satin stainless steel

**AR.500
AR.750**

AR.500 - 580mm
AR.750 - 830mm   40mm

AR.500/750

GLASS CUT OUT DETAIL


80mm

AR.500 - 500mm
AR.830 - 750mm   Ø12

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

H STYLE PULL HANDLE ROUND PROFILE
32MM DIAMETER

Item number	DH60
Description	• H style pull handle round profile • 32mm diameter • 600mm overall length • hole centres 500mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH60

600mm   DH60

32mm

GLASS CUT OUT DETAIL

80mm

500mm

Ø14

H STYLE PULL HANDLE ROUND PROFILE
25MM DIAMETER

Item number	• MF.600.25 600mm overall length 25mm diameter hole diameter 14mm hole centres 400mm apart • MF.900.25 900mm overall length 25mm diameter hole diameter 14mm hole centres 700mm apart • MF.1200.32 900mm overall length 32mm diameter hole diameter 12mm hole centres 1 meter apart
Description	• H style pull handle round profile • lengths available in 600mm, 900mm or 1.2 meters
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

MF.600/900 1200

MF.600 - 600mm
MF.900 - 900mm
MF.1200 - 1.2 meters

MF.600/900/1200

25mm

GLASS CUT OUT DETAIL

100mm

MF.600 - 400mm
MF.900 - 700mm
MF.1200 - 1 meter

Ø14 - MF.600/900
Ø12 - MF.1200

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

H STYLE PULL HANDLE ROUND PROFILE
25MM DIAMETER - FLARED LEG

Item number	• CHF.480 600mm overall length hole centres 480mm apart • CHF.600 800mm overall length hole centres 600mm apart • CHF.800 1 meter overall length hole centres 800mm apart • CHF.1200 1.4 meters overall length hole centres 1.2 meter apart • CHF.1500 1.7 meters overall length hole centres 1.5 meter apart
Description	• H style pull handle round profile, flared leg • 25mm diameter • lengths available in 600mm, 800mm, 1 meter, 1.4 meters or 1.7 meters • hole diameter 12mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

CHF

CHF.480 - 600mm
CHF.600 - 800mm
CHF.800 - 1 meter
CHF.1200 - 1.4 meters
CHF.1500 - 1.7 meters

CHF

25mm

GLASS CUT OUT DETAIL

100mm

CHF.480 - 480mm
CHF.600 - 600mm
CHF.800 - 800mm
CHF.1200 - 1.2 meters
CHF.1500 - 1.5 meters

Ø12

SQUARELINE PULL HANDLE
25/30MM DIAMETER

Item number	• SQ.600.25 25mm diameter 600mm overall length hole centres 425mm apart hole diameter 12mm • SQ.600 30mm diameter 600mm overall length hole centres 400mm apart hole diameter 14mm • SQ.1000 30mm diameter 1 meter overall length hole centres 800mm apart hole diameter 14mm
Description	• square line pull handle • lengths available in 600mm or 1 meter
Suitable for	• swing or sliding doors
Material finish	• stainless steel

SQ.600
SQ.1000

SQ.600.25 - 600mm
SQ.600 - 600mm
SQ.1000 - 1 meter

SQ.600/600.25
SQ.1000

SQ.600.25 - 25mm
SQ.600 - 30mm
SQ.1000 - 30mm

GLASS CUT OUT DETAIL

100mm

SQ.600.25 - 425mm
SQ.600 - 400mm
SQ.1000 - 800mm

SQ.600.25 - Ø12
SQ.600 - Ø14
SQ.1000 - Ø14

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

H STYLE PULL HANDLE SQUARE PROFILE 25 DIAMETER

Item number	• CHM.480.SQ 600mm overall length hole centres 480mm apart • CHM.600.SQ 800mm overall length hole centres 600mm apart • CHM.800.SQ 1 meter overall length hole centres 800mm apart • CHM.1200.SQ 1.4 meters overall length hole centres 1.2 meters apart • CHM.1500.SQ 1.7 meters overall length hole centres 1.5 meters apart
Description	• H style pull handle square profile • 25mm diameter • lengths available in 600mm, 800mm, 1 meter, 1.4 meters or 1.7 meters • hole diameter 12mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

CHM

CHM.480SQ - 600mm
CHM.600SQ - 800mm
CHM.800SQ - 1 meter
CHM.1200SQ - 1.4 meters
CHM.1500SQ - 1.7 meters

CHM.SQ

25mm

GLASS CUT OUT DETAIL

100mm

CHM.480SQ - 480mm
CHM.600SQ - 600mm
CHM.800SQ - 800mm
CHM.1200SQ - 1.2 meters
CHM.1500SQ - 1.5 meters

Ø12

H STYLE PULL HANDLE SQUARE PROFILE 32MM DIAMETER

| Item number	DH70
Description	• H style pull handle square profile • 32mm diameter • 600mm overall length • hole centres 400mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH70

600mm

DH70

32mm

GLASS CUT OUT DETAIL

100mm

400mm

Ø14

ELITE GLASS SOLUTIONS

D STYLE PULL HANDLE SQUARE PROFILE 32MM DIAMETER

| Item number	DH80
Description	• D style pull handle square profile • 32mm diameter • 600mm overall length • hole centres 600mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH80

600mm

DH80

32mm

GLASS CUT OUT DETAIL

100mm

600mm

Ø14

SQUARE D PULL HANDLE

Item number	• SQD.450 475mm overall length hole centres 450mm apart • SQD.600 600mm overall length hole centres 600mm apart
Description	• square D pull handle • 25mm diameter • lengths available in 475mm or 600mm • hole diameter 12mm
Suitable for	• swing or sliding doors
Material finish	• satin stainless steel

SQD.450
SQD.600

SQD.450 - 475mm
SQD.600 - 600mm

SQD.450/600

25mm

GLASS CUT OUT DETAIL

100mm

SQD.450 - 450mm
SQD.600 - 600mm

Ø12

DOOR HANDLES

PULL HANDLES

JULY 2016

DOOR HANDLES

PULL HANDLES

RECTANGULAR D PULL HANDLE

Item number	• RA.450 475mm overall length hole centres 450mm apart • RA.600 625mm overall length hole centres 600mm apart
Description	• rectangular D pull handle • 50mm x 25mm diameter • lengths available in 475mm or 625mm • hole diameter 12mm
Suitable for	• swing or sliding doors
Material finish	• satin stainless steel

RA.450 RA.600

25mm

RA.450 - 475mm
RA.600 - 625mm

RA.450/600

GLASS CUT OUT DETAIL

100mm

RA.450 - 450mm
RA.600 - 600mm

Ø12

SQUARE D PULL HANDLE OFFSET

| Item number	DH90
Description	• square D pull handle offset • 32mm diameter • 620mm overall length • hole centres 600mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• polished or satin stainless steel

DH90

32mm

DH90

620mm

GLASS CUT OUT DETAIL

80mm

600mm

Ø14

ICON PULL HANDLE

Item number	• IP.750
	  750mm overall length
	• IP.1250
	  1.25 meters overall length
	• IP.1750
	  1.75 meters overall length

Description	• icon pull handle • solid round section • 25mm diameter • lengths available in 750mm, 1.25 meters or 1.75 meters • hole centres 500mm apart • hole diameter 14mm
Suitable for	• swing or sliding doors
Material finish	• stainless steel

IP

IP.750   IP.1250   IP.1750

25 mm   25 mm   25 mm
750mm   1.25 meters   1.75 meters

GLASS CUT OUT DETAIL

100mm
500mm
Ø14

FLUSH PULL HANDLE

Item number	SFP
Description	• flush pull handle
Suitable for	• sliding doors • 10mm and 12mm glass thickness
Material finish	• natural anodised

SFP

65mm
150mm
SFP

GLASS CUT OUT DETAIL

52mm
116mm
R12

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

DOOR STOPPERS

DOOR STOPPERS

DOOR STOPPER

Item number	• SS.7.R round with spring stop • SS.7.FL flat stop - left hand • SS.7.FR flat stop - right hand
Description	• door stopper
Suitable for	• sliding doors
Material finish	• satin stainless steel

SS.7

SS.7

FLOOR GUIDE

Item number	SS.8
Description	• floor guide
Suitable for	• sliding doors • adjustable to suit 8mm, 10mm or 12mm glass thickness
Material finish	• satin stainless steel

SS.8

SS.8

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

FRAMELESS ASSEMBLIES

ELITE GLASS
SOLUTIONS

FRAMELESS ASSEMBLIES

CONTENTS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

GLASS CANOPY HARDWARE KIT
SUITABLE FOR 1 PANEL

Item number	• C1.10 length = 1.5 meters, B = 1.4 meters • C1.12 length = 1.7 meters, B = 1.6 meters
Description	• glass canopy hardware kit no glass included
Suitable for	• 10mm glass thickness (C1.10) • 12mm glass thickness (C1.12)
Material finish	• 316 stainless steel satin

C1.10 C1.12

C1.10/C1.12

GLASS CANOPY HARDWARE KIT
SUITABLE FOR 3 PANELS

Item number	• C3.10 length = 3.7 meters, B = 1.4 meters • C3.12 length = 4.3 meters, B = 1.6 meters
Description	• glass canopy hardware kit no glass included
Suitable for	• 10mm glass thickness (C3.10) • 12mm glass thickness (C3.12)
Material finish	• 316 stainless steel satin

C3.10 C3.12

C3.10/C3.12

GLASS CANOPY HARDWARE KIT
SUITABLE FOR 2 PANELS

Item number	• C2.10 length = 2.6 meters, B = 1.4 meters • C2.12 length = 3 meter, B = 1.6 meters
Description	• glass canopy hardware kit no glass included
Suitable for	• 10mm glass thickness (C2.10) • 12mm glass thickness (C2.12)
Material finish	• 316 stainless steel satin

C2.10 C2.12

C2.10/C2.12

GLASS CANOPY HARDWARE KIT
SUITABLE FOR 4 PANELS

Item number	• C4.10 length = 3.7 meters, B = 1.4 meters • C4.12 length = 4.3 meters, B = 1.6 meters
Description	• glass canopy hardware kit no glass included
Suitable for	• 10mm glass thickness (C4.10) • 12mm glass thickness (C4.12)
Material finish	• 316 stainless steel satin

C4.10 C4.12

C4.10/C4.12

PROUDLY SUPPLIED BY
AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FRAMELESS ASSEMBLIES

GLASS CANOPY COMPONENTS

GLASS CANOPY COMPONENTS

ONE WAY GLASS TO WALL BRACKET

Item number	CB3018
Description	• one way glass to wall bracket
Suitable for	• glass canopy hardware kits

CB3018

CB3018

ONE WAY WALL TO TIE ROD BRACKET

Item number	CB523
Description	• one way wall to tie rod bracket
Suitable for	• glass canopy hardware kits

CB523

CB523

ONE WAY WALL TO TIE ROD BRACKET

Item number	CB1234
Description	• one way wall to tie rod bracket
Suitable for	• glass canopy hardware kits

CB1234

CB1234

PROUDLY
SUPPLIED
BY

AGA (INT.)
AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

ONE WAY TIE ROD TO GLASS BRACKET

Item number	CGF220
Description	• one way tie rod to glass bracket
Suitable for	• glass canopy hardware kits

CGF220

CGF220

TIE ROD WITH FORKS

Item number	TR12
Description	• tie rod with forks
Suitable for	• glass canopy hardware kits

TR12

TR12

TWO WAY TIE ROD TO GLASS BRACKET

Item number	CGF443
Description	• two way tie rod to glass bracket
Suitable for	• glass canopy hardware kits

CGF443

CGF443

WOOD SCREW FOR FIXING OF CB WALL TIE ROD BRACKETS

Item number	CSW100
Description	• M10 and 100mm counter sunk wood screw for fixing of CB wall tie rod brackets
Suitable for	• glass canopy hardware kits

CSW100

CSW100

THREE WAY WALL TO TIE ROD BRACKET

Item number	CB1235
Description	• three way wall to tie rod bracket
Suitable for	• glass canopy hardware kits

CB1235

CB1235

PROUDLY
SUPPLIED
BY

AGA (INT.)
AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING
LIGHT WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING LIGHT WEIGHT

Item number	444.4
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

444.4

57mm 57mm
Ø35
120mm
Ø11 hole in glass
Ø20 hole in glass
444.4

mm steel/glass fin
mm silicone gap
mm toughened glass
mm silicone gap

SIDE VIEW

30mm
63mm
48mm
mm silicone gap
48mm
63mm
Ø24 Ø18
43mm
56mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum
	• M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw — Toughened — Toughened laminated
Ø35, Ø16, 45°, Ø24, Ø20, 8TMin, Ø16, Ø24

M8 DISC

M8 Disc — Toughened — Toughened laminated
Ø35, Ø16, Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw — Toughened — Toughened laminated
7mm, Ø50, Ø20, 45°, Ø29, Ø24, 8TMin, Ø20, Ø29

M10 DISC

M10 Disc — Toughened — Toughened laminated
7mm, Ø50, Ø20, Ø24

PROUDLY SUPPLIED BY AGA (INT.) AUSTVISION

FRAMELESS ASSEMBLIES
SPIDER FITTING LIGHT WEIGHT

JULY 2016

SPIDER FITTING LIGHT WEIGHT

Item number	444.4.2
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

444.4.2

57mm

96mm

120mm

Ø35

Ø11 hole in steel
Ø20 hole in glass

444.4.2

mm steel /glass fin

mm toughened glass

mm silicone gap

SIDE VIEW

30mm

63mm

48mm

48mm

63mm

Ø24 Ø18

43mm

56mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw | Toughened | Toughened laminated

Ø35

Ø16
45°
Ø24

Ø20
8TMin
45°
Ø16
Ø24

M8 DISC

M8 Disc | Toughened | Toughened laminated

Ø35

Ø16

Ø20
Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

7mm
Ø50

Ø20
45°
Ø29

Ø24
8TMin
45°
Ø20
Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated


7mm
Ø50

Ø20
Ø20

Ø24
Ø24

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING LIGHT WEIGHT

Item number	444.2
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

444.2

Ø35

Ø11 hole in steel
Ø20 hole in glass

57mm   57mm

mm steel/glass fin
mm silicone gap
mm toughened glass
mm silicone gap

444.2

SIDE VIEW

30mm
51mm
36mm
36mm
51mm
Ø24   Ø18
43mm
56mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw | Toughened | Toughened laminated
Ø35 | Ø16 / Ø24 / 45° | Ø20 / 8TMin / Ø16 / Ø24 / 45°

M8 DISC

M8 Disc | Toughened | Toughened laminated
Ø35 | Ø16 | Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated
7mm / Ø50 | Ø20 / Ø29 / 45° | Ø24 / 8TMin / Ø20 / Ø29 / 45°

M10 DISC

M10 Disc | Toughened | Toughened laminated
7mm / Ø50 | Ø20 / Ø20 | Ø24 / Ø24

FRAMELESS ASSEMBLIES

SPIDER FITTING LIGHT WEIGHT

PROUDLY SUPPLIED BY
AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING LIGHT WEIGHT

Item number	444.2.1
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

444.2.1

444.2.1

Ø35

Ø11 hole in steel
Ø20 hole in glass

mm steel /glass fin

mm toughened glass

mm silicone gap

57mm
72mm

SIDE VIEW

30mm
36mm
36mm
51mm
51mm
Ø24
Ø18
43mm
56mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw | Toughened | Toughened laminated

Ø35
Ø16
45°
Ø24
Ø20
8TMin
45°
Ø16
Ø24

M8 DISC

M8 Disc | Toughened | Toughened laminated

Ø35
Ø16
Ø20
Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

7mm
Ø50
Ø20
45°
Ø29
Ø24
8TMin
45°
Ø20
Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated

7mm
Ø50
Ø20
Ø20
Ø24
Ø24

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING LIGHT WEIGHT

Item number	443.4
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

443.4

120mm
Ø35
120mm
Ø30
443.4

SIDE VIEW

mm toughened glass
41mm
26mm
50mm
mm silicone gap
15 mm
M10 x 67mm threaded rod

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw / Toughened / Toughened laminated
Ø35, Ø16, Ø24, 45°, Ø20, 8TMin, Ø16, Ø24

M8 DISC

M8 Disc / Toughened / Toughened laminated
Ø35, Ø16, Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw / Toughened / Toughened laminated
7mm, Ø50, Ø20, Ø29, 45°, Ø24, 8TMin, Ø20, Ø29

M10 DISC

M10 Disc / Toughened / Toughened laminated
7mm, Ø50, Ø20, Ø24

PROUDLY SUPPLIED BY — AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

JULY 2016

FRAMELESS ASSEMBLIES

SPIDER FITTING LIGHT WEIGHT

SPIDER FITTING LIGHT WEIGHT

| Item number	443.2
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

443.2

Ø35

120mm

443.2

SIDE VIEW

mm toughened glass

41mm

26mm

50mm

mm silicone gap

M10 x 67mm threaded rod

15 mm

GLASS FASTENER OPTIONS HOLE DETAILS

| Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw | Toughened | Toughened laminated

Ø35 | Ø16, 45°, Ø24 | Ø20, 8TMin, 45°, Ø16, Ø24

M8 DISC

M8 Disc | Toughened | Toughened laminated

Ø35 | Ø16 | Ø20, Ø20

| Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

7mm, Ø50 | Ø20, 45°, Ø29 | Ø24, 8TMin, 45°, Ø20, Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated

7mm, Ø50 | Ø20, Ø20 | Ø24, Ø24

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING LIGHT WEIGHT

| Item number	443.4.2
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

443.4.2

443.4.2

SIDE VIEW

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 DISC

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 DISC

FRAMELESS ASSEMBLIES

SPIDER FITTING LIGHT WEIGHT

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING LIGHT WEIGHT

| Item number	443.2.1
Description	• spider fitting light weight
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

443.2.1

Ø35

60mm

443.2.1

Ø30

SIDE VIEW

41mm

mm toughened glass

50mm

15 mm

26mm

M10 x 67mm threaded rod

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M8
Description	• M8 counter sunk screw 12T maximum • M8 counter sunk disc 12L maximum

M8 SCREW

M8 Screw   Toughened   Toughened laminated

Ø35   Ø16   Ø24   45°   Ø20   8TMin   45°   Ø16   Ø24

M8 DISC

M8 Disc   Toughened   Toughened laminated

Ø35   Ø16   Ø20   Ø20

Item Number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø50   Ø20   45°   Ø29   Ø24   8TMin   45°   Ø20   Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø50   Ø20   Ø20   Ø24   Ø24

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY DUTY

| Item number	445.4M
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

445.4M

91mm   91mm   Ø50
Ø40
445.4M
Ø20mm hole in glass
Ø16mm hole in steel
200 mm
mm glass/ steel fin
65mm
7mm
mm silicone gap

SIDE VIEW

40mm
65mm
65mm
170mm
57mm
72mm
mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated
7mm
Ø50
Ø20
45°   Ø29
Ø24
8TMin
45°   Ø20
Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated
7mm
Ø50
Ø20
Ø20
Ø24
Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated
50mm
Ø59
Ø27
Ø30
Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)
70 mm
Ø59
Ø29
Inner
Outer
Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY DUTY

| Item number	445.2M
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

445.2M

91mm   91mm

Ø50
Ø40

445.2M

Ø20 hole in glass
Ø16 hole in steel

mm glass/steel fin

mm silicone gap

65mm

7mm

mm silicone gap

SIDE VIEW

40mm

Ø29 Ø22

50mm

50mm

140mm

57mm

72mm

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø20   Ø24
                                                            8TMin
Ø50   45°   Ø29   45°   Ø20
                                                            Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum
	• 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated

50mm   Ø27   Ø30

Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)

70 mm   Ø29
                              Inner   Inner Lite: _____ mm
                              Outer   Air Space: _____ mm
Ø59   Ø27   Outer Lite: _____ mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	445.4M.2
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

445.4M.2

91mm
Ø50
Ø40
200mm
Ø20 hole in glass
Ø16 hole in steel
445.4M.2
mm glass/ steel fin
65mm
7mm

SIDE VIEW

40mm
Ø29 Ø22
mm silicone gap
65mm
170mm
65mm
Ø29 Ø22
57mm
72mm
mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw
7mm
Ø50

Toughened
Ø20
45°
Ø29

Toughened laminated
Ø24
8TMin
45° Ø20
Ø29

M10 DISC

M10 Disc
7mm
Ø50

Toughened
Ø20
Ø20

Toughened laminated
Ø24
Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel
50mm
Ø59

Toughened
Ø27

Toughened laminated
Ø30
Ø30

60/22-42N SWIVEL

60/22-42n swivel
70 mm
Ø59

Insulated glass units (IGU)
Ø29
Inner
Outer
Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY DUTY

| Item number	445.2M.1
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

445.2M.1

91mm

Ø50

Ø40

445.2M.1

mm glass/steel fin

mm silicone gap

65mm

7mm

SIDE VIEW

40mm

Ø29 Ø22

50mm

50mm

140mm

57mm

72mm

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   45°   Ø29   8TMin   45°   Ø20   Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated

50mm   Ø27   Ø30

Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)

70 mm   Ø29   Inner Lite: _____ mm

Inner   Air Space: _____ mm

Outer   Outer Lite: _____ mm

Ø59   Ø27

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	445.4M.2Y
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

445.4M.2Y

445.4M.2Y
Ø20 hole in glass
Ø40
Ø50
90mm 90mm

SIDE VIEW

40mm
45mm 130mm
45mm
81mm
15mm
50mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated
7mm
Ø50
Ø20
45° Ø29
Ø24
8TMin 45° Ø20 Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated
7mm
Ø50
Ø20 Ø20
Ø24 Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel | Toughened | Toughened laminated
50mm
Ø59
Ø27
Ø30 Ø30

60/22-42N SWIVEL

60/22-42n swivel | Insulated glass units (IGU)
70 mm
Ø59
Ø29
Inner
Outer
Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY DUTY

| Item number	446.4M
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.4M

200mm

mm silicone gap

446.4M

Ø35

Ø50

mm silicone gap

SIDE VIEW

30mm 80mm

100mm

100mm

105 standard stock length

70mm

77mm

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

7mm Ø50 Ø20 45° Ø29 Ø24 8TMin 45° Ø20 Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated

7mm Ø50 Ø20 Ø20 Ø24 Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel | Toughened | Toughened laminated

50mm Ø59 Ø27 Ø30 Ø30

60/22-42N SWIVEL

60/22-42n swivel | Insulated glass units (IGU)

70 mm Ø59 Ø29 Inner Outer Ø27

Inner Lite: ____ mm
Air Space: ____ mm
Outer Lite: ____ mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

SPIDER FITTING HEAVY DUTY

| Item number	446.2M
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.2M

100mm

mm silicone gap

100mm

446.2M

Ø50 Ø35

SIDE VIEW

80mm

105 standard stock length

30 mm

Ø40

70 mm 77 mm

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   45° Ø29   8TMin 45° Ø20 Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum
	• 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated

50mm   Ø27   Ø30

Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)

70 mm   Ø29

Inner

Outer

Ø59   Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	446.4M.3
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.4M.3

200mm
Ø50
Ø35
mm silicone gap
446.4M.3
100mm
100mm
mm silicone gap

SIDE VIEW

30mm 80mm
105 standard stock length
70mm
77mm
mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

| Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw / Toughened / Toughened laminated
7mm, Ø50, Ø20, Ø29, 45°, Ø24, 8TMin, Ø20, Ø29, 45°

M10 DISC

M10 Disc / Toughened / Toughened laminated
7mm, Ø50, Ø20, Ø20, Ø24, Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel / Toughened / Toughened laminated
50mm, Ø59, Ø27, Ø30, Ø30

60/22-42N SWIVEL

60/22-42n swivel / Insulated glass units (IGU)
70mm, Ø59, Ø29, Inner, Outer, Ø27
Inner Lite: ___ mm
Air Space: ___ mm
Outer Lite: ___ mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	446.4M.2
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.4M.2

446.4M.2

SIDE VIEW

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

M10 DISC

M10 Disc | Toughened | Toughened laminated

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel | Toughened | Toughened laminated

60/22-42N SWIVEL

60/22-42n swivel | Insulated glass units (IGU)

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	446.2M.1
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.2M.1

446.2M.1

SIDE VIEW

mm toughened glass

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 DISC

Item Number	• 60/22-22N swivel 22mm maximum
	• 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-42N SWIVEL

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	446.4M.1
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.4M.1

446.4M.1

100mm
100mm
Ø50
Ø35

SIDE VIEW

30mm   80mm
M16 threaded rod
105 standard stock length
68mm

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated
7mm   Ø20   Ø24
Ø50   45°   Ø29   8TMin   45°   Ø20   Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated
7mm   Ø20   Ø24
Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated
50mm   Ø27   Ø30
Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)
70 mm   Ø29
Inner
Outer
Ø59   Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING HEAVY DUTY

| Item number	446.4M.90º
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.4M.90º

200mm

446.4M.90°

SIDE VIEW

mm toughened glass

Plugs silicone in place

30mm

mm toughened glass

90°

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw | Toughened | Toughened laminated

7mm
Ø50
Ø20
45°
Ø29
Ø24
8TMin
45°
Ø20
Ø29

M10 DISC

M10 Disc | Toughened | Toughened laminated

7mm
Ø50
Ø20
Ø20
Ø24
Ø24

Item Number	• 60/22-22N swivel 22mm maximum
	• 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel | Toughened | Toughened laminated

50mm
Ø59
Ø27
Ø30
Ø30

60/22-42N SWIVEL

60/22-42n swivel | Insulated glass units (IGU)

70 mm
Ø59
Ø29
Inner
Outer
Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY DUTY

| Item number	446.2M.90º
Description	• spider fitting heavy duty
Application	• post fix
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

446.2M.90º

446.2M.90°

SIDE VIEW

mm toughened glass

Plugs silicone in place

mm toughened glass

30mm

Ø40

90°

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum • M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   45°   Ø29   8TMin   45°   Ø20
                                                                    Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø20   Ø24

Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum • 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated

50mm   Ø27   Ø30

Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)

                                          Ø29
70 mm   Inner
                 Outer
Ø59   Ø27

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

ONE WAY GLASS CONNECTOR

| Item number	447
Description	• one way glass connector
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

447

447

122mm
52mm
70mm   80mm

Ø35 x 70mm x M14/ M16 or
Ø35 x 70mm x M10/ M16

mm toughened glass

Ø59

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
	• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated

7mm   Ø20   Ø24
Ø50   Ø29   8TMin
45°   45°   Ø20
Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated

7mm   Ø20   Ø24
Ø50   Ø20   Ø24

Item Number	• 60/22-22N swivel 22mm maximum
	• 60/22-42N swivel 42mm maximum

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated

50mm   Ø27   Ø30
Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)

70 mm   Ø29
Inner   Inner Lite: _____ mm
Outer   Air Space: _____ mm
Ø59   Ø27   Outer Lite: _____ mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

TWO WAY LINK CONNECTOR

| Item number	448.2M
Description	• two way link connector
Material	• 316 grade stainless steel
Material finish	• polished or satin 316 stainless steel
Order	• please specify glass thickness and fixing type

448.2M

448.2M

200mm
Ø50
Ø35
Ø50

100mm   100mm
34mm
7mm
mm toughened glass → || ← mm silicone gap

GLASS FASTENER OPTIONS HOLE DETAILS

Item number	M10
Description	• M10 counter sunk screw 10T minimum
• M10 counter sunk disc 10L minimum

M10 SCREW

M10 Screw   Toughened   Toughened laminated
7mm   Ø20   Ø24
Ø50   45°   Ø29   8TMin   Ø20
                           45°   Ø29

M10 DISC

M10 Disc   Toughened   Toughened laminated
7mm   Ø20   Ø24
Ø50   Ø20   Ø24

| Item Number | • 60/22-22N swivel 22mm maximum
• 60/22-42N swivel 42mm maximum |
|---|---|

60/22-22N SWIVEL

60/22-22n swivel   Toughened   Toughened laminated
50mm   Ø27   Ø30
Ø59   Ø30

60/22-42N SWIVEL

60/22-42n swivel   Insulated glass units (IGU)
70 mm   Ø29
Inner   Ø27
Outer
Ø59

Inner Lite: _____ mm
Air Space: _____ mm
Outer Lite: _____ mm

PROUDLY SUPPLIED BY

AGA (INT.) AUSTVISION

ELITE GLASS SOLUTIONS

JULY 2016

SPIDER FITTING ONE WAY - HOLE FIXED

CX1

Item number	CX1
Description	• spider fitting one way • hole fixed • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

CX1

FIXING OPTION A

CX1

Barrel nut and flat washer

50mm

61mm

Steel predrilled by others

Nylon insulating top hat

M16 stainless steel threaded rod

Barrel nut, flat and spring washers

FIXING OPTION B

50mm

90mm

M16 barrel nut, flat and spring washers and threaded rod

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø32

Articulated rotule

Ø50

CX1

110mm

100 mm

JULY 2016

SPIDER FITTING TWO WAY 180° - HOLE FIXED

CX2

| Item number	CX2
Description	• spider fitting two way 180° • hole fixed • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

CX2

CX2

FIXING OPTION A

CX2

50 mm
61 mm

Barrel nut and flat washer
Steel predrilled by others
M16 stainless steel threaded rod
Nylon insulating top hat
Barrel nut, flat and spring washers

FIXING OPTION B

50mm
90mm

M16 barrel nut, flat and spring washers and threaded rod
Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø32

Articulated rotule
Ø50
110mm

100 mm
100 mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING TWO WAY 90°- HOLE FIXED

| Item number	CX290
Description	• spider fitting two way 90° • hole fixed • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

CX290

CX290

Ø50

Articulated rotule

110mm

100mm

100mm

100mm

CX290

FIXING OPTION A

CX290

50 mm

61 mm

Barrel nut and flat washer

Steel predrilled by others

M16 stainless steel threaded rod

Nylon insulating top hat

Barrel nut, flat and spring washers

FIXING OPTION B

50mm

90mm

M16 barrel nut, flat and spring washers and threaded rod

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø32

HOLE SIZE

Ø32

Ø35

ELITE GLASS SOLUTIONS

JULY 2016

SPIDER FITTING FOUR WAY - HOLE FIXED

| Item number	CX4
Description	• spider fitting four way • hole fixed • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

CX4

FIXING OPTION A

CX4

50 mm

61 mm

Barrel nut and flat washer

Steel predrilled by others

M16 stainless steel threaded rod

Nylon insulating top hat

Barrel nut, flat and spring washers

FIXING OPTION B

50mm

90mm

M16 barrel nut, flat and spring washers and threaded rod

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø32

HOLE SIZE

Ø32

Ø35

CX4

CX4

Articulated rotule

Ø50

110mm

200mm

200mm

JULY 2016

SPIDER FITTING ONE WAY WITH ROTULE COVER CAP - HOLE FIXED

Item number	C1
Description	• spider fitting one way with rotule cover cap • hole fixed • supplied with flat head articulated rotules • CFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished or satin (subject to price and leadtime) 316 stainless steel

C1

C1

Ø50

Articulated rotule

116mm

100mm

C1

FIXING OPTION A

C1

117mm

M16 barrel nut

Steel predrilled by others

M16 stainless steel threaded rod

Nylon insulating top hat

Barrel nut, flat and spring washers

FIXING OPTION B

116mm

30mm

M16 barrel nut

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø32

HOLE SIZE

Ø32

Ø35

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING TWO WAY 90°
WITH ROTULE COVER CAP - HOLE FIXED

C290

Item number	C290
Description	• spider fitting two way 90° with rotule cover cap • hole fixed • supplied with flat head articulated rotules • CFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished or satin (subject to price and leadtime) 316 stainless steel

C290

C290

FIXING OPTION A

C290

117 mm

M16 barrel nut

Steel predrilled by others

M16 stainless steel threaded rod

Nylon insulating top hat

Barrel nut, flat and spring washers

FIXING OPTION B

116 mm

30mm

M16 barrel nut

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

Ø50

Articulated rotule

116mm

Ø32

HOLE SIZE

Ø32

Ø35

100mm
100mm
100mm
100mm

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

JULY 2016

SPIDER FITTING FOUR WAY
WITH ROTULE COVER CAP - HOLE FIXED

FRAMELESS ASSEMBLIES

**SPIDER FITTING HEAVY WEIGHT**

C4

| Item number	C4
Description	• spider fitting four way with rotule cover cap • hole fixed • supplied with flat head articulated rotules • CFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass hole diameter 32mm (see detail below) • N.B. fixings to the supporting structure are project specific and are supplied as an extra
Material	• 316 grade stainless steel
Material finish	• polished or satin (subject to price and leadtime) 316 stainless steel

C4

Articulated rotule

Ø50

116mm

C4

FIXING OPTION A

C4

M16 barrel nut

Steel predrilled by others

M16 stainless steel threaded rod

117 mm

Nylon insulating top hat

Barrel nut, flat and spring washers

FIXING OPTION B

M16 barrel nut

Ø30 x 30mm grade 316 stainless steel stub with M16 hole by others

116 mm

30mm

Ø32

HOLE SIZE

Ø32

Ø35

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105

sales@eliteglasssolutions.com.au

www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING TWO WAY 180° WITH ROTULE PLATE MOUNTED

Item number	FNZCX1
Description	• spider fitting two way 180° with rotule • plate mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX1

FNZCX1

60mm

9mm   100mm

150mm

15 or 19 fin

FNZCX1

FNZCX1

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness

Articulated rotule

110 mm

Ø50

50mm

Ø32

FACADE GLASS HOLE SIZE

Ø32

Ø35

Ø26

FIN HOLE

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING HEAVY WEIGHT

SPIDER FITTING FOUR WAY WITH ROTULE PLATE MOUNTED

| Item number	FNZCX2
Description	• spider fitting four way with rotule • plate mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX2

FNZCX2

100mm   100mm

200mm

15 or 19 fin

60mm

FNZCX2

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness

FNZCX2

Articulated rotule

50mm

110mm

Ø32

FACADE GLASS HOLE SIZE

Ø32

Ø35

Ø26

FIN HOLE

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

SPIDER FITTING ONE WAY WITH ROTULE
PLATE MOUNTED

| Item number	FNZCX1G
Description	• spider fitting one way with rotule • plate mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX1G

FNZCX1G

60mm

FNZCX1G

100mm

9mm

150mm

15 or 19 fin

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness

Articulated rotule

FNZCX1G

110 mm

Ø50

50mm

Ø32

FACADE GLASS HOLE SIZE

Ø32

Ø35

Ø26

FIN HOLE

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

JULY 2016

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

SPIDER FITTING TWO WAY 90° WITH ROTULE
PLATE MOUNTED

Item number	FNZCX2G
Description	• spider fitting two way 90° with rotule • plate mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX2G

FNZCX2G

FNZCX2G

100mm

9mm

150mm

200mm

15 or 19 fin

60mm

FNZCX2G

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness

Articulated rotule

Ø50

50mm

110mm

Ø32

FACADE GLASS HOLE SIZE

Ø32

Ø35

Ø26

FIN HOLE

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER FITTING ONE WAY WITH ROTULE
WALL MOUNTED

Item number	FNZCX1W
Description	• spider fitting one way with rotule • wall mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX1W

FNZCX1W

FNZCX1W

60mm

9mm

Fixing to wall to specific requirement

150mm

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness

Articulated rotule

110 mm

Ø50

50mm

Ø32

FACADE GLASS HOLE SIZE

Ø32

Ø35

Ø26

FIN HOLE

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

JULY 2016

FRAMELESS ASSEMBLIES

SPIDER FITTING HEAVY WEIGHT

SPIDER FITTING TWO WAY 90° WITH ROTULE WALL MOUNTED

Item number	FNZCX2W
Description	• spider fitting two way 90° with rotule • wall mounted • supplied with flat head articulated rotules • CXFHABM12 articulated rotule takes 10mm to 17.5mm glass thicknesses • glass fin hole diameter 26mm (see detail below) • spider fits to 15mm and 19mm glass fins
Material	• 316 grade stainless steel
Material finish	• polished (subject to price and leadtime) or satin 316 stainless steel

FNZCX2W

FNZCX2W

100mm
200mm
9mm
60mm

Ø32
FACADE GLASS HOLE SIZE

Ø32
Ø35

Ø26
FIN HOLE

109mm for 10mm glass thickness
101mm for 17.5mm glass thickness
Articulated rotule
Ø50
50mm
110 mm

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

# STRUCTURAL BRACKETS

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

**ADELAIDE OFFICE**
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

SPIDER GLASS FIN SHOE
BOLT TO THE FLOOR

Item number	FS300
Description	• spider glass fin shoe • bolted to the floor
Suitable for	• 12mm Viridian toughened safety glass
Material finish	• subject to price and leadtime – zinc plated steel – powder coated steel – polished or satin stainless steel

FS300

FS300

300mm

50mm

5mm thick welded end wall

3mm thick neoprene at either end

12 mm

20mm

3mm thick PVC packer on either side

50mm

50 x 50 x 5 steel angle

SPIDER GLASS FIN SHOE
FLOOR MOUNTED

Item number	FS400
Description	• spider glass fin shoe • floor mounted
Suitable for	• 15mm Viridian toughened safety glass
Material finish	• subject to price and leadtime – zinc plated steel – powder coated steel – polished or satin stainless steel

FS400

FS400

400mm

50mm   50mm

6mm thick welded end wall

14mm

3mm thick neoprene at either end

25mm

406mm

3mm thick PVC packer on either side

65mm

65 x 65 x 6 steel angle

ELITE GLASS SOLUTIONS

JULY 2016

SPIDER GLASS FIN BRACKET
SUITABLE FOR 12MM GLASS THICKNESS

Item number	FB300
Description	• spider glass fin bracket • glass fin hole diameter 18mm • recommended torque for non lubricated M12 grade 8.8 bolts = 212Nm
Suitable for	• 12mm Viridian toughened safety glass

Material finish	• subject to price and leadtime
	  – zinc plated steel
	  – powder coated steel
	  – polished or satin stainless steel

FB300

SPIDER GLASS FIN BRACKET
SUITABLE FOR 15MM GLASS THICKNESS

| Item number	FB400
Description	• spider glass fin bracket • glass fin hole diameter 26mm • recommended torque for non lubricated M12 grade 8.8 bolts = 212Nm
Suitable for	• 15mm Viridian toughened safety glass

Material finish	• subject to price and leadtime
	  – zinc plated steel
	  – powder coated steel
	  – polished or satin stainless steel

FB400

300mm

Ø12 x 20 slot

65 mm

60mm 180mm 60mm

FB300

400mm

Ø14 x 25 slot

45 mm
30 mm

25mm 25mm

75mm 125mm 125mm 75mm

FB400

65 x 65 x 6
zinc plated steel angle

2mm

24mm minimum

36 mm 38 mm

Ø18 hole

M12 grade 8.8 high tensile bolt and flat washer

12mm toughened safety glass

75 x 75 x 6 steel angle

2mm

14mm 14mm

25 x Ø14 slot for M12 bolts

45mm

32 mm 30mm

M16 grade 8.8 high tensile bolt and flat washers

1.6mm thick compressed fibre gasket

Ø25 hole

15mm toughened safety glass

FRAMELESS ASSEMBLIES

STRUCTURAL BRACKETS

MFG HARDWARE WARRANTY

MFG HARDWARE WARRANTY – Austvision Export

Metropolitan Glass and Glazing Limited and its subsidiaries Metro GlassTech (MGT) & Metro Frameless Glass Systems (MFG), warrant that all Austvision Hardware supplied by MFG will be;
1.   Fit for all purposes for which they are commonly supplied and
2.   be acceptable in appearance and finish and
3.   be safe and durable.

MFG warrant that **for a period of five (5) years** from the date of delivery, the Austvision hardware will not suffer from any manufacturing defects.

In the event that the above occurs, MFG will re-supply the defective hardware and the warranty period will extend to for a **further period of five (5) years from delivery**.

MFG advises that all its products carry a guarantee of acceptable quality and a guarantee that the goods correspond with MFG description of them, but MFG will not be liable under the guarantee of acceptable quality for any loss caused as a result of:
1.   Any act of default or omission of, or any representation made by, any person other than employees or agents of MGT or MFG.
2.   Goods which have not been properly handled, installed or maintained and used in good practice in accordance with relevant glazing Standards and/or MGT/MFG instructions.

MFG reserves the right to inspect in the field any hardware which is alleged to be defective and which is subject to a claim under this warranty.

July 2014

MFG is a Divison of

METRO
PERFORMANCE GLASS

Metro Frameless Glass Systems
Unit O, 35 Maurice Rd, Penrose, Auckland
Ph: 09 622 2643 Fax: 09 622 2648
www.metroframeless.co.nz

ELITE GLASS SOLUTIONS

HEAD OFFICE
114 Endeavour Way
Sunshine West
VIC 3020 Australia

ADELAIDE OFFICE
7 Manfull Street
Melrose Park
SA 5039 Australia

1300 4 ELITE | 03 9314 6105
sales@eliteglasssolutions.com.au
www.eliteglasssolutions.com.au

ELITE GLASS
SOLUTIONS